Annual Tropical Cyclone Report


U. S. NAVAL OCEANOGRAPHY COMMAND CENTER JOINT TYPHOON WARNING CENTER COMNAVMARIANAS BOX 12 FPO SAN FRANCISCO, CA 96630-2926

ROBERT J. PLANTE

CAPTAIN, UNITED STATES NAVY COMMANDING OFFICER

CHARLES P. GUARD

LIEUTENANT COLONEL, UNITED STATES AIR FORCE DIRECTOR, JOINT TYPHOON WARNING CENTER COMMANDER, DETACHMENT 1, 1ST WEATHER WING





STAFF

JOINT TYPHOON WARNING CENTER

LCDR	NICHOLAS D. GURAL	USN	DEPUTY DIRECTOR
LCDR	LESTER E. CARR, III	USN	TECHNIQUE DEVELOPMENT
* LCDR	JOHN L. HEISHMAN	USN	DEPUTY DIRECTOR
* LT	DOUGLAS H. SCOVIL, JR.	USN	TDO
* CAPT			
	ROBERT F. CROSBY	USAF	TDO
* LT	RYAN R. SCHULTZ	USN	TDO
* CAPT	JOHN M. ROGERS	USAF	TDO
CAPT	DANIEL N. SHOEMAKER	USAF	TDO
LT	DIANNE K. CRITTENDEN	USN	TDO, STATISTICS
CAPT	ANN R. OSTDIEK	USAF	TDO, BEST TRACKS
CAPT	BRUCE W. THOMPSON	USAF	TDO
* CAPT	JOHN D. PICKLE	USAF	TDO
LT		USNR	TDO **
			**
LT	MICHAEL FIORINO	USNR	
ENS	RICHARD L. JEFFRIES	USN	TDO, TRAINING
* SSGT	DONALD L. NOVAK, JR.	USAF	TDA
AG2	BARRY F. BROCKMAN	USN	TDA
* SGT	ANGELIA C. BLAISDELL	USAF	TDA
* SGT	JAMES B. BUNKER	USAF	TDA
* SRA	DONALD L. MILLER	USAF	TDA
* AG3	JEFFERY L. CHAPIN	USN	
			TDA
AG3	KIMBERLEY J. WOODS	USN	TDA
* AG3	AVERY G. DUNCAN	USN	TDA
SRA	RAY O. BELEW	USAF	TDA
AMN	LANCE W. CASHMAN	USAF	TDA
AGAA	TRACEY R. MARTIN	USN	TDA
AGAR	LAURA A. MASTERS	USN	TDA
	DET 1. 1WW		
MAI	DET 1, IWW	IISAF	TECHNIQUE DEVELOPMENT TOO
MAJ	JOEL D. MARTIN	USAF	TECHNIQUE DEVELOPMENT, TDO
CAPT	JOEL D. MARTIN TIM D. HUTCHISON	USAF	MSC
CAPT 1LT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY	USAF USAF	MSC DATA DEVELOPMENT, TDO
CAPT 1LT * MSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER	USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC
CAPT 1LT * MSGT MSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI	USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC
CAPT 1LT * MSGT MSGT * TSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER	USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST
CAPT 1LT * MSGT MSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI	USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE	USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO	USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY	USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST ANALYST ANALYST ANALYST ANALYST
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT SSGT STGT STGT SSGT STGT ST	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY ATCR STAFF RICHARD H. BOUCHARD FRANK H. WELLS	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST ANALYST ANALYST ANALYST ANALYST ANALYST ANALYST TDO, EDITOR TECHNICAL EDITOR
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT * SSGT SSGT SSGT SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY ATCR STAFF RICHARD H. BOUCHARD FRANK H. WELLS JAMES B. WIEMANN	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST TDO, EDITOR TECHNICAL EDITOR TDA, CHIEF GRAPHICS
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT SSGT SSGT SSGT SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY ATCR STAFF RICHARD H. BOUCHARD FRANK H. WELLS JAMES B. WIEMANN HOLLY A. JENNINGS	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST TDO, EDITOR TECHNICAL EDITOR TDA, CHIEF GRAPHICS TDA, GRAPHICS
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT SSGT SSGT SSGT SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY ATCR STAFF RICHARD H. BOUCHARD FRANK H. WELLS JAMES B. WIEMANN HOLLY A. JENNINGS JEREMY D. WILLIAMS	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST TDO, EDITOR TECHNICAL EDITOR TDA, CHIEF GRAPHICS TDA, GRAPHICS TDA, STATISTICS
CAPT 1LT * MSGT MSGT * TSGT TSGT TSGT * SSGT SSGT SSGT SSGT SSGT SSGT SSGT SSGT	JOEL D. MARTIN TIM D. HUTCHISON ROBERT J. FALVEY ROBERT E. REDINGER CHARLES J. BONINI TONI D. HUMPHREY BRIAN P. BURKE DANILO O. MONTILLANO ROBERT C. GRAY JACK L. WILSON MICHELLE TIMPERIO PAUL F. HARPER RAYMOND L. SOUZA WAYNE I. GENTRY ATCR STAFF RICHARD H. BOUCHARD FRANK H. WELLS JAMES B. WIEMANN HOLLY A. JENNINGS	USAF USAF USAF USAF USAF USAF USAF USAF	MSC DATA DEVELOPMENT, TDO TECHNIQUE DEVELOPMENT, NCOIC ANALYST, NCOIC ANALYST ANALYST ADMINISTRATION ANALYST ADMINISTRATION ANALYST TDO, EDITOR TECHNICAL EDITOR TDA, CHIEF GRAPHICS TDA, GRAPHICS

- MARK A. LANDER
- UNIVERSITY OF HAWAII

- * TRANSFERRED DURING 1989
 ** ACTIVE DUTY TRAINING

DR

ONR POST - DOCTORATE FELLOW

DISTRIBUTION LIST

	*
1 COPY	HO MACIDOOS
ANALYSIS AND PROCESSING CENTER, INDONESIA	HQ MAC/DOOS HO USAF/XOORZ
BRUNEI SHELL PETROLEUM CO	
CATHOLIC UNIVERSITY OF AMERICA	HUGHES AIRCRAFT CO
CENTRAL MET OBSERVATORY, BEIJING	INDIAN INSTITUTE OF TROPICAL METEOROLOGY
	INSTITUO DE GEOFISICA, MEXICO
CENTRAL METEOROLOGICAL OFFICE, SEOUL	JCS ENV SERVICES DIV (J3(OES))
CHULALONGKORN UNIVERSITY, BANGKOK	LOS ANGELES PUBLIC LIBRARY
CHUNG CHENG INSTITUTE, TAIWAN	MASS INST OF TECH
CITIES SERVICES OIL GAS CORP	MCAS FUTENMA
CIUDAD UNIVERSITARIA, MEXICO	MCAS IWAKUNI
CIVIL DEFENSE, BELAU	MCAS KANEOHE BAY HI
CIVIL DEFENSE, MAJURO	METEOROLOGICAL DEPARTMENT, PAKISTAN
CIVIL DEFENSE, POHNPEI	METEOROLOGICAL SERVICE, FRENCH POLYNESIA
CIVIL DEFENSE, SAIPAN	METEOROLOGICAL SERVICE, MAURITIUS
CIVIL DEFENSE, TRUK	METEOROLOGICAL SERVICE, REUNION
CIVIL DEFENSE, YAP	METEOROLOGY SOCIETY OF NEW SOUTH WALES, AUST
CINCPACFLT	MIL ASST ENV SCI (R & AT / E & LS)
CNO (OP-096)	MOBIL OIL GUAM INC.
CNO (OP-096T)	MOUNTAIN STATES WEATHER SERVICES
CNO (OP-981D)	NATIONAL TAIWAN UNIVERSITY
CNO (OP-943G)	NATIONAL WEATHER SERVICE, PAPUA NEW GUINEA
COLORADO STATE UNIVERSITY LIBRARY	NAVAL CIVIL ENG LAB, PORT HUENEME, CA
COMMONWEALTH NORTHERN MARIANAS ISLANDS	NAVAL RESEARCH LAB
COMNAVFOR PHILIPPINES	NAVDEP NOAA
COMNAVMAR	NAVEASTOCEANCEN NORFOLK
COMNAVOCEANCOM	NAVHISTCEN
COMNAVSURFGRU WESTPAC	NAVOCEANCOMCEN ROTA
COMNAVSURFPAC	NAVOCEANCOMDET AGANA
COMPATRECFOR	NAVOCEANCOMDET ALAMEDA
COMPHIBGRU ONE	NAVOCEANCOMDET ASHEVILLE
COMSC	NAVOCEANCOMDET ATSUGI
COMSEVENTHFLT	NAVOCEANCOMDET BARBERS POINT
COMSPAWARSYSCOM	NAVOCEANCOMDET KADENA
COMSUBGRU SEVEN	NAVOCEANCOMDET MONTEREY
COMTHIRDFLT	NAVOCEAN COMFAC JACKSONVILLE
CONGRESSIONAL INFORMATION SERVICE, MD	NAVOCEANCOMFAC YOKOSUKA
DCA GUAM	NAVOCEANO NAVOCEANO
DET 2, 20 WS/CC	NAVPGSCOL LIBRARY
DET 4, 20 WS/CC	NAVPOLAROCEANCEN SUITLAND
DET 5, 20 WS/CC	NEW ZEALAND MET SERVICE
DET 7, 20 WS/CC	NOAA/ACQUISITION SECTION, ROCKVILLE, MD
DET 8, 20 WS/CC	
DET 10, 30 WS/CC	NOAA/AOML, HRD, MIAMI, FL
DET 13, 20 WS/CC	NOAA/HYDROMETEOROLOGY BR, SILVER SPRINGS, MD
DET 15, 20 WS/CC	NOAA/NESDIS, HONOLULU, HI
· · · · · · · · · · · · · · · · · · ·	NOAA/NESDIS, REDWOOD CITY, CA
DET 18, 30 WS/CC	NOAA/NESDIS, SYNOPTIC ANAL BRANCH
DET 19, 30 WS/CC	NOAA/PMEL, SEATTLE, WA
DET 20, 30 WS/CC	NOAA LIBRARY, MIAMI, FL
DISASTER CONTROL OFFICE, SAIPAN	NOBEL DENTON
ECMWF, BERKSHIRE, UK	OCEAN ROUTES INC., CA
FAIRECONRON ONE	OCEANO SERVICES INC. LIBRARY
FIJI METEOROLOGICAL SERVICE	OCEANWEATHER, INC.
FOREST DIVISION, JMA	OFFICE OF FEDERAL COORDINATOR METEOROLOGY
GEOLOGICAL FLUID DYNAMICS LAB, PRINCETON, NJ	OFFICE OF FOREIGN DISASTER ASST, AID
GEOLOGICAL SURVEY, GUAM	OFFICE OF NAVAL RESEARCH
GEOPHYSICS LAB/LYS	PACAF/DOW
GODDARD SPACE FLIGHT CENTER	PACAF/WSU
GUAM COMMUNITY COLLEGE	PACIFIC STARS & STRIPES
GUAM PUBLIC LIBRARY	PACNAVFACENGCOM
HQ AWS/DO	PENNSYLVANIA STATE UNIVERSITY
HQ AWS/DOOF	SAINT LOUIS UNIVERSITY
HQ AWS/XT	SAT APPL LAB, NOAA/NESDIS, WASHINGTON, DC

SERVICE DE LA MET NATIONAL, MALAGASY REPUBLIC SHANGHAI TYPHOON INSTITUTE SRI LANKA METEOROLOGICAL SOCIETY **SRI LIBRARY** TAO PROJECT OFFICE TEXAS A & M UNIVERSITY UNIVERSITY OF CHICAGO UNIVERSITY OF GUAM, BIOLOGY DEPT UNIVERSITY OF HAWAII LIBRARY UNIVERSITY OF WASHINGTON USAFETAC/DN USCINCPAC USCINCPAC REP GUAM USCINCPAC REP FIJI USCINCPAC REP PHILIPPINES USNA (OCEANOGRAPHY DEPT/LIBRARY) USS AMERICA (CV 66) USS BELLEAU WOOD (LHA 3) USS CARL VINSON (CVN 70) USS CONSTELLATION (CV 64) USS CORAL SEA (CV 43) USS EISENHOWER (CVN 69) USS ENTERPRISE (CVN 65) USS FORRESTAL (CV 59) USS INDEPENDENCE (CV 62) USS IOWA (BB 61) USS J. F. KENNEDY (CV 67) USS KITTY HAWK (CV 63) USS LINCOLN (CVN 72) USS MIDWAY (CV 41) USS MISSOURI (BB 63) USS NEW JERSEY (BB 62) **USS NEW ORLEANS (LPH 11)** USS NIMITZ (CVN 68) USS OKINAWA (LPH 3) USS PELELIU (LHA 5) USS RANGER (CV 61) USS SARATOGA (CV 60) USS TARAWA (LHA 1) USS TRIPOLI (LPH 10) USS T. ROOSEVELT (CVN 71) USS WISCONSIN (BB 64) WORLD DATA CENTER B1, MOSCOW 5WW/CC

2 COPIES

7WW/OL-A

34 AWF, 920 WRG 3350 TCHTG/TTMV-S

20 WS/DO 30WS/DO

AFGWC/WFMP
AWS TECH LIBRARY
BUREAU OF METEOROLOGY, BRISBANE
BUREAU OF METEOROLOGY, DARWIN
BUREAU OF METEOROLOGY, MELBOURNE
BUREAU OF METEOROLOGY, PERTH
BUREAU OF PLANNING, GUAM

CIVIL DEFENSE, GUAM DEPARTMENT OF COMMERCE ESCAP LIBRARY, BANGKOK FLENUMOCEANCEN MONTEREY FLORIDA STATE UNIVERSITY HQ AWS GP, JAPAN INSTITUTE OF PHYSICS, TAIWAN MARATHON OIL CO, TX MARINERS WEATHER LOG MET RESEARCH INST LIBRARY, TOKYO MICRONESIAN RESEARCH CENTER UOG, GUAM NATIONAL CLIMATIC DATA CENTER NATIONAL METEOROLOGICAL LIBRARY, BRACKNELL, UK NATIONAL WEATHER SERVICE, HONOLULU NAVOCEANCOMDET DIEGO GARCIA NAVOCEANCOMDET MISAWA NAVOCEANCOMFAC CUBI PI NAVWESTOCEANCEN PEARL HARBOR NOAA CORAL GABLES LIBRARY **NOAA GUAM** NORA 1570 DALLAS, TX OKINAWA METEOROLOGY OBSERVATORY SAT APPL LAB, NOAA/NESDIS, CAMP SPRINGS, MD TYPHOON COM SECR, MANILA UNIVERSITY OF PHILIPPINES US ARMY, FORT SHAFTER WORLD DATA CENTER A, NOAA 1WW/DN 17 WS/DON 23 AF/HO 73 WEATHER GROUP, ROK AF

3 COPIES

CENTRAL WEATHER BUREAU, TAIWAN INDIA METEOROLOGICAL DEPT INOSHAC, DDGM (WF)
JAPAN METEOROLOGICAL AGENCY NATIONAL HURRICANE CENTER, MIAMI NAVPGSCOL DEPT OF METEOROLOGY UNIVERSITY OF HAWAII, METEOROLOGY WEATHER CENTRAL, CAF

4 COPIES

COLORADO STATE UNIVERSITY METEOROLOGY DEPT, BANGKOK

5 COPIES

PAGASA WEATHER BUREAU, RP R & D UNIT, NHC, MIAMI ROYAL OBSERVATORY HONG KONG

6 COPIES NOARL WEST

NATIONAL WEATHER ASSOCIATION

12 COPIES

DEFENSE TECHNICAL INFORMATION CENTER

FOREWORD

The Annual Tropical Cyclone Report is prepared by the staff of the Joint Typhoon Warning Center (JTWC), a combined Air Force/Navy organization operating under the command of the Commanding Officer, U.S. Naval Oceanography Command Center/Joint Typhoon Warning Center, Guam. JTWC was established 1 May 1959 when USCINCPAC directed USCINCPACFLT to provide a single tropical cyclone warning center for the western North Pacific region. The operations of JTWC are guided by CINCPACINST 3140.1T.

The mission of the Joint Typhoon Warning Center is multi-faceted and includes:

- 1. Continuous monitoring of all tropical weather activity in the Northern and Southern Hemispheres, from 180 degrees longitude westward to the east coast of Africa, and the prompt issuance of appropriate advisories and alerts when tropical cyclone development is anticipated.
- 2. Issuing warnings on all significant tropical cyclones in the above area of responsibility.
- 3. Determination of requirements for tropical cyclone reconnaissance and assignment of appropriate priorities.
- 4. Post-storm analysis of all significant tropical cyclones occurring within the western North Pacific and North Indian Oceans, which includes an in-depth analysis of tropical cyclones of note and all typhoons.
- 5. Cooperation with the Naval Oceanographic and Atmopheric Research Laboratory (NOARL), Monterey, California, on the operational evaluation of tropical cyclone models and forecast aids, and the development of new techniques to support operational forecast scenarios.

Satellite imagery used throughout this report represents data obtained by the DMSP network. The personnel of Detachment 1, 1WW, collocated with JTWC at Nimitz Hill, Guam, coordinate the satellite acquisitions and tropical cyclone reconnaissance with the following units:

Det 4, 20WS, Hickam AFB, Hawaii

Det 5, 20WS, Clark AB, Republic of the Philippines

Det 8, 20WS, Kadena AB, Japan

Det 15, 30WS, Osan AB, Korea

Air Force Global Weather Central, Offutt AFB, Nebraska

In addition, the Naval Oceanography Command Detachment, Diego Garcia, and Defense Meteorological Satellite Program (DMSP) equipped U.S. Navy ships have been instrumental in providing vital fixes of tropical cyclones in the Indian Ocean from satellite data.

Should JTWC become incapacitated, the Alternate Joint Typhoon Warning Center (AJTWC) located at the U.S. Naval Western Oceanography Center, Pearl Harbor, Hawaii, assumes warning responsibilities. Assistance in determining satellite reconnaissance requirements, and in obtaining the resultant data, is provided by the PACAF Weather Support Unit, Hickam AFB, Hawaii.

Changes in this year's publication include: a new list of tropical cyclone names was implemented after Typhoon Wayne (25W); old Annex A now appears under the heading Tropical Cyclone Warning Statistics, Track and Fix Data; the Satellite Reconnaissance section was expanded to include technique development efforts and future developments; and the numbering of the sections was modified to make indexing the material easier.

Special thanks to: Lieutenant Colonel Daniel J. McMorrow for his significant contributions and support; the men and women of the 27th Communications Squadron, Operating Location Charlie and the Operations and Equipment Support departments of the Naval Oceanography Command Center, Guam for their continuing support by providing high quality real-time satellite imagery; Marine Corps Air Station, Futenma, Japan for sharing their satellite imagery of tropical cyclones; the Pacific Fleet Audio-Visual Center, Guam for their assistance in the reproduction of satellite data for this report; to the Navy Publications and Printing Service Branch Office, Guam; Dr. Bob Abbey and the Office of Naval Research for their technical support to this publication and support to the University of Hawaii for the Post Doctorate Fellow at JTWC; Dr. Mark Lander for his training efforts and suggestions; the Australian Meteorological Service for the coastal radar reports on tropical cyclones via the AFTN to JTWC; National Weather Service Pacific Region for their able assistance installing the AMOS equipment at Ujae and Enewetak, and AFTN hardware at JTWC; and the Republic of the Marshall Islands for endorsing the AMOS installations at Ujae and Enewetak; Mr John Brown and Mr. David Saltzberger of the Naval Oceanographic Office for their efforts regarding buoys and the Local User's Terminal data.

Note: Appendix A contains definitions, Appendix B names of tropical cyclones, Appendix C references and Appendix D information on how to obtain past issues of the Annual Tropical Cyclone Report (titled Annual Typhoon Report prior to 1980).

TABLE OF CONTENTS

rional Processing Sources a Sources amunications a Displays llyses	OCEDURES				
neral		•••••		1 1	
a Sources nmunications a Displays llyses ecast Procedu	• • • • • • • • • • • • • • • • • • • •	• • • • • • •		1	
gnostic Reaso pical Cyclone	ning Messa Formation	ges			
NAISSANCE	AND FIXE	ES	• • • • • • • • • • • • • • • • • • • •	9	
onnaissance A ellite Reconna ar Reconnaiss pical Cyclone RY OF WES INDIAN OCI eral	Availability issance Sunsance Summ Fix Data TERN NOFEAN TROP	nmary nary RTH PA ICAL (CIFIC AND CYCLONES	9 16 16 17	
UTHOR	PAGE	TROPIC	CAL CYCLONE	AUTHOR	PAGE
HULTZ COVIL HOEMAKER ICKLE EFFRIES OUCHARD STDIEK ALVEY RITTENDEN HOEMAKER HOMPSON EFFRIES OUCHARD OUCHARD RITTENDEN HOEMAKER HOMPSON EFFRIES	32 38 46 50 52 56 60 64 70 74 78 84 86 92 98 102 106 108	(20W) (21W) (22W) (23W) (24W) (25W) (26W) (27W) (28W) (29W) (30W) (31W) (32W) (33W) (34W) (35W)	TS ROGER TD 21W TY SARAH TS TIP TS VERA TY WAYNE STY ANGELA TY BRIAN TY COLLEEN TY DAN STY ELSIE TY FORREST TY GAY TY HUNT STY IRMA TD 35W	OSTDIEK OSTDIEK GURAL CRITTENDEN CRITTENDEN SHOEMAKER THOMPSON JEFFRIES BOUCHARD OSTDIEK THOMPSON GUARD CRITTENDEN SHOEMAKER THOMPSON CARR/JEFFRIES CARR	110 114 118 126 130 134 138 142 146 152 156 160 166 172 176 180
EFT CELECTER CONTRACTOR OF THE	mings gnostic Reaso pical Cyclone inficant Tropic NAISSANCE eral onnaissance A illite Reconnaiss pical Cyclone ar Reconnaiss pical Cyclone RY OF WES INDIAN OCI eral tern North Pa INDIVI UTHOR HULTZ COVIL HOEMAKER HOEMAKER ICKLE EFFRIES OUCHARD STDIEK ALVEY RITTENDEN HOEMAKER HOMPSON EFFRIES OUCHARD OUCHARD RITTENDEN HOEMAKER HOMPSON HOEMAKER HOMPSON	ecast Procedures	cast Procedures. mings. gnostic Reasoning Messages cical Cyclone Formation Alerts. mificant Tropical Weather Advisor NAISSANCE AND FIXES eral connaissance Availability clite Reconnaissance Summary ar Reconnaissance Summary coical Cyclone Fix Data RY OF WESTERN NORTH PA INDIAN OCEAN TROPICAL OF tern North Pacific Tropical Cycl INDIVIDUAL TROPICAL UTHOR PAGE HULTZ 32 (20W) COVIL 38 (21W) HOEMAKER 46 (22W) ICKLE 50 (23W) EFFRIES 52 (24W) OUCHARD 56 (25W) STDIEK 60 (26W) ALVEY 64 (27W) RITTENDEN 70 (28W) HOEMAKER 74 (29W) HOEMAKER 75 (23W) OUCHARD 76 (23W) OUCHARD 77 (23W) HOEMAKER 78 (23W) OUCHARD 79 (23W) HOEMAKER 79 (23W) HOEMAKER 79 (23W) HOEMAKER 70 (23W)	ecast Procedures mings. gnostic Reasoning Messages bical Cyclone Formation Alerts. hificant Tropical Weather Advisories. NAISSANCE AND FIXES eral connaissance Availability hilite Reconnaissance Summary ar Reconnaissance Summary bical Cyclone Fix Data RY OF WESTERN NORTH PACIFIC AND INDIAN OCEAN TROPICAL CYCLONES INDIVIDUAL TROPICAL CYCLONES INDIVIDUAL TROPICAL CYCLONES UTHOR PAGE TROPICAL CYCLONES HULTZ 32 (20W) TS ROGER COVIL 38 (21W) TD 21W HOEMAKER 46 (22W) TY SARAH ICKLE 50 (23W) TS TIP EFFRIES 52 (24W) TS VERA OUCHARD 56 (25W) TY WAYNE EFFRIES 52 (24W) TS VERA OUCHARD 56 (25W) TY BRIAN RITTENDEN 70 (28W) TY DAN HOEMAKER 74 (29W) TY GAY HOMPSON 78 (30W) STY ELSIE EFFRIES 84 (31W) TY FORREST OUCHARD 86 (32W) TY GAY OUCHARD 92 (33W) TY HUNT RITTENDEN 98 (34W) STY IRMA HOEMAKER 102 (35W) TD 35W HOEMAKER 102 (35W) TD 35W HOMPSON 106 (36W) TY JACK EFFRIES 108	INDIAN OCEAN TROPICAL CYCLONES

	3.3	North Indian Ocea	n Tropical (Cyclones		186
		INDIVID	UAL TRO	PICAL CYCLO	ONES	
		TROPICAL	CYCLONE	<u>AUTHOR</u>	PAGE	
		TC 0 TC 0 TC 3	1B 2A 2W (GAY)	GURAL BOUCHARD CRITTENDEN	188 190 166	
4.		MMARY OF SOUT JTH INDIAN OCE			IES	193
	4.1 4.2	General South Pacific and	South India	n Ocean Tropic	al Cyclones	193 193
5.	SUI	MMARY OF FORE	CAST VER	RIFICATION		199
	5.2	Annual Forecast V Comparison of Ob Testing and Result	jective Tecl	nniques		213
6.	NO	ARL TROPICAL C	YCLONE	SUPPORT SUM	MMARY	221
7.	TRO TR	OPICAL CYCLON ACK AND FIX DA	E WARNIN	G STATISTIC	S,	223
	7.1 7.2	General Warning Verification	on Statistic			223
AI AI	PPEN PPEN	NDIX A - Definition IDIX B - Names for IDIX C - Reference IDIX D - Past Annu	Tropical C	cyclones		251 252

CONTRACTIONS

AB	Air Base	CINCPAC	Commander-in-Chief Pacific AF - Air Force, FLT - Navy	GOES	Geostationary Operational Environmental Satellite	
ABIO	Significant Tropical Weather Advisory for the	CLD	Cloud	HATTRACK	Hurricane and Typhoon	
	Indian Ocean	CLIM	Climatology		Tracking and Steering Program	
ABPW	Significant Tropical Weather Advisory for the Western Pacific Ocean	CLIP or CLIPER	Climatology and Persistence Technique	НРАС	Mean of XTRP and CLIM Techniques (Half Persistence and Climatology)	
ACFT	Aircraft	CM	Centimeter(s)	HR	Hour(s)	
ADP	Automated Data Processing	CNOC	Commander Naval	ICAO	International Civil Aviation	
AFB	Air Force Base	CNOC	Oceanography Command	10110	Organization	
AFGWC	Air Force Global Weather	COSM or	Caralana Obiantina Stantina	INIT	Initial	
	Central	COSMOS	Cyclops Objective Steering Model Output Statistics	INST	Instruction	
AIREP	Aircraft (Weather) Report (Commercial and Military)	CPA	Closest Point of Approach	IR	Infrared	
AMOS	Automatic Meteorological	CPHC	Central Pacific Hurricane Center	KM	Kilometer(s)	
	Observing Station			KT	Knot(s)	
AOR	Area of Responsibility	CSC	Cloud System Center	LAN	Local Area Network	
APT	Automatic Picture Transmission	CSUM	Colorado State University Model	LLCC	Low-Level Circulation Center	
ARGOS	International Service for Drifting Buoys	CYCLOPS	Tropical Cyclone Steering Program (HATTRACK and MOHATT)	LUT	Local User's Terminal	
ATCF	Automated Tropical Cyclone	DDM	Defense Data Network	LVL	Level	
	Forecast System	DDN		M	Meter(s)	
ATCM	Advanced Tropical Cyclone Model	DEG	Degree(s)	MAX	Maximum	
AUTODIN	Automated Digital Network	DFS	Digital Facsimile System	MB	Millibar(s)	
AWDS	Automated Weather	DMSP	Defense Meteorological Satellite Program	MET	Meteorological	
	Distribution System	DSAT	Digital Satellite Acquitition	MIN	Minimum	
AWN	Automated Weather Network		System	MM	Millimeter(s)	
BT LAT	Best Track Latitude	DSN	Defense Switched Network	МОНАТТ	Modified HATTRACK	
		DTG	Date Time Group	MOVG	Moving	
BT LON	Best Track Longitude	DWIPS	Digital Weather Image		<u> </u>	
BT WN	Best Track Wind		Processing System	MSLP	Minimum Sea-level Pressure	
CCWF	Combined Confidence Wieghted Forecast	FI	Forecast Intensity (Dvorak) Fleet Numerical	NARDAC	Naval Regional Data Automation Center	
CDO	Central Dense Overcast	FNOC	Oceanography Center	MAG		
CI	Cirriform Cloud or Cirrus (or)	FT	Feet	NAS NEDN	Naval Environmental Data	
	Current Intensity (Dvorak)	GMT	Greenwich Mean Time	MEDIA	Naval Environmental Data Network	

NEDS	Naval Environmental Display Station	PACDIGS	Pacific Digital Information Graphics System	TOGA	Tropical Ocean Global Atmosphere
NEPRF	Naval Environmental Prediction Research	PACMEDS	Pacific Meteorological Data System	TS	Tropical Storm
NESDIS	Facility National Environmental	PACOM	Pacific Command	TUTT	Tropical Upper-Tropospheric Trough
1,20210	Satellite, Data, and Information Service	PCN	Position Code Number	TY	Typhoon
MEGN		PDN	Public Data Network		
NESN	Naval Environmental Satellite Network	PIREP	Pilot Weather Report(s)	TYAN	Typhoon Analog (Program)
NM	Nautical Mile(s)	POS ER	(Initial) Position Error	TYMNET	Time-Sharing Network: Commercial wide area network connecting micro-
NOAA	National Oceanic and	RADOB	Radar Observation		and mainframe computers
	Atmospheric Administration	RECON	Reconnaissance	ULAC	Upper-Level Anticyclone
NOARL	Naval Oceanographic and Atmospheric Research	RRDB	Reference Roster Data Base	ULCC	Upper-Level Circulation Center
	Laboratory	RSDB	Raw Satellite Data Base	USAF	United States Air Force
NOCC	Naval Oceanography	SAT	Satellite		
	Command Center	SEC	Second	USN	United States Navy
NODDES	Naval Environmental Data Network Oceanographic Data	SDHS	Satellite Data Handling	VIS	Visual
	Distribution and Expansion System		System	WESTPAC	Western (North) Pacific
NODDS	Navy/NOAA Oceanographic	SFC	Surface	WMO	World Meteorological Organization
NODDS	Data Distribution System	SGDB	Satellite Global Data Base	WRNG	_
NOGAPS	Navy Operational Global	SLP	Sea-Level Pressure		Warning(s)
	Atmospheric Prediction System	SSM/I	Special Sensor Microwave/	WW ER	Wind Warning Error
NRPS or			Imager	W#	Warning Number
NORAPS	Navy Operational Regional Atmospheric Prediction	SST	Sea Surface Temperature	XTRP	Extrapolation
	System	STNRY	Stationary	Z	Zulu Time (Greenwich Mean Time)
NSDS	Naval Satellite Display System	ST	Subtropical	24 ER	24-Hour (Position) Error
Mapa a	•	STR	Subtropical Ridge		
NSDS-G	Naval Satellite Display System - Geostationary	STY	Super Typhoon	48 ER	48-Hour (Position) Error
NWOC	Naval Western	TAPT	Typhoon Acceleration	72 ER	72-Hour (Position) Error
	Oceanography Center		Prediction Technique	24 WE	24-Hour Wind (Warning) Error
NWS	National Weather Service	TC	Tropical Cyclone	48 WE	48-Hour Wind (Warning)
NR	Number	TCFA	Tropical Cyclone Formation Alert	40 W B	Error
NRL	Naval Research Laboratory	mp.		72 WE	72-Hour Wind (Warning)
OBS	Observations	TD	Tropical Depression		Ептог
ONR	Office of Naval Research	TDA	Typhoon Duty Assistant		
ОТСМ	One Way (Interactive)	TDO	Typhoon Duty Officer		
010111	Tropical Cyclone Model	TIROS	Television Infrared Observational Satellite		

Intentionally left blank.

1. OPERATIONAL PROCEDURES

1.1 GENERAL

The Joint Typhoon Warning Center (JTWC) provides a variety of routine products and services to the organizations within its area of responsibility, including:

- 1.1.1 SIGNIFICANT TROPICAL WEATHER ADVISORIES Issued daily, to describe all tropical disturbances and their potential for further development during the advisory period.
- 1.1.2 TROPICAL CYCLONE FORMATION ALERTS Issued when synoptic or satellite data indicate the development of a tropical cyclone is likely within 24 hours in a specified area.
- 1.1.3 TROPICAL CYCLONE/ TROPICAL DEPRESSION WARNINGS Issued periodically throughout each day to provide forecasts of position, intensity, and wind distribution for tropical cyclones in JTWC's area of responsibility (AOR).
- 1.1.4 PROGNOSTIC REASONING MES-SAGES Issued with each warning for tropical depressions, tropical storms, typhoons and super typhoons in the western North Pacific to discuss the rationale for JTWC's warnings.
- 1.1.5 PRODUCT CHANGES The contents and availability of the above JTWC products are stipulated in USCINCPACINST 3140.1 (series). Changes to USCINCPACINST 3140.1T and JTWC products and services are proposed and discussed at the Annual Tropical Cyclone Conference. Significant changes this year to the warning system include: a new list of tropical cyclone names for the western North Pacific, Tropical Depression Warnings, inclusion of 30-kt wind radii at 48- and 72-hour forecast periods, and changing the message identifiers for the Prognostic Reasoning Messages and the Significant Tropical Weather Advisories.

1.2 DATA SOURCES

- 1.2.1 COMPUTER PRODUCTS Numerical and statistical guidance are available from the USN Fleet Numerical Oceanography Center (FNOC) at Monterey, California. products along with selected ones from the National Meteorological Center (NMC) are received through the Naval Environmental Data Network (NEDN), the Naval Environmental Satellite Network (NESN), and by microcomputer dial-up connections using military and commercial telephone lines. Numerical guidance is also received from Air Force Global Weather Center (AFGWC) at Omaha, Nebraska via the Pacific Digital Information Graphics System (PACDIGS), and from indigenous sources within our AOR.
- 1.2.2 CONVENTIONAL DATA These data sets are comprised of land and shipboard surface observations, and enroute meteorological observations from commercial and military aircraft (AIREPS) recorded within six hours of synoptic times, and cloud-motion winds derived from satellite data. conventional data is hand- and computerplotted, and hand-analyzed in the tropics for the surface/gradient and 200 mb levels. These analyses are prepared twice daily from 0000Z and 1200Z synoptic data. Also, FNOC supplies JTWC with computer generated analyses and prognoses, from 0000Z and 1200Z synoptic data, at the surface, 850 mb, 700 mb, 500 mb, 400 mb, 200 mb levels, and deep layer mean winds.
- 1.2.3 SATELLITE RECONNAISSANCE Meteorological satellite imagery recorded at USAF/USN ground sites and USN ships supply day and night coverage in JTWC's area of responsibility. Interpretation of these satellite data provides tropical cyclone positions and estimates of current and forecast intensities (Dvorak, 1984). A USAF tactical satellite site

and Air Force Global Weather Central currently receive and analyze special sensor microwave/imager (SSM/I) data to provide estimates of 30-knot wind radii near tropical cyclones. Use of satellite reconnaissance is discussed further in section 2. Reconnaissance and Fixes.

1.2.4 RADAR RECONNAISSANCE — Landbased radar observations are used to position tropical cyclones. Once a well-defined tropical cyclone moves within the range of land-based radar sites, their reports are invaluable for determination of movement. Use of radar reports during 1989 is discussed in section 2. Reconnaissance and Fixes.

1.2.5 DRIFTING METEOROLOGICAL BUOYS — In 1989, no drifting meteorological buoys were specifically deployed in the western North Pacific for tropical cyclone warning support. Five of the nine buoys from the 1988 deployment and one from the 1987 deployment continued operations into 1989. Buoys provided data as Tropical Storm Winona (01W) and Typhoon Brenda (03W) crossed the Philippine Sea, but by late May the last buoy ceased operation. In 1989 Commander, Naval Oceanography Command put into action the NAVOCEANCOM Integrated Drifting Buoy Plan 1989-1994 to provide mini-drifter buoys to meet USCINCPACFLT requirements including tropical cyclone warning support.

JTWC acquires drifting buoy data directly through its Local User Terminal (LUT). The buoys transmit data to the TIROS-N polar orbiting satellites, which in turn relay the data to JTWC's LUT. Additionally, the data stored aboard the satellite are recovered via Service ARGOS and NOAA/NESDIS. NOAA/NESDIS processes and distributes the meteorological data to users via the National Meteorological Center (NMC) and the Automated Weather Network (AWN).

1.2.6 AUTOMATIC WEATHER OBSERVING STATIONS—Through a cooperative effort between Naval Oceanography Command and NOAA, the first of two HANDAR stations in the Mariana Islands was installed on Saipan in 1986. The second installation followed the next year on Rota. HANDAR data are received at **JTWC** through the Airfield Fixed Telecommunications Network (AFTN) and the AWN. Now, with the cooperation of NOAA, the Department of the Interior, and the Naval Oceanography Command, a network of 20 Automated Meteorological Observing Stations (AMOS) is planned to be completed throughout Micronesia by 1993. In 1988, the first AMOS site was installed at Faraulep Island (WMO 52005) in the central Carolines. In 1989, two more AMOS started operations at Ujae and Enewetak in the Marshall Islands. JTWC receives AMOS data from all sites via the AWN. In addition, data from the Faraulep site

Table 1-1.	1-1. AUTOMATIC WEATHER OBSERVING STATIONS SUMMARY					
Site Saipan Rota Faraulep Ujae Enewetak		Callsign 15D151D2 15D16448 FARP2/52005 UJAP2 ENIP2			Installed 1986 1987 1988 1989 1989	
** Automated Remote Collection system (via GOES West) *** Coastal-Marine Automated Network (via GOES West)						

can be received real time via service ARGOS. Summary of current AMOS appears in Table 1.1.

1.3 COMMUNICATIONS

Primary communications support is provided by the Naval Telecommunications Center (NTCC), Nimitz Hill, a component of the Naval Communications Area Master Station, Western Pacific (NAVCAMS WESTPAC). JTWC uses the following communications systems:

- 1.3.1 AUTOMATED DIGITAL NETWORK (AUTODIN) AUTODIN is used for dissemination of warnings, alerts and other related bulletins to DOD and other US Government installations. These messages are relayed for further transmission over Navy Fleet Broadcasts, and Coast Guard CW (continuous wave Morse Code) and voice broadcasts. AUTODIN messages can be relayed to commercial telecommunications for delivery to non-DOD users. Inbound message traffic for JTWC is received via AUTODIN addressed to NAVOCEANCOMCEN GQ//JTWC// or DET 1 1WW NIMITZ HILL GQ//CC//.
- 1.3.2 AUTOMATED WEATHER NETWORK (AWN) — The AWN provides weather data over the Pacific Meteorological Data System (PACMEDS). Operational at JTWC since April 1988, the PACMEDS allows Pacific-Theater agencies to receive weather information at 1200 baud. Early in 1989, JTWC also became the first Pacific unit to use the AWNCOM/WINDS software and a microcomputer to send and receive data via the PACMEDS. The system will eventually provide effective storage and manipulation of the large volume of meteorological reports available from throughout JTWC's vast AOR. Through the AWN, JTWC has limited access to data available on the Global Telecommunications System (GTS).
- 1.3.3 DEFENSE SWITCHED NETWORK (DSN) DSN, formerly AUTOVON, is a

- world-wide general purpose switched telecommunications network for the Department of Defense. The network provides a rapid and vital voice link for JTWC to communicate tropical cyclone information to DOD installations. The DSN telephone numbers for JTWC are 344-4224 or 321-2345.
- 1.3.4 NAVAL ENVIRONMENTAL DATA NETWORK (NEDN) The NEDN is the primary link to FNOC to obtain computer generated analyses and prognoses. It is also a backup communication line for requesting and receiving the objective tropical cyclone forecast aids from FNOC's mainframe computers. The NEDN allows JTWC to communicate directly to the other Naval Oceanography Command Centers around the world.
- 1.3.5 PUBLIC DATA NETWORK (PDN) A commercial packet switching network that provides low-speed interactive transmission to users of FNOC products. The PDN is now the primary method for JTWC to request and receive FNOC produced objective tropical cyclone forecast aids. The PDN allows direct access of FNOC products via the Automated Tropical Cyclone Forecast (ATCF) system. The PDN also serves as an alternate method of obtaining FNOC analyses and forecast fields. TYMNET is the contractor providing PDN services to FNOC.
- 1.3.6 DEFENSE DATA NETWORK (DDN)—The DDN is a DOD computer communications network utilized to exchange data files. Because the DDN has links, or gateways, to non-military information networks, it is primarily used to exchange data with the research community.
- 1.3.7 TELEPHONE FACSIMILE (TELEFAX) TELEFAX provides the capability to rapidly scan and transmit, or receive, documents over commercial telephone lines or DSN. TELEFAX is used to disseminate tropical cyclone advisories and warnings to key agencies on Guam and, in special situations, the other Micronesian Islands. Inbound documents

for JTWC are received via commercial telephone at (671) 477-6186. If inbound through DSN, the Guam DSN operator 322-1110 can transfer the call to the commercial number 477-6186.

- 1.3.8 NAVAL ENVIRONMENTAL SATELLITE NETWORK (NESN) The NESN's primary function is to pass satellite data from the satellite global data base at FNOC to regional centers. Similarly, it can pass satellite data from NOCC/JTWC to FNOC or other regional centers. Also, it provides a limited back-up for the NEDN.
- 1.3.9 AIRFIELD FIXED TELECOMMUNICATIONS NETWORK (AFTN) AFTN was installed at JTWC in January 1990. Though AFTN is primarily for the exchange of aviation information; weather information and warnings are also distributed via this network. AFTN also provides point-to-point communication with other warning agencies. JTWC's AFTN identifier is PGUMYMYT.
- 1.3.10 LOCAL USER'S TERMINAL (LUT) JTWC uses a LUT, provided by the Naval Oceanographic Office, as the primary means of receiving real-time data from drifting meteorological buoys and some of the Micronesia AMOS via the polar orbiting NOAA satellites.

1.4 DATA DISPLAYS

Equipment maintenance is provided by the Equipment Support Department of the Naval Oceanography Command Center, Guam.

1.4.1 NAVAL ENVIRONMENTAL DISPLAY STATION (NEDS) — The NEDS receives, processes, stores, displays and prints copies of FNOC environmental products. It drives the fleet facsimile broadcast and can also be used to generate the requests for objective tropical cyclone forecast techniques.

- 1.4.2 AUTOMATED TROPICAL CYCLONE FORECAST SYSTEM (ATCF) — The ATCF has decreased message preparation time and reduced the number of corrections to JTWC's alerts and warnings. In 1989 for the first time, the ATCF automatically computed the myriad of statistics calculated by JTWC. Links were established through a Local Area Network (LAN) to the NOCC Operations watch team to facilitate the generation of Tropical Cyclone Warning graphics for the Fleet Facsimile Broadcasts and their local metwatch and warning products for Micronesia. A module permits satellite reconnaissance fixes to be input from Det 1, 1WW into the LAN. Several other modules are still under development including: direct links to NTCC, the LUT, and AWNCOM.
- 1.4.3 PACIFIC DIGITAL INFORMATION GRAPHICS SYSTEM (PACDIGS) The PACDIGS is a communications circuit that was expanded to include JTWC in 1988. Air Force Global Weather Central (AFGWC) at Omaha, Nebraska provides a standard set of numerical products to the PACDIGS circuit which can be used for additional evaluation in the development of tropical cyclone warnings.
- 1.4.4 NAVAL SATELLITE DISPLAY SYSTEM (NSDS) The NSDS functions as a display of FNOC stored Defense Meteorological Satellite Program (DMSP) imagery and low resolution geostationary imagery. It is the primary means for JTWC to observe the Indian Ocean.
- 1.4.5 NAVAL SATELLITE DISPLAY SYSTEM-GEOSTATIONARY(NSDS-G) The NSDS-G is the primary system used to process high resolution geostationary imagery for tropical cyclone positioning and intensity estimates for the western Pacific Ocean. Its built-in sectorizer allows monitoring of numerous cyclones or suspect areas on a small enough scale to expand and evaluate the data effectively.

1.5 ANALYSES

The JTWC Typhoon Duty Officer (TDO) routinely does manual streamline analyses of composite surface/gradient-level (3000 ft (914 m)) and Upper-tropospheric (centered on the 200 mb level) data for 0000Z and 1200Z each day. Manual sea-level pressure analyses concentrating on the mid-latitudes are available from the NOCC Operations watch team. Computer analyses of the surface, 850, 700, 500, 400, and 200 mb levels, deep layer mean winds, and frontal boundaries are available from the 0000Z and 1200Z FNOC data bases. Additional sectional charts at intermediate synoptic times and auxiliary charts, such as station-time plot diagrams and pressure-change charts, are analyzed during periods of significant tropical cyclone activity.

1.6 FORECAST PROCEDURES

- 1.6.1 INITIAL POSITIONING The warning position is the best estimate of the center of the surface circulation at synoptic time. It is estimated from an analysis of all fix information received from one hour before to one and onehalf hours after synoptic time. The analysis is aided by a computer-generated objective best track scheme that weights fix information based on its statistical accuracy. The TDO includes synoptic observations and other information to adjust the position, testing consistency with the past direction, speed of movement and the influence of the different scales of motions. If the fix data are not available due to reconnaissance platform malfunction or communication problems, or are considered unrepresentative, synoptic data and/or extrapolation from previous fixes are used.
- 1.6.2 TRACK FORECASTING A preliminary forecast track is developed based on an evaluation of the rationale behind the previous warning and the guidance given by the most recent set of objective techniques (see 5.2), numerical prognoses, recent movement, satellite animation, and other objective and empirical

techniques. This preliminary track is then subjectively modified based on the following considerations:

- 1.6.2.1 The prospects for recurvature or erratic movement are evaluated. This determination is based primarily on the present and forecast positions and amplitudes of the middle-tropospheric, mid-latitude troughs and ridges as depicted on the latest upper-air analyses and numerical forecasts.
- 1.6.2.2 Determination of the best steering level is partly influenced by the maturity and vertical extent of the tropical cyclone. Shallow or sheared systems would be steered by the lower tropospheric flow, whereas deep or mature cyclones would be affected by mid-level or deep-layer steering. For mature tropical cyclones located south of the subtropical ridge axis, forecast changes in speed of movement are closely correlated with anticipated changes in the intensity or relative position of the ridge. When steering currents are relatively weak, the tendency for tropical cyclones to move northward due to internal forces are considered. North of the subtropical ridge the polar westerlies and shortwaves greatly affect tropical cyclone steering and intensity.
- 1.6.2.3 Over the 12- to 72-hour (12- to 48-hour in the Southern Hemisphere) forecast period, speed of movement during the early forecast period is usually biased towards persistence, while the later forecast periods are biased towards objective techniques. When a tropical cyclone moves poleward, and toward the midlatitude steering currents, speed of movement becomes increasingly more biased toward a selective group of objective techniques capable of estimating acceleration.
- 1.6.2.4 The proximity of the tropical cyclone to other tropical cyclones is closely evaluated to determine if there is a possibility of interaction. If the proximity is less than 900 nm (1665 km), binary interaction tracking techniques are considered.

A final check is made against climatology to determine if the forecast track is reasonable. If the forecast deviates greatly from one of the climatological tracks, the forecast rationale is reevaluated.

1.6.3 INTENSITY FORECASTING — Heavy reliance is placed on the empirically derived Dvorak (1984) technique for forecasting tropical cyclone intensity. Other techniques used for forecasting intensity are extrapolation of synoptic wind and pressure data and climatology. An evaluation of the entire synoptic situation is made, including the location of major troughs and ridges, the position and intensity of the Tropical Upper-Tropospheric Trough (TUTT), if present. The vertical and horizontal extent of the tropical cyclone's cyclonic circulation, and the extent of the associated upper-level outflow patterns are considered. Animated satellite data plays a key role in the evaluation of intensification potential. Each intensity forecast is affected by the accompanying forecast track and environmental influences along that track; such as, terrain, vertical wind shear and extratropical weather features. JTWC also incorporates a new interactive climatology scheme to help determine intensity forecasts.

1.6.4 WIND-RADII FORECASTING — JTWC uses a wind profile and steering diagnostic developed by Major J. Martin and Dr. G. J. Holland (Office of Naval Research contractor). The technique adapts an earlier work (Holland, 1980) and specifically addresses the need for realistic 30-, 50- and 100-kt wind radii around tropical cyclones. It solves equations for basic gradient wind relations within the tropical cyclone area, using input parameters obtained from enhanced infrared satellite imagery. The diagnosis also addresses asymmetric areas of winds caused by tropical cyclone movement. Size and intensity parameters are used to diagnose internal steering components of tropical cyclone motion known collectively as "beta-drift".

1.6.5 EXTRATROPICAL TRANSITION — When a tropical cyclone is forecast to become an extratropical system, JTWC coordinates the transfer of warning responsibility with the appropriate Naval Oceanography Command Regional Center, which assumes warning responsibilities for the extratropical system.

1.6.6 TRANSFER OF WARNING RESPON-SIBILITIES — JTWC coordinates the transfer of tropical warning responsibility for tropical cyclones entering or exiting its AOR. For tropical cyclones crossing the dateline in the North Pacific Ocean, JTWC coordinates with the Central Pacific Hurricane Center (CPHC), Honolulu via the Naval Western Oceanography Center (NWOC), Pearl Harbor. For the South Pacific Ocean, JTWC coordinates with NWOC.

In the event JTWC should become incapacitated, the Alternate Joint Typhoon Warning Center (AJTWC), co-located with NWOC, assumes JTWC's functions.

1.7 WARNINGS

JTWC issues two types of warnings: Tropical Cyclone Warnings and Tropical Depression Warnings.

Tropical Cyclone Warnings are issued when a closed circulation is evident and maximum sustained winds are forecast to reach 34 kt (18 m/sec) within 48 hours, or when the tropical cyclone is in such a position that life or property may be endangered within 72 hours.

Each Tropical Cyclone Warning is numbered sequentially and includes the following information: the current position of the surface center; estimate of the position accuracy and the supporting reconnaissance (fix) platforms; the direction and speed of movement during the past six hours (past 12 hours in the Southern Hemisphere); and the intensity and radial extent of over 30-, 50-, and 100-kt surface winds, when applicable. At

forecast intervals of 12, 24, 48, and 72 hours (12, 24, and 48 hours in the Southern Hemisphere), information on the tropical cyclone's anticipated position, intensity and wind radii is provided. In addition, vectors indicating the mean direction and mean speed between forecast positions are included in all warnings.

Warnings in the western North Pacific and North Indian Oceans are issued every six hours valid at standard times: 0000Z, 0600Z, 1200Z and 1800Z (every 12 hours: 0000Z, 1200Z or 0600Z, 1800Z in the Southern Hemisphere). All warnings are released to the communications network no earlier than synoptic time and no later than synoptic time plus two and one-half hours, so that recipients are assured of having all warnings in hand by synoptic time plus three hours (0300Z, 0900Z, 1500Z and 2100Z).

Tropical Depression Warnings are issued only for western North Pacific tropical depressions that are not expected to reach the criteria for Tropical Cyclone Warnings, as mentioned above. The depression warning contains the same information as a Tropical Cyclone Warning except the Tropical Depression Warning is issued every 12 hours at standard synoptic times and extends only to the 36-hour forecast period.

Both Tropical Cyclone and Tropical Depression Warning forecast positions are later verified against the corresponding best track positions (obtained during detailed post-storm analyses) to determine the most probable path and intensity of the cyclone. A summary of the verification results for 1989 is presented in section 5. Summary of Forecast Verification.

1.8 PROGNOSTIC REASONING MESSAGES

These plain language messages provide meteorologists with the rationale for the forecasts for tropical cyclones in the western North Pacific Ocean. It also discusses alternate forecast scenarios. Prognostic reasoning

messages are prepared to complement each warning. In addition to this message, prognostic reasoning information is provided in the remarks section of warnings when significant forecast changes are made or when deemed appropriate by the TDO.

1.9 TROPICAL CYCLONE FORMATION ALERTS

Tropical Cyclone Formation Alerts are issued whenever interpretation of satellite imagery and other meteorological data indicates that the formation of a significant tropical cyclone is likely. These alerts will specify a valid period not to exceed 24 hours and must either be canceled, reissued, or superseded by a warning prior to expiration.

1.10 SIGNIFICANT TROPICAL WEATHER ADVISORIES

This product contains a description of all tropical disturbances in JTWC's area of responsibility (AOR) and their potential for further (tropical cyclone) development. In addition, all tropical cyclones in warning status are briefly discussed.

Two separate messages are issued daily and each is valid for a 24-hour period. The Significant Tropical Weather Advisory for the Western Pacific Ocean (ABPW10 PGTW) covers the area east of 100° east longitude to the dateline and is issued by 0600Z. Significant Tropical Weather Advisory for the Indian Ocean (ABIO10 PGTW) covers the area west of 100° east longitude to the coast of Africa and is issued by 1800Z. These are reissued whenever the situation warrants. For each suspect area, the words "poor", "fair", or "good" are used to describe the potential for development. "Poor" will be used to describe a tropical disturbance in which the meteorological conditions are currently unfavorable for development. "Fair" will be used to describe a tropical disturbance in which the meteorological conditions are favorable for development, but significant development has not commenced.

"Good" will be used to describe the potential for development of a disturbance covered by an alert.

2. RECONNAISSANCE AND FIXES

2.1 GENERAL

The Joint Typhoon Warning Center depends on reconnaissance to provide necessary, accurate, and timely meteorological information in support of advisories, alerts and warnings. JTWC relies primarily on two reconnaissance platforms: satellite and radar. In data rich areas, synoptic data are also used to supplement the above. As in past years, the optimum use of all available reconnaissance resources to support JTWC's products remains a primary concern. The weighing of the specific capabilities and limitations of each reconnaissance platform, and the tropical cyclone's threat to life and property both afloat and ashore, continue to be an important part of careful product preparation.

2.2 RECONNAISSANCE AVAILABILITY

- 2.2.1 SATELLITE Fixes from Air Force/Navy ground sites and Navy ships provide day and night coverage in JTWC's area of responsibility. Interpretation of this satellite imagery yields tropical cyclone positions and estimates of current and forecast intensities through the Dvorak technique. A new capability provided by the Special Sensor Microwave/Imager (SSM/I) data is used to determine the extent of the 30-kt winds around the tropical cyclone and to aid in tropical cyclone positioning.
- 2.2.2 RADAR Land-based radar remotely senses and maps precipitation within tropical cyclones in the proximity (usually within 175 nm (325 km) of radar sites in the Republic of the Philippines, Taiwan, Hong Kong, Japan, South Korea, Kwajalein and Guam. The next radar upgrade will be the arrival of the next generation Doppler radars in the early 1990's.
- 2.2.3 SYNOPTIC JTWC also determines tropical cyclone positions based on the analysis

of the surface/gradient-level synoptic data. These positions are an important supplement to fixes provided by remote sensing platforms and become invaluable in situations where neither satellite nor radar fixes are available.

2.3 SATELLITE RECONNAISSANCE SUMMARY

The Air Force provides satellite reconnaissance support to JTWC through the DMSP Tropical Cyclone Reporting Network (DMSP Network), which consists of tactical sites and a centralized facility. Tactical DMSP sites monitoring DMSP, NOAA geostationary satellite data are located at Nimitz Hill, Guam; Clark AB, Republic of the Philippines; Kadena AB, Okinawa, Japan; Osan AB, Republic of Korea; and Hickam AFB, Hawaii. These sites provide a combined coverage that includes most of JTWC's area of responsibility in the western North Pacific, from near the date line westward to the Malay Peninsula. For the remainder of its AOR. JTWC relies on the AFGWC to provide coverage using stored satellite data. The Naval Oceanography Command Detachment, Diego Garcia, furnishes interpretation of NOAA polar orbiting coverage in the central Indian Ocean and USN ships equipped for direct satellite readout contribute supplementary support. Additionally, civilian contractors with the U.S. Army at Kwajalein Atoll provide satellite and radar information on tropical cyclones that develop in the Marshall Islands to supplement Det 1, 1WW's satellite coverage. An additional source of satellite data is DMSP satellite mosaics available from the Fleet Numerical Oceanography Center via the NEDN and NESN lines. This valuable data is used to metwatch the areas not in the DMSP tactical site satellite coverage and provides forecasters the capability to monitor tropical cyclones that AFGWC satellite analysts are fixing.

In addition to polar orbiter imagery, Det 1, 1 WW uses geostationary imagery to support the reconnaissance mission. Low resolution imagery is received through animation loopers at the DMSP tactical sites. The animation of these images is invaluable in depicting systems in their formative stages and determining coarse motion vectors. Animation is also valuable in assessing environmental changes affecting tropical cyclone behavior. In addition to this capability, Det 1, 1WW is able to receive high resolution digital geostationary data through the Naval Satellite Dissemination System-Geostationary (NSDS-G) which is the primary source of geostationary data used for positioning and intensity analyses.

AFGWC is the centralized member of the DMSP network. In support of JTWC, AFGWC processes stored imagery from DMSP and NOAA spacecraft. Stored imagery is recorded onboard the spacecraft as they pass over the earth and is later down-linked to AFGWC via a network of command readout sites and communication satellites. This enables AFGWC to obtain the coverage necessary to fix all tropical cyclones within JTWC's AOR. AFGWC has the primary responsibility to provide tropical cyclone reconnaissance over the entire Indian Ocean. southwest Pacific, and the area near the dateline in the western North Pacific Ocean. Additionally, AFGWC can be tasked to provide tropical cyclone support in the western North Pacific as backup to coverage routinely available in that region.

The hub of the DMSP network is Det 1, 1WW, colocated with JTWC at Nimitz Hill, Guam. Based on available satellite coverage, Det 1, 1WW is responsible for coordinating satellite reconnaissance requirements with JTWC and tasking the individual network sites for the necessary tropical cyclone fixes, current intensity estimates and forecast intensities. When a particular satellite pass is selected to support the development of JTWC's next tropical cyclone warning, two sites are tasked to fix the tropical cyclone from the same pass.

This "dual-site" concept provides the necessary redundancy that virtually guarantees JTWC a satellite fix to support each warning.

The network provides JTWC with several products and services. The main service is one of monitoring the AOR for indications of tropical cyclone development. If development is detected, JTWC is notified. Once JTWC issues either a Tropical Cyclone Formation Alert or warning, the network provides three products: tropical cyclone positions, current intensity estimates and forecast intensities. Each satellite tropical cyclone position is assigned a Position Code Number (PCN), which is a measure of positioning confidence. The PCN is determined by the combination of availability of visible landmarks in the image that can be used as references for precise gridding and the degree of organization of the tropical cyclone's cloud system (Table 2-1).

Det 1, 1 WW provides two estimates of the tropical cyclone's current intensity per day once JTWC is in alert status and four estimates when in warning status. Current intensity estimates and 24-hour intensity forecasts are made using the Dvorak technique (NOAA Technical Report NESDIS 11) for both visual and enhanced infrared imagery (Figure 2-1). The enhanced infrared technique is preferred due to its increased objectivity and accuracy, however, the visual technique is used to supplement this information during the daylight hours. For subtropical cyclones, intensity estimates are made using the Hebert and Poteat technique (NOAA Technical Memorandum NWS SR-83, 1975).


TABLE 2-1 POSITION CODE NUMBERS (PCN)

PCN METHOD FOR CENTER DETERMINATION/GRIDDING

- 1 EYE/GEOGRAPHY
- 2 EYE/EPHEMERIS
- 3 WELL DEFINED CIRCULATION CENTER/GEOGRAPHY
 - WELL DEFINED CIRCULATION CENTER/EPHEMERIS
- 5 POORLY DEFINED CIRCULATION CENTER/GEOGRAPHY
- 6 POORLY DEFINED CIRCULATION CENTER/EPHEMERIS

2.3.1 SATELLLITE PLATFORM SUMMARY Figure 2-2 shows the status of operational polar orbiting spacecraft. Two DMSP spacecraft were operational during 1989. Spacecraft 19543 (F8), which carries the Special Sensor Microwave/Imager (SSM/I), was operational throughout the year. Spacecraft 20542 (F9) was operational throughout the year, despite some thermal channel degradation problems which were corrected in early 1989. The NOAA 10 and NOAA 11 spacecraft performed well throughout the year.

2.3.2 STATISTICAL SUMMARY — During 1989, the DMSP network was the primary input to JTWC for operational warnings and post analysis best tracks in the entire 53 million square mile area of responsibility for the warning center. Almost all the warnings were based on satellite reconnaissance. received a total of 3133 satellite fixes from the DMSP network on 35 tropical cyclones in the western North Pacific Ocean. Of this, 49 percent were from polar orbiters, while 51 percent were from geostationary. With the increased emphasis this year on the early detection of tropical depressions, the DMSP network began fixing storms earlier in their lifecycle and continued fixing them until they weakened below 25 kt or became extratropical. This emphasis contributed significantly to the 50 percent increase in the total number of fixes this year as compared to 1988. In addition, 124 fixes were made on tropical cyclones in the North Indian Ocean and 1625 on cyclones in the Southern Hemisphere. A comparison of those fixes with their corresponding best track positions is shown in Tables 2-2A and 2-2B. For the western North Pacific, the total mean error was comparable to the multi-year average and has essentially remained constant. In addition to the mean errors verses JTWC best track, Figure 2-3 depicts the 90th percentile values, i.e. 90 percent of the fixes fall within these limits, stratified by current intensity. This figure shows that errors decrease as a system becomes more intense. The greatest errors are found in the formative stages, with maximum sustained winds less than 25 kt. In general,



Example: T 3.5 / 4.5+ /W1.5 / 24 HRS

Figure 2-1. Dvorak code for communicating estimates of current and forecast intensity derived from satellite data. In the example, the current "T-number" is 3.5, but the current intensity is 4.5. The cloud system has weakened by 1.5 "T-numbers" since the previous evaluation conducted 24-hours earlier. The plus (+) symbol indicates an expected reversal of the weakening trend or very little further weakening of the tropical cyclone during the next 24-hour period.




Figure 2-2. Polar orbitters for 1989.




Figure 2-3. A stratification of western North Pacific satellite fix errors (90th percentile) and current intensities (Dvorak Tnumbers). For example: for a tropical cyclone with a current intensity of T1.0, 90% of the fixes fell within 105 nm (195 km) of the final best track position.

TABLE 2-2A MEAN DEVIATION (NM) OF ALL SATELLITE DERIVED TROPICAL CYCLONE
POSITIONS FROM JTWC BEST TRACK POSITIONS IN THE
WESTERN NORTH PACIFIC AND NORTH INDIAN OCEANS
(NUMBER OF CASES IN PARENTHESES)

	WESTERN NORTH PA	CIFIC OCEAN	NORTH INDIAN	OCEAN
PCN	1979-1988 AVERAGE	1989 AVERAGE	1980-1988 AVERAGE	1989 AVERAGE
1	14.0 (1698)	11.4 (150)	16.5 (44)	10.7 (20)
2	14.9 (3070)	11.8 (583)	15.2 (13)	12.0 (20)
3	21.0 (2275)	19.2 (140)	24.7 (42)	17.4 (5)
4	21.7 (2441)	19.6 (550)	41.3 (26)	18.4 (13)
5	36.8 (3932)	26.4 (209)	38.2 (343)	28.9 (32)
6	36.1 (6120)	31.7 (1467)	40.3 (481)	31.1 (15)
1&2	14.6 (4768)	11.7 (733)	16.2 (57)	11.3 (40)
3&4	21.3 (4716)	19.6 (690)	31.1 (68)	18.1 (18)
5&6	36.4 (10052)	31.1 (1676)	39.4 (824)	29.6 (47)
1,3&5	27.4 (7905)	19.9 (499)	34.7 (429)	21.5 (57)
2,4&6	27.4 (11631)	24.7 (2600)	39.7 (520)	19.7 (48)
TOTALS:	27.4 (19536)	23.9 (3099)	37.4 (949)	20.7 (105)

	Positions from jtwo best track positions in the Western South Pacific and South Indian Oceans (Number Of Cases in Parentheses)						
	PCN	1985 - 19	88 AVERAGE	1989 A	VERAGE		
	1	16.3	(103)	15.3	(108)		
	2	16.5	(564)	15.3	(240)		
	3	34.8	(125)	20.3	(45)		
	4	27.0	(538)	23.7	(93)		
	5		(548)	30.9	(210)		
	6	37.1	(3651)	33.7	(735)		
	1 & 2	16.5	(667)	15.3	(348)		
	3 & 4	28.5	(663)	22.6	(138)		
	5 & 6	37.6	(4199)	33.1	(945)		
1	, 3 & 5	36.4	(776)	24.9	(363)		
2	, 4 & 6	33.5	(4753)	28.7	(1068)		
	TOTALS:	33.9	(5529)	27.7	(1431)		

TABLE 2-3	AS A FUNCI FORECAS	ustained wind sp ion of dvorak cu tintensity num ea-level pressu	URRENT AND SER AND
	TROPICAL CYCLONE	WIND	MSLP
	INTENSITY NUMBER	SPEED	(NW PACIFIC)
	0.0	<25	
	0.5	25	
	1.0	25	
	1.5	25	
	2.0	30	1000
	2.5	35	997
	3.0	45	991
	3.5	55	984
	4.0	65	976
	4.5	77	966
	5.0	90	954
	5.5	102	941
	6.0	115	927
	6.5	127	914
	7.0	140	898
	7.5	155	879
	8.0	170	858

errors become smaller with increasing intensity. The network also provided an additional 345 fixes on tropical disturbances which did not develop into significant tropical cyclones. The standard relationship between tropical cyclone "T-number", maximum sustained surface wind speed (Dvorak, 1984) and minimum sea-level pressure (Atkinson and Holliday, 1977) for the Pacific is shown in Table 2-3.

2.3.3 NEW TECHNIQUES — In the past, one of the biggest challenges in providing satellite reconnaissance to JTWC has been in detecting and tracking low-level circulation centers and low level clouds lines at night. When available, the satellite analyst used the low light visual capability of the DMSP spacecraft. However, during 1989, DMSP network satellite forecasters developed an infrared enhancement for the NOAA spacecraft 3.7 micrometer channel which significantly improves the capability to identify and track exposed or partially exposed low-level circulations and low level cloud lines through the nighttime hours when mid or high cloud do not obscure the low clouds. This enhancement also accentuates the land-sea contrast, highlighting geography which can be used for more precise gridding. This enhancement is now routinely applied to images of tropical cyclones where shearing is either suspected or in progress.

As was mentioned earlier, the SSM/I, mounted on the F8 DMSP spacecraft, was operational most of 1989. Through the majority of the 1989 season, SSM/I technique development support was provided exclusively by analysts in the AFGWC Tropical Section. This support included bulletins describing the extent of 30-kt winds surrounding the tropical cyclone for all systems with maximum sustained winds of 50 kt or greater. Winds can only be obtained in rain-free areas and areas free of deep moisture. If the cloud system center was rain free, analysts provided center/eye positions based on the 85 gigahertz (GHz) microwave channel display. These positions provided a comparison with those made using visual and infrared spectral windows. Multispectral imaging, particularly with the 85 GHz channel which is able to "see through" the cirrus canopy, offers a rich area for development. In October 1989, Det 1, 1 WW obtained a prototype capability to ingest,

TABLE	2-4A
-------	------

1989 NORTHERN HEMISPHERE FIX PLATFORM SUMMARY

WESTERN NORTH PACIFIC	SATELLITE	RADAR	SYNOPTIC	TOTAL
TS WINONA (01W)	78	11	1	90
STY ANDY (02W)	129	50	Ō	180*
TY BRENDA (03W)	96	24	0	120
TY CECIL (04W)	53	6	Ö	59
TY DOT (05W)	116	17	Ö	133
TS ELLIS (06W)	39	2	ĺ	42
TS FAYE (07W)	102	9	ī	111
STY GORDON (08W)	160	24	ō	184
TS HOPE (09W)	109	69	Õ	178
TS IRVING (10W)	, 48	16	Ö	64
TY JUDY (11W)	132	93	Ö	225
TD 12W (12W)	23	6	Ö	29
TS KEN-LOLA (13W-14W)	94	112	4	210
TY MAC (15W)	123	61	1	185
TY OWEN (16W)	104	1	7	112
TY NANCY (17W)	65	ō	o O	65
TS PEGGY (18W)	37	Ō	Ö	37
TD 19W (19W)	43	9	2	54
TS ROGER (20W)	61	98	2	161
TD 21W (21W)	37	0	ī	38
TY SARAH (22W)	140	73	Ō	213
TS TIP (23W)	60	0	Ö	60
TS VERA (24W)	70	62	0	132
TY WAYNE (25W)	54	160	ŏ	214
STY ANGELA (26W)	182	31	Ö	213
TY BRIAN (27W)	57	6	0	63
TY COLLEEN (28W)	108	Ö	0	108
TY DAN (29W)	81	21	1	103
STY ELSIE (30W)	153	15	Ō	168
TY FORREST (31W)	141	7	Ö	148
TY GAY (32W)	38	14	Ö	52
TY HUNT (33W)	127	18	3	148
TY IRMA (34W)	146	0	Õ	146
TD 35W (35W)	30	Ö	3	33
TY JACK (36W)	97	63	0	160
	•	03	· ·	100
TOTALS NWP:	3133	1068	27	4238*
PERCENTAGE OF TOTAL:	73.9%	25.4%	0.7%	100%
NORTH INDIAN OCEAN	SATELLITE	RADAR	SYNOPTIC	TOTAL
TC 01B (01B)	27	0	0	27
TC 02A (02A)	24	0	0	24
TC 32W (32W)	73	0	0	73
(5211)	73	J	U	13
TOTALS NIO:	124	0	0	124
			-	
PERCENTAGE OF TOTAL:	100%	0%	0%	100%

^{*} ONE AIRBORNE RADAR FIX WAS RECEIVED

BLE	2-4B		1989		IC AND SOUTH ATFORM SUMM		n oceans	
	TROP	ICAL	CYCLONES	SATELL	ITE SYN	OPTIC	RADAR	TOTAL
	TC	01S	ADELININA	. 35		0	0	35
	TC	02S	BARISAONA	125		0	0	125
	TC	03\$	ILONA	55		0	5	60
	TC	04P	DILILAH	42		0	0	42
	TC	05P	GINA	20		0	0	20
	TC	06S		34		0	0	34
	TC	07S	EDME	37		0	0	37
	TC	08S	FIRINGA	61		0	0	61
	TC	09S	KIRRILY	68		0	0	68
	TC	10P	HARRY	156		0	0	156
	TC	115	HANITRA	91		0	0	91
	TC	125	GIZELA	32		0	0	32
	TC	13P	IVY	85		0	0	85
	TC	14P		21		0	0	21
	TC	15P	JUDY	29		0	0	29
	TC	16S		16		0	0	16
		178	MARCIA	23		0	0	23
	TC	18S		14		0	0	14
	TC	198	JINABO	66	•	0	0	66
		205	NED	88		0	0	88
		218	KRISSY	80		0	0	80
	TC	22P	KERRY	26		0	0	26
	TC	23P	AIVU	57		0	0	57
		248	LEZISSY	22		0	0	22
		25P	LILI	68		0	Ō	68
		265	ORSON	91		Ō	Ō	91
		27P	MEENA	112		0	Ö	112
		28P	ERNIE	71		Ō	Ö	71
	тот	'AL N	UMBER OF F	IXES: 1625		0	5	1630

process and display the SSM/I data realtime. Current plans are for the prototype system to be upgraded with improved hardware and software. Installation of these new systems is projected for Det 1, 1 WW and for DMSP sites at Clark AB, Kadena AB and Hickam AFB during the summer of 1990.

2.3.4 FUTURE OF SATELLITE RECONNAISSANCE — The future of satellite reconnaissance provides many unique challenges. As the SSM/I imagery becomes available throughout the DMSP network, training must be accomplished quickly to maximize the benefit. At this time, the majority of the emphasis has been placed on the 85 GHz and surface wind information. However, a great deal of unrealized information may lie in the other channels. Several Air Force investigators are examining this potential.

Det 1, 1 WW expects to receive an automated satellite imagery processing and display system designed specifically for the tropical cyclone reconnaissance mission during the 1991-1992 timeframe. The system will process and display polar orbiter and geostationary satellite data. It will have a broad spectrum of satellite data manipulation applications which will significantly enhance Det 1, 1WW support to the reconnaissance mission. In the meantime, Det 1, 1WW is developing its capabilities using a MacIntosh IIxTM computer system which has been programmed to ingest and display polar orbiter and geostationary satellite data.

In addition to SSM/I, the Mark III and Mark IV DMSP ground systems located at the Pacific DMSP sites should be upgraded with the Mark IVB state-of-the-art satellite imagery

ingest and display system during the 1992-93 timeframe. The near future of satellite reconnaissance is becoming more and more dependent on this upgrade, as the current systems become more difficult to support.

2.4 RADAR RECONNAISSANCE SUMMARY

Twenty-eight of the thirty-five significant tropical cyclones in the western North Pacific during 1989 passed within range of land-based radar with sufficient cloud pattern organization to be fixed. The land-based radar fixes that were obtained and transmitted to JTWC totaled 1068 for the Northern Hemisphere and 5 for the Southern Hemisphere. One radar fix was obtained by an aircraft of opportunity.

The WMO radar code defines three categories of accuracy: good (within 10 km (5 nm)), fair (within 10-30 km (5-16 nm)), and poor (within 30-50 km (16-27 nm)). Of the 1073 radar fixes encoded in this manner; 314 were good, 341 were fair, and 418 were poor. Compared to JTWC's best track, the mean

vector deviation for land-based radar sites was 20 nm (37 km). Excellent support from the radar network through timely and accurate radar fix positioning allowed JTWC to track and forecast tropical cyclone movement through even the most difficult erratic tracks.

Five radar reports were received on Southern Hemisphere tropical cyclones; however, as in previous years, no radar reports were received on North Indian Ocean tropical cyclones.

2.5 TROPICAL CYCLONE FIX DATA

A total of 4238 fixes on thirty-five western North Pacific tropical cyclones and 124 fixes on three North Indian Ocean tropical cyclones were received at JTWC. Table 2-4A delineates the number of fixes per platform for each individual tropical cyclone for the western North Pacific and North Indian Oceans. Season totals and percentages are also indicated. Table 2-4B provides similar information for the South Pacific and South Indian Oceans.

3. SUMMARY OF WESTERN NORTH PACIFIC AND NORTH INDIAN OCEAN TROPICAL CYCLONES

3.1 GENERAL

The calendar year 1989 was a very busy year. JTWC issued warnings on a total of 35 tropical depressions, tropical storms and typhoons in the western North Pacific - 5 super typhoons, 16 less intense typhoons, 10 tropical storms and 4 tropical depressions — the most tropical cyclones since 1974 and the most typhoons since 1972. An extensive post analysis indicated that dissipating Ken (13W) and developing Lola (14W) merged into a single system, thus the total of 36 numbered cyclones was revised to 35 (Table 3-1). In any case, this is more than the climatological mean of 31 tropical cyclones in the western North Pacific (Table 3-2). The North Indian Ocean was fairly inactive with only 3 tropical cyclones occurring there — below the 5 per year average. During 1989, warnings were issued on a total of 37* Northern Hemisphere tropical cyclones. A chronology of western North Pacific and North Indian Ocean tropical cyclones is provided in Figure 3-1.

For the year, JTWC was in warning status 154 days compared to 114 in 1988. Again, considering only the western North Pacific, there were 46 days when the Center issued warnings on two cyclones and 9 days

* TC-32W (Gay) counted only once.

when it warned on three cyclones (Table 3-3). When the North Indian Ocean is included, there were a total of 167 days with warnings on one cyclone, 49 days with warnings on two cyclones, and 9 days with warnings on three. There were no days when warnings were issued on four or five tropical cyclones at once. Thus, JTWC was in Northern Hemisphere warning status 40% of the year; it was warning on two or more tropical cyclones during 58 days or 16% of the year.

JTWC issued 710 warnings on 35 western North Pacific tropical cyclones, 147 more than in 1987 and 239 more than last year. In addition, the Center put out 44 warnings on North Indian Ocean tropical cyclones, for a grand total of 754 Northern Hemisphere warnings. There were 51 initial Tropical Cyclone Formation Alerts issued on western North Pacific tropical disturbances (Table 3-4) and 8 on disturbances in the North Indian Ocean. Three out of the 35 significant tropical cyclones that developed in the western North Pacific did so without Formation Alerts. Alerts were issued on all tropical cyclones that formed in the North Indian Ocean. Tropical Cyclone 32W (Gay) was already in warning status when it entered the Bay of Bengal from the Gulf of Thailand.

TABLE 3-1

WESTERN NORTH PACIFIC SIGNIFICANT TROPICAL CYCLONES FOR 1989

			NUMBER OF	MAXIMUM	
			WARNINGS	SURFACE WINDS	ESTIMATED
	CAL CYCLONE	PERIOD OF WARNING	_ISSUED	KT (M/SEC)	MSLP (MB)
(O1W)	TS WINONA	18 JAN - 19 JAN	5	55 (28)	984
(01W)	TS WINONA*	20 JAN - 21 JAN	8	30 (15)	1000
(02W)	STY ANDY	17 APR - 24 APR	26	140 (72)	898
(WEO)	TY BRENDA	15 MAY - 20 MAY	20	75 (39)	967
(04W)	TY CECIL	22 MAY - 24 MAY	9	75 (39)	967
(05W)	TY DOT	05 JUN - 11 JUN	25	100 (51)	944
(06W)	TS ELLIS	20 JUN - 20 JUN	2	25 (13)	1002
(06W)	TS ELLIS*	22 JUN - 23 JUN	4	35 (18)	997
(07W)	TS FAYE	06 JUL - 11 JUL	21	55 (28)	980
(W8O)		11 JUL - 18 JUL	30	135 (69)	898†
(09W)	TS HOPE	16 JUL - 21 JUL	21	55 (28)	984
(10W)	TS IRVING	21 JUL - 24 JUL	14	55 (28)	984
(11W)	TY JUDY	22 JUL - 29 JUL	28	95 (49)	949
(12W)	TD 12W	29 JUL - 30 JUL	3	30 (15)	1000
(13W-14W)	TS KEN-LOLA	30 JUL - 04 AUG	23	50 (26)	982†
(15W)	TY MAC	01 AUG - 07 AUG	28	80 (41)	963
(16W)	TY OWEN	11 AUG - 18 AUG	28	75 (39)	967
(17W)	TY NANCY	11 AUG - 16 AUG	22	75 (39)	967
(18W)	TS PEGGY	16 AUG - 18 AUG	9	35 (18)	997
(19W)	TD 19W	17 AUG - 19 AUG	6	30 (15)	1000
(20W)	TS ROGER	24 AUG - 28 AUG	14	50 (26)	983†
(21W)	TD 21W	25 AUG - 28 AUG	7	30 (15)	1000
(22W)	TY SARAH	06 SEP - 14 SEP	33	125 (64)	916
(23W)	TS TIP	09 SEP - 13 SEP	20	50 (26)	987
(24W)	TS VERA	12 SEP - 16 SEP	16	50 (26)	987
(25W)	TY WAYNE	17 SEP - 20 SEP	12	65 (33)	976
(26W)	STY ANGELA	29 SEP - 10 OCT	46	130 (67)	910
(27W)	TY BRIAN	30 SEP - 03 OCT	13	80 (41)	963
(28W)	TY COLLEEN	01 OCT - 08 OCT	27	80 (41)	963
(29W)	TY DAN	08 OCT - 13 OCT	21	70 (36)	972
(30W)	STY ELSIE	14 OCT - 22 OCT	34**	140 (72)	898
(31W)	TY FORREST	22 OCT - 29 OCT	30	95 (49)	949
(32W)	TY GAY	02 NOV - 04 NOV	9***	100 (51)	943
(33W)	TY HUNT	16 NOV - 23 NOV	27	90 (46)	954
	STY IRMA	21 NOV - 22 NOV	3	25 (13)	1002
	STY IRMA*	25 NOV - 04 DEC	36	140 (72)	898
(35W)	TD 35W	07 DEC - 09 DEC	9	30 (15)	1000
(36W)	TY JACK	20 DEC - 28 DEC	21	125 (64)	916
		TO	TAL: 710		

- * REGENERATED
- ** FOUR ISSUED BY AJTWC.
- *** WARNINGS IN WESTPAC BASIN. SEE TABLE 3-5 FOR WARNINGS IN INDIAN OCEAN.
 - † BASED ON SYNOPTIC DATA.

The criteria used in Table 3-2 are as follows:

- 1. If a tropical cyclone was first warned on during the last two days of a particular month and continued into the next month for longer than two days, then that system was attributed to the second month.
- If a tropical cyclone was warned on prior to the last two days of a month, it was attributed to the first month, regardless of how long the system lasted.
- 3. If a tropical cyclone began on the last day of the month and ended on the first day of the next month, that system was attributed to the first month. However, if a tropical cyclone began on the last day of the month and continued into the next month for only two days, then it was attributed to the second month.

TABLE 3-2 LEGEND




TABLE	3-2	WESTE	RN N	ORTH	PACI	FIC	TROPI	CAL	CYCLO	NE D	ISTRI	BUTI	ON
YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	TOTALS
1959	0	1	1	1	0	1	3	8	9	3	2	2	31
1960	000 1	010 0	010 1	100 1	000 1	001 3	111 3	512 9	423 5	210 4	200 1	200 1	17 7 7 30
1961	001 1	000 1	001 1	100 1	010 4	210 6	210 5	810 7	041 6	400 7	100 2	100 1	19 8 3 42
1962	010 0	010 1	100 0	010 1	211 3	114 0	320 8	313 8	510 7	322 5	101 4	100 2	20 11 11 39
1963	000	010	000	100	201 0	000	512 5	701 4	313 4	311 6	301 0	020 3	24 6 9 28
1	000	000	001	1 100	000	310	311	301	220	510	000	210	19 6 3
1964	0 000	0 000	0 000	0 000	3 201	2 200	8 611	8 350	8 521	7 331	6 420	2 101	44 26 13 5
1965	2 110	2 020	1 010	1 100	2 101	4 310	6 411	7 322	9 531	3 201	2 110	1 010	40 21 13 6
1966	0 000	0	000	1 100	2 200	1 100	4 310	9 531	10 532	4 112	5 122	2 101	38 20 10 8
1967	1	0	2	1	1	1	8	10	8	4	4	1	41
1968	010 0	000 1	110 0	100 1	010 0	100 4	332 3	343 8	530 4	211 6	400 4	010 0	20 15 6 31
1969	000	001 0	000	100 1	000 0	202 0	120 3	341 3	400 6	510 5	400 2	000 1	20 7 4 1 23
1970	100 0	000 1	010 0	100 0	000 0	000 2	210 3	210 7	204 4	410 6	110 4	010 0	13 6 4 27
l	000	100	000	000	000	110	021	421	220	321	130	000	12 12 3
1971	1 010	0 000	1 010	2 200	5 230	2 200	620	5 311	7 511	4 310	2 110	0 000	37 24 11 2
1972	1 100	0 000	1 001	0 000	0 000	4 220	5 410	5 320	6 411	5 410	2 200	3 210	32 22 8 2
1973	0 000	0 000	0 000	0 000	0 000	0 000	7 430	6 231	3 201	4 400	3 030	0 000	23 12 9 2
1974	1	0	1	1	1	4 121	5	7 232	5 320	4 400	4 220	2 020	35 15 17 3
1975	010 1	000	010 0	010 1	100 0	0	230 1	6	5	6	3	2	25
1976	100 1	000 1	000	001 2	000 2	000 2	010 4	411 4	410 5	321 0	210 2	002 2	14 6 5 25
1977	100 0	010 0	000 1	110 0	200 1	200 1	220 4	130 2	410 5	000 4	110 2	020 1	14 11 0 21
1978	000	000	010	000	001 0	010 3	301	020 8	230 4	310 7	200 4	100	11 8 2 32
	010	000	000	1 100	000	030	4 310	341	310	412	121	000	15 13 4
1979	1 100	0 000	1 100	1 100	2 011	0 000	5 221	4 202	6 330	3 210	2 110	3 111	28 14 9 5
1980	0 000	0 000	1 001	1 010	4 220	1 010	5 311	3 201	7 511	4 220	1 100	1 010	28 15 9 4
1981	0 000	0 000	1 100	1 010	1 010	2 200	5 230	8 251	4 400	2 110	3 210	2 200	29 16 12 1
1982	0	0	3	0	1	3	4	5	6	4	1	1	28
1983	000	000 0	210 0	000 0	100 0	120 1	220 3	500 6	321 3	301 5	100 5	100 2	19 7 2 25
1984	000	000 0	000	000 0	000 0	010 2	300 5	231 7	111 4	320 8	320 3	020 1	12 11 2 30
1985	000 2	000	000	000 0	000 1	020 3	410 1	232 7	130 5	521 5	300 1	100 2	16 11 3 27
	020	000	000	000	100	201	100	520	320	410	010	110	17 9 1
1986	000	1 100	000	1 100	2 110	2 110	2 200	5 410	2 200	5 320	4 220	3 210	27 19 8 0
1987	1 100	0 000	0 000	1 010	0 000	2 110	4 400	4 310	7 511	2 200	3 120	1 100	25 18 6 1
1988	1 100	0 000	0 000	0 000	1 100	3 111	2 110	5 230	8 260	4 400	2 200	1 010	27 14 12 1
1989	1 010	0	0	1 100	2 200	2 110	6	8 332	4 220	6 600	3 300	2 101	35 21 10 4
(1959-19	989)						231						
MEAN:	0.6	0.3	0.6	0.7	1.3	2.1	4.5	6.2	5.7	4.6	2.8	1.5	30.8
CASES:	18	9	18	23	39	65	140	193	176	142	86	45	954

Figure 3-1. Chronology of western North Pacific and North Indian Ocean tropical cyclones for 1989.




TABLE 3-	3		WEST	ern n	ORTH !	Pacif	IC TR	OPICAL	ר כגכו	LONES			
					7	TYP: 1945	ноомs - 195						
	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	<u>oct</u>	NOV	DEC	TOTALS
MEAN:	0.4	0.1	0.3	0.4	0.7	1.1	2.0	2.9	3.2	2.4	2.0	0.9	16.3
CASES:	5	1	4	5	10	15	28	41	45	34	28	12	228
					1	1959	<u>- 198</u>	9)					
	JAN	FEB	MAR	APR	MAY	JUN	TOL	AUG	SEP	OCT	NOV	DEC	TOTALS
MEAN:	0.3	0.1	0.2	0.5	0.7	1.0	2.7	3.2	3.2	3.1	1.7	0.7	17.4
CASES:	8	2	6	16	22	32	83	99	100	97	53	21	539
				TROP		STORM 945 -		TYPHO	OONS				
	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	TOTALS
MEAN:	0.4	0.1	0.4	0.5	8.0	1.6	3.0	3.9	4.1	3.3	2.8	1.1	22.0
CASES:	6	1	6	7	11	22	42	54	58	46	39	16	308
					n	959 -	1989	īΤ					
	JAN	FEB	MAR	APR	MAY	JUN	TAT	AUG	SEP	OCT	NOV	DEC	TOTAL
MEAN:	0.5	0.3	0.5	0.7	1.0	1.8	4.1	5.3	5.0	4.1	2.6	1.3	27.6
CASES:	17	9	14	22	33	55	127	166	154	128	81	39	855
FORMATI SIGNIFI REGENER TROPICA WARNIN	CANT (ATED) L CYC	TROPI . TRO CLONES	CAL C PICAL 5 08W,	YCLON CYCL 25W	NES (N LONE F AND 3	OT IN FORMAT 34W.	CLUDI	NG TH	REE O	N SYS	TEMS '	THAT	

		Western north pacifi		
		TROPICAL	TOTAL	FALSE
	INITIAL	CYCLONES	TROPICAL	ALARM
YEAR	TCFAS	WITH TCFAS	CYCLONES	RATE
1975	34	25	25	26%
1976	34	25	25	26%
1977	26	20	21	23%
1978	32	27	32	16%
1979	27	23	28	15%
1980	37	28	28	24%
1981	29	28	29	3%
1982	36	26	28	28%
1983	31	25	25	19%
1984	37	30	30	19%
1985	39	26	27	33%
1986	38	27	27	29%
1987	31	24	25	23%
1988	33	26	27	21%
1989	51	32	35	32%
(1975-1989)				
MEAN:	34.3	26.1	27.5	23.9%

3.2 WESTERN NORTH PACIFIC TROPICAL CYCLONES

1989 was unique in many regards. The monsoon trough was very active, even into November. Because the trough was extremely broad and because of the abnormally large diurnal fluctuations in convection, disturbances were slow to develop to intensities above 30 to 40 kt (15 to 20 m/sec). As a result, JTWC used the new 36-hour Tropical Depression Warning on systems not expected to reach tropical storm intensity within 48 hours. The mid-tropospheric ridge was narrow — averaging less than 250 nm (465 km). This made forecasts, even for straight running tropical cyclones difficult. There were a large number of erratically moving cyclones with tracks containing several bifurcation points where difficult forecast decisions had to be made as to significant changes in direction of motion. Several tropical cyclones stalled for prolonged periods of time. Some examples are Typhoons Gay (32W), Irma (34W), Mac (15W) and Jack (36W), among others. In fact, Jack (36W) sat 175 nm (325 km) directly east of Guam for nearly two days. JTWC experienced several occasions where tropical cyclones engaged in binary interaction with each other or with other circulations in the environment. Most notable was the interaction between Typhoons Owen (16W), Nancy (17W) and towards the end Tropical Storm Peggy (18W). The Tropical Upper-Tropospheric Trough (TUTT) was extremely active and played a major role in the development, intensification and movement of numerous tropical cyclones. Of particular interest was Typhoon Gordon (08W) which actually developed explosively from a thunderstorm that built beneath, and directly up into a cold-cored TUTT low aloft. And finally, 1989 had a large number of very compact, yet very intense typhoons. The presence of Tropical Cyclone 32W (Gay) with super typhoon intensity in the Bay of Bengal was a rare occurance. The variety of synoptic influences on the 1989 tropical cyclone season made it one of the most unique and challenging in JTWC's 30-year history.

JANUARY THROUGH JUNE

The first western North Pacific tropical cyclone of 1989, Winona (01W), quietly began in the eastern North Pacific southeast of the Hawaiian Islands. The system was unusual because of its compact size and persistence. In two weeks it traveled over 5500 nm (10,185 km) before finally dissipating in the Philippine Islands. Following Tropical Storm Winona (01W), there was a long break in activity until mid-April when Andy (02W) developed. Super Typhoon Andy (02W) was the second typhoon in the past nine years to form in April, the first super typhoon of 1989, and the first typhoon of the year to seriously threaten Guam. It developed very slowly, and after recurving at the extremely low latitude of 10° north, passed 70 nm (130 km) southeast of Guam. A month later Brenda (03W), the first of two typhoons to form in May, generated in the western Caroline Islands, moved northwestward across the central Philippine Islands, and then made landfall in China. It was the second of eleven tropical cyclones to cross the Philippines during the year. An extensive monsoon trough spread across the Bay of Bengal into the South China Sea. Typhoon Brenda (03W) formed at the end of the trough. As Brenda (03W) moved northwestward and dissipated over southern China, it left behind an area of enhanced low-level southwesterly flow. Typhoon Cecil (04W) developed in the South China Sea in the wake of the enhanced flow from Typhoon Brenda (03W). After Cecil (04W) churned across the South China Sea and into Vietnam during the last week of May, the tropics were relatively quiet for two weeks. Then came Typhoon Dot (05W), the first of two significant tropical cyclones in June. Dot (05W) formed in low latitudes south of the central Caroline islands. moved steadily west-northwestward and crossed the Philippine Islands. It reached typhoon intensity in the South China Sea and eventually dissipated over northern Vietnam. The second tropical cyclone to form in June, Tropical Storm Ellis (06W) interrupted the series of "straight runners" that occurred from Brenda (03W) through Dot (05W). The asymmetric displacement of a broad area of gale force winds away and to the east of the low-level circulation center accompanied Ellis (06W). After five days as a poorly defined system, Ellis (06W) briefly peaked at tropical storm intensity before becoming extratropical and making landfall in Japan.

JULY

After another two-week break in activity, a surge in the southwest monsoon caused widespread convective activity in the area west of the Mariana Islands, culminating in the genesis of Faye (07W), the first of seven tropical cyclones to form in July. Faye (07W) intensified at a normal rate as it tracked westnorthwestward towards the Philippines. The cyclone weakened as it crossed north-central Luzon and reintensified slightly in the South China Sea. It weakened again in the central South China Sea, and crossed the island of Hainan before making landfall on the coast of northern Vietnam. At the start of the second week of July, while Tropical Storm Faye (07W) was affecting the Philippine Islands and the Tropical Upper-Tropospheric Trough (TUTT) was influencing weather near Wake Island, the second super typhoon of the year, Gordon (08W), developed. It was unique in that it developed from a single cumulonimbus directly beneath a cyclonic cell in the TUTT. The cumulonimbus was initially small, but underwent a dramatic rapid, almost explosive, deepening phase. Hope (09W) generated in the wake of Gordon (08W) in a broad area of convection enhanced by divergence aloft associated with a TUTT cell. Hope (09W) failed to develop to typhoon intensity as a result of the upper-level shear caused by the outflow from Super Typhoon Gordon (08W). During its life, Hope (09W) moved generally northwestward, occasionally "stair stepping" in response to the passage of a series of mid-latitude shortwave troughs. Although no binary interaction was apparent, the tropical cyclone tracked along the periphery of Gordon's (08W) low-level circulation for most of its lifetime. As Super Typhoon Gordon (08W) was about to make landfall on the coast of China and Tropical Storm Hope (09W) was reaching peak intensity, Irving (10W) formed in the monsoon trough near the southwestern Caroline Islands. Tropical Storm Irving (10W) was the fourth tropical cyclone of 1989 to cross the South China Sea and the last to enter the South China Sea until Typhoon Brian (27W) late in September. Irving was short-lived and actually reached its maximum intensity as it made landfall on the coast of northern Vietnam. The day after Irving (10W) developed in the western Caroline Islands, Judy (11W) developed in the monsoon trough just west of Guam. The second of two typhoons to develop during the month of July, Judy (11W), followed a north-oriented track with a critical turn to the northwest, just to the south of Honshu. It brushed by the southern coast of Kyushu, made landfall on the south coast of the Korean Peninsula and dissipated rapidly. After a major track change on 26 July, it took JTWC a day to get the forecast back on track to the northwest. This situation highlighted the value of the alternate scenario and rapid telephone communications between the customer and the forecaster when forecast difficulties arise. While Typhoon Judy (11W) was tracking northwestward towards Korea, an associated area of deep convection became persistent to the south-southeast in the monsoon trough that had already proven itself the most active since July 1973. The disturbance became Ken-Lola (13W-14W) and took an elongated cycloidal track, passing close to Okinawa before making landfall on the coast of eastern China. While in warning status, JTWC considered the system as two separate tropical cyclones. A detailed post-analysis, even though not absolutely conclusive, strongly suggested that Tropical Storms Ken (13W) and Lola (14W) were most probably the same system. Tropical Storm Ken-Lola (13W-14W) underscored the limitations of remote sensing for locating some poorly organized systems. Synoptic data proved invaluable in identifying and classifying the system while in warning status and in postanalysis. A much larger mid-level cy-clone in which the tropical cyclone was embedded appeared to be the major influence on Ken-

AUGUST

As the most active July since 1973 came to a close, Typhoon Judy (11W) was dissipating over Korea and Tropical Storm Ken-Lola (13W-14W) was threatening Okinawa. During this time, Mac (15W) developed northeast of Saipan in an extremely active monsoon trough that extended as far east as Wake Island. Typhoon Mac (15W) also developed at a higher than normal latitude. In addition, its track and intensity were influenced by a complex midlatitude synoptic regime and complicated by a multi-storm environment. The typhoon had a general northwest track, interrupted by 48 hours of westward movement before it resumed an accelerated north orientated track, and made landfall east of Tokyo. Mac (15W) weakened rapidly as it moved into and across the Sea of Japan and dissipated over southern Sakhalin Island. Soon thereafter, Typhoon Owen (16W) slowly spun up in the monsoon trough while moving on a general northwestward to northward track. Due to the proximity of Nancy (17W), which developed at the extreme eastern end of the monsoon trough and was intensifying to the east, Owen (16W) took more than a week to reach tropical storm intensity. Later, Owen's (16W) three days of binary interaction with Typhoon Nancy (17W) resulted in an unusual southeasterly track during its developing stage. Then, the tropical cyclone followed Nancy (17W) through recurvature, extratropical transition and into high latitudes. The third tropical cyclone to develop in the monsoon trough, was Peggy (18W). After a brief interaction with Owen (16W), Peggy (18W) was short-lived and only reached minimal tropical storm intensity. Then came Tropical Depression 19W with its unusual curved track to the north, west, and then south which appeared to coincide with the overall motion displayed by a larger, mid-level low. As the mid-level low began to fill, the tropical depression escaped its influence, and the track of the cyclone straightened out, moving westward within the easterly steering flow.

Forming just north of Taiwan, Roger (20W) moved south-eastward into the southern Rvukvu's, abruptly turned northeastward, and made landfall on Honshu. At the start, the forecast problem for this tropical cyclone was exacerbated by the difficulty in locating the system's complex center during its formative stages and the immediate threat it posed to DOD assets on Okinawa. The eighth and final tropical cyclone of August, Tropical Depression 21W, developed on the eastern end of the monsoon trough which was located to the northeast of the Mariana Islands. Because JTWC recognized that intensification would be inhibited by strong vertical wind shear, only Tropical Depression Warnings were issued.

SEPTEMBER

The first of the September tropical cyclones, Sarah (22W) proved to be a bona fide challenge to forecasters. The cyclone apparently underwent a binary interaction with a secondary low east of Luzon and later, when it stalled east of Luzon, was involved with the development of a sympathetic low on the lee side of Luzon. From genesis involving two distinct cloud masses to accelerating toward the Philippines, stalling just east of Luzon, moving north and rapidly reintensifying, then looping over eastern Taiwan, Sarah (22W) was one of the most difficult storms of the year to forecast. Sarah (22W) finally moved northwestward across northern Taiwan and dissipated in China. Generating in early September at the eastern end of the monsoon trough, Tip (23W) executed an unusual track to the northeast, then recurved after moving northwestward around the subtropical ridge, and finally tracked eastward with the polar westerlies. Tropical Storm Tip (23W) reached its peak intensity at 37° north latitude, two days after recurvature. Developing in the monsoon trough north of Guam, Tropical Storm Vera (24W), after some initial erratic motion, moved on a westnorthwestward track, threatened Okinawa, and made a devastating landfall just south of Shanghai. About 24 hours after Tropical Storm Vera (24W) had dissipated over eastern China.


the first warning on Wayne (25W) was issued. The last of four tropical cyclones to mature in September, Typhoon Wayne (25W) was also the last tropical cyclone of 1989 to affect Japan. It was unique in that it intensified after recurvature, partly as a result of its rapid acceleration. Wayne (25W) caused considerable destruction, mudslides and some deaths in Japan.


OCTOBER


During late September, the monsoon trough, located near 10° north latitude, became very active after a week of little convective activity. The first tropical cyclone of a threecyclone outbreak in the monsoon trough during a three-day period, Angela (26W) had the unique distinction of being in warning status longer than any other tropical cyclone in the western North Pacific this year — 12 days. JTWC issued a total of 46 warnings on this typhoon. Angela (26W) was also one of five tropical cyclones to reach super typhoon intensity in 1989. Developing south of Guam, Angela (26W) tracked slowly westward and struck northern Luzon with super typhoon intensity causing a large number of casualties and widespread destruction. It then continued into the South China Sea, where it reintensified, and finally made landfall in central Vietnam. As Angela (26W) developed over the Philippine Sea, the monsoon trough became active across the South China Sea from western Luzon to Vietnam and spawned typhoon Brian (27W). Typhoon Cecil (04W) in May and Brian (27W) in late September and early October were the only tropical cyclones of the year to develop and spend their entire lifetimes within the confines of the South China Sea. Nearly 4000 nm (7400 km) to the east, a deep trough penetrated into the tropical western North Pacific near the dateline and Colleen (28W) formed at the base of the trough. Colleen (28W) passed through the northern Mariana Islands before recurving south of Japan. The tropical cyclone maintained typhoon intensity until it completed extratropical transition, threatening PACEX 89 - the largest US Navy exercise conducted in the Pacific since the Korean War. (28W) highlighted the difficulty of tracking poorly organized systems with only nighttime infrared satellite imagery, but also showed the value of data from the microwave imager as a tool to help locate these systems. Forming from a disturbance in the monsoon trough near Truk in the central Caroline Islands. Dan (29W) followed a steady west-northwestward track and crossed the central Philippine Islands. Coming just days after Typhoon Angela's (26W) destructive passage across northern Luzon, Dan (29W) added to the misery heaped on the Philippines by its predecessor. The cyclone reintensified in the South China Sea and made landfall on the coast of central Vietnam where it caused more destruction. In the wake of Super Typhoon Angela (26W) and Typhoon Dan (29W), Super Typhoon Elsie (30W) became the third tropical cyclone to hit the Philippine Islands within 12 days. Elsie (30W) developed from a TUTT-induced wave in the easterlies and tracked westward throughout its life. In the Philippine Sea, Elsie (30W) rapidly intensified and struck central Luzon with an intensity of 140 kt (72 m/sec). It was cited as the most intense cyclone to strike the Philippine Islands this year. Because of its small size, Elsie (30W) weakened dramatically as it moved across the Philippines, and did not reintensify as it traversed the South China Sea. The cyclone dissipated after making landfall in central Vietnam. The last of six tropical cyclones in October and the 17th cyclone of at least typhoon intensity for the year, Forrest (31W) was slow and erratic in its development. Throughout its early life, Forrest (31W) was a sloppy, broad system. After passing Guam, Forrest (31W) finally intensified and ultimately became a respectable 95-kt (49-m/sec) typhoon. Soon thereafter, it recurved and accelerated rapidly to the northeast becoming one of the year's strongest extratropical cyclones.


NOVEMBER THROUGH DECEMBER

The first tropical cyclone of November turned out to be the worst tropical cyclone to affect the Malay Peninsula in 35 years. Gay (32W) generated in the Gulf of Thailand, sank numerous ships, crossed the Malay Peninsula into the Bay of Bengal and slammed into India with peak sustained winds of 140 kt (70 m/sec). Unique because of its small size, great intensity, and point of origin, Gay (32W) challenged forecasters by crossing two different tropical cyclone basins and almost entering a third. Except for Typhoon Gay (32W), early November was relatively inactive in the western North Pacific. In mid-November, Hunt (33W) initially appeared as a weak tropical disturbance in the monsoon trough. Hunt (33W) was the fourth typhoon, following Angela (26W), Dan (29W) and Elsie (30W), to strike the Philippine Islands within six weeks. Generally a westward moving system, Hunt (33W) was slow to develop, but intensified rapidly in the western Philippine Sea. As it approached the Philippines, the cyclone underwent a "stair step" before resuming a westward course into central Luzon. Unlike its predecessors, Hunt (33W) dissipated in the South China Sea after crossing Luzon. Irma (34W) was the third and final tropical cyclone to form in November. It's development and track were dictated by complex mid-latitude and monsoonal regimes. Initially, Irma (34W) was slow to develop, however, rapid intensification followed once it entered in the Philippine Sea. Irma (34W) lasted 17 days and required a total of 39 warnings — only Super Typhoon Angela (26W) exceeded this longevity with its 46 warnings. As Super Typhoon Irma (34W) weakened in the Philippine Sea, Tropical Depression 35W was detected on the first day of December in the western Marshall Islands. The depression lasted more than a week as a discrete system, although it was in warning status only 48 hours. The second tropical cyclone to form in December, Jack (36W) was the twenty-first tropical cyclone of the year to attain at least typhoon intensity, and was the final tropical cyclone of the year. Typhoon Jack (36W) was noteworthy for the unusually long period it remained Not surprisingly, the unusual stationary. motion of Typhoon Jack (36W) was accompanied by an equally unusual intensification and dissipation pattern. The cyclone rapidly intensified from 30 to 125 kt (15 to 64 m/sec) in three and a half days, then fell apart completely. In this remarkable dissipation, Jack's (36W) maximum winds dropped from 105 to 30 kt (54 to 15 m/sec) in 24 hours.










Intentionally left blank.



TROPICAL STORM WINONA (01W)

The first western North Pacific tropical cyclone of 1989, Winona quietly began in the eastern North Pacific southeast of the Hawaiian Islands. The system was unusual because of its compact size and persistence. In two weeks it traveled over 5500 nm (10,185 km) before finally dissipating in the Philippine Islands.

At the start of the second week of January, 40-kt (21-m/sec) upper-level westerly winds funneled through a trough located just east of the Hawaiian Islands and created a broad area of divergence aloft to the southeast. In response, an area of deep convection persisted under the divergence and over the east-southeasterly winter trades. As the upper-level trough relocated eastward at 091200Z, a swirl of low-level cloudiness (Figure 3-01-1) became exposed, leaving behind its convective cloudiness, and moved to the west-northwest as a wave until 11 January. Then the supporting convection flared up (Figure 3-01-2), triggering flash floods on Kauai. As the system assumed a

more westward track on 12 January, it again passed under another upper-level trough. This time, however, the central convection persisted. Sparse surface data indicated a small area of light westerly winds to the south of the circulation center and a minimum sea-level pressure center of 1010 mb.

On 16 January, the compact system still retained its deep convection. It had traversed the Central Pacific in the dead of winter at 20° north latitude and persisted, which is extremely unusual. In fact, Winona was so unique that the analog and climatological forecast guidance was not available, or very limited, for most of the tropical cyclone's It had crossed the international lifetime. dateline the day before and was now approaching Wake Island. At 160600Z, the Significant Tropical Weather Advisory mentioned its persistent circulation and central convection. Later, at 161800Z, it was 75 nm (140 km) south of Wake Island (WMO 91245),




Figure 3-01-1. The low-level cloud system is passing south of the island of Hawaii. The area of bright cloudiness near point A is located east of the upper-level trough (102316Z January GOES West visual imagery courtesy of the National Weather Service Forecast Office, Honolulu, Hawaii).

which experienced maximum sustained surface winds of 25 kt (13 m/sec) and gradient-level winds (Figure 3-01-3) of 30 kt (15 m/sec).

After Winona passed Wake Island, a satellite intensity estimate of 25 kt (13 m/sec) coupled with the system's translational speed of more than 20 kt (37 km/hr) prompted a Tropical Cyclone Formation Alert at 170030Z. The subject of the Alert was upgraded to Tropical Storm Winona at 180000Z based on persistent central convection, the satellite intensity analysis and the cyclones rapid translational speed to the west, which would cause higher winds to the north of the circulation center. Since the tropical cyclone was embedded in broad easterly flow, a "straight runner" was forecast.

Just at the end of 18 January invaluable insight came from the ship MV Williams as follows, "Believe to have passed through center at 180700Z......Barometer pressure 991 (mb) max sustained winds 045 (gusts to) 65-70 kts, combined sea-swell 35 (ft)." This ship observation resulted in a warning and final best track intensity* increase (Figure 3-01-4). Without any additional direct measurements. satellite remote sensing tracked the cold cloud tops throughout the night. First light visual satellite data and later initial radar reports from Andersen AFB, Guam (WMO 91218) found Winona south and west of the expected track (Figure 3-01-5). The tropical storm (Figure 3-01-6) with peak winds of 55 kt (28 m/sec). passed just to the north of Saipan at 190000Z. The International Airport (91232) reported




Figure 3-01-2. As the low-level vortex enters an area more favorable for development, the convection flares up (112346Z January GOES West visual imagery courtesy of the National Weather Service Forecast Office, Honolulu, Hawaii).

^{*}This underscores a limitation of the Dvorak technique (1984), when applied to tropical cyclones that are moving along track at speeds greater than the climatic mean. Tropical cyclone forecasters should consider excess translational speed in addition to the intensity estimate, that is derived from the cloud signature, to better approximate maximum sustained surface winds.




Figure 3-01-3. The gradient winds at Wake Island (91245) peak at 30 kt (15 m/sec) and undergo a directional change between 161200Z and 170000Z, as Winona passes to the south. Note the gradual speed increase from two days before Winona's passage and decrease for two days afterward.

winds of 25 kt (13 m/sec) with gusts to 35 kt (18 m/sec). No loss of life was reported Saipan.

Winona continued accelerating to the west-southwest along the southern edge of a shallow modifying polar air mass until the deep supporting convection was lost. A final warning was issued at 191800Z. However, the central convection flared up again and a regenerated warning followed at 200600Z. Just prior to landfall in the central Philippine Islands, Winona's deep central convection fell apart and the system was finalled at 210600Z.




Figure 3-01-4. Impact of the ship MV Williams' 180700Z report on the warning and final best track intensities for Winona.




Figure 3-01-5. Comparison of expected track, raw fix data and final best track for Winona. The first daylight visual satellite fixes (A and B) were key elements in establishing Winona's continued movement to the west-southwest.





Figure 3-01-6. Tropical Storm Winona approaches Saipan. Note the compact size of the system (182321Z January DMSP visual imagery).

Intentionally left blank.



SUPER TYPHOON ANDY (02W)

For the western North Pacific, Andy was the second typhoon in the past nine years to form in April, the first super typhoon of 1989 and the first typhoon of the year to seriously threaten Guam.

The weather pattern the second week of April mirrored climatology with brisk, east-northeast trade winds dominating the low latitudes and only token deep convection. However, by the close of the week, the trade winds became lighter and equatorial westerlies replaced the cross-equatorial flow, or buffer, as Tropical Cyclone 26S (Orson) developed south of the equator in the Arafura Sea. North of the equator increased convection persisted near

Truk Atoll in the eastern Caroline Islands. This increased convection was first mentioned in the Significant Tropical Weather Advisory at 130600Z. Continued cloud development prompted the first Tropical Cyclone Formation Alert at 151430Z. Intensification of the system (Figure 3-02-1) was slow, however, and follow-on Alerts were issued at 161430Z and 171430Z.

As this area slowly moved westward and gradually intensified, it was finally upgraded at 171800Z to Tropical Depression 02W. Data from the Automated Meteorological Observing Station (AMOS) installed in 1988 on Faraulep Island (WMO 52005) in the central Carolines became very important as it monitored the




Figure 3-02-1. Satellite global data base display from the Air Force Global Weather Central captures the two tropical cyclones — Andy near Truk and Orson (26S) in the Arafura Sea (170000Z April DMSP infrared imagery).

approach of the tropical cyclone (Figure 3-02-2). In this normally data sparse area the Faraulep AMOS provided needed observations of surface pressure, wind speed and direction which provided the ground truth for the satellite data. These AMOS data (Figure 3-02-3) reflected the change of Andy's track from the west to northwest at 171800Z. After the

passage of a mid-latitude trough to the north of the system, the track returned to westward at 181200Z.

Following Andy's passage to the north of Faraulep and south of Guam, satellite fixes from 190530Z through 191730Z indicated it had ceased its westward movement and had




Figure 3-02-2. Andy bears down on Faraulep Island. Guam is just under the leading edge of the cirrus (172219Z April DMSP visual imagery).




Figure 3-02-3. Faraulep AMOS reports showing: (a) time series of pressure, (b) wind speed and (c) wind direction. Andy's closest point of approach was at 181800Z. Note the major shift of wind direction and increase of wind speed preceded the lowest pressure.

begun to move to the north. Continued intensification (Figure 3-02-4) further aggravated the forecaster's dilemma. With recurvature possible as another mid-latitude trough moved eastward from Asia, there was an increasing threat to life and property in the Marianas. Until 200000Z, it appeared that the track would return to the west-northwest after a mid-latitude trough to the north progressed eastward and the lower tropospheric high pressure reestablished itself north of the

cyclone. OTCM supported this synoptic assessment (Figure 3-02-5) in contrast to the climatological techniques, primarily CLIPER, which indicated a track to the north and just to the west of Guam. But Andy's continued slow northward movement required a reassessment of the synoptic situation. The track forecast was changed from west-northwestward to north, just west of Guam, followed by recurvature. The alternate forecast scenario became an early recurvature with passage southeast of Guam.




Figure 3-03-4. The low sun angle enhances the cloud top topography. Andy poses an imminent threat to the Marianas (210816Z April DMSP visual imagery).

The primary forecast held until 201700Z at which time it became apparent that recurvature had already taken place. A special tropical cyclone warning was issued with the updated forecast reflecting that Andy (Figure 3-02-6) would pass 45 nm (70 km) southeast of Guam.

Andy's closest point of approach (CPA) to Guam occurred at 202100Z 70 nm (130 km) to the southeast. The island was spared the intense maximum sustained winds near the center estimated to be 135-140 kt (69-72 m/sec). Sustained surface winds recorded on the island were 35-45 kt (18-23 m/sec) with peak gusts to 68 kt (35 m/sec). These resulted

in crop damage, power outages and minor property damage, primarily due to fallen trees. In addition, torrential downpours caused localized flooding. At sea, the combat stores ship, USS San Jose came to the aid of a disabled fishing vessel in the path of the super typhoon.

After CPA, Andy continued to track northeastward and weaken as the vertical shear from the westerly winds aloft increased. Three days later, at 240000Z, when the central convection completely separated from the dissipating low-level circulation center (Figure 3-02-7), the final warning was issued.





Figure 3-02-5. Comparison of OTCM guidance tracks from 191800Z through 211800Z with the final best track. After the start time for OTCM, the dots embedded in the dashed line indicate the location of the 24, 48 and 72 hour guidance.



As a point of interest, Figure 3-02-8 is included to deomonstrate the value of multispectral imaging. In the visual image the low-

level eye is completely obscured; however, a part of it can be seen in the enhanced infrared image.





Figure 3-02-7. Remnants of Andy's low-level circulation (242322Z April DMSP visual imagery).







Figure 3-02-8. As Andy moves away from Guam, this picture pair shows the importance of multispectral since the eye is located at the extreme lower right edge of the polar orbiter image. Note a small portion of the low-level eye shows on the enhanced infrared (to the left). On the visual (to the right) the low-level eye is completely masked by the bright sunlight reflected from the eastern side of wall cloud (210434Z April NOAA visual and infrared imagery).



TYPHOON BRENDA (03W)

The first of two typhoons to form in May, Brenda generated in the western Caroline Islands, moved northwestward across the central Philippine Islands, and then made landfall in China. It was the second of eleven tropical cyclones to cross the Philippines during the year.

After spawning Super Typhoon Andy in April, the tropics remained relatively quiet for two weeks. Then, on 14 May, the Significant Tropical Weather Advisory mentioned an area of broad convection with weak turning in the monsoon trough south of Yap. Continued organization of clouds and winds prompted the issuance of a Tropical Cyclone Formation Alert

at 150730Z and the first warning at 151800Z. The system was upgraded to tropical storm at 160000Z.

Brenda (Figure 3-03-1) tracked across Samar and southern Luzon, exiting at the tip of the Bataan Peninsula. Closest point of approach to both NAS Cubi Point and Manila was 18 nm (35 km). Cubi Point's barograph recorded a minimum sea level pressure of 989 mb at 171800Z. To the north, Clark AB (WMO 98327) experienced maximum gusts of 38 kt (20 m/sec) and received minor damage. News reports indicated at least four water craft sank, and that more than 50 people were killed or missing in the Philippine Islands. In addition,




Figure 3-03-1. Brenda slams into the southern Luzon (170025Z May DMSP visual imagery).

thousands were left homeless, and communications and power were significantly disrupted.

Once in the South China Sea and again over warm water, Brenda (Figure 3-03-2) continued northwestward and intensified, reaching typhoon status at 191200Z. Meanwhile, the NOGAPs prognostic series forecast a mid-latitude short wave to move north of the tropical cyclone, indicating potential for recurvature. JTWC did forecast recurvature at 181200Z, based on an apparent

northward motion of the circulation center on the nighttime infrared satellite imagery. Low confidence radar signatures also indicated a northward motion. Subsequent fixes based on visual imagery returned the cyclone's track to a northwestward direction. In turn, JTWC returned forecasts to a northwest motion and into the coast of China, west of Hong Kong.

Typhoon Brenda reached a maximum intensity of 75 kt (39 m/sec) at 191800Z before passing within 81 nm (150 km) of Hong Kong at 201200Z. The Royal Observatory at Hong




Figure 3-03-2. Moving over water, Brenda regains organization and reintensifies (180146Z May DMSP visual imagery).

Kong reported maximum gusts of 54 kt (28 m/sec), a minimum sea-level pressure of 995 mb and 17 inches (441 mm) of rain during the six days that Brenda and its enhanced southwest flow affected the area.

Brenda (Figure 3-03-3) made landfall on the south coast of China at 201400Z and dissipated over land in the Guangdong Province. Preliminary reports indicated that at least 84 people perished in southern China, and that widespread flooding due to the heavy rains damaged about 3.5 million acres (1.4 million hectares) of land. In Hong Kong six people were killed, one was missing, and the heavy rains resulted in landslides, floods and large losses in livestock and fish farming.





Figure 3-03-3. This brightly lit low sun angle photo shows Brenda's convective spirals as the typhoon approaches the coast. The sun is low to the west, and its rays scatter forward, through the aerosols, and out to space. The gray, milky-looking areas around the periphery of Brenda reveal the presence of aerosols in the lower layer of the atmosphere that are being trapped, and concentrated, as a the result of subsidence (201021Z DMSP visual imagery).



TYPHOON CECIL (04W)

The second of two typhoons during the month of May, Cecil developed in the South China Sea in the wake of Typhoon Brenda (03W).

On 20 May, an extensive monsoon trough spread across the Bay of Bengal into the South China Sea where it terminated in Typhoon Brenda (03W). As Brenda moved northwestward and dissipated over southern China, it left behind an area of enhanced lowlevel southwesterly flow. Additionally, the dissipation of Brenda (03W) reduced the vertical wind shear from the north over the genesis area for Cecil. Cecil was first detected on 21 May as a low-level cyclonic circulation associated with the enhanced southwesterly flow. The Significant Tropical Weather Advisory was reissued at 212000Z to cover this circulation and its persistent cloudiness. When surface synoptic reports and additional satellite data indicated that the system was becoming better organized, a Tropical Cyclone Formation Alert was issued at 220230Z.

Initially, the deep convection was only located in the southern semicircle, but on 22 May the convection wrapped around the circulation center. This event, along with falling central pressures precipitated the first

warning on Tropical Depression 04W at 221800Z. The warning was then amended based on subsequent synoptic reports, and the system upgraded to a tropical storm.

At the start, Cecil was forecast to track northward through the weakness in the subtropical ridge created by Brenda (03W). This forecast was supported by guidance from the dynamic aid, OTCM, and HPAC, an aid which blends one half persistence with one half climatology. But, the tropical cyclone turned towards the west on 23 May and tracked into central Vietnam in response to ridging to the north over China.

With inflow from the extensive low-level southwest monsoonal flow, divergence aloft and weak vertical wind shear, Cecil reached typhoon intensity at 240000Z (Figure 3-04-1). The typhoon tracked across the coast of Vietnam at 241800Z with maximum sustained surface winds estimated at 70 kt (35 m/sec). News agencies reported that at least 52 people perished, 37 were injured, over 100,000 were left homeless and 700 water craft were destroyed. Persistent convection associated with Cecil produced heavy rains inland which resulted in flooding and crop damage in Laos and northeastern Thailand.





Figure 3-04-1. Cecil with a large ragged 40 nm (75 km) diameter eye approaches the coast of Vietnam (240539Z May NOAA visual imagery.)



TYPHOON DOT (05W)

Dot, the first of two significant tropical cyclones in June, formed in low latitudes south of the central Caroline islands, moved steadily west-northwestward and crossed the Philippine Islands. It reached typhoon intensity in the South China Sea and eventually dissipated over northern Vietnam.

After Cecil (04W) tracked across the South China Sea and into Vietnam the last week of May, the tropics were relatively quiet. Then light westerly surface winds appeared in the southern Philippine Sea and cloudiness increased. In this zone of maximum cloudiness on 2 June Dot, as a tropical disturbance, was

identified and noted in the Significant Tropical Weather Advisory as having fair potential for development. On 4 June the disturbance passed north of the island of Palau in the western Carolines and became better organized, which prompted a Tropical Cyclone Formation Alert at 041230Z. A further increase in convection and organization led to the first warning at 050000Z when the system was approximately 300 nm (555 km) southwest of the island of Samar in the Republic of the Philippines.

Tropical Depression 05W was upgraded to Tropical Storm Dot (Figure 3-05-1) at 051200Z, twelve hours before making




Figure 3-05-1. As Dot reaches tropical storm intensity, it's central dense overcast and surrounding band of convection blanket a large portion of the Philippine Sea (051801Z June NOAA infrared imagery).

landfall on Samar. Dot accelerated slightly while crossing the central Philippine Islands which was in agreement with the results of Sikora's (1976) movement study. The open waters of the Sibuyan Sea and the relatively low relief of the adjacent islands allowed the circulation aloft to intensify slowly, but the rugged topography limited the surface effects. Clark Air Base's radar (WMO 98327) located the circulation center at 061835Z over south central Mindoro. As suspected from the previous satellite imagery, the analysis of surface pressure reports from land stations revealed the system's large size (Figure 3-05-2).

Upon entering the South China Sea, Dot initially took a more northward track. This increase in northward component, coupled with

the approaching frontal system and the guidance of most of JTWC's objective aids, led JTWC to forecast Dot's track to the east and north of Hainan Island (Figure 3-05-3). However, the tropical cyclone never linked up with the approaching frontal system and continued westnorthwestward. Weak vertical wind shear and the warm waters of the South China Sea allowed Dot to reach typhoon intensity. Peaking at an intensity of 100 kt (51 m/sec) on 9 June (Figure 3-05-4), the typhoon then weakened as it approached and crossed southern Hainan Island. Dot crossed the Gulf of Tonkin as a tropical storm and made landfall near Haiphong, Vietnam at 110600Z. It dissipated six hours later in the mountains northwest of Hanoi.




Figure 3-05-2. Based on the surface wind and pressure plots for 061200Z, the isobaric analysis shows the large size of the circulation.




Figure 3-05-3. Objective guidance and the forecast from 071800Z through 24, 48 and 72 hours. Note: the displacement of the 071800Z starting point to the north of the best track. This is the result of adjustment to the best track caused by later data.





Figure 3-05-4. Nearing peak intensity, Typhoon Dot tracks towards Hainan Island (082225Z June DMSP visual imagery).



TROPICAL STORM ELLIS (06W)

The second of two tropical cyclones to form in June, Ellis interrupted the series of "straight runners" that occurred from Typhoon Brenda (03W) through Typhoon Dot (05W). After five days as a poorly defined system, Ellis briefly peaked at tropical storm intensity before becoming extratropical and making landfall in Japan. (This tropical cyclone provided the first opportunity for JTWC to use the newly instituted Tropical Depression Warning format as stated in a change to USCINCPACINST 3140.1T. This change addressed warnings when the depression was not expected to reach tropical storm intensity. These warnings were to be issued every twelve hours instead of every six hours as is the case for Tropical Cyclone Warnings.)

On 18 June, a disturbance formed in the Philippine Sea 210 nm (390 km) northwest of Guam and was mentioned on the Significant Tropical Weather Advisory. The disturbance was classified as having poor potential for further development, due to the lack of favorable upper-level support. It appeared that the proximity of the TUTT to the north through northeast restricted the outflow from the convection. However, the next Advisory was reissued at 192100Z to upgrade the potential for further development to fair after the central convection flared at the morning convective maximum and synoptic data revealed the development of the low level cyclonic A Tropical Cyclone Formation circulation. Alert followed at 200430Z when the deep convection had persisted. Within ninety minutes, the first Tropical Depression Warning The application of the Tropical was issued. Depression Warning was appropriate since this depression (Figure 3-06-1) appeared deeply embedded in the monsoon trough and further development was unlikely. At 201800Z, the second, and final, Tropical Depression Warning followed as the poorly defined cloud system weakened 450 nm (835 km) east of Luzon.

As the disturbance moved westward toward Luzon, the 200 mb pattern underwent a substantial change. On 18 June, a narrow ridge aloft with an east to west orientation extended through the Bonin Islands (south of Japan). Simultaneously, a weak trough existed across Korea and western Honshu. Short waves exiting China deepened this trough until it extended southward from the Yellow Sea to Taiwan. The rawinsonde data from Okinawa (WMO 47936) showed 60-meter height falls at 200 mb from 19 to 20 June. This adjustment of the upper-level pattern favorably positioned divergence over the remnants of the tropical depression.

With synoptic data indicating minimum sea-level pressures near 1001 mb, the next convective flare up prompted a second Alert at 211900Z. Then, with the synoptic situation unchanged, a third Alert followed 24 hours later. This Alert addressed the fact that the maximum winds were displaced 180 nm (335 km) east of the system's center. asymmetric displacement of a broad area of gales away and to the east of the low-level circulation center was unusual and accompanied Ellis for the remainder of its lifetime. At 222100Z, JTWC issued the first Tropical Cyclone Warning on Tropical Depression 06W (Figure 3-06-2). The system was forecast to move slowly toward the northeast, steered by the southwesterly flow ahead of the trough. Further, it would only reach minimal tropical storm intensity before encountering increased vertical wind shear and cooler air behind a stationary front. The front had pushed south of Okinawa during the preceding three days.

While the intensity was correctly forecast, Tropical Storm Ellis led JTWC on a high speed chase, doubling its forward speed from 12 to 24 kt (6 to 12 m/sec) as it sped toward Okinawa. By the fourth warning at 231200Z, Ellis was becoming extratropical, having linked with the previously mentioned stationary front; but it was not weakening. The

system passed 90 nm (165 km) east of Kadena AB. Kadena (WMO 97931) provided two radar fixes on Ellis, as it passed by, and reported peak gusts to 22 kt (11 m/sec). The system passed over Kyushu and extreme western Honshu

before dissipating over the Sea of Japan on 24 June. Although gales persisted as Ellis continued northward, no reports of major damage or fatalities were received.




Figure 3-06-1. Nighttime visual picture of the disorganized cloud signature of the tropical depression after the first warning. Bright moonlight makes the image look like daytime. Note the city lights of Taiwan (201327Z June DMSP visual imagery).





Figure 3-06-2. Ellis starts moving northward towards Okinawa (222106Z June DMSP visual imagery).



TROPICAL STORM FAYE (07W)

After a two-week break in activity, Faye was the first of seven tropical cyclones to form in July. It formed in the monsoon trough and intensified at a normal rate as it tracked west-northwestward towards the Philippines. Faye weakened as it crossed north-central Luzon and reintensified slightly in the South China Sea. It weakened again in the central South China Sea, and crossed the island of Hainan before making landfall on the coast of northern Vietnam.

On 4 July, a surge in the southwest monsoon caused a widespread increase of convective activity in an area west of the Mariana Islands. This convection was short-lived — peaking at 050000Z and dissipating for the most part by 051200Z. Out of the remnants of this convection arose a small area of deep convection near 15° north latitude and 130° east longitude. This deep convection continued to

develop after the early morning convective maximum, and at 060200Z a Tropical Cyclone Formation Alert was issued on the disturbance. The first tropical cyclone warning on Tropical Depression 07W followed at 060600Z. At that time, the depression had a partially exposed low-level circulation to the north of the deep convection with restricted upper-level outflow in the northern semicircle. This displacement of convection introduced some uncertainty in the location of the low-level circulation center (Figure 3-07-1) until first light the next day.

A short wave trough passing to the north induced a small northward shift in track during the first 24 hours in warning. As the short wave trough moved eastward, the subtropical ridge strengthened to its west and the depression began moving to the west. Continued development resulted in an upgrade to tropical




Figure 3-07-1. After the last visual fix at 060730Z (point A), plots of satellite fixes (encircled) through the night show that cold cloud top targets on the infrared imagery can be misleading. The visual data the next day at 062330Z (point B) enabled the forecaster to get the weak circulation back on track.

storm intensity at 070600Z. Throughout the next 24 hours, the subtropical ridge remained unchanged and Faye tracked westward and intensified.

Tropical Storm Faye reached its peak intensity of 60 kt (31 m/sec) at 081200Z, just prior to making landfall in north-central Luzon. Remarks from the radar site at Baguio (WMO 98321) about the change of wind direction from northwest to southwest and 35 kt (18 m/sec) gusts proved invaluable in tracking Faye as it accelerated over Luzon and retained tropical storm intensity as it entered the warm waters of the South China Sea late on 8 July. Moving out into open waters, it began to reintensify. In the central South China Sea, Faye moved into an

environment of strong upper-level northeasterlies which began to shear the system. Despite this strong shear, Faye (Figure 3-07-2) retained much of its convective organization and its tropical storm intensity until it reached the island of Hainan.

Late on the 10 July, Faye crossed northern Hainan causing telecommunication interruptions and the destruction of pepper, sugar cane and coffee crops. It was downgraded to a tropical depression as it entered the Gulf of Tonkin. The low-level circulation, which was displaced 45 nm (85 km) from the deep convection, made landfall near Haiphong, Vietnam at 110600Z and quickly dissipated.





Figure 3-07-2. The exposed low-level circulation center is evidence of a shearing regime in the South China Sea (090607Z July NOAA visual imagery).

Intentionally left blank.



SUPER TYPHOON GORDON (08W)

The second super typhoon in the western North Pacific for 1989, Gordon was also the second of seven significant tropical cyclones to form in July. The system was unique in that it developed from a single cumulonimbus directly beneath a cyclonic cell in the Tropical Upper-Tropospheric Trough (TUTT). The cumulo-

nimbus was initially small, but underwent a dramatic rapid, almost explosive, deepening phase.

At the start of the second week of July, Tropical Storm Faye (07W) was affecting the Philippine Islands. Aloft, the TUTT, which




Figure 3-08-1. Typhoon Gordon four hours before reaching super typhoon intensity. The eye diameter is 20 nm (37 km) (142304Z July DMSP visual imagery).

extended eastward, was the major uppertropospheric feature. It overlaid an extensive cloud minimum area that extended eastward to the date line. Just to the west of Wake Island on 9 July, a discrete cloud system became associated with a deep TUTT low.

On 11 July after the early morning convective maximum, a very small, ragged central dense overcast persisted, and the Significant Tropical Weather Advisory was reissued at 110200Z to include the system. Subsequent satellite imagery indicated the system's vigorous central convection was expanding rapidly, too rapidly to enable JTWC to issue a Tropical Cyclone Formation Alert. As a result, an abbreviated warning was issued on Tropical Depression 08W at 110400Z, followed by the first 72-hour warning at 110600Z. This development was unusual. Gordon appeared to blossom directly beneath the upper cold low. This was in contrast to the normal sympathetic development of convection to the south and east of the upper low (Sadler, 1976). To our knowledge such a distal development has never been documented. Sadler (1974) does discuss a similar development where convection wraps around the TUTT cell, finally converting the cold-core cyclone to a warm-core one. This is generally a slow process. He also alludes to occasional cumulonimbus near the center of TUTT cells as a clue to locating their centers, but does not discuss the development of tropical cyclones from the thunderstorms.

The system's track was west-southwest to westward for two days, becoming west-northwestward as Gordon approached the Philippine Islands. The guidance from the NOGAPS fields correctly foretold that no break in the subtropical ridge would occur, and that Gordon's westward movement would be uninterrupted.

Initially, forecasters expected slow to normal intensification as the TUTT restricted the system's upper-level outflow. However, the depression was quickly upgraded to Tropical




Figure 3-08-2. Gordon's rapid intensification after 140000Z compared with an increase of one "T" number per day.

Storm Gordon 24 hours after the initial warning, to typhoon after 48 hours, and to super typhoon after 96 hours (Figure 3-08-1). In only 30 hours from 140000Z to 150600Z, Gordon intensified rapidly - two-and-one-half "T" numbers (Figure 3-08-2). This represents an estimated 70-mb fall in central pressure over this period, or a deepening rate of 2.3 mb/hr, just short of the 2.5 mb/hr required for explosive deepening (Dunnavan, 1981).

Super Typhoon Gordon slammed into the rice-producing region of northern Luzon with maximum sustained winds of 140 kt (72 m/sec). News reports indicated that 27 people died, 15 were missing, at least 120,000 were evacuated and thousands were left homeless in its wake. To the south, the peak winds reported from US military installations in the Philippines were 68 knots (35 m/sec) at Wallace AS, 54

knots (28 m/s) at John Hay AB, 40 kt (21 m/sec) at Cubi Point NAS (WMO 98426), and 18 kt (9 m/sec) at Clark AB(WMO 98327). John Hay AB also recorded a total of 29.8 inches (747 mm) of rain. The SS OVERSEAS VIVIAN reported 35 kt (18 m/sec) sustained winds as it approached Subic Bay late on 15 July when Gordon was more than 200 nm (370 km) away.

After exiting northern Luzon, the

typhoon moved west-northwestward across the South China Sea and passed 100 nm (185 km) to the southwest of Hong Kong at 171800Z (Figure 3-08-3). U.S. Navy ships in port at Hong Kong had sortied 24 hours earlier. Though the system was weakening as it made landfall near the coastal city of Zhanjiang, 215 nm (398 km) west-southwest of Hong Kong, where Gordon inflicted more fatalities and property loss. The final warning was issued at 181200Z, as Gordon left the Leizhou peninsula.




Figure 3-08-3. The large ragged eye is visible as Tropical Storm Gordon moves southwest of Hong Kong (180126Z July DMSP visual imagery).

During the next three hours, Gordon's area of convection (Figure 3-08-4) expanded nearly three times in size as it moved across the shallow, warm waters of the Gulf of Tonkin. Synoptic data indicated continued weakening

during the convective expansion. The remnants of Gordon were identifiable on satellite imagery for the next 24 hours as the dissipating system moved into the mountains of northern Vietnam.






Figure 3-08-4. Tropical Storm Gordon (above) enters northern Gulf of Tonkin (181115Z July DMSP enhanced infrared imagery) and (below) Gordon's area of convection expands rapidly (181407Z July DMSP enhanced infrared imagery).



Intentionally left blank.



TROPICAL STORM HOPE (09W)

The third of seven tropical cyclones to form in July, Hope was a TUTT-induced tropical cyclone that failed to develop to typhoon intensity as a result of the upper-level shear from outflow from Super Typhoon Gordon (08W). During its life, Hope moved generally northwestward, occasionally "stair-stepping" in response to the passage of a series of mid-latitude short-wave troughs. Although no binary interaction was apparent, the tropical cyclone tracked along the periphery of Gordon's low-level inflow for most of its lifetime.

Hope generated in the wake of Gordon (08W) in a broad area of convection enhanced by the divergence aloft associated with a TUTT When the convection persisted for more than 18 hours, it was included as a suspect area on the Significant Tropical Weather Advisory at 130600Z. Synoptic data indicated a low-level cyclonic circulation embedded in the convection. Surface winds were estimated to be 10 to 20 kt (5 to 10 m/sec) and the MSLP 1007 mb. During the next 48 hours, the convection became disorganized due to increased vertical wind shear aloft from Super Typhoon Gordon (08W), which was intensifying to the west. A weak surface circulation persisted in the synoptic data.

At 151740Z JTWC issued a Tropical Cyclone Formation Alert when Hope's central convection increased after the combined

restrictive effects of the passage of a midlatitude trough to the north and outflow from Gordon (08W) to the west decreased. Winds in the area were estimated to be 20 to 30 kt (10 to 15 m/sec). The first warning followed at 160000Z. Tropical Depression 09W tracked westward for the next 18 hours under the influence of the building mid-tropospheric subtropical ridge to the north. The low-level circulation center remained partially exposed until 161800Z, when a central dense overcast formed. In response, Hope intensified to 35 kt (17 m/sec) and was upgraded to a tropical storm.

Late on 16 July, Hope's track returned to the northwest in contrast to the guidance provided by the NOGAPS forecast fields, which indicated the subtropical ridge would remain intact despite the approach of a series of shortwave troughs. The NOGAPS guidance was reinforced by the statistical-dynamic aid As a result, JTWC adjusted the forecast track southward with each succeeding warning until, by 171800Z, Hope was forecast to pass near Taiwan. However, the tropical cyclone remained north of the forecast track and slowly intensified. Kadena AB (WMO 47931) on Okinawa, approximately 100 nm (185 km) northeast of the tropical storm, measured a peak gust of 31 kt (16 m/sec) at 180411Z.

From 180000Z through 191800Z the

synoptic situation was complex (Figure 3-09-1). Hope responded to another short-wave trough and tracked north-northwestward. Once again JTWC abandoned the westward track into China and changed the forecast track to take Hope through a possible break in the subtropical ridge into the East China Sea and then on to Korea. The change in track was prompted by several factors: (1) the failure of the expected westward movement to develop, (2) the

possibility that NOGAPS was overforecasting the strength in the ridge to the north, (3) the expectation that Hope would remain a shallow system and be influenced by the more southerly low- to mid-level steering flow rather than the weak easterly mid- to upper-level flow, and (4) guidance from the dynamic aid OTCM. However, after the passage of another shortwave trough, the ridge strengthened north of Hope. At 200000Z, the tropical storm (Figure




Figure 3-09-1. Complex synoptic situation with Gordon (08W) to the west, and the mid-latitude trough to the north. The island of Okinawa is nearby (172338Z July NOAA visual image.;').

3-09-2) executed an abrupt turn to the west and moved into mainland China.

While Hope was over warm ocean waters, it intensified slowly, reaching its peak intensity of 55 kt (27 m/sec) at 181800Z. However, the northeasterly upper-level flow restricted Hope's outflow and prevented further development into a typhoon. Hope was down-

graded to a tropical depression at landfall. The tropical cyclone weakened rapidly as it moved over land, and the final warning was issued at 210000Z. News reports indicated that at least 24 people died and more than 1000 were injured in eastern China. In addition, landslides and widespread flooding resulted from locally heavy rains. Totals up to 7.5 inches (109 mm) in 24 hours were recorded in some areas.





Figure 3-09-2. Hope near landfall. The low-level anticyclonic flow (indicated by the curved arrow) in the subtropical ridge is defined by the cumulus streets across southern Korea, coastal China, and the brightness pattern in the lee of Kyushu. Frontal cloudiness associated with the passing trough trails across central Korea and the Yellow Sea (200046Z July DMSP)



TROPICAL STORM IRVING (10W)

Tropical Storm Irving was the fourth tropical cyclone of 1989 to cross the South China Sea and the last to enter the South China Sea until Typhoon Brian (27W) late in September. In August and September the tropical cyclone tracks shifted northward. Irving was short-lived and actually reached its maximum intensity as it made landfall on the coast of northern Vietnam.

As Super Typhoon Gordon (08W) was about to make landfall on the coast of China and Tropical Storm Hope (09W) was reaching peak intensity, the disturbance that would eventually develop into Irving formed on 18 July in the monsoon trough near the southwestern Caroline Islands. The disturbance moved slowly northwestward across the Philippine Sea. Synoptic data at 190000Z July indicated a surface circulation, and the disturbance was

considered a suspect area on that day's Significant Tropical Weather Advisory.

The disturbance crossed the Philippine Sea from southeast of Palau to over the Philippine Islands in three days. The lowest observed minimum sea-level pressure was 1004 mb. Once in the South China Sea, the disturbance became better organized and JTWC issued a Tropical Cyclone Formation Alert at 202000Z. The first warning on Tropical Depression 10W was issued four hours later. The depression was upgraded to tropical storm intensity at 210600Z.

The tropical easterly jet was weakly established across the Southeast Asia; still, the vertical wind shear over the South China Sea due to the northerly flow aloft was sufficient to prevent Tropical Storm Irving (Figure 3-10-1)




Figure 3-10-1. Vertical wind shear is responsible for the separation between the low-level circulation center and the bright cloud tops to the southwest. The area of cloudiness at the top right of the picture is the remnants of Tropical Storm Hope (09W) over eastern China (NOAA visual imagery 220533Z July).

from reaching typhoon intensity. Throughout Irving's lifetime, the upper-level cloud circulation center was located southwest of the low-level center. As a result, the nighttime infrared satellite fixes of the upper-level cloud features were displaced to the southwest of the low-level circulation center. This tilt to the system also resulted in differences between the radar and corresponding satellite fixes.

Based on satellite imagery, Irving was downgraded to a tropical depression on the 230600Z warning. However, a reanalysis of the imagery indicated Irving actually continued to intensify as it entered the warm waters of the

Gulf of Tonkin. In addition, the Gulf of Tonkin is a natural region of forced low-level convergence due to the surrounding topography. The 240000Z warning upgraded the system again to tropical storm intensity. Irving was downgraded for a second time to a tropical depression on the final warning when it moved into northern Vietnam at 240600Z.

The remnants of Irving moved across the mountains and dissipated over Laos. News reports estimated that at least 102 people died and another 488 were injured in Vietnam. In addition, more than 80,000 houses and 160,000 acres of crops were destroyed.


Intentionally left blank.


TYPHOON JUDY (11W)

The second of two typhoons to develop during the month of July, Judy formed just west of Guam in the monsoon trough and followed a north oriented track with a critical turn to the northwest, just to the south of Honshu. It crossed the southern coast of Kyushu, made landfall on the south coast of the Korean Peninsula and dissipated rapidly.

As Tropical Storm Hope (09W) weakened over China, two tropical cyclones developed in the monsoon trough which was located near 10° north latitude. First, on July 20, Tropical Storm Irving (10W) developed in the South China Sea. The following day Judy developed 300 nm (555 km) west of Guam. The disturbance that was to become Judy was first mentioned on the Significant Tropical Weather Advisory at 200600Z as a slowly moving tropical disturbance with a poor potential for further development. The potential was upgraded to fair the following day. At 212000Z, JTWC issued a Tropical Cyclone Formation Alert based on synoptic data that indicated a low-level cyclonic circulation beneath an upper-level anticyclone and satellite imagery that showed increased convection and organization.

As the disturbance's organization and upper-level outflow continued to improve, the first warning followed for Tropical Depression 11W at 220600Z when satellite intensity analysis indicated surface winds of 25 kt (13 m/sec). A cyclonic circulation in the Tropical Upper Tropospheric Trough (TUTT)(Sadler, 1976) to the northwest of the depression provided a source of upper-level divergence needed for further intensification. At 230000Z. the depression was upgraded to tropical storm intensity when satellite analysts estimated 35-kt (18-m/sec) surface winds were present. Judy continued to intensify as the system stayed southeast of the TUTT low, a favorable position for development. At 250600Z, it was again upgraded — this time to a typhoon (Figure 3-11-1). Although most ships avoided Judy's dangerous winds, the moored buoy (WMO





21004) at 29° north latitude and 135° east longitude provided valuable data to track Judy. Fifty-seven-knot (29 m/sec) winds and a minimum sea-level pressure of 974 mb were recorded as the typhoon passed close by.

Using NOGAPS and satellite data as a guide, JTWC forecast Judy to track northward to Japan and then recurve to the northeast. In contrast, OTCM guidance suggested a northwestward track from the start. When the subtropical ridge did finally build in from the east, OTCM was discounted since all the previous model guidance (Figure 3-11-2)

indicated a northwest track while July tracked north. By comparison, Figure 3-11-3 shows JTWC's initial success with the track forecasts. However, after the direction change on 26 July, it took a day for the forecasts to get back on track to the northwest. This situation highlighted the value of the alternate scenario and rapid communications between the customer and the forecaster when forecast difficulties arise.

Judy's interaction with the southern coast of Kyushu at 271800Z resulted in rapid weakening. This trend continued until the




Figure 3-11-2. Comparison of OTCM guidance with the best track. After 251800Z July (point A), the guidance proved correct.




Figure 3-11-3. JTWC forecasts compared with the best track. The major track change to the northwest on 26 July was not reflected in the forecasts until the next day.

tropical cyclone (Figure 3-11-4) made landfall approximately 110 nm (205 km) southwest of Pusan, Korea. By the time Judy reached Osan AB near Seoul, it had weakened significantly. Osan AB (WMO 47122) reported maximum

winds of 22 kt (11 m/sec). At 290000Z, the final warning was issued as the remnants of the system moved towards the Sea of Japan. No reports of damage were received.





Figure 3-11-4. In the Korea Straits, Judy is about to be downgraded to a tropical storm (280430Z July DMSP visual imagery).

Intentionally left blank.



TROPICAL DEPRESSION 12W

While Typhoon Judy (11W) was tracking northwestward towards Korea, an area of deep convection became persistent to the south-southeast of Judy. This persistent convection, first mentioned in the Significant Tropical Weather Advisory for 27 July, looped around in the monsoon trough and headed west, passing 50 nm (80 km) south of Okinawa at 281200Z. The discovery of a well-developed low-level circulation and falling pressures

prompted the issuance of a Tropical Cyclone Formation Alert at 290630Z, followed by the first Tropical Depression Warning at 291200Z. Because of strong vertical wind shear, the depression was not forecast to intensify to a minimal tropical storm. After the last warning at 300000Z, the deep convection sheared away and continued westward into China while the dissipating low-level circulation tracked southward into the Taiwan Strait.





Figure 3-12-1. TD 12W shortly after the first warning (291131Z July DMSP infrared imagery).



TROPICAL STORM KEN-LOLA (13W-14W)

Tropical Storm Ken-Lola underscored the limitations of remote sensing for locating poorly organized systems. Synoptic data proved invaluable in identifying and classifying the system while in warning status and in the post-analysis. While in warning status, JTWC considered the system as two separate tropical cyclones. A detailed post-analysis, even though not absolutely conclusive, strongly suggested that Tropical Storms Ken and Lola were probably the same system. The system generated in the monsoon trough that had already proven itself the most active since July 1973. The system then took an elongated cycloidal track, passing close to Okinawa before making landfall on the coast of eastern China.

In the last week of July, as Tropical Depression 12W tracked through the southern Ryukyu's and Typhoon Judy (11W) dissipated in the Sea of Japan, an active monsoon trough with several small embedded circulation centers extended across Taiwan, eastward to 140° east longitude. A pool of warmer than normal sea surface temperatures engulfed the southern Ryukyu's and extended southeastward to 130° east longitude. On 29 July, synoptic data indicated that a circulation center in the lowlevel wind field formed over the warm pool about 300 nm (555 km) southeast of Okinawa. While the circulation had a central pressure of 995 mb and winds near the center of only 15 kt (8 m/sec), a broad area of southwesterly monsoonal gales extended 100 to 300 nm (185 to 555 km) south of the center. The first mention of the disturbance appeared on that day's Significant Tropical Weather Advisory as a suspect area having fair potential for development.

Further evaluation of the 290600Z synoptic data and subsequent satellite imagery led to issuance of a Tropical Cyclone Formation Alert at 290930Z even though the low-level cyclonic circulation center was displaced to the north of the associated convection. Improving organization during the subsequent 18 hours prompted the first warning on Tropical Depression 13W at 300400Z. The depression was forecast to move northward, along the periphery of the monsoon gale area, and loop cyclonically around a mid- to upper-level low located between the depression and Okinawa. This low aloft would restrict the depression's outflow and result in slow development and peaking below typhoon intensity. JTWC correctly forecast the overall character of the track and the limited intensity.

At 300900Z, the second warning valid at 300600Z, was amended to upgrade the depression to Tropical Storm Ken, when synoptic data showed the maximum sustained winds were 45 kt (23 m/sec). For the next 18 hours fixes from (mostly nighttime) satellite imagery indicated continued northeast movement until the final warning was issued at 310000Z. JTWC expected Ken to shear apart and follow the monsoon surge around the northern periphery of an exposed low-level circulation that later would be called Lola. Post-analysis suggests that the 310000Z

position was most likely 250 nm (465 km) northwest of the warning position (Figure 3-13-1) and that the low-level system had moved northwestward since 301200Z.

At 310600Z, JTWC issued a Tropical Cyclone Formation Alert for a disturbance located about 300 nm (555 km) northeast of Okinawa. The satellite imagery (Figure 3-13-2) indicated an exposed low-level center with increasing convection to the south. This system now had gales extending several hundred miles north of the center. At 311030Z, an abbreviated

warning on Tropical Storm Lola was issued after the USS Dubuque (LPD8) reported sustained winds of 50 kt (26 m/sec) at 310300Z followed by 40 kt (21 m/sec) and falling surface pressure three hours later. Also, at 0600Z, another ship (call sign 9MTS) reported westerly winds approximately 90 nm (165 km) south of the USS Dubuque. These data demonstrated that the winds reported by the Dubuque were associated with a circulation center and not the tight pressure gradient near Japan (Figure 3-13-3), as initially thought.




Figure 3-13-1. Ken's expected track verses the best track.




Figure 3-13-2. Imagery supporting the final warning on Tropical Storm Ken and formation of Lola. Note remnants of TD12W in the Taiwan Strait (310025Z July DMSP visual imagery).




Figure 3-13-3. Wind and pressure reports from the USS Dubuque (LPD8) from 300000Z through 311200Z July with a report from ship 9MTS at 310600Z help define the circulation center. Tropical storm symbols represent six-hourly best track positions for Tropical Storm Ken-Lola.

The first 72-hour forecast for Lola followed at 311200Z. The problems that aggravated this initial warning were the inconsistencies between fix platforms. Radar fixes were displaced to the west of the satellite fixes and suggested the system was moving rapidly southwestward. In contrast, the satellite fixes, based on cold cloud tops on infrared imagery, implied slow westward movement. Based on the prevailing northeasterly steering flow, the system was forecast to track west-southwestward and pass about 100 nm (185 km) northwest of Okinawa.

In a short time an understanding of the track became clearer. The radars were tracking a band of convection that was spiraling around the mid-level low. Also, the pressure at Kadena AB (WMO 47931) on Okinawa was not falling

rapidly indicating Lola probably was not tracking rapidly to the southwest as had been suggested by the radar fixes. As a consequence, JTWC slowed the forecast speed of movement and angled the track towards Taiwan.

The mid-level cyclone appears to have been the major influence on Ken-Lola's track (Figure 3-13-4). In fact Ken-Lola's path described a elongated cycloid with the storm representing a point on the rotating "rim" of the westward moving 500 mb "wheel". The track made a cusp near Okinawa as the 500 mb center passed to the west of the system. The mid-level low pulled Ken-Lola northward and then westward into the East China Sea.

Kadena AB (WMO 47931) recorded peak winds of 30 kt (15 m/sec) as the system




Figure 3-13-4. Spatial relationship between the tropical cyclone and accompanying 500 mb circulation center. Minimum 500 mb heights are in meters. Positions are for 0000Z from 29 July through 4 August.

passed within 80 nm (150 km) between 011800Z and 020000Z (Figure 3-13-5). The USS Dubuque (LPD 8), which remained near Okinawa, reported 35-kt (18- m/sec) winds at 020600Z that decreased to 24 kt (12 m/sec) by 021200Z.

On 3 August, a building ridge over Manchuria caused Ken-Lola to take a more westward track toward Shanghai. Due to

concern that a trough, approaching eastern China could reverse the tropical cyclone's track and take it northeastward into the Yellow Sea and Korea, the warnings continued until 041800Z when it was more than 250 nm (465 km) inland. The low relief and wetlands of the Yangtze River Valley allowed the weak circulation to maintain itself inland for several days. No reports of damage were received.





Figure 3-13-5. Ken-Lola nears Okinawa. Typhoon Mac (15W) is at the lower right (012344Z August DMSP visual imagery).



TYPHOON MAC (15W)

The first typhoon of August, Mac developed at a higher than average latitude. Its track and intensity were influenced by a complex mid-latitude synoptic regime and complicated by a multi-storm environment. JTWC and NOGAPS had considerable difficulty distinguishing between short-term and long-term trends. Developing northeast of the Mariana Islands, Mac began with a general northwest track, moved westward 48 hours, then accelerated on a northwestward track and made landfall northeast of Tokyo. Mac weakened rapidly as it moved into and across the Sea of Japan, and finally dissipated over southern Sakhalin Island.

As the most active July since 1973 came to a close, Typhoon Judy (11W) was dissipating over Korea and Tropical Storm Ken-Lola (13W) was threatening Okinawa. At the same time, an

area of convection developed approximately 600 nm (1111 km) northeast of Saipan in an extremely active monsoon trough that extended as far east as Wake Island. The 300000Z July surface analysis indicated that a low-level cyclonic circulation with a 1008 mb pressure was associated with an area of disturbed weather. JTWC classified the disturbance as having poor potential for further development on the 300600Z Significant Tropical Weather Subsequent synoptic reports Advisory. indicated that the central pressure had decreased to 1006 mb and surface winds had increased. Thus, JTWC reissued the Significant Tropical Weather Advisory at 301000Z to upgrade the disturbance's potential to fair.

The disturbance's central convection increased and additional synoptic reports indicated that the central pressure had fallen to




Figure 3-15-1. Mac's cirrus outflow (at left) is impressive compared to Ken-Lola (13W-14W) (012344Z August DMSP visual imagery).

1000 mb. The surface winds north of the system were 20 to 25 kt (10 to 13 m/sec) and monsoon gales were present to the south. JTWC issued a Tropical Cyclone Formation Alert at 310400Z with the disturbance moving to the southeast. Subsequent fix information indicated that the disturbance had actually made a cyclonic loop and was moving northwestward out of the Alert area. In response, JTWC reissued the Alert at 311700Z.

While the first warning on Tropical Storm Mac was issued at 010000Z August, post-analysis indicated that the system did not reach tropical storm intensity until 12 hours

later. The first series of forecasts called for Mac to track northward along the 150° east meridian. Due to the mid-tropospheric subtropical high weakening, the early stages of the forecasts verified well — as Mac tracked north-northwestward for the next 36 hours.

While Tropical Storm Ken-Lola (13W-14W) was in the vicinity of Okinawa on 2 August, JTWC changed its forecast outlook on Mac (Figure 3-15-1). The 020600Z warning had Mac moving westward along 30° north latitude in the 48- to 72-hour period as a complex series of events began to unfold. At the same time as a long-wave trough moved




Figure 3-15-2. At peak intensity, Mac is surrounded by a ring of subsidence (032304Z August DMSP visual imagery).

eastward into the Sea of Japan, a large TUTT cyclone began to tumble rapidly westward from the date line. While the TUTT cell moved northwest of Mac, the mid-tropospheric subtropical ridge strengthened, placing Mac under the influence of easterly flow. This was similar to events that had recently forced Typhoon Judy (11W) to move westward. JTWC would remain with the westward track along 30° north latitude for the next nine warnings.

The westward movement began much earlier than forecast, in fact, along 27° instead of 30° north latitude and within 12 hours instead of 48 hours. Mac continued the westward movement for the next 48 hours reaching typhoon intensity at 030300Z. JTWC had high confidence in its forecast as NOGAPS built a high over the Sea of Japan and most of the objective techniques supported slow westward movement. Confidence was further heightened when Mac began tracking west-southwestward at 030000Z. JTWC forecasters recognized the unfavorable upper-level regime and displayed great success with the intensity forecasts. Mac reached its peak intensity of 80 kt (41 m/sec) at 031800Z (Figure 3-15-2).

During its westward track, an ominous slowing of Mac's forward speed occurred. At 040600Z Mac was moving very slowly westsouthwestward. The 040000Z analysis indicated that a jet maximum approaching the trough axis which could deepen the trough. The Prognostic Reasoning accompanying the 040600Z warning did mention recurvature as a low-probability alternate scenario. JTWC's westward scenario was reinforced by the movement of a high from Mongolia to coastal Manchuria. Forecasters thought the continued eastward movement of that high and Mac's westward movement would allow the typhoon to escape the influence of the digging trough as ridging reestablished itself to Mac's north.

In the meantime, the TUTT cell that had tumbled westward slowed down and linked up with the mid-latitude trough in the Sea of Japan. This blocked significant eastward movement of the high over Manchuria and changed Mac's steering flow from westward to northward around the east side of the the TUTT cell. JTWC added northward movement to the Prognostic Reasoning accompanying that 041200Z warning as a moderate probability alternate scenario. At 041800Z, the westward forecast was abandoned as Mac made a slow move northward and the new 041200Z NOGAPS no longer showed the high building over the Sea of Japan. JTWC swung the forecast track to the northwest toward Osaka near the 72-hour point. JTWC remained with that forecast for the next two warnings.

Meanwhile Mac had accelerated from 3 kt (6 km/hr) at 041200Z to 13 kt (24 km/hr) toward the north-northwest at 050600Z as it ran along the east side of the TUTT cell. The TUTT cell was expected to resume its normal southwestward movement causing Mac to resume a northwestward track toward Osaka. This reasoning was reinforced by height falls occurring west of Tokyo.

By 051200Z, Mac had accelerated to 17 kt (32 km/hr). At this time, JTWC shifted the forecast track to pass 180 nm (335 km) east of Tokyo within 24 hours. Satellite fixes indicated a northward movement and subsequent radar observations from Tori-Shima (WMO 47639) confirmed the north-northwestward track. In addition, the TUTT cell and an upper-level low over the northern Sea of Japan linked producing an extended trough. Mac would now maintain a forward speed of 17 kt (32 km/hr), or more, during the next 30 hours.

After 051800Z, Mac shifted from a north-northwestward course to a more north-westward course, as the tough in the Sea of

Japan began to weaken. Mac finally passed east of Tokyo at 060700Z, but only by 60 nm (111 km) with an intensity of 45 kt (23 m/sec) (Figure 3-15-3). The tropical cyclone made landfall at 061000Z. At 061200Z, Mac was downgraded to tropical storm intensity, however, post-analysis indicates Mac was a tropical storm at least six hours earlier.

Mac weakened while crossing Japan, but without the benefit of satellite intensity analysis and availability of continuous observations, JTWC conservatively maintained Mac at tropical storm intensity until 070600Z. MAC actually entered the Sea of Japan, near Sakata, as a tropical depression at 061700Z. The final warning on Tropical Depression 15W was issued at 071800Z. The remnants turned northeastward and dissipated over southern Sakhalin island on 8 August.





Figure 3-15-3. Mac approaches Japan (060438Z August NOAA visual imagery).

Intentionally left blank.



TYPHOON OWEN (16W)

Typhoon Owen generated in the monsoon trough and intensified slowly while moving on a general northwest to northward track. Due to the proximity* of Typhoon Nancy (17W) to the east, Owen took more than a week to reach tropical storm intensity. Later, its binary interaction with Typhoon Nancy (17W) resulted in an unusual southeastward track during its developing stage. Then, the tropical cyclone followed Nancy (17W) through recurvature, extratropical transition and into high latitudes.

The initial disturbance that spawned Typhoon Owen began as an area of convection in the monsoon trough south of Pohnpei in the eastern Caroline Islands. After the convection persisted for 24 hours, JTWC included the disturbance as a suspect area on the Significant Tropical Weather Advisory at 040600Z. Synoptic data indicated a weak low-level circulation under easterly flow aloft. During the next six days, the amount and organization of the convection associated with the disturbance fluctuated as the monsoon trough repositioned further north. Finally convection consolidated beneath upper-level an anticyclone, prompting JTWC to issue a Tropical Cyclone Formation Alert at 100600Z.

During the next 18 hours, the system continued to organize, although its upper-level outflow was restricted by a TUTT cell centered four to five degrees latitude to the northnorthwest. At 110000Z, JTWC issued a 36 hour tropical depression warning on Tropical Depression 16W and forecast no intensification because of its proximity to the TUTT cell. The tropical cyclone tracked northeastward along the monsoon trough axis and through the northern Mariana Islands for the next 18 hours. influenced both by the TUTT cell and by Tropical Depression 17W. By 120000Z, a well-defined upper-level anticyclone had established itself over Owen, and the system improved its organization and convection. Anticipating further intensification, JTWC transitioned to a regular 72-hour warning. At 121200Z, the depression reached tropical storm intensity based on satellite intensity estimates. By this time, a binary interaction with Nancy (17W) was beginning to influence Owen's track and resulting in a slow southeastward movement until 131200Z. (For specific diagrams of this binary interaction, please see the following article on Typhoon Nancy (17W). Owen became a typhoon at 131800Z and reached its peak intensity of 75 kt (38 m/sec) at 141200Z.

^{*} If formative tropical cyclones are separated by distances of less than fifteen degrees, interaction (at the expense of one, or the other) between the two circulations is often observed.

As Owen followed Nancy (17W) to the north-northwest, the recently formed eye began to fill (Figure 3-16-1). With the subtropical ridge close by, at 161500Z, Owen weakened to tropical storm intensity and began to be buffeted by upper-level westerly flow. Twelve hours later Owen recurved around the ridge and

accelerated to the northeast. At 180000Z, JTWC issued its final warning on Owen as it crossed 40° north latitude and was becoming extratropical. During its lifetime, Owen was a threat primarily to maritime interests. No reports of damage or loss of life were received.





Figure 3-16-1. Typhoon Owen with a cloud filled eye follows Nancy (17W) north-northwestward (142243Z August DMSP visual imagery).



TYPHOON NANCY (17W)

Of the eight August tropical cyclones, Nancy was the third typhoon. It underwent a prolonged binary interaction with Typhoon Owen (16W), tracked rapidly toward Japan, then abruptly turned northward, and finally became extratropical.

The disturbance that eventually became Typhoon Nancy appeared as an area of persistent convection in the monsoon trough. It was first considered as a suspect area on the 9 August Significant Tropical Weather Advisory. The disturbance tracked northeastward in response to surging monsoon southwesterlies. At 110100Z, JTWC issued a Tropical Cyclone Formation Alert based on increased curvature in

the convective bands and a cyclonic tumbling motion of the convection on animated satellite imagery. The first warning for Tropical Depression 17W followed at 110600Z when satellite imagery revealed a developing central dense overcast. At first, JTWC forecast Tropical Depression 17W to make a curve to the north and then track northwestward, as it separated from the monsoon trough and interacted with the subtropical ridge which was building westward. The system did, indeed, follow the forecast, however, only after an unforecast 18-hour jog to the southeast. During this early stage, both Tropical Depressions 17W and 16W competed for low-level inflow and favorable upper-level outflow channels, causing




Figure 3-17-1. Typhoons Nancy and Owen (16W) at peak intensity (140313Z August NOAA infrared imagery).

a high degree of uncertainty as to which system would dominate.

As Tropical Depression 17W turned to the north, it was upgraded to Tropical Storm Nancy at 120600Z. Six hours later, Tropical Depression 16W also would become a tropical storm. Then, Nancy broke free of the monsoon trough and began rapid intensification, reaching typhoon intensity within 24 hours of its upgrade to a tropical storm.

JTWC anticipated the possibility of binary interaction with Tropical Depression 16W as soon as Nancy formed. While Tropical Depression 16W intensified, the two systems closed to within 600 nm (1110 km) of each other, and binary interaction became evident when Nancy turned northward. Nancy and Owen (16W) rotated around each other from 120000Z until 150000Z (Figure 3-17-1), an exceptionally long period. The rotation between the two systems about a common

center point totaled 105 degrees. During this time, Nancy accelerated from 6 kt (11 km/hr) on 12 August to 24 kt (44 km/hr) on 14 August in response to the combined effects of increased steering flow and the interaction with Owen (16W). A comparison of both typhoon tracks referenced to the center of motion, or centroid, is shown in Figure 3-17-2. The centroid's track (Figure 3-17-3) during the binary interaction moved east and then turned to the northwest. JTWC used this as a forecast aid for both cyclones, with good results. JTWC propagated the centroid northward, however, results would have been even better had JTWC steered the centroid with the north-northwestward steering flow. At 131800Z, Nancy reached a peak intensity of 75 kt (39 m/sec) and started accelerating towards Tokyo, a track that would reach the metropolis in 24 hours. Based on the expected behavior from the binary interaction, JTWC forecasters projected the cyclone to slow down and veer to the north. Twelve hours later, the forecast motion away from Japan




Figure 3-17-2. Tracks of Typhoons Nancy and Owen (16W) relative to their common center. Binary interaction lasted for 72 hours and through 105 degrees of rotation.

materialized. On 15 August, the binary interaction between Nancy and Owen (16W) ended abruptly. There is, to our knowledge, no research that indicates when a binary interaction will cease and the storms will resume independent tracks.

In retrospect, and in light of a similar north-orientated track of Typhoon Mac (15W) two weeks before, there was concern whether Nancy would cross over Japan. But, the NOGAPS prognostic series were quite consistent in moving a trough, which could

induce recurvature, to the east of Japan. The series also built a mid-tropospheric ridge that would stop any further northwest movement over the northern Sea of Japan. At 160000Z, Nancy was moving north of the mid-tropospheric subtropical ridge. It had weakened to tropical storm intensity, and began extratropical transition. Without deep convection to maintain the warm core, the cyclone completed its extratropical transition. The final warning was issued at 161200Z as the low-level circulation center tracked north-northeastward just east of Hokkaido.





Figure 3-17-3. Path of mid-points between Typhoons Nancy and Owen (16W).



TROPICAL STORM PEGGY (18W)

The third tropical cyclone to develop in the monsoon trough between 11 and 16 August, Peggy was short-lived and only reached minimal tropical storm intensity.


While tropical cyclones Owen (16W) and Nancy (17W) were completing their binary interaction and moving northward, the disturbance that would eventually become Peggy formed in the monsoon trough roughly 200 nm (370 km) north of Guam. Late on 14 August, satellite imagery displayed a new area of convection associated with a low-level circulation center. After sparse synoptic data indicated falling pressures and wind shifts

MINAMI TORI-SHIMA
PEGGY

reflected the circulation's development, JTWC issued a Tropical Cyclone Formation Alert at 150000Z.

Initially, the disturbance moved northeastward and a small ragged area of central convection persisted. This persistent, but small, central dense overcast led JTWC to issue the first warning on Tropical Depression 18W at 160000Z. The depression then turned north to follow Owen's (16W) track. Increased convection resulted in an upgrade to tropical storm intensity on the 161200Z warning. The outflow from Owen (16W) restricted Peggy's outflow This increased vertical shear, in combination with the subsidence associated with a Tropical Upper Tropospheric Trough (TUTT) cell to the northeast, kept Peggy from developing further. Minor flare-ups of convection were, however, sufficient to allow Peggy to maintain its 35-kt (18 m/sec) intensity despite the shear. Meanwhile, lower tropospheric ridging northeast of Peggy caused the cyclone to turn to the west. At 180000Z, the final warning was issued when satellite imagery (Figure 3-18-1) indicated the separation of the low-level circulation from its convection and that the low-level center would remain in an area of strong subsidence. The residual lowlevel vorticity center drifted west-northwestward and dissipated on 19 August near Iwo Jima.

Figure 3-18-1. Vertical wind shear from the northwest exposes the low-level circulation center as a TUTT cell to the northeast of Peggy is becomes the dominant feature (172206Z August NOAA visual imagery).



TROPICAL DEPRESSION 19W

Developing from a large area of low pressure and disturbed weather, this system was first detected on satellite imagery approximately 180 nm (335 km) northwest of Okinawa on 16 August. Initially, there was just a large cloud minimum area that was caused by subsidence beneath a mid-level low. Based on the expected movement of upper-level divergence into this area, JTWC forecast the development of Tropical Depression 19W. When strong upperlevel divergence did move into this area, convection began to rapidly develop. This cloudiness began to coil beneath the mid-level low, and estimates of 20- to 25-kt (10- to 13m/sec) surface winds from satellite data prompted the issuance of a Tropical Cyclone

Formation Alert at 160230Z. The first warning, at 170000Z, addressed further development of the tropical cyclone.

Tropical Depression 19W's unusual curved track to the north, west, and then south appears to coincide with the overall motion displayed by the larger, mid-level low. On 18 August, the mid-level low began to fill, weakening its influence on the tropical depression (Figure 3-19-1). The track of the cyclone straightened out, moving westward with the easterly steering flow. JTWC issued the final warning at 191200Z as the tropical depression approached the coast of China. No reports of damage were received.





Figure 3-19-1. A tight spiral of low cloudiness is associated with the exposed low-level circulation of Tropical Depression 19W (172346Z August NOAA visual imagery).



TROPICAL STORM ROGER (20W)

Forming just north of Taiwan, Roger moved southeastward into the southern Ryukyu Islands, abruptly turned northeastward, and made landfall on Honshu. At the start, the forecast problem for this tropical cyclone was exacerbated by the difficulty in locating the system's complex center during its formative stages and the immediate threat it posed to DOD assets on Okinawa.

On 23 August, a tropical disturbance rapidly consolidated just north of Taiwan. Because of the developed cloud signature, JTWC opted to issue a Tropical Cyclone Formation Alert at 230500Z instead of reissuing the Significant Tropical Weather Advisory. When further development did not occur as rapidly as anticipated, the Alert was reissued the following day. Satellite data detected multiple vortices near the main convection mass and there was uncertainty about just where the system was going to consolidate. The fairly dense network of ship and land observations in the southern Ryukyu Islands began to show significant 12-hour pressure falls, and winds near the center of the disturbance increased to 25 kt (13 m/sec). In response, JTWC issued a 36-hour Tropical Depression Warning at 241200Z. Pressures continued to drop during the following 12 hours, and satellite and synoptic fixes appeared to converge. Finally, when it became apparent that one circulation center was going to emerge and intensify, JTWC issued a 72-hour Tropical Cyclone Warning at 250000Z.

On 25 August, in response to a short wave trough approaching from the north-northwest, the depression turned northeastward. The reason for the abrupt track change to the northeast was not immediately apparent because two vortices were involved. The low-level circulation center, in the southern portion of the cloud system, weakened, and another center in the northern portion strengthened. This switch in circulation centers initially made it appear as if Roger had executed a sharper turn and had accelerated faster than it actually did.

In addition to the major track change on 25 August, Roger also intensified to a tropical storm. Synoptic data revealed that gale force winds extended out from the circulation center more than 300 nm (555 km) into the southeastern semicircle. This large asymmetrical pattern of gales would accompany

Roger during the remainder of its lifetime. As the tropical cyclone (Figure 3-20-1) moved steadily northeastward, it gradually intensified. Roger reached a peak intensity of 50 kt (26 m/sec) early on 27 August, just prior to making landfall on Shikoku at Cape Muroto, which is located 100 nm (185 km) southwest of the city of Osaka.

At landfall, Roger's convection became more centralized and upper-level outflow remained good. In addition, the cyclone accelerated, increasing winds in the southeastern semicircle. As a consequence, Roger's track across central Honshu created considerable havoc. Two people drowned in swollen rivers and a third was killed in one of many landslides. Some areas in Roger's path recorded over 19 inches (485 mm) of rain.

Widespread disruption of air traffic and railway service stranded over 37,000 travelers. Also, due to high winds, the new Seto Ohashi Bridge across the Inland Sea between Honshu and Shikoku was closed for the first time since it opened in April 1988.

At 271200Z, Tropical Storm Roger moved into the Sea of Japan and continued to accelerate under the influence of stronger westerly winds aloft. Even though the circulation center was over water, the combined effects of surface friction from the rugged topography of northern Honshu and increased westerly winds aloft weakened the tropical cyclone. At 280000Z, the final warning was issued as the extratropical remnants of Roger sped northeastward across Hokkaido.





Figure 3-20-1. Near peak intensity, Roger approaches central Honshu (262343Z August DMSP visual imagery).



TROPICAL DEPRESSION 21W

The eighth and final tropical cyclone of August, Tropical Depression 21W developed northeast of the Mariana Islands. Because JTWC recognized that intensification would be inhibited by strong vertical wind shear, only Tropical Depression Warnings were issued.

As Tropical Storm Roger (20W) passed through the southern Ryukyu Islands on 23 August, a disturbance formed on the eastern end of the monsoon trough which extended eastward across the northern-most Mariana Islands. The 24 August Significant Tropical Weather Advisory mentioned the disturbance and its poor potential for development. During the night, the disturbance became better organized and its potential for development was upgraded to fair. A Tropical Cyclone Formation Alert was issued at 241200Z, after the disturbance continued to develop during the normal diurnal convective minimum. Further development (Figure 3-21-1) led to the first




Figure 3-21-1. Convective organization continues to increase after the Alert was issued (242242Z August DMSP visual imagery).


warning at 250600Z. A Tropical Depression Warning was issued rather than a tropical cyclone warning since the low-level circulation was displaced to the west of the deep convection and the system was not expected to be long-lived because of strong westerly wind shear aloft.

While the upper-level winds restricted the tropical cyclone's outflow, the deep southwesterly monsoonal flow carried the low-level circulation center on an unusually long track to the northeast. Late on 25 August, Tropical Depression 21W slowed abruptly as it moved into an area of weaker vertical shear. Coincidentally, the low-level circulation center moved beneath the central cloud mass, and the intensity increased to 30 kt (15 m/sec).

On 26 August, the depression accelerated in response to a surge in the southwest

monsoon. Shortly thereafter it started interacting with a shear zone that trailed from a weak cold front. Tropical Depression 21W appeared to be on the verge of transitioning to an extratropical system; however, on 27 August, mid-level steering weakened, the system stalled, and central convection reappeared.

Within a day, unfavorable conditions returned aloft, as northwesterlies moved over the system and began once more to strip away the central convection. As a consequence, the amount of convection decreased and the low-level circulation center became exposed. A weakening Tropical Depression 21W suddenly started tracking northwestward. At 280600Z, with the low-level circulation center separated more than one degree to the west of the convection, the final warning was issued. JTWC did not receive any reports of damage caused by the tropical cyclone.



TYPHOON SARAH (22W)

The first of the September tropical cyclones, Sarah proved to be a bona fide challenge to forecasters. The cyclone apparently underwent a binary interaction with a secondary low east of Luzon and later, when it stalled, was involved with the development of a sympathetic low* on the lee side of Luzon. From genesis involving two distinct cloud masses to accelerating toward the Philippines, stalling just east of Luzon, moving north and rapidly reintensifying, then looping over eastern Taiwan, Sarah was one of the most difficult storms of the year to forecast.

The first day of September, the monsoon trough stretched across the western Pacific in a southwest to northeast orientation between 10° to 20° north latitude, and supported several discrete convective cloud masses. Near Minami Tori-shima, a distinct TUTT cell was evident in satellite imagery. About 600 nm (1110 km) to the southeast, a disturbed area of weather persisted in the monsoon trough. There was little convection associated with the TUTT cell, however, the convection associated with the

The Depression tracked as forecast to the west and was upgraded to Tropical Storm Sarah on the 061800Z warning. By midday on 7 September, Sarah started to accelerate to the northwest towards Okinawa and the tropical storm was relocated on the 071800Z to reflect the acceleration.

Forecasters at JTWC expected the northwestward motion to be short-lived and predicted a turn back to the west. However, on 8 September, the tropical storm turned westsouthwest, then south-southwest, and nearly stalled east of Luzon on 9 September. Binary interaction with a secondary low appeared to be

disturbance was listed on the Significant Tropical Weather Advisory. Two Tropical Cyclone Formation Alerts were issued before the first warning. Complex interactions between the TUTT cell, the disturbance and a second disturbance resulted in conditions favorable for development, and the first warning on Tropical Depression 22W was issued at 060000Z.

^{*} The formation of a sympathetic low is documented in relation to systems approaching Taiwan (Brand and Blelloch, 1973), but not for systems off the Philippine Islands





Figure 3-22-1. Matched pair of visual (above) and enhanced infrared (below) images showing two centers of convection. Point A is the mass of persistent convection that appears to have undergone binary interaction with Sarah which is at point B (080043Z September DMSP infrared imagery).



the cause for Sarah's unusual movement. While there was a persistent convective mass (Figure 3-22-1) on the satellite images, there was no firm evidence of this secondary low at the surface on 8 September.

Upgraded to typhoon intensity at 081800Z, Sarah drifted south slowly and then abruptly headed north. During this time, a sympathetic lee-side low (Figure 3-22-2) formed along the northwest side of Luzon. As Sarah moved north, the cloud mass associated with this lee-side low crossed Basco Island north of Luzon and tracked rapidly around the east side of Sarah and to the northeast. Since Basco Island (WMO 98135) reports did not indicate a wind shift as the convective mass

passed by, no Alert on this secondary convective area was issued. Sarah's prolonged stay just east of Luzon, coupled with the enhanced southwesterly monsoon flow being drawn over the Philippine Islands resulted in at least 31 fatalities, and extensive property and crop damage on Luzon. In addition, rare tornadoes touched down on 10 September. One caused approximately \$150,000 of damage to the San Miguel Naval Communications Station located 38 nm (70 km) northwest of Manila. No other U. S. military installations reported major damage. Camp John Hay located near Baguio reported the strongest winds observed at a U.S. military installation of 42 - 48 kt (22-25) m/sec) during the period from 091500Z to 110430Z.




Figure 3-22-2. 101220Z surface/gradient wind analyses shows the sympathetic low along the northwest coast of Luzon.

Moving north into an area of efficient multiple outflow channels, Sarah (Figures 3-22-3 and 3-22-4) explosively deepened. The typhoon peaked at 125 kt (64 m/sec) before interaction with the rugged mountains of Taiwan caused it to weaken. On 10 September, the typhoon was forecast to track north, passing approximately 60 nm (110 km) east of Taiwan on 11 September. It was expected to merge with an approaching mid-latitude front and recurve to the northeast into Kyushu, Japan. Although this was the overall track taken by the secondary cloud maximum that had formed on

the lee-side of Luzon and looped around the east side of Sarah as both systems moved north, Sarah did not follow suit. Sarah moved onshore Taiwan with maximum winds near 90 kt (46 m/sec). It then tracked south a short distance along the eastern edge of the mountain range and finally completed a counterclockwise loop off the coast. Approximately 12 hours later, Sarah reentered the coast farther north, weakened and was downgraded to a tropical storm Sarah at 121200Z as it crossed the rugged mountains of Taiwan. The cyclone did not regain its organization as it crossed the Taiwan




Figure 3-22-3. Radar display of Sarah from Hualien (WMO 46699) at 110500Z. Comparison with Figure 3-22-4, which is close in time, shows the contrast between the remotely sensed precipitation echoes from radar and the cloud top topography as viewed from space (photograph courtesy of the Central Weather Bureau, Taipei, Taiwan).




Figure 3-22-4. Matched visual (above) and enhanced infrared (below) pair of images showing Sarah near peak intensity (100517Z September DMSP visual and infrared imagery).



Straits and was downgraded to a tropical depression after it entered the eastern coast of China at 130600Z (Figure 3-22-5). The last warning was issued at 140000Z as the system dissipated over eastern China. Press reports

indicated that 13 people died on Taiwan, and that the 12000-ton freighter Lung Hao (Figure 3-22-6) broke in half off Hualien, Taiwan. No reports of damage were received from China.




Figure 3-22-5. Sarah weakens over the coast of China (130006Z NOAA visual imagery).





Figure 3-22-6. The wreck of the freighter Lung Hao, which was broken in half on the coast of Taiwan by Typhoon Sarah (photo courtesy *Pacific Daily News*, Agana, Guam).



TROPICAL STORM TIP (23W)

Generating in early September at the eastern end of the monsoon trough, Tip executed an unusual track to the northeast, then recurved after moving northwestward around the subtropical ridge, and finally tracked eastward with the polar westerlies. Tip reached its peak intensity at 37° north latitude two days after recurvature.

Tip developed east of the Mariana Islands in an area of enhanced convection at the eastern-most extension of the southwest monsoon. At 080600Z, JTWC mentioned the area on the Significant Tropical Weather Advisory as having fair potential for further development. Increases in the amount, depth, and organization of the convection caused JTWC to issue a Tropical Cyclone Formation Alert at 082300Z. With synoptic data

supporting a closed low-level circulation and indicating 25 kt (13 m/s) sustained surface winds, JTWC issued the first warning on Tropical Depression 23W.

During the time that the depression moved rapidly northeastward, and then northwestward, the "spin-up" of the system was slow, partially due to the large size of the vortex. By the time Tip reached the axis of the subtropical ridge and slowed late on 10 September, the bulk of the supporting convection from the monsoonal flow had moved away to the east and north, and had dissipated, leaving only a small ragged patch of dense overcast near the partially exposed low-level circulation center.

At 110600Z, Tip (Figure 3-23-1) began





Figure 3-23-1. Tip accelerates to the northeast and begins recurving 400 nm (640 km) north-northeast of Minami Tori-shima (110324Z September NOAA visual imagery).

to accelerate to the north-northeast. During the next 18 hours, Tip appeared to be undergoing extratropical transition, but, at 120000Z, the tropical cyclone regained enough of its central convection to maintain its warm core. This additional translational effect from the acceleration assisted Tip in reaching its peak intensity of 50 kt (26 m/sec) at 130000Z.

During the early morning hours of the 13 September, Tip's convection tracked south-southeastward with the upper-level flow. Daylight satellite imagery revealed that the low-level circulation was well to the north of the convection. At 131800Z, JTWC issued the final warning on Tropical Storm Tip and passed warning responsibility for the extratropical gales to the Naval Western Oceanography Center at Pearl Harbor, Hawaii.



TROPICAL STORM VERA (24W)

The third tropical cyclone in September, Vera generated north of Guam. After some initial erratic motion, the cyclone moved on a west-northwestward track, threatened Okinawa, and made a devastating landfall just south of Shanghai.

Vera generated in an area of low-level convergent flow in the monsoon trough approximately 250 nm (465 km) north of Guam. Persistent convection had not been observed with this system prior to 101200Z. By then, however, the combination of persistent convection, a preexisting low-level circulation center, and sea-level pressures below 1004 mb triggered JTWC to issue the first Tropical Cyclone Formation Alert at 110430Z. Both satellite imagery and synoptic data indicated efficient outflow over the low-level circulation center suggesting good potential for further

development. JTWC reissued the Alert at 111500Z as the disturbance moved to the southeast, and out of the original Alert box.

After the initial erratic motion, the convection organized around the circulation center, and the cyclone settled into a track to the west-northwest. JTWC issued the first warning on Tropical Depression 24W at 120600Z. Moving into increased steering flow along the southern side of the subtropical ridge, the tropical cyclone increased its translational speed and continued to intensify. At 121200Z, JTWC upgraded the depression to Tropical Storm Vera.

Due to two impinging TUTT cells, which constricted the efficiency of its upperlevel outflow, one to the northwest and one to the northeast, Vera (Figure 3-24-1) intensified





Figure 3-24-1. Convection flares shortly before Vera reaches it peak intensity (130042Z September DMSP visual imagery).

slowly, reaching only a peak intensity of 50 kt (26 m/sec) at 130600Z. On 14 and 15 September, as the tropical cyclone accelerated to a forward speed of 20 kt (10 m/sec), it started to weakened due to strong vertical wind shear. Vera passed 100 nm (185 km) southwest of Okinawa and maintained tropical storm intensity until after it made landfall approximately 150 nm (240 km) south of Shanghai. At 151800Z, the cyclone was downgraded to a tropical depression. JTWC

issued the final warning at 160000Z, and the system dissipated over land 18 hours later. No damage reports were noted from Okinawa, however, press releases from China cited Vera as the most powerful cyclone to hit the low-lying Zhejiang province in southeastern China in decades. Estimates ran as high as 500 fatalities, 700 injured and hundreds missing. Heavy rains reportedly caused extensive flooding and crop damage.





TYPHOON WAYNE (25W)

The last of four tropical cyclones to develop in September, Wayne was also the last tropical cyclone of 1989 to affect Japan. It was unique in that it intensified after recurvature. Wayne caused considerable destruction, mudslides and some deaths in Japan.

About 24 hours after Tropical Storm Vera (24W) had dissipated over eastern China, the first warning on Tropical Depression 25W was issued at 170600Z indicating maximum sustained winds of 25 kt (13 m/sec). The depression formed approximately 300 nm (555 km) southwest of Okinawa and was expected to continue on a northwestward track into China before it could reach tropical storm intensity. JTWC issued a second Tropical Depression Warning at 171800Z. At that time, the six-hour

movement was thought to have been to the west; however, detailed post-analysis indicated that the system had, in fact, turned northward. The turn to the north as well as further intensification became evident by 180000Z. The depression was upgraded to Tropical Storm Wayne and was forecast to track northeast through central Honshu and dissipate near Tokyo.

JTWC forecasters maintained that forecast scenario until 181200Z, when they took the track more northward into the Sea of Japan. This change in thinking was based on the persistent northward movement and the NOGAPS prognostic series that indicated a deepening low in the Sea of Japan would attract the system. JTWC's prognostic reasoning




Figure 3-25-1. Typhoon Wayne along the southern coast of Japan (190932Z September DMSP enhanced infrared imagery).

discussed the possibility of the system being caught by the approaching frontal system and remaining south of Japan. The strong vertical wind shear present east of Korea was expected to prevent Wayne from exceeding tropical storm intensity.


Surprisingly, satellite imagery at 181800Z indicated Wayne had apparently developed an eye. The warning was amended four hours later as subsequent satellite imagery confirmed the presence of an eye and further intensification. At 190000Z, Wayne was upgraded to a typhoon. While not a common occurrence, intensification after recurvature can occur when a tropical cyclone recurves at relatively low latitudes; and the jet stream provides an efficient outflow channel. A favored time for such intensification (Guard, 1983) is during the fall when warm sea surface temperatures extend into higher latitudes.

Significant acceleration started at 190000Z, and Wayne (Figure 3-25-1) was downgraded to a tropical storm at 191800Z.

Fortunately for Japan, as Wayne accelerated, the translational speed diminished the maximum sustained wind speeds in the northwest quadrant, which was over land. Yokota AB, Japan (WMO 47642), experienced maximum sustained winds of 14 kt (7 m/sec) with a peak gust to 19 knots (10 m/sec), even though Wayne passed only 45 nm (85 km) to the southeast. Tatevama (WMO 47672), southeast of Yokosuka at the mouth of Sagami Bay, took a direct hit from Tropical Storm Wayne, and after the storm passed, the station recorded 60 kt (31 m/sec) sustained winds with gusts to 84 kt (43 m/sec). Heavy rains caused flooding and mudslides. News reports indicated at least seven people died and over 4000 homes were flooded.

By 191800Z, Wayne's translational speed had increased to 40 kt (74 km/hr) and the system began to transition into an extratropical low. JTWC issued the final warning on Wayne at 200600Z as it underwent a compound transition (Brand and Guard, 1978) and merged with a cold-core low east of Hokkaido.

Intentionally left blank



SUPER TYPHOON ANGELA (26W)

Angela was the first of three tropical cyclones to form in the monsoon trough during the three-day period 29 September to 2 October. It had the unique distinction of being in warning status longer than any other tropical cyclone in the western North Pacific this year — 12 days. From 29 September to 10 October, JTWC issued a total of 46 warnings on Angela. Angela also was one of five tropical cyclones to reach super typhoon intensity in 1989. Developing south of Guam, Angela tracked slowly westward and struck northern Luzon with super typhoon intensity causing a large number of casualties and wide spread destruction. It then continued into the South China Sea, where it reintensified, finally making landfall in central Vietnam.

During late September, the monsoon trough, located near 10° north latitude, became very active after a week of little convective On 26 September an area of convection developed in the western Caroline Islands. The disturbed weather persisted for two more days, and was added as a suspect area to the 280600Z Significant Tropical Weather Advisory. As the disturbance moved to the southeast side of a Tropical Upper Tropospheric Trough (TUTT) cyclone, it organized rapidly. This resulted in the issuance of a Tropical Cyclone Formation Alert at 281730Z. The enhanced upper-level outflow from the TUTT low aided further development, and the first warning on Tropical Depression 34W (Figure 3-26-1) was issued at 290600Z.




Figure 3-26-1. Angela just after the initial warning was issued. The TUTT low northwest of Angela is enhancing upper-level outflow and divergence (290904Z September DMSP enhanced infrared imagery).

The depression was upgraded to Tropical Storm Angela at 291800Z. Angela initially tracked northwestward, as it developed, influenced by a mid-latitude short wave to the northwest. At 010600Z, the short wave had moved to the east, and Angela started tracking westward along the south side of the subtropical ridge. In the meantime as the short wave approached, Angela developed dual outflow channels and rapid intensification occurred. Angela intensified from 45 kt (23 m/sec) to 90

kt (46 m/sec) during the period 301200Z to 010000Z, reaching typhoon intensity at 301800Z. After 010000Z, intensification was slower as Angela lost the outflow channel to the north. It wasn't until four days later, at 050600Z, that Angela (Figure 3-26-2) was upgraded to a super typhoon.

Between 051500Z and 060300Z, Angela skirted along the northern coast of Luzon and was downgraded to a typhoon at





Figure 3-26-2. Super Typhoon Angela at peak intensity just prior to hitting northern Luzon (050558Z October NOAA visual imagery). Note: The spot in the eye is a blemish on the original transparency.

060600Z as it moved into the South China Sea. News reports from the Philippines indicated that the death toll from Angela was 62, mostly drowning victims, with 50 others missing and 21 injured. The high winds and heavy rains triggered flooding and caused heavy damage to crops and infrastructure. Angela destroyed more than 22,000 houses and sent 118,000 people fleeing to evacuation centers.

In the South China Sea, the typhoon started to track west-southwestward with high pressure building over China. As vertical wind shear weakened, Angela reintensified reaching 95 kt (49 m/sec) at 090600Z. Interacting with the topography of Hainan, the typhoon weakened before it moved inland in central Vietnam. At 100600Z, Angela made landfall approximately 30 nm (55 km) north of Hue, Vietnam and the last warning followed at 101200Z.



TYPHOON BRIAN (27W)

Typhoon Cecil (04W) in May and Typhoon Brian in late September and early October were the only tropical cyclones of the year to develop and spend their entire lifetimes within the confines of the South China Sea.

As Super Typhoon Angela (26W) developed over the Philippine Sea, the monsoon trough became active across the South China Sea from western Luzon to Vietnam. A broad area of moderate convection developed in the trough and was first mentioned on the 280600Z September Significant Tropical Weather Advisory as a fair suspect area about 390 nm (720 km) southeast of Hong Kong. The satellite

signature indicated a well defined upper-level anticyclone, but a weak surface circulation with very little deep convection.

The strong upper-level anticyclone persisted for the next 24 hours and synoptic data indicated that the low-level cyclonic circulation had intensified, prompting the issuance of a Tropical Cyclone Formation Alert at 290830Z. The circulation moved slowly westward along the southern side of the mid-tropospheric subtropical ridge. At 300000Z, the ridge weakened and the disturbance became quasistationary 195 nm (360 km) southeast of Hong Kong.



Figure 3-27-1. Tropical Storm Brian tracks toward Hainan (010641Z October NOAA visual imagery).

Over the next six hours, the disturbance drifted northward in an area of weak mid-level steering flow. As JTWC did not expect the depression to intensify during the next 48 hours, a 36-hour Tropical Depression Warning was issued for Tropical Depression 27W at 300600Z. Shortly thereafter, the subtropical ridge strengthened to the north and the depression moved west-southwestward and intensified. Brian (Figure 3-27-1) was upgraded to tropical storm intensity at 301800Z and to typhoon status 24 hours later when it was 240 nm (445 km) southwest of Hong Kong.

On 2 October at 0000Z, Brian (Figure 3-27-2) settled on a westward course and increased its forward speed to 9 kt (17 km/hr). At 021200Z, the typhoon reached a peak

intensity of 80 kt (41 m/sec) approximately 20 nm (35 km) off the southeast coast of Hainan Island. Three hours later the cyclone crossed the extreme southern coast of Hainan and weakened to 75 kt (39 m/sec). News releases from the area reported that at least 31 people perished and 500 were injured. In addition, Brian damaged an estimated 190,000 acres (77,000 hectares) of rice.

After mauling Hainan, the typhoon maintained its westward course and 75-kt (39-m/sec) intensity until it made landfall near Vinh, Vietnam. JTWC issued its last warning on Brian at 031200Z. The convection continued westward into the mountains of Vietnam and dissipated the next day.





Figure 3-27-2. Typhoons Angela (26W) and Brian. Angela's intensity of 115 kt (59 m/sec) is almost twice that of Brian's (020100Z October DMSP visual imagery).

Intentionally left blank



TYPHOON COLLEEN (28W)

Forming just north of the Marshall Islands, Colleen passed through the northern Mariana Islands before recurving south of Japan. The tropical cyclone maintained typhoon intensity until it completed extratropical transition. Also, Colleen threatened PACEX 89 — the largest US Navy exercise conducted in the Pacific since the Korean War. Colleen underscored the difficulty of tracking poorly organized systems with only nighttime infrared satellite imagery, but also showed the value of the microwave imager data as a tool to help locate these systems.

In the last week of September, Super Typhoon Angela (26W) was forming in the Philippine Sea and Typhoon Brian (27W) in the South China Sea. A deep trough penetrated into the tropical northwestern Pacific near the dateline. An area of cloudiness formed at the base of the trough on 23 September and moved slowly southwestward toward the Marshall Islands. In the data sparse area there were no

indications of a surface circulation until 271200Z when pressure falls and wind shifts throughout the northern Marshall Islands reflected the passage of a surface circulation or a tropical wave. JTWC first identified the disturbance as a suspect area on the Significant Tropical Weather Advisory at 280600Z. The disturbance was tracked on the Advisories for the next three days until a Tropical Cyclone Formation Alert was issued at 010030Z October. At that time, based on satellite imagery, the disturbance was analyzed as moving west-northwestward at 15 kt (28 km/hr). Forecasters noted that gradient-level winds at Guam (WMO 91217) had slowly veered from the south-southeast to the westnorthwest from 290000Z September until 010000Z October despite the presence of Tropical Storm Angela (26W) to the west of Guam.

The Alert was reissued at 011400Z when satellite analysts determined that the disturbance was moving westward at 9 kt (17




Figure 3-28-1. Tropical Storm Colleen approaching Guam (021159Z October DMSP enhanced infrared imagery).

km/hr). The first warning on Tropical Depression 28W followed at 011800Z after satellite imagery indicated the development of a central dense overcast. The depression was upgraded to Tropical Storm Colleen with the second warning at 020000Z. The forecasts for the initial five warnings called for the system to track south of Guam, however, the accompanying Prognostic Reasoning Messages discussed the possibility of a "stair step" in response to the passage of a short wave trough indicated by the NOGAPS prognostic series.

Tracking Colleen (Figure 3-28-1) became a problem during the night of 2 October. Earlier in the evening, a USAF contractor was installing a computer at Detachment 1, 1WW to process and display DMSP microwave imager information. Between 020800Z and 020900Z, microwave imager data from the 85-gigahertz channel was acquired and processed. These data were able to "see through" the high overcast clouds and the analyst could locate the center of the tropical storm and verify the positions obtained from the infrared channel. Subsequent nighttime infrared positions, without the benefit of the microwave data,

indicated that the system was moving westnorthwestward in excess of 12 kt (22 km/hr). The 021200Z satellite fix placed the position of the storm within 100 nm (185 km) of Guam, but neither the weather radar at Andersen AFB nor the Air Traffic Control radar operated by the Federal Aviation Administration on Guam could confidently locate the center. Because of the contradictory information presented by the satellite fixes, the lack of central or banding features on radar, and the absence of falling pressures that should accompany a rapidly approaching system, the 021200Z warning position was based only partly on the satellitederived position. In the post-analysis, the 021200Z satellite position was 96 nm (178 km) west of the final best track position. The average error of the eight infrared satellite fixes made during the night of 2 October was 68 nm (126 km) compared to the 20-nm (37-km) average error for the visual fixes on the 2 and 3 Warning number five, valid at October. 021800Z, was amended at 022300Z and relocated the position of the system to the north based on the first available visual satellite imagery. Also, at that time, 24-hour surface pressure falls at Saipan (WMO 91232) in-

24 HOUR PRESSURE FALLS 020300Z - 030000Z




Figure 3-28-2. Twenty-four hour pressure falls at Guam, Saipan, and Faraulep from 020300Z through 030000Z.

creased while Guam (WMO 91212) and the Faraulep AMOS station (WMO 52005) indicated slowing trends (Figure 3-28-2). The relocated position indicated the system had tracked northwestward during the night and was moving towards a weakness in the subtropical ridge. JTWC's amended warning took the system near Saipan in 36 hours. Colleen would eventually pass 120 nm (220 km) to the east of Guam and 30 nm (55 km) to the northeast of Saipan. Colleen tracked northwestward through the northern Marianas (Figure 3-28-3) passing within 60 nm (110 km) of the islands of Pagan and Farallon de Pajaros -- both proposed sites for future Automated Meteorological Observing Stations (AMOS). Heavy rains during Colleen's passage caused widespread flooding on Guam.

Warning number 6, valid at 030000Z, called for the start of recurvature in the vicinity

of Iwo Jima near the 72-hour point. However, Colleen slowed to 5 kt (9 km/hr) on 5 October and recurvature was delayed until 061800Z. Subsequent warnings retained the recurvature scenario well south of Japan with significant acceleration to the northeast.

At 040600Z, satellite imagery indicated a partial eyewall, and Colleen was upgraded to a typhoon. The system reached peak intensity at 051200Z -- 210 nm (390 km) southeast of Iwo Jima -- and weakened only slightly as it headed for its recurvature point. Ships involved in PACEX 89 altered course to avoid any encounter with Colleen. After 061800Z, the tropical cyclone moved northeastward and weakened to 70 kt (36 m/sec). Colleen maintained its intensity but doubled its speed of movement to 21 kt (39 km/hr) during the next 18 hours, and almost doubled it again to 40 kt




Figure 3-28-3. Typhoon Colleen leaving the northern Marianas. The cloud mass on the left is Typhoon Angela (26W) (042358Z October DMSP visual imagery).

(74 km/hr) during the following 12 hours.

JTWC issued its final warning at 080600Z (Figure 3-28-4) when Colleen was approximately 660 nm (1220 km) east of northern Honshu moving at 54 kt (100 km/hr) to

the northeast and still packing sustained winds of 70 kt (36 m/sec). It became one of the most intense extratropical cyclones of the year. In satellite imagery at 081200Z the extratropical remnants of Colleen were discernible near 46° north latitude.





Figure 3-28-4. Typhoon Colleen undergoing extratropical transition (080344Z October NOAA visual imagery).

Intentionally left blank.



TYPHOON DAN (29W)

Forming in October in the Caroline Islands near Truk, Dan followed a steady west-northwestward track and crossed the central Philippine Islands. Coming just days after Typhoon Angela's (26W) destructive passage through northern Luzon, Dan had a devastating effect on southern Luzon. The cyclone reintensified in the South China Sea and made landfall on the coast of central Vietnam where it caused more destruction.

On 6 October a disturbance formed in the monsoon trough near Truk in the central Caroline Islands. JTWC evaluated the weak low-level circulation center and its divergent flow aloft. On the Significant Tropical Weather Advisory at 060600Z, in light of strong vertical wind shear affecting the disturbance, JTWC classified it as having poor potential for development. After the disturbance persisted for another day, the potential was upgraded to fair. On 8 October, weaker vertical wind shear and the presence of a well-developed band of convection near the low-level circulation center led to the issuance of a Tropical Cyclone Formation Alert at 0330Z.

At 081200Z, JTWC issued the first warning on Tropical Depression 29W which was located 60 nm (110 km) northeast of Yap in the western Caroline Islands. Eighteen hours

later, the depression was upgraded to Tropical Storm Dan. The moderate flow south of the mid-level subtropical ridge axis kept the system on a 15- to 20-kt (28- to 37-km/hr) west-north-westward course toward the central Philippine Islands. Deep convection continued to improve with upper-level outflow efficient in all but the northwest quadrant, where it was restricted by the outflow from Typhoon Angela (26W). After outflow in the northwest improved and the eye become visible, Dan was upgraded to a typhoon at 100600Z.

At 101300Z, Typhoon Dan made landfall on the extreme southeastern coast of Luzon and later passed 20 nm (37 km) south of Manila's Ninoy Aquino International Airport (WMO 98429). The weather station reported sustained winds of 45 kt (23 m/sec) with gusts to 65 kt (33 m/sec). The strong winds rearranged some of the aircraft parked on the tarmac, blowing an Omani Boeing 707 and a Bangladesh presidential DC-10 into each other. Forty-eight nm (90 km) north of Manila, Clark AB (WMO 98327) received winds of 30 kt (15 m/sec) with gusts to 50 kt (26 m/sec) from 110100Z to 110400Z. Cubi Point NAS (WMO 98426), 40 nm (75 km) northwest of Manila, reported sustained winds of 40 kt (21 m/sec) with gusts to 75 kt (39 m/sec). From 100000Z to 120000Z Cubi Point reported 5 inches (125 mm) of rain, while Clark AB measured 3.5 inches (90 mm).

As Dan moved into the South China Sea, it lost its eye feature and weakened to tropical storm intensity at 110300Z (Figure 3-29-1). Tracking west-northwestward over the warm sea, the cyclone regained its convection, reformed its eye, and was again upgraded to a typhoon at 120000Z. Dan reached a peak intensity of 70 kt (36 m/sec) six hours later. The typhoon weakened slightly as it approached and passed 60 nm (110 km) to the south of Hainan Island. As Dan approached the coast of central Vietnam, increased mid- to upper-level shear elongated the cloud shield and weakened the system. Dan made landfall on the central coast of Vietnam at 131200Z, and at that time

JTWC issued a final warning. The circulation dissipated in the mountains and the disorganized convection continued westward into Laos.

Dan, despite being only a minimal typhoon, proved to be a very destructive one. In the Philippines the Department of Social Welfare reported at least 41 people killed; 16,185 houses damaged; and, 232,555 left homeless or without livelihoods. Electrical power was lost to 95% of Metropolitan Manila because of downed power lines; "brown-outs" continued for weeks afterward. In Vietnam, Dan ripped the roofs off buildings, downed communication lines, and flooded over 320,000 acres.





Figure 3-29-1. Moonlit photo of Typhoon Dan as it enters the South China Sea and the eye reforms (111348Z October DMSP visual imagery).

Intentionally left blank.




SUPER TYPHOON ELSIE (30W)

In the wake of Super Typhoon Angela (26W) and Typhoon Dan (29W), Super Typhoon Elsie became the third tropical cyclone to hit the Philippine Islands within 12 days. Elsie developed from a TUTT-induced wave in the easterlies and tracked westward throughout its life. In the Philippine Sea, Elsie rapidly intensified and struck central Luzon with an intensity of 140 kt (72 m/sec). In news reports it was cited as the most intense cyclone to strike the Philippine Islands this year. Elsie weakened dramatically as it moved across the Philippines, and did not reintensity as it traversed the South China Sea. The cyclone dissipated after making landfall in central Vietnam.

In the middle of October the Tropical Upper Tropospheric Trough (TUTT) was well established in a east-west orientation across the western North Pacific. As Typhoon Dan (29W) made landfall in central Vietnam, a tropical disturbance developed approximately 670 nm (1240 km) east-northeast of Manila and started tracking west-northwestward. The system, first

mentioned on the Significant Tropical Weather Advisory at 130600Z, was located between two small TUTT lows -- one located to the southwest and one located to the northeast of the disturbance. These TUTT lows enhanced the disturbance's upper-level outflow, and at 132330Z a Tropical Cyclone Formation Alert was issued. As the disturbance intensified, the first warning was issued on Tropical Depression 30W at 140000Z, followed by an upgrade to Tropical Storm Elsie at 141200Z. At that time, Elsie stalled as it moved into an area of weak steering flow between two subtropical highs.

Late on 15 October, Elsie began a "stair step" northwestward, as a mid-latitude short wave passed to the north. This short wave enhanced the outflow, and Elsie rapidly intensified from 60 kt (31 m/sec) to 110 kt (57 m/sec) in 24 hours. At 160600Z, Elsie was upgraded to a typhoon and became a super typhoon at 180600Z. Super Typhoon Elsie (Figure 3-30-1) reached its maximum intensity of 140 knots (72 m/sec) at 181800Z and then






Figure 3-30-1. A matched pair of enhanced infrared (left) and visual (right) data show Elsie's classic cloud-free eye and surrounding central dense overcast (190000Z October NOAA visual and infrared imagery).

made landfall in central Luzon at 190300Z.

As it crossed Luzon, Elsie weakened rapidly due to frictional effects and the loss of oceanic sensible and latent heat sources. The system was downgraded to a typhoon at 190600Z, and then to a tropical storm at 191200Z. The tropical cyclone tracked westward along the south side of a northeast monsoonal surge. Vertical wind shear associated with the surge prevented Elsie from reintensifying in the South China Sea (Figure 3-

30-2). The final warning was issued at 220600Z as Tropical Storm Elsie made landfall in central Vietnam. The remnants remained identifiable until they reached the mountainous terrain of Laos.

In the Philippines Super Typhoon Elsie left at least 17 dead, 50,000 homeless, and damage in the millions of dollars. John Hay Air Station and Wallace Air Station sustained a total of \$30,000 damage, including damaged roofs, uprooted trees and destroyed sheds.





Figure 3-30-2. Elsie spins westward across the South China Sea and never regains typhoon intensity (192233Z October DMSP visual imagery).

Intentionally left blank.



TYPHOON FORREST (31W)

The last of six tropical cyclones in October and the 17th typhoon of the year, Forrest was slow and erratic in its development. In fact, JTWC issued and reissued three Tropical Cyclone Formation Alerts before finally disseminating the first warning on Tropical Depression 31W. Throughout its early life, Forrest was a sloppy, broad system with large diurnal variations in its convection. After passing Guam, Forrest finally intensified and ultimately became a 95-kt (49- m/sec) typhoon. Soon thereafter, it recurved and accelerated rapidly to the northeast, becoming one of the year's strongest extra-tropical cyclones in the Pacific. Forrest's track was striking in its similarity to the track of Typhoon Colleen (28W).

As Super Typhoon Elsie (30W) approached the northern Philippines on 17 October, the near-equatorial trough reestab-

lished itself through the Marshall and eastern Caroline Islands and generated a tropical disturbance. JTWC initially discussed the disturbance located about 100 nm (185 km) south of Pohnpei on the Significant Tropical Weather Advisory on 18 October. During the next two days, the disturbance moved toward the west-southwest. Then on the morning of 20 October, it took a turn to the northwest approximately 180 nm (335 km) southeast of Truk. At 200200Z, JTWC issued the first of three Tropical Cyclone Formation Alerts, when the apparent cloud rotation on animated cloud imagery changed from anticyclonic to cyclonic, indicating the development of organized deep convection. From 20 to 22 October, the disturbance (Figure 3-31-1) underwent extremely large diurnal fluctuations in convection creating a broad circulation center and slowing intensification. The disturbance passed about 45 nm (85 km) west of Truk in the evening of 21




Figure 3-31-1. Forrest prior to the first warning shows a large, poorly defined circulation center (212315Z October DMSP visual imagery).





Figure 3-31-2. (a) 230000Z October 200 mb composite streamline analysis showing unrestricted outflow channels to the north and south. (b) 231200Z October 200 mb composite analysis showing the large anticyclone southeast of Forrest's main upper-level circulation center.



October. From 212100Z to 230900Z, Truk experienced sustained 20 to 25 kt (10 to 13 m/sec) surface winds from the monsoon surge associated with the disturbance. At 222000Z, the first warning was issued on Tropical Depression 31W as it reached 30 kt (15 m/sec) and developed efficient outflow channels to the north and south. Twelve hours later, the depression was upgraded to a tropical storm. Forrest moved toward the northwest and

intensified at a rate of 5 kt (3 m/sec) every 6 hours. Forecasters at JTWC expected Forrest to reach typhoon intensity as it approached Guam and to rapidly intensify 24 hours later. However, on 23 October the southern outflow channel was completely severed as a large upper-level anticyclone developed to the south of the cyclone (Figure 3-31-2) as a result of the vigorous convection in the rainband to the southeast (Figure 3-31-3). This, coupled with




Figure 3-31-3. As Forrest nears Guam, a wide ribbon of deep convection to the southeast of the center contrasts with small area of central convection (232207Z October NOAA visual imagery).

the normal tendency for suppressed daytime convection, resulted in a convectively inactive, broad circulation center. Without the organized convection, winds remained relatively strong aloft, but weak at the surface, especially over land. At 240800Z, Forrest passed within 75 nm (140 km) of the International Airfield on Guam. The weather station (WMO 91212) recorded gusts to 34 kt (18 m/sec) and a minimum sea level pressure of 998 mb. Strong vertical wind

shear the following day did ground aircraft on Guam and Saipan. During the day, convection remained disorganized, but about 8 hours after passing Guam, convection rapidly increased and Forrest, which was close to Saipan, intensified and formed a banding type eye. Even though the typhoon was moving away from Saipan, it buffeted the island with moderately strong winds, downing tree limbs and power lines. The airport at Saipan (WMO 91232) recorded a




Figure 3-31-4. Enhanced infrared image of Typhoon Forrest at peak intensity (271632Z October NOAA infrared imagery).

minimum pressure of 991 mb at 250400Z, several hours after Forrest had passed. Capitol Hill at an elevation of 1000 ft (305 m) above sea level unofficially recorded wind gusts to 50 kt (26 m/sec). Reports stated that Forrest left most of the island without power, stopped air travel, closed schools, and flooded low-lying areas.

The typhoon continued its northwestward track at an average speed of 10 kt (19 km/hr). Twelve hours prior to recurvature, Forrest attained its peak intensity of 95 kt (49 m/sec) as it crossed the axis of the midtropospheric sub-tropical ridge (Figure 3-31-4). Following recurvature at 271200Z, the cyclone began to accelerate to the northeast. On the evening of 26 October, a typhoon acceleration prediction technique (Weir, 1982) used to help determine the timing of recurvature and acceleration indicated that Forrest was about to recurve, and that it would rapidly accelerate. In response, JTWC altered its forecast considerably to reflect the anticipated changes. This caused the USS Carl Vinson battle group to alter its course from one passing across the storm's expected track to one that kept it

northwest of that track off the coast of Japan. While recurvature and acceleration were delayed 12 to 18 hours making and the speed of JTWC's forecast too fast, the direction forecast was correct. Remaining over relatively warm water and maintaining an efficient outflow channel into the mid-latitude westerlies. Forrest did not rapidly weaken. At 281200Z, the typhoon had accelerated to nearly 30 kt (56 km/hr), and still packed 75-kt (39-m/sec) winds, partly as a result of its rapid motion along track. At this time, Forrest passed within 175 nm (325 km) to the northwest of Chichijima (WMO 47971) where 850 mb winds were recorded at 230 degrees at 65 kt (33 m/sec). Interacting with the mid-latitude westerlies, Forrest's convective heat engine finally gave way to baroclinic energy-producing processes and the storm became extratropical while moving northeastward at nearly 50 kt (93 km/hr). The final warning on Typhoon Forrest was issued at 290600Z. Like Colleen, the resulting extratropical system became one of the strongest winter storms in the Pacific during 1989, packing storm force winds in excess of 60 kt (31 m/sec).



TYPHOON GAY (32W)

The first tropical cyclone of November turned out to be the worst tropical cyclone to affect the Malay Peninsula in 35 years. Gay developed in the Gulf of Thailand, crossed the Malay Peninsula into the Bay of Bengal and slammed into India with peak sustained winds of 140 kt (70 m/sec). Unique because of its small size, intensity, and point of origin, Gay challenged forecasters by crossing two different tropical cyclone basins and almost entering a third.

From a climatological point of view, an occasional tropical cyclone may move into the Gulf of Thailand from the South China Sea, but it is rare for genesis and intensification to occur in the Gulf — a relatively small body of water surrounded by land on three sides. However, on the first of November, satellite imagery detected the presence of a concentrated area of convection with a well-organized upper-level anticyclone. At the same time, sparse ship reports in the Gulf showed that sea-level pressures were relatively high — near 1008 mb. The continued increase in the amount and organization of convection prompted JTWC to mention it on the 010600Z Significant Tropical Weather Advisory, noting that a low-level circulation was evident in the monsoon trough. Maximum sustained surface winds were estimated to be 10 to 15 kt (5 to 8 m/sec). During the next 15 hours, the disturbance continued to consolidate and estimated winds increased to 25 kt (13 m/sec). At 012100Z, JTWC issued a Tropical Cyclone Formation Alert.

Aided by its small size, dual outflow channels to the north and south, and the warm Gulf waters, the tropical cyclone spun up rapidly, and at 020000Z JTWC issued a 36-hour Tropical Depression Warning on Tropical Depression 32W. It became apparent that the cyclone would continue intensification, and six hours later, JTWC issued the first 72-hour Tropical Cyclone Warning on the system, upgrading it to tropical storm intensity. As Gay intensified, it presented a paradox to forecasters. While the satellite intensity estimates correctly diagnosed intensification, the synoptic data in Malaysia and Thailand indicated weakening winds and higher pressures. The synoptic data were correctly interpreted as indicators of increased subsidence produced by the intensifying midget system. Subsequent JTWC warnings thus reflected that Gay would reach typhoon intensity.

At 021800Z, Gay began to intensify more rapidly than anticipated reaching typhoon intensity at 030000Z. The eye apparently passed directly over the Seacrest, a commercial oil drilling ship moored in the Gulf. Confused seas with estimated heights of 35 to 45 feet (11 to 14 m) caused the ship to capsize shortly after eye passage. Gay's intensification continued, reaching 100 kt (51 m/s) at 040600Z just before it crashed into Champhun, Thailand which is located 210 nm (390 km) south-southwest of Bangkok. The radar at Champhun (WMO 48517) had tracked Gay for 18 hours, before its reports abruptly ceased shortly before the

typhoon (Figure 3-32-1) came inshore. At least four hundred and fifty-eight people were died and over 600 fishermen were reported missing at sea. In addition, two hundred fishing vessels were lost or missing.

As Gay moved slowly to the northwest in the Gulf, JTWC forecasters anticipated that a ridge would build to the north, and correctly forecast the cyclone to make a left turn and move across the Malay Peninsula. Gay weakened briefly as it crossed the Peninsula, entering the Bay of Bengal with maximum winds of 65 kt (33 m/s) at 041200Z. Situated south of the mid-level ridge, Gay continued to track west-northwestward across the Bay of Bengal at an average speed of 10 kt (19 km/hr).

Gay intensified slowly in an area of weak vertical wind shear and warm sea surface temperatures, reaching an intensity of 95 kt (49 m/sec) by 051200Z. Restrictions to the upper-level outflow inhibited further development for the next 36 hours.

At 070000Z, Gay attained an intensity of 100 kt (51 m/sec), and took a more westward course as the mid-level ridge strengthened to the north. Without any significant restrictions to its outflow, the cyclone intensified for the next 42 hours until it reached the coast of India. Gay (Figure 3-32-2) reached super typhoon intensity at 080600Z, with winds of 130 kt (67 m/sec). Gay (Figure 3-32-3) made landfall in a sparsely populated area of India approximately 120 nm




Figure 3-32-1. Typhoon Gay as it makes landfall on the Malay Peninsula. More than 1000 people were reported dead or missing in Gay's aftermath (040042Z November NOAA visual imagery).

(220 km) north of Madras at 081800Z, with maximum sustained winds estimated at 140 kt (72 m/sec). While there was concern that the Dvorak intensity estimation technique might have overestimated Gay's intensity, photos of destruction showed that Gay was a very intense, but very small, cyclone. In-country analyses of Indian synoptic data indicated that the 30-kt (15-m/sec) wind radii did not extend much beyond 50 nm (95 km) — (personal communication with Dr. G. S. Mandal, Indian Meteorological Service).

Twelve hours after making landfall, Gay had weakened to 45 kt (23 m/s). Because of the possibility of its reemergence into the

Arabian Sea, JTWC continued to issue warnings on the system as it moved across India at 13 kt (24 km/hr). After 090600Z, Gay took a more northwestward overland track. At 100600Z, JTWC issued its final warning as the system dissipated in the Western Ghats approximately 75 nm (140 km) southeast of Bombay. Gay weakened much faster than anticipated as it moved across India. This was a result of its small size and small over-water fetch. Once inland the small fetch, which supplied Gay's latent heat source, was rapidly cut off. Because Gay was so small and went inshore in a rural area, it caused only 39 deaths. However, over 20,000 homes were destroyed or damaged.




Figure 3-32-2. Gay approaches super typhoon intensity. The small eye appears in a small, compact central dense overcast (080340Z November DMSP visual imagery).






Figure 3-32-3. Enhanced infrared (above) and low-light visual (below) satellite picture pair of Gay at the coast of India. The city lights, the moonlit coast line and Gay's cloudiness show on the visual image. The enhanced infrared reveals the small eye and cold surrounding overcast (081612Z November DMSP visual and infrared imagery).



Intentionally left blank.



TYPHOON HUNT (33W)

Typhoon Hunt was the fourth typhoon, following Angela (26W), Dan (29W) and Elsie (30W), to strike the Philippine Islands within six weeks. Generally a westward moving system, it was slow to develop, but finally intensified rapidly in the western Philippine Sea. As it intensified and approached the Philippines, it underwent a northwestward "stair step" before resuming a westward course into central Luzon. Unlike Angela (26W), Dan (29W) and Elsie (30W) which reintensified after crossing Luzon, Hunt weakened dramatically and dissipated in the South China Sea.

Except for Typhoon Gay (32W), early November was relatively inactive in the western North Pacific. The cloud cluster that became Typhoon Hunt was first identified on the 10 November Significant Tropical Weather Advisory. This system was a weak tropical disturbance embedded in the monsoon trough north of the island of Truk in the central Caroline Islands. The cloud cluster remained poorly defined and drifted slowly westward for two days. After synoptic data indicated falling surface pressures, JTWC issued a Tropical Cyclone Formation Alert at 121000Z. The disturbance was located 270 nm (500 km) southeast of Guam. As the passage of a midlatitude trough to the northeast of Guam weakened the mid-level subtropical ridge. On 13 November, the disturbance executed an abrupt track change to the north towards Guam. The Alert was reissued at 131000Z, approximately 220 nm (405 km) southsoutheast of Guam.

The system moved northward for a day, then turned sharply westward, passing 90 nm (165 km) south of Guam. Increasing vertical shear weakened the convection significantly, and the Alert was canceled at 140400Z. On 16 November, the organization of the disturbance improved, as southwesterly winds of 20 to 30 kt (10 to 15 m/sec) were reported by ships and land stations. JTWC issued its third Alert on

the system at 160730Z.

Continued organization led to the first warning on Tropical Depression 33W at 161200Z. In response to a mid-latitude trough passage to the north, the depression appeared to slow and then dip southward for six hours. As the trough moved out to the northeast, the 500 mb ridge remained very narrow but split into two cells, one to the northwest of the tropical cyclone and another to the northeast. A broad col area remained north of the tropical depression which then moved northwestward towards this weakness.

At 180000Z, the depression upgraded to Tropical Storm Hunt with maximum sustained winds of 35 kt (18 m/sec). Hunt intensified rapidly while moving northwestward and was upgraded to a typhoon at 181800Z. JTWC continued to forecast movement over Luzon and predict the system would enter the South China Sea just south of Manila Bay. This was based on NOGAPS prognostic fields which indicated that the narrow 500 mb ridge would reestablish and maintain itself to the north of the system, thus forcing a westward track. At the same time, a strong 850 mb ridge of continental polar air associated with the winter monsoon extended eastward from southern China. This was also expected to block Hunt's northward progression. However, the NOGAPS forecast series proved to be too fast at reestablishing the ridge and Hunt turned northward toward the weakness in the ridge.

At this time, the typhoon also slowed to 4 kt (7 km/hr). Now JTWC and U.S. forces from the Philippines to Okinawa faced the dilemma of having a destructive system either affect forces in the Philippines should Hunt make only a "stair step," or in Okinawa, should it recurve. Because weak mid-latitude troughs, embedded in the predominantly zonal flow, continued to pass north of the tropical cyclone, and the prognostic series continued to build the

narrow 500 mb ridge as a barrier to Hunt's continued northward movement, JTWC persisted with its forecast of westward movement.

At 091500Z Typhoon Hunt, with its 90-kt (46-m/sec) maximum sustained winds, turned sharply to the west toward central Luzon as the 500 mb ridge to the system's northeast built westward and strengthened. Hunt remarkably maintained its 90-kt (46-m/sec) intensity for 66 continuous hours before moving ashore in central Luzon at 212000Z (Figure 3-33-1). Army personnel involved in the joint-combined U.S.-Philippine exercise, BALIKATAN 89, were deployed to Fort Magsaysay near Clark AB. The Weather Support Force for the exercise reported peak winds of 52 kt (27 m/sec) at 212200Z when Hunt was 40 nm (75

km) northeast of its location. As the typhoon crossed Luzon, it killed at least seven Filipino people. Damage to military installations was slight.

Hunt was downgraded to a tropical storm at 220600Z as it entered the Lingayen Gulf. The northeast monsoon was of moderate strength in the South China Sea, and Hunt, despite moving over warm water, continued to weaken due to strong vertical wind shear. Deep convection had completely subsided by 230000Z when Hunt was downgraded to a tropical depression and the final warning was issued. The remains of the low-level circulation, although not visible on satellite imagery, were last discernible on synoptic charts at 240000Z drifting southward in the monsoonal flow.





Figure 3-33-1. Typhoon Hunt approximately nine hours before landfall on central Luzon. Maximum sustained winds are estimated at 90 kt (46 m/sec) (211130Z November DMSP visual imagery).



SUPER TYPHOON IRMA (34W)

Irma was the third and final tropical cyclone to form in November. It's development and track were dictated by complex mid-latitude and monsoonal regimes. Initially, Irma was slow to develop, however, rapid intensification followed once it was in the Philippine Sea. Irma lasted 17 days and required a total of 39 warnings -- only Super Typhoon Angela (26W) exceeded this longevity with a total of 46 warnings.

In the middle of November, disturbed weather associated with a TUTT low developed 580 nm (1075 km) northeast of Kwajalein Atoll in the Marshall Islands. The disturbance was first mentioned on the Significant Tropical Weather Advisory at 182300Z. Because of significant vertical wind shear affecting the system, JTWC opted for a 36-hour Tropical

Depression Warning at 210600Z instead of a 72-hour Tropical Cyclone Warning. Increasing upper-level flow around the TUTT low led to increasing shear above the depression, and a final Tropical Depression Warning followed at 220600Z. However, JTWC continued to mention the poorly defined remnants each day on the Significant Tropical Weather Advisory.

From 22 to 27 November, the system moved a record-breaking five days to the southwest, traveling from 20° to 10° north latitude. During this period from 22 to 24 November, the system tracked southwestward along the edge of a shear zone and continued to exhibit partially tropical characteristics. Eventually the southwestward track carried the system into an area of less vertical wind shear, where a flare up in convective activity led to a




Figure 3-34-1. An extensive field of closed cell stratocumulus appear to the north through west of Super Typhoon Irma (300431Z November NOAA visual imagery).

Tropical Cyclone Formation Alert at 240600Z. This development continued and at 250000Z a Tropical Depression Warning was issued. As the polar air mass along the shear line became well-modified in the tropics and anticyclonic outflow became more symmetric aloft, conditions improved for development. At 261200Z, JTWC issued the first Tropical Cyclone Warning on Tropical Depression 34W.

As the track became more westerly at 261800Z, Tropical Depression 34W was upgraded to Tropical Storm Irma. As a midlatitude short wave trough approached from the northwest, enhancing Irma's outflow, rapid intensification occurred and JTWC upgraded

the tropical cyclone to a typhoon at 280600Z. As a second short wave approached, Irma (Figure 3-34-1) attained super typhoon intensity at 300000Z. This increase in intensity was short lived, however. With the passage to the east of the shortwave also came stronger westerly winds aloft and an accompanying surge in the low-level northeast monsoon. These factors, plus the entrainment of cold air, weakened Irma (Figure 3-34-2) below super typhoon intensity at 010000Z.

Since 27 November the track to the west-northwest brought Irma closer to the polar westerlies aloft. Irma's forward motion slowed gradually as the cyclone approached the western





Figure 3-34-2. Irma's central dense overcast is elongated and asymmetrical. The eye is filling with clouds and the super typhoon is weakening (302151Z November DMSP visual imagery).

periphery of the subtropical ridge. The entire fall of 1989 had be characterized by zonal westerly mid-tropospheric flow and a very narrow subtropical ridge in the extreme western Pacific. Because of the 250 nm (465 km) wide ridge, even straight moving cyclones were very close to becoming recurvature ones. JTWC expected the flow to remain zonal, and for Irma to resume westward movement into the Philippine Islands. However, on 2 December, another short wave moved eastward from the

coast of Asia. This trough deepening further equatorward than the previous short waves and Irma recurved 630 nm (1165 km) east of Manila. The typhoon accelerated in response to the stronger westerly flow aloft and weakened in the strong shearing environment. The final warning was issued at 041200Z. The remnants of Irma were no longer visible on the satellite imagery on 5 December. JTWC received no reports of damage caused by Irma.



TROPICAL DEPRESSION 35W

Detected on the first day of December, Tropical Depression 35W lasted more than a week as a discrete system, although it was in warning status only 48 hours.

As Super Typhoon Irma (34W) was weakening in the Philippine Sea, a weak surface circulation and an associated area of convection were detected in the western Marshall Islands. The tropical disturbance was mentioned on the 010600Z Significant Tropical Weather Advisory as a poor suspect area. Over the next five days this tropical disturbance moved generally westnorthwestward and continued to organize very slowly. The presence of strong vertical wind shear arrested development and eventually

weakened the system. After the disturbance passed to the south of Guam, the convection flared and at 050500Z the first Tropical Cyclone Formation Alert was issued. The Alert was reissued at 060500Z. Then, based on a satellite intensity estimate of 30-kt (15-m/sec) surface winds (Figure 3-35-1), a Tropical Cyclone Warning was issued at 070000Z. At 080000Z. the approach of a mid-level short wave trough from the northwest resulted in the depression abruptly changing track and recurving northeastward. Increased vertical wind shear from the west-southwest was responsible for further weakening the system. The final warning was issued at 090000Z as the cyclone dissipated over water.





Figure 3-35-1. Tropical Depression 35W with 30-kt (15-m/sec) maximum sustained surface winds (070457Z December NOAA visual imagery).



TYPHOON JACK (36W)

The second tropical cyclone to form in December, Jack was the twenty-first typhoon and final tropical cyclone of the year. Typhoon Jack was noteworthy for the unusually long period it remained quasi-stationary and the extremely rapid dissipation that followed.

A broad area of poorly organized convection located approximately 240 nm (445 km) southeast of Truk was first noted on the 210600Z Significant Tropical Weather Advisory. The disturbed area of weather continued to organize slowly and a Tropical Cyclone Formation Alert was issued at 221900Z. At that time, the disturbance was 150 nm (275 km) northeast of Truk, moving westnorthwestward at 8 kt (15 km/hr) with surface winds of 20 to 30 kt (10 to 15 m/sec). Over the next 8 hours, the upper-level anticyclonic circulation and the spiral bands of the disturbance increased significantly in organization, however, the low-level circulation

remained weak. The combination of the rather tentative intensification of the disturbance and its movement in the general direction of Guam prompted the issuance of a Tropical Depression Warning at 230000Z. At that time Tropical Depression 36W was approximately 400 nm (740 km) southeast of Guam and forecast to move northwestward at 11 kt (20 km/hr).

The low-level organization of Tropical Depression 36W appeared to improve markedly on satellite imagery resulting in the issuance of a Tropical Cyclone Warning at 230600Z. The motion forecast for the next four days called for continued northwestward movement toward a weakness in the subtropical ridge near Guam, followed by recurvature due to an approaching short-wave trough. The system did reach a weak area at the axis of the subtropical ridge in about two days. However, the broad nature of the ridge blocked Jack's movement in all directions. This caused the cyclone to stall in a




Figure 3-36-1. Jack near super typhoon intensity (252148Z December NOAA visual imagery).

large area of weak mid-level steering at a latitude too far south to permit the passing short-wave trough to initiate recur-vature. Jack had closed to within 185 nm (345 km) of Guam before stalling. The proximity to Guam allowed surveillance to be conducted by the weather radar at Andersen AFB (WMO 91218). In what is almost certainly a record for almost no motion, radar surveillance doc-umented that Jack moved only about 60 nm (110 km) from 250710Z to 270335Z, and moved less than 20 nm (35 km) from 251210Z to 261210Z. Jack's eye, with a diameter of 20 to 30 nm (37 km to 55 km), made an ideal target for remote sensing. The typhoon was essentially stationary in a nonshearing environment for nearly 48 hours.

Not surprisingly, the unusual motion of Typhoon Jack was accompanied by an equally unusual intensification and dissipation pattern. From a maximum wind speed of 30 kt (15

m/sec) at 222330Z, Jack rapidly deepened to a maximum wind speed of 115 kt (57 m/sec) at 250530Z, which corresponds to nearly two T-numbers per day using the Dvorak intensity estimation technique. It reached a peak intensity of 125 kt (67 m/sec; Dvorak T6.5) during the period 251800Z to 261200Z (Figure 3-36-1). Such an intensification pattern was unusual since Jack appeared to have only one well-defined outflow channel to the northeast. Normally, rapid deepening and the attainment of super-typhoon intensity are associated with the development of two efficient outflow channels.

As Jack began to show signs of prolonged quasi-stationary behavior, JTWC anticipated on the 260000Z warning that the upwelling of cold water at the cyclone's center, normally associated with the wind stress on the ocean's surface, might initiate a rapid weakening of the system due to its slow movement. Although




Figure 3-36-2. Jack as an intense typhoon only 24 hours before dissipation (262126Z December NOAA visual imagery).

such weakening did indeed occur, the extreme nature of the ensuing dissipation was surprising. At 270000Z, JTWC assessed the intensity of Jack (Figure 3-36-2) to be about 105 kt (54 m/sec). Figure 3-36-3 shows the remnants of Jack 24 hours later. All that remained was a 30-kt (15-m/sec) exposed low-level circulation located 120 nm (220 km) northeast of Guam. This remarkable weakening rate exceeded 15 kt (8 m/sec) per 6 hour forecast period. The

remnants of the associated convective cloud mass were about 300 nm (555 km) to the south of the low-level circulation center. The vorticity associated with the cloud mass actually developed a secondary low-level circulation center that moved south of Guam on 28 December. Of interest, NOAA imagery on 29 December detected a cold water cyclonic eddy in the ocean where Jack had been quasistationary for nearly two days.




Figure 3-36-3. The remnants of Jack: an exposed low-level circulation center northeast of Guam, and the last vestige of the convection cloud mass to the south (272357Z December DMSP visual imagery).

3.3 NORTH INDIAN OCEAN TROPICAL CYCLONES

Spring and fall in the North Indian Ocean are periods of transition between major climatic controls and the most favorable seasons for tropical cyclone activity (Tables 3-5 and 3-6). Two significant tropical cyclones developed in the North Indian Ocean in the spring, however, no tropical cyclones developed in the fall transition season. The most interesting

event was the passage of Tropical Cyclone 32W (Gay) into the Bay of Bengal from the Gulf of Thailand. It maintained typhoon intensity while crossing the Malay Peninsula and reached super typhoon intensity which is rare in the Bay of Bengal.

In summary, 1989 tropical cyclone activity was below the 1988 and 15-year average of five (Table 3-6).

TABLE 3-5.		NIFICANT TROP UTH INDIAN OCI	ical cyclones Ean	
		NUMBER OF	MAXIMUM	
TROPICAL		WARNINGS	SURFACE	ESTIMATE
CYCLONE	PERIOD OF WARNING	ISSUED	WINDS-KT (M/SEC)	MSLP (MB)
TC 01B	23 MAY - 26 MAY	14	55 (28)	984
TC 02A	12 JUN - 13 JUN	5	35 (18)	996*
TC 32W	04 NOV - 10 NOV	<u> 25</u>	140 (72)	898
	TOTAL:	44		

TABLE 3-6. NORTH INDIAN OCEAN TROPICAL CYCLONES DISTRIBUTION													
YEAR	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC	TOTAL
1971:		-	=	-	-	0	0	0	0	1	1	0	2
1972		0	0	1	0	0	0	0	2	٥	1	0	4
1973		0	0	0	0	0	0	0	0	1	2	1	4
1974	. 0	0	0	0	0	0	0	0	0	0	1	0	1
1975	1	0	0	0	2	0	0	0	0	1	2	0	6
1976	0	0	0	1	0	1	0	0	1	1	0	1	5
1977	0	0	0	0	1	1	0	0	0	1	2	0	5
1978	0	0	0	0	1	0	0	0	0	1	2	0	4
1979	0	0	0	0	1	1	0	0	2	1	2	0	7
1980	0	0	0	0	0	0	0	0	0	0	1	1	2
1981	0	O	0	0	0	0	0	0	0	1	1	1	3
1982	0	0	0	0	1	1	0	0	0	2	1	0	5
1983	0	0	0	0	0	0	0	1	0	1	1	0	3
1984	0	0	0	0	1	0	0	0	0	1	2	0	4
1985	0	0	0	0	2	0	0	0	0	2	1	1	6
1986	1	0	0	0	0	0	0	0	0	0	2	0	3
1987	0	1	0	0	0	2	0	0	0	1	2	2	8
1988	0	0	0	0	0	1	0	0	0	1	2	1	5 3
1989*	* 0	0	0	0	1	1	0	0	0	0	1	0	3
(1975-19	89)												
AVERA	GE: 0.1	0.1	0.0	0.1	0.7	0.5	0.0	0.1	0.2	1.0	1.5	0.5	4.6
TOTAL	: 2	1	0	1	10	8	0	1	3	14	22	7	69


^{*} JTWC WARNING RESPONSIBILITY BEGAN ON 4 JUNE 1971 FOR THE BAY OF BENGAL, EAST OF 90° EAST LONGITUDE.
AS DIRECTED BY CINCPAC, JTWC ISSUED WARNINGS ONLY FOR THOSE TROPICAL CYCLONES THAT DEVELOPED OR
TRACKED THROUGH THAT PART OF THE BAY OF BENGAL. COMMENCING WITH THE 1975 TROPICAL CYCLONE SEASON,
JTWC'S AREA OF RESPONSIBILITY WAS EXTENDED WESTWARD TO INCLUDE THE WESTERN PART OF THE BAY OF BENGAL
AND THE ENTIRE ARABIAN SEA.


WARNINGS:

NUMBER OF CALENDAR WARNING DAYS: 13

THERE WERE NO CALENDAR WARNING DAYS WITH TWO OR MORE TROPICAL CYCLONES.

^{**} JTWC ISSUED EIGHT TROPICAL CYCLONE FORMATION ALERTS. FORMATION ALERTS WERE ISSUED FOR ALL OF THE SIGNIFICANT TROPICAL CYCLONES THAT DEVELOPED IN 1989. TROPICAL CYCLONE 32W WAS IN WARNING STATUS WHEN IT ENTERED THE BAY OF BENGAL.





TROPICAL CYCLONE 01B

Tropical Cyclone 01B was the first of two cyclones to affect the Bay of Bengal and the only one to form in the Bay this year.

In mid-May, the monsoon trough was well-established throughout the Bay of Bengal between 8° to 10° north latitude with the heaviest convection persisting over the southwestern portion of the Bay. On 20 May, there was a broad area of poorly organized convection formed in the eastern half of the Bay and sparse synoptic data suggested a circulation center. But it wasn't until late on 22 May that the organization improved and convection increased dramatically. This development prompted JTWC to issue a Tropical Cyclone Formation Alert at 230330Z and the first

warning followed at 231500Z. The basic track to the north-northwest was interrupted on 24 and 25 May when weak mid-level steering resulted in an erratic and very slow movement.

Even though the system's development was slowed by northeast winds aloft, Tropical Cyclone 01B (Figure 3-01B-1) did attain a intensity of 55 kt (28 m/sec) at 261200Z, just before making landfall. After landfall the cyclone passed 60 nm (110 km) west of Calcutta, which recorded 25 kt (13 m/sec) sustained surface winds and a minimum sealevel pressure of 988 mb. Then, the dissipating circulation tracked northward into the heat low. No reports of damage were received.





Figure 3-01B-1. Digitized mosaic from the satellite global data base at AFGWC shows Tropical Cyclone 01B moving towards landfall and Calcutta (240300Z-240400Z May DMSP visual data).



TROPICAL CYCLONE 02A

The only significant tropical cyclone to develop in the Arabian Sea this year, Tropical Cyclone 02A, generated from a pre-existing low-level circulation beneath an area of weak upper-level divergence. The disturbance was first mentioned at 071800Z June on the Significant Tropical Weather Advisory. Subsequent satellite imagery indicated the convection was organizing as it tracked toward the northwestern coast of India. The first satellite fix was made at 090148Z, and it estimated the intensity to be 25 kt (13 m/sec). This prompted JTWC to issue a Tropical Cyclone Formation Alert at 090600Z. Although a day later the circulation was technically overland, the presence of enhanced convection overwater resulted in reissuance of the Alert at 100600Z. This Alert was later canceled as satellite and synoptic data showed that the circulation had remained overland for more than 24 hours.

At 111629Z, satellite imagery (Figure 3-02A-1) revealed that the deep convection had moved rapidly westward into the Arabian Sea as an upper-level anticyclone advanced from the Arabian peninsula into Afghanistan and increased the eastern flow aloft over the Arabian Sea. A third Alert followed at 111800Z. Late arriving 110600Z ship observations reported 35 kt (18 m/sec) and a 998 mb pressure near the circulation center. Rapidly increasing convection and low-level organization led to an Abbreviated Warning at 120600Z. Mid-level flow around the subtropical ridge over Iran and Afghanistan carried the cyclone westward, but the strong northeasterly upper-level flow from the anticyclone aloft restricted its outflow and suppressed further development. The last warning was issued at 130600Z when satellite imagery indicated that the convection had separated more than 60 nm (110 km) to the west of the low-level circulation.




Figure 3-02A-1. A digitized mosaic of satellite data shows Tropical Cyclone 02A over the Arabian Sea (111600Z to 111800Z June DMSP infrared imagery).

Intentionally left blank.

4. SUMMARY OF SOUTH PACIFIC AND SOUTH INDIAN OCEAN TROPICAL CYCLONES

4.1 GENERAL

On 1 October 1980 JTWC's area of responsibility (AOR) was expanded to include the Southern Hemisphere from 180° longitude westward to the coast of Africa. Details on Southern Hemisphere tropical cyclones and JTWC warnings from July 1980 through June 1982 are contained in Diercks *et al.* (1982) and from July 1982 through June 1984, in Wirfel and Sandgathe (1986). Information on Southern Hemisphere tropical cyclones after June 1984 can be found in the applicable Annual Tropical Cyclone Report.

The Naval Western Oceanography Center (NWOC) Pearl Harbor, HI issues warnings on tropical cyclones in the South Pacific east of 180° longitude. Tropical cyclones in NWOC's AOR are included in this and previous Annual Tropical Cyclone Reports.

In accordance with USCINCPACINST 3140.1 (series), Southern Hemisphere tropical cyclones are numbered sequentially from 1 July through 30 June. This convention is established to encompass the Southern Hemisphere tropical cyclone season, which normally occurs from January through April. There are two ocean basins for warning purposes - the South Indian (west of 135° east longitude) and the South Pacific (east of 135° east longitude) - which are identified by appending the suffixes "S" and "P" respectively to the tropical cyclone number.

CAVEAT: Intensity estimates for Southern Hemisphere tropical cyclones are derived from the evaluation of satellite imagery (Dvorak, 1984) and in rare instances by surface observations. Estimates for minimum sea-level pressure are derived by applying the Atkinson and Holliday (1977) relationship between maximum sustained one-minute average surface wind and minimum sea-level pressure (Table 4-1) to the intensity estimates derived from satellite imagery. Note: This relationship was based on data from the western North

Pacific. A modified relationship has been adopted for the Atlantic basin.

4.2 SOUTH PACIFIC AND INDIAN OCEAN TROPICAL CYCLONES

After a below average number of tropical cyclones in 1988, 1989 (Table 4-2) activity rose to the near climatological mean of 27 storms (Table 4-3). A comparison of tropical cyclone activity for these two years shows that both started in the beginning of November and ended by mid-May. Although December 1989 proved to be below average with only one tropical cyclone in a month which normally has three, the multiple outbreaks (Figure 4-1) in late February and in the late March/early April timeframe resulted in the total being near normal. During the year, two tropical cyclones achieved super typhoon intensity—Harry (10P) and Orson (26S). Harry (10P) also shared the

Table 4-1 Maximum Sustained Surface Winds and equivalent minimum Sea-Level Pressure (Atkinson and Holliday, 1977)								
MAXIMUM SUSTAINED	MINIMUM SEA-LEVEL							
SURFACE WIND (KT)	PRESSURE (MB)							
30	1000							
35	997							
40	994							
45	991							
- 50	987							
55	984							
60	980							
65	976							
70	972							
75	967							
80	963							
85	958							
90	954							
95	948							
100	943							
105	938							
110	933							
115	927							
120	922							
125	916							
130	910							
135	906							
140	898							
145	892							

distinction of requiring warnings for almost two weeks with Barisaona (02S) and Hanitra (11S). A comparison of activity by basin appears in

Table 4-4. Plots of the tropical cyclone best tracks are provided in Figures 4-2 and 4-3.

TABLE 4-2	SOUTH PACIFIC AND 1989 SIGNIFICAN (1 July 1988	TROPICAL	CYCLONES	
		NUMBER	MAXIMUM	
		WARNINGS	SURFACE	ESTIMATED
TROPICAL CYCLONE	PERIOD OF WARNING	ISSUED	WINDS-KT (M/SEC)	MSLP (MB)
01S ADELININA	01 NOV - 04 NOV	9	75 (39)	968***
02S BARISAONA	08 NOV - 20 NOV	2.6	100 (51)	944***
03S ILONA	13 DEC - 18 DEC	10	85 (44)	958
04P DELILAH	01 JAN - 03 JAN	4	60 (31)	980
05P GINA	07 JAN - 09 JAN	6**	45 (23)	991
06S	10 JAN - 14 JAN	9	75 (39)	968***
07S EDME	20 JAN - 25 JAN	11	115 (59)	927
08S FIRINGA	26 JAN - 01 FEB	14	90 (46)	954
09S KIRRILY	06 FEB - 10 FEB	9	75 (39)	967
10P HARRY	08 FEB - 19 FEB	24	130 (67)	910
11S HANITRA	17 FEB - 28 FEB	23	125 (64)	916
12S GIZELA	18 FEB - 22 FEB	9	65 (33)	976
13P IVY	23 FEB - 01 MAR	13	100 (51)	944***
14P	24 FEB - 01 MAR	10**	90 (46)	954
15P JUDY	24 FEB - 28 FEB	9**	90 (46)	954
16S	24 FEB - 25 FEB	3	45 (23)	991
17S MARCIA	03 MAR - 04 MAR	.3	35 (18)	987***
188	09 MAR - 10 MAR	4	35 (18)	997
19S JINARO	25 MAR - 30 MAR	13	65 (33)	976
20S NED	26 MAR - 31 MAR	19	100 (51)	943
21S KRISSY	30 MAR - 07 APR	18	105 (54)	938
22P KERRY	31 MAR - 02 APR	5	50 (26)	987
23P AIVU	01 APR - 04 APR	8	120 (62)	922
24S LEZISSY	06 APR - 09 APR	6	45 (23)	991
25P LILI	07 APR - 11 APR	10	110 (57)	933
26S ORSON	18 APR - 23 APR	12	140 (72)	898
27P MEENA	03 MAY - 10 MAY	16	50 (26)	987
28P ERNIE	07 MAY - 09 MAY	5	35 (18)	997
28P ERNIE*	10 MAY - 12 MAY	4	30 (15)	1000
	TOTAL	312		

^{*} REGENERATED

NOTE: NAMES OF SOUTHERN HEMISPHERE TROPICAL CYCLONES ARE GIVEN BY THE REGIONAL WARNING CENTERS (NADI, BRISBANE, DARWIN, PERTH, REUNION AND MAURITIUS) AND ARE APPENDED TO JTWC WARNINGS, WHEN AVAILABLE.

^{**} ISSUED BY NWOC

^{***} BASED ON SYNOPTIC DATA

Figure 4-1. Chronology of South Pacific and South Indian Ocean tropical cyclones for 1989.




TABLE 4-3 TROPICAL CYCLONE DISTRIBUTION SOUTH PACIFIC AND SOUTH INDIAN OCEANS													
YEAR	JUL	AUG	SEP	OCT	NOV	DEC	JAN	FEB	MAR	APR	MAY	JUN	TOTAL
(1959-1978)													
AVERAGE*	-	-	-	0.4	1.5	3.6	6.1	5.8	4.7	2.1	0.5		24.7
1981	0	0	0	1	3	2	6	5	3	3	1	0	24
1982	1	0	0	. 1	1	3	9	4	2	3	1	ō	25
1983	1	0	0	1	1	3	5	6	3	5	O	Ō	25
1984	1	0	0	1	2	5	5	10	4	2	0	Ō	30
1985	0	0	0	0	1	7	9	9	6	3	0	Ó	35
1986	0	0	1	0	1	1	9	9	6	4	2	0	33
1987	0	1	0	0	1	3	6	8	3	4	1	1	28
1988	0	0	0	0	2	3	5	5	3	1	2	0	21
1989	0	0	0	0	2	1	5	8	6	4	2	0	28
TOTAL CASES:	3	1	1	4	14	28	59	64	36	29	9	1	249
(1981–1989)													
AVERAGE:	0.3	0.1	0.1	0.4	1.6	3.1	6.6	7.1	4.0	3.2	1.0	0.1	27.7
* (GRAY, 197	9)												

	SOUTH INDIAN	AUSTRALIAN	SOUTH PACIFIC	
YEAR	(WEST OF 105° E)	(105° E - 165° E)	(EAST OF 165° E)	TOTAL
(1959-1978	3)			
AVERAGE*	8.4	10.3	5.9	24.7
1981	13	8	3	24
1982	12	11	2	25
1983	7	6	12	25
1984	14	14	2	30
1985	14	15	6	35
1986	14	16	3	33
1987	9	8	11	28
1988	14	2	5	21
1989	12	9	7	28
TOTAL CASE	S: 109	89	51	249
(1981–1989)			
AVERAGE:	12.1	9.9	5.7	27.7




Figure 4-2




Figure 4-3

5. SUMMARY OF FORECAST VERIFICATION

5.1 ANNUAL FORECAST VERIFICATION

5.1.1 WESTERN NORTH PACIFIC OCEAN - Verification of warnings at initial, 24-, 48and 72-hour forecast positions was made against the final best track. The (scalar) forecast, along-track and cross-track errors (illustrated in Figure 5-1) were then calculated for each tropical cyclone and are presented in Tables 5-1A, 5-1B, 5-1C and 5-1D, as appropriate. Table 5-2 includes mean alongtrack and cross-track forecast errors for 1978-1989. The frequency distributions of errors for warning positions, and 24-, 48-, and 72-hour forecasts are in Figures 5-2A through 5-2D, respectively. A comparison of the annual mean forecast errors for all tropical cyclones as compared to those tropical cyclones that reached typhoon intensity can be seen in Table 5-3. The mean forecast errors for 1989 as compared to the twenty previous years are graphed in Figure 5-3.

5.1.2 NORTH INDIAN OCEAN — The positions given for warning times and those at

the 24-, 48-, and 72-hour valid times were verified for tropical cyclones in the North Indian Ocean by the same methods used for the western North Pacific. Table 5-4 is the initial and forecast along-track and cross-track error summary for the North Indian Ocean. Forecast errors are plotted in Figure 5-4 (72-hour forecast errors were evaluated for the first time in 1979). There were no verifying 72-hour forecasts in 1983 and 1985. Table 5-5 contains a summary of the annual mean forecast errors for each year.

5.1.3 SOUTH PACIFIC AND SOUTH INDIAN OCEANS — The positions given for warning times and those at the 24-, 48-, and 72-hour valid times were verified for tropical cyclones in the Southern Hemisphere by the same methods used for the western North Pacific. Table 5-6A is the initial, forecast along-track and cross-track error summary for the Southern Hemisphere. Table 5-6B has the number of warnings verified at each forecast period. Forecast errors are plotted in Figure 5-5. Table 5-7 contains a summary of the annual mean forecast errors.

Figure 5-1. Definition of cross-track error (XTE), along-track error (ATE) and forecast track error (FTE). In this example, the XTE is positive (to the right of the best track) and the ATE is negative (behind or slower than the best track).




TABLE 5-1A INITIAL POSITION ERRORS (NM)
WESTERN NORTH PACIFIC OCEAN
1989 SIGNIFICANT TROPICAL CYCLONES

TROPIC	CAL (CYCLONE	ERROR (NM	NUMBER OF WARNINGS
(01W)	TS	WINONA	25	13
(02W)	STY	ANDY	12	26
		BRENDA	31	20
(04W)	TY	CECIL	19	9
(05W)			16	25
		ELLIS	33	6
(07W)	TS	FAYE	25	21
(08W)	STY	GORDON	13	30
(WPO)	TS	HOPE	21	21
(10W)	TS	IRVING		14
(11W)	TY	JUDY	15	28
(12W)			14	3
(13W-14W)	TS	KEN-LOLA		23
(15W)	TY	MAC	17	28
		OWEN	21	28
(17W)	TY	NANCY	19	22
(18W)	TS	PEGGY	24	9
(19W)	TD	19W	19	6
		ROGER	32	14
(21W)			23	7
		SARAH	28	33
(23W)			23	20
		VERA	25	16
		WAYNE	19	12
		ANGELA		46
		BRIAN		13
(28W)	TY	COLLEEN		27
		DAN	16	21
		ELSIE	12	34
(31W)	TY	FORREST		30
(32W)			6	9
		HUNT	14	27
		IRMA	18	39
(35W)	TD	35W Jack	73	9
(36W)	TY	JACK	28	21
			MEAN: 20	TOTAL: 710

24-HOUR FORECAST ERRORS (NM) WESTERN HORTH PACIFIC OCEAN 1989 SIGNIFICANT TROPICAL CYCLORES

		FORECAST		-TRACK ROR		-TRACK ROR	SAMPLE
TROPICAL C	CYCLONE I	ERROR (NM)	MEAN*	MEDIAN	MEAN*	MEDIAN	SIZE
(01W) TS	WINONA	171	152	**	88	**	10
(02W) STY	ANDY	111	77	-44	65	-18	26
(03W) TY	BRENDA	133	103	-78	68	14	18
(04W) TY	CECIL	127	64	**	108	**	8
(05W) TY	DOT	78	55	-10	48	30	23
(06W) TS	ELLIS	347	294	**	126	**	6
(07W) TS	FAYE	72	48	-28	41	-12	18
(08W) STY	GORDON	68	41	21	47	5	26
(09W) TS	HOPE	112	39	25	101	-10	17
(10W) TS	IRVING	91	73	**	41	**	9
(11W) TY	JUDY	85	55	-32	54	34	24
(12W) TD	12W	61	32	**	52	**	2
•	KEN-LOLA	195	114	-115	124	-61	18
(15W) TY	MAC	167	126	-83	86	-13	26
	OWEN	115	78	-60	66	9	27
(17W) TY	NANCY	146	127	-98	52	-34	20
•	PEGGY	143	91	**	100	**	8
, ,	19W	95	60	**	53	**	4
(20W) TS	ROGER	223	192	-167	97	-80	12
	21W	135	107	**	55	**	6
	SARAH	165	9 5	-37	122	-16	29
(23W) TS	TIP	204	110	-74	152	-127	18
(24W) TS	VERA	173	145	-135	68	-25	13
(25W) TY	WAYNE	231	201	**	105	**	10
(26W) STY	ANGELA	68	46	-17	40	15	43
	BRIAN	104	69	**	52	**	10
• •	COLLEEN	153	116	-68	74	-35	24
• •	DAN	105	88	-55	38	-10	18
• • • •	ELSIE	75	48	-37	44	-15	31
•	FORREST	93	61	-5	56	-37	27
,, ++	GAY	46	25	**	30	**	9
• • •	HUNT	98	64	6	58	-44	25
• •	IRMA	97	69	-37	53	-32	35
• •	35 W	212	79	**	192	**	5
(36W) TY	JACK	95	55	-11	67	-31	20
	MEAN	I: 120		83		69 :	IOTAL: 625
	MEDIAN			47		13	— -
STANDA	RD DEVIATION			05		90	

^{*} THE MEAN WAS COMPUTED FROM ABSOLUTE VALUES.

^{**} THE MEDIAN WAS NOT COMPUTED FOR INSTANCES OF TEN CASES OR LESS.

^{1.} THE MEAN IS THE SUM OF ALL THE VALUES DIVIDED BY THE NUMBER OF OBSERVATIONS.

^{2.} THE MEDIAN IS THE MIDDLE VALUE OF THE SAMPLE, ESTIMATED THROUGH A GAMMA PROBABILITY DISTRIBUTION.

^{3.} THE ALONG-TRACK ERROR COMPONENT IS HOW FAR THE WARNING POSITION WAS DISPLACED AHEAD OR BEHIND THE BEST TRACK POSITION. THE SAMPLE CONSISTS OF TWO PARTS: THE MEAN (DISTANCE) AND THE MEDIAN (NEGATIVE VALUES WERE BEHIND TRACK OR SLOW, AND POSITIVE VALUES WERE AHEAD OF TRACK OR FAST).

^{4.} THE CROSS-TRACK ERROR COMPONENT IS HOW FAR THE WARNING POSITION WAS DISPLACED TO THE LEFT OR RIGHT OF THE BEST TRACK POSITION. THE SAMPLE CONSISTS OF TWO PARTS: THE MEAN (DISTANCE) AND THE MEDIAN (NEGATIVE VALUES WERE LEFT OF TRACK AND POSITIVE VALUES WERE RIGHT OF TRACK).

TABLE 5-1C

48-HOUR FORECAST ERRORS (NM) WESTERN NORTH PACIFIC OCEAN 1989 SIGNIFICANT TROPICAL CYCLONES

FORECAST ERROR ERROR SAMPLE TROPICAL CYCLONE FORCA (MM) MEAN* MEDIAN MEAN* MEDIAN SIZE (02W) STY ANDY 290 205 -167 174 -74 22 (03W) TY BRENDA 227 178 -180 104 48 12 (04W) TY CECLL 330 80 ** 318 ** 6 (05W) TY DOT 148 113 -8 80 73 17 (06W) TS ELLIS *** *** *** *** *** *** 0 (07W) TS FAYE 124 106 -106 54 -12 12 (08W) STY GORDON 118 65 30 85 23 24 (09W) TS HOPE 224 111 82 172 -57 14 (10W) TS IRVING 152 133 ** 44 ** 4 (11W) TY JUDY 195 98 -92 144 107 20 (12W) TD 12W *** *** *** *** *** 0 (13W-14W) TS KEN-LOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY COMEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (18W) TD 19W *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 19W *** *** *** *** *** *** *** 0 (22W) TS ROGER 474 459 ** 94 ** 7 (21W) TS SARAH 302 140 5 240 -18 25 (23W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 240 -190 11 (24W) TY SARAH 302 140 5 25 3 84 4 (25W) TY SARAH 302 140 5 240 -190 66 -39 27 (25W) TY SARAH 302 140 5 5 240 -190 66 -39 2				FORECAST		G-TRACK		-TRACK	
(01W) TS WINONA 346 322 ** 118 ** 6 (02W) STY ANDY 290 205 -167 174 -74 22 (03W) TY BRENDA 227 178 -180 104 48 12 (04W) TY CECIL 330 80 ** 318 ** 6 (05W) TY CECIL 330 80 ** 318 ** 6 (05W) TY DOT 148 113 -8 80 73 17 (06W) TS ELLIS *** *** *** *** *** *** *** 0 (07W) TS FAYE 124 106 -106 54 -12 12 (06W) STY GORDON 118 65 30 85 23 24 (09W) TS HOPE 224 111 82 172 -57 14 (10W) TS IRVING 152 133 ** 44 ** 4 (11W) TY JUDY 195 98 -92 144 107 20 (12W) TO 12W *** *** *** *** *** *** 0 (13W-14W) TS KEN-LOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY OWEN 239 189 -151 108 37 23 (17W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TS PEGGY 335 147 ** 281 ** 6 (19W) TS PEGGY 335 147 ** 281 ** 6 (19W) TS PEGGY 335 147 ** 281 ** 6 (19W) TS PEGGY 335 147 ** 281 ** 6 (19W) TS PEGGY 335 147 ** 281 ** 6 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** *** *** *** *	TTD OD T	-CD-T	MIOT OUT						SAMPLE
(02W) STY ANDY 290 205 -167 174 -74 22 (03W) TY BRENDA 227 178 -180 104 48 12 (04W) TY CECIL 330 80 ** 318 ** 6 (05W) TY DOT 148 113 -8 80 73 17 (06W) TY DOT 148 113 -8 80 73 17 (06W) TS ELLIS *** *** *** *** *** *** *** 0 (07W) TS ELLIS *** *** *** *** *** *** *** *** *** *	IROPI	CAL	CICLONE	ERROR (NM)	MEAN*	MEDIAN	MEAN*	MEDIAN	<u>SIZE</u>
(03W) TY BRENDA 227 178 -180 104 48 12 (04W) TY CECIL 330 80 ** 318 ** 6 (05W) TY CECIL 330 80 ** 318 ** 6 (05W) TY CECIL 330 80 ** 318 ** 6 (05W) TY CECIL 330 80 ** 318 ** 6 (05W) TY CECIL 330 80 ** 318 ** 6 (05W) TY CECIL 330 80 ** 318 ** 4 (05W) TY CECIL 330 80 73 17 (06W) TS ELLIS *** ** *** *** *** *** *** *** *** **	(01W)	TS	WINONA	346	322	**	118	**	6
(03W) TY BRENDA 227 178 -180 104 48 12 (04W) TY CECIL 330 80 ** 318 ** 6 (05W) TY DOT 148 113 -8 80 73 17 (06W) TS ELLIS *** *** *** *** *** *** *** *** *** *	(02W)	STY	ANDY	290	205	-167	174	-74	22
(04W) TY CECIL 330 80 ** 318 ** 6 (05W) TY DOT 148 113 -8 80 73 17 (06W) TS DOT 148 113 -8 80 73 17 (06W) TS EILIS *** *** *** *** *** *** *** 0 (07W) TS FAYE 124 106 -106 54 -12 12 (08W) STY GORDON 118 65 30 85 23 24 (10W) TS HOPE 224 111 82 172 -57 14 (10W) TS IRVING 152 133 ** 44 ** 4 (11W) TY JUDY 195 98 -92 144 107 20 (12W) TD 12W *** *** *** *** *** 0 (13W-14W) TS KEN-IOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY MAC 335 244 -146 198 -132 23 (16W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 12W *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 1W *** *** *** *** *** 0 (20W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TS VERA 381 373 ** 69 ** 10 (25W) TY VERA 381 373 ** 69 ** 10 (25W) TY VERA 381 373 ** 69 ** 10 (25W) TY SARAH 135 79 ** 10 540 -18 25 (25W) TY SARAH 135 79 ** 10 540 -18 25 (25W) TY DAN 222 202 -206 55 -29 13 (30W) STY EISIE 145 115 -90 66 -39 27 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY EISIE 145 115 -90 66 -39 27 (29W) TY DAN 222 202 -206 55 -29 13 (30W) TY FORREST 169 122 -16 85 -81 23 (32W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (33W) TY HUNT 173 123 41 103 -64 23 (35W) TY JACK 167 135 -14 83 -25 18	(03W)	TY	BRENDA	227	178	-180	104	48	
(05W) TY DOT	(04W)	TY	CECIL	330	80	**	318	**	
(06W) TS ELLIS	(05W)	TY	DOT	148	113	-8	80	73	
(08W) STY GORDON 118 65 30 85 23 24 (09W) TS HOPE 224 111 82 172 -57 14 (10W) TS HOPE 224 111 82 172 -57 14 (11W) TS IRVING 152 133 ** 44 ** 4 (11W) TY JUDY 195 98 -92 144 107 20 (12W) TD 12W *** *** *** *** *** *** *** 0 (13W-14W) TS KEN-LOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 4** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) TY WAYNE 623 564 ** 253 ** 4 (26W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ERISE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (33W) TY FORREST 169 122 -16 85 -81 23 (33W) TY FORREST 169 122 -16 85 -81 23 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (35W) TY JACK 167 135 -14 83 -25 18	(06W)	TS	ELLIS	***	***	***	***	***	0
(09W) TS HOPE 224 111 82 172 -57 14 (10W) TS IRVING 152 133 ** 44 ** 4 (11W) TY JUDY 195 98 -92 144 107 20 (12W) TD 12W *** ** *** *** *** *** 0 (13W-14W) TS KEN-LOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY MAC 335 244 -146 198 -132 23 (16W) TY MAC 335 147 ** 281 ** 6 (19W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 8 (33W) TY GAY 101 87 ** 8 (33W) STY IRMA 226 188 -179 104 -74 25 (35W) TY JACK 167 135 -14 83 -25 18	(07W)	TS	FAYE	124	106	-106	54	-12	12
(10W) TS IRVING 152 133 ** 44 ** 4 (11W) TY JUDY 195 98 -92 144 107 20 (12W) TD 12W *** *** *** *** *** *** 0 (13W-14W) TS KEN-LOIA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (16W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY SARAH 302 140 5 240 -18 25 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 11 (36W) TY JACK 167 135 -14 83 -25 18	(W8O)	STY	GORDON	118	65	30	85	23	24
(11W) TY JUDY 195 98 -92 144 107 20 (12W) TD 12W *** *** *** *** *** *** *** *** 0 (13W-14W) TS KEN-LOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (16W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (25W) TY BRIAN 135 79 ** 93 ** 5 (25W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (21W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TJ JACK 167 135 -14 83 -25 18	(O9W)	TS	HOPE	224	111	82	172	-57	14
(12W) TD 12W *** *** *** *** *** *** 0 (13W-14W) TS KEN-LOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18	(10W)	TS	IRVI N G	152	133	**	44	**	4
(13W-14W) TS KEN-LOLA 313 180 -106 225 -194 14 (15W) TY MAC 335 244 -146 198 -132 23 (16W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (16W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (26W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18	(11W)	TY	JUDY	195	98	-92	144	107	20
(15W) TY MAC 335 244 -146 198 -132 23 (16W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TY JACK 167 135 -14 83 -25 18	(12W)	TD	12W	***	***	***	***	***	0
(16W) TY OWEN 239 189 -151 108 37 23 (17W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 459 ** 47 (21W) TD 21W *** *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TY JACK 167 135 -14 83 -25 18	(13W-14W)	TS	KEN-LOLA	313	180	-106	225	-194	14
(17W) TY NANCY 348 294 -266 110 12 19 (18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** ** *** *** *** *** *** 0 (20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18	(15W)	TY	MAC	335	244	-146	198	-132	23
(18W) TS PEGGY 335 147 ** 281 ** 6 (19W) TD 19W *** *** *** *** *** *** *** *** *** *	(16W)	TY	OWEN	239	189	-151	108	37	23
(19W) TD 19W	(17W)	TY	NANCY	348	294	-266	110	12	19
(20W) TS ROGER 474 459 ** 94 ** 7 (21W) TD 21W *** *** *** *** *** *** 0 (22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18				335	147	**	281	**	6
(21W) TD 21W *** *** *** *** *** *** ***	(19W)			***	***	***	***	***	0
(22W) TY SARAH 302 140 5 240 -18 25 (23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18	(20W)	TS	ROGER	474	459	**	94	**	7
(23W) TS TIP 374 206 -193 270 -190 11 (24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18				***	***	***	***	***	0
(24W) TS VERA 381 373 ** 69 ** 10 (25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18				302	140	5	240	-18	25
(25W) TY WAYNE 623 564 ** 253 ** 4 (26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18				374	206	-193	270	-190	11
(26W) STY ANGELA 165 112 -51 96 73 39 (27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18				381	373	**	69	**	10
(27W) TY BRIAN 135 79 ** 93 ** 5 (28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18				623	564	**	253	**	4
(28W) TY COLLEEN 207 132 -25 135 -75 20 (29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18	• •			165	112	-51	96	73	39
(29W) TY DAN 222 202 -206 55 -29 13 (30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18	. ,			135	79	**	93	**	5
(30W) STY ELSIE 145 115 -90 66 -39 27 (31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18					132	-25	135	-75	20
(31W) TY FORREST 169 122 -16 85 -81 23 (32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18				222	202	-206	55	-29	13
(32W) TY GAY 101 87 ** 39 ** 8 (33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18 MEAN: 231 162 127 TOTAL: 481					115	~90	66	-39	27
(33W) TY HUNT 173 123 41 103 -64 23 (34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18	, ,			169	122	-16	85	-81	23
(34W) STY IRMA 226 188 -179 104 -74 25 (35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18 MEAN: 231 162 127 TOTAL: 481	(32W)			101	87	**	39	**	8
(35W) TD 35W 440 30 ** 439 ** 1 (36W) TY JACK 167 135 -14 83 -25 18					123	41	103	-64	23
(36W) TY JACK 167 135 -14 83 -25 18 MEAN: 231 162 127 TOTAL: 481	, ,			226	188	-179	104	-74	25
MEAN: 231 162 127 TOTAL: 481				440		**	439	**	1
	(36W)	TY	JACK	167	135	-14	83	-25	18
			MEAN	N: 231	14	62	11	77 11)/PAT. • 481
					_				

* THE MEAN WAS COMPUTED FROM ABSOLUTE VALUES.

STANDARD DEVIATION: 145

190

SEE TABLE 5-1B FOR EXPLANATIONS OF THE TERMS MEAN, MEDIAN, ALONG-TRACK ERROR AND CROSS-TRACK ERROR.

171

^{**} THE MEDIAN WAS NOT COMPUTED FOR INSTANCES OF TEN CASES OR LESS.

^{***} FORECASTS WERE NOT ISSUED OR DID NOT VERIFY.

TABLE 5-1D

72-HOUR FORECAST ERRORS (NM) WESTERN NORTH PACIFIC OCEAN 1989 SIGNIFICANT TROPICAL CYCLONES

WDODICZY (FORECAST TROPICAL CYCLONE ERROR (NM)		ALONO ER	ER	S-TRACK ROR	SAMPLE	
TROPICAL	SICLORE P	RROR (NM)	<u>MEAN*</u>	MEDIAN	MEAN*	MEDIAN	SIZE
(01W) TS	WINONA	507	439	**	242	**	5
, ,	ANDY	569	385	-352	378	-212	18
• • • •	BRENDA	251	188	**	142	**	9
• •	CECIL	***	***	***	***	***	ō
• •	DOT	163	123	1	81	79	11
• • • • • • • • • • • • • • • • • • • •	ELLIS	***	***	***	***	***	0
, ,	FAYE	220	213	**	49	**	10
1	GORDON	146	111	75	75	9	18
•	HOPE	309	145	**	259	**	5
• •	IRVING	232	227	**	45	**	2
• •	JUDY	323	190	-150	219	135	16
(12W) TD	12W	***	***	***	***	***	0
(13W-14W) TS	KEN-LOLA	382	168	**	320	**	10
(15W) TY	MAC	520	352	-185	357	-136	19
(16W) TY	OWEN	380	336	-248	132	73	19
(17W) TY	NANCY	510	483	-489	132	21	16
(18W) TS	PEGGY	506	187	**	462	**	2
(19W) TD	19W	***	***	***	***	***	0
(20W) TS	ROGER	949	921	**	233	**	3
(21W) TD	21W	***	***	***	***	***	0
(22W) TY	SARAH	450	236	-30	322	-38	21
(23W) TS	TIP	502	440	**	206	**	8
(24W) TS	VERA	662	641	**	129	**	7
(25W) TY	WAYNE	***	***	***	***	***	0
(26W) STY	ANGELA	293	202	-117	178	149	35
(27W) TY	BRIAN	***	***	***	***	***	0
(28W) TY	COLLEEN	303	193	-78	189	-177	16
(29W) TY	DAN	376	359	**	89	**	10
(30W) STY	ELSIE	231	222	-155	58	-25	23
(31W) TY	FORREST	318	242	-228	138	-111	18
(32W) TY	GAY	197	185	**	57	**	8
(33W) TY	HUNT	208	156	112	103	-83	19
(34W) STY	IRMA	341	289	-300	146	-56	21
(35W) TD	35W	***	***	***	***	***	0
(36W) TY	JACK	317	254	-32	159	105	14
	Mean	I: 350	2	65	1	77 '	TOTAL: 363
	MEDIAN		-1		_	77 15	AVARMI, JUJ
QT NIDZ	RD DEVIATION			87		36	
	TA THE TOTAL	. 200	2	· ,	2	50	

^{*} THE MEAN WAS COMPUTED FROM ABSOLUTE VALUES.

SEE TABLE 5-1B FOR EXPLANATIONS OF THE TERMS MEAN, MEDIAN, ALONG-TRACK ERROR AND CROSS-TRACK ERROR.

^{**} THE MEDIAN WAS NOT COMPUTED FOR INSTANCES OF TEN CASES OR LESS.

^{***} FORECASTS WERE NOT ISSUED OR DID NOT VERIFY.

TABLE 5-2. JTWC ANNUAL INITIAL POSITION AND FORECAST POSITION ERRORS (NM) 1978-1989 FOR THE WESTERN NORTH PACIFIC INITIAL 24 - HOUR 48 - HOUR 72 - HOUR YEAR WARNINGS POSITION FORECASTS TRACK ALONG CROSS FORECASTS TRACK **ALONG** CROSS FORECASTS TRACK ALONG CROSS TOTALS: AVERAGE 78-88: TOTALS: AVERAGE 78-89:

Sources: 1978-85 24-, 48- & 72-hour errors from Tsul and Miller (1986) Initial Position & 1988-89 errors from ATCR




Figure 5-2A. Frequency distribution of initial position errors (15 nm increments) for the western North Pacific in 1989.




Figure 5-2B. Frequency distribution of 24-hour forecast errors (30 nm increments) for the western North Pacific in 1989.




Figure 5-2C. Frequency distribution of 48-hour forecast errors (60 nm increments) for the western North Pacific in 1989.




Figure 5-2D. Frequency distribution of 72-hour forecast errors (90 nm increments) for the western North Pacific in 1989.

MEAN: 350

231

203

145

481

307 MEDIAN:

STANDARD DEVIATION: 206

CASES: 363

The median is the middle value obtained by sorting, and differs from median computed for Tables 5-1B, 5-1C,5-1D, 5-4 and 5-6A.

ABLE 5-3		annual Mez West	IN FORECAS ERN NORTH		(MM)	
		24-HOUR	48	-HOUR		72-HOUR
YEAR	ALL	/ TYPHOONS*	ALL /	TYPHOONS*	ALL	/ TYPHOONS*
1959		117**		267**		
1960		177**		354**		
1961		136		274		
1962		144		287		476
1963		127		246		374
1964		133		284		429
1965		151		303		418
1966		136		280		432
1967		125		276		414
1968		105		229		337
1969		111		237		349
1970	104	98	190	181	279	272
1971	111	99	212	203	317	308
1972	117	116	245	245	381	382
1973	108	102	197	193	253	245
1974	120	114	226	218	348	357
1975	138	129	288	279	450	442
1976	117	117	230	232	338	336
1977	148	140	283	266	407	390
1978	127	120	271	241	410	459
1979	124	113	226	219	316	319
1980	126	116	243	221	389	362
1981	123	117	220	215	334	342
1982	113	114	237	229	341	337
1983	117	110	259	247	405	384
1984	117	110	233	228	363	361
1985	117	112	231	228	367	355
1986	121	117	261	261	394	403
1987	107	101	204	211	303	318
1988	114	107	216	222	315	327
1989	120	107	231	214	350	325

^{*} FORECASTS WERE VERIFIED WHEN THE TROPICAL CYCLONE INTENSITIES WERE AT LEAST 35 KT (18 M/SEC).

^{**} FORECAST POSITIONS NORTH OF 35 DEGREES NORTH LATITUDE WERE NOT VERIFIED.




Figure 5-3. Annual mean forecast errors (nm) for all significant tropical cyclones in the western North Pacific.

TABLE 5-4		FOR THE	NAME FORECT	AN OCEAN	•	
		INITIAL I	POSITION			
TROPICAL CYCLONE		ERROR				NUMBER OF WARNINGS
TC 01B		23				14
TC 02A		41				5
TC 32W		13	3			<u>25</u>
TOTAL			-			44
MEAN		19	•			
STANDARD DEVIATION		15	5			
	FCST	24-HOUR I		CROSS-TR	ACK ERROR	₹
TROPICAL CYCLONE	ERROR	MEAN	MEDIAN	MEAN	MEDIAN	SAMPLE SIZE
TC 01B	106	88	**	45	**	11
TC 02A	134	129	**	35	**	1
TC 32W	<u> 76</u>	51	-52	43	<u>-15</u>	21
TOTAL		-				33
MEAN	88	•	52		50	
MEDIAN	88	-3	32	_	·13	
STANDARD DEVIATION	44	•	58		61	
	FCST-	48-HOUR I		CROSS-TR	ACK ERROR	₹
TROPICAL CYCLONE	ERROR	MEAN	MEDIAN	MEAN	<u>MEDIAN</u>	SAMPLE SIZE
TC 01B						0
TC 02A						0
TC 32W	146	94	<u>-95</u>	86	<u>-2</u>	17
TOTAL		-				17
MEAN	146	9	94		86	
MEDIAN	145	-9	95		-2	
STANDARD DEVIATION	48	7	13		97	
		72-HOUR F				
	FCST	ALONG-TRA			ACK ERROR	
TROPICAL CYCLONE	ERROR	MEAN	MEDIAN	MEAN	MEDIAN	SAMPLE SIZE
TC 01B						O
TC 02A						0
TC 32W	216	164	<u>-166</u>	111	<u>-31</u>	12
TOTAL		-	-			12
MEAN	216	16	54	1	.11	
MEDIAN	215	-16	6	_	31	
STANDARD DEVIATION	61	9	3	1	18	

^{**} THE MEDIAN WAS NOT COMPUTED FOR INSTANCES OF TEN CASES OR LESS.

SEE TABLE 5-1B FOR EXPLANATION OF THE TERMS MEAN, MEDIAN, ALONG-TRACK ERROR AND CROSS-TRACK ERROR.




Figure 5-4. Annual mean forecast errors (nm) for all significant tropical cyclones in the North Indian Ocean.

TABLE 5-5			EAN FORECAS EE NORTH IN	et errors (NM) Dian ocean		
	24-	-HOUR	48-	-HOUR	72-	HOUR
YEAR	FORECAST	RIGHT-ANGLE	FORECAST	RIGHT-ANGLE	FORECAST	RIGHT-ANGLE
1971*	232		410			
1972*	224	101	292	112		
1973*	182	99	299	160		
1974*	137	81	238	146		
1975	145	99	228	144		
1976	138	108	204	159		
1977	122	94	292	214		
1978	133	86	202	128		
1979	151	99	270	202	437	371
1980	115	73	93	87	167	126
1981**	109	65	176	103	197	73
1982**	138	66	368	175	762	404
1983**	117	46	153	67		
1984**	154	71	274	127	388	159
1985**	123	51	242	109		
1986	134	***	168	***	269	***
1987	144	***	205	***	305	***
1988	120	***	219	***	409	***
1989	84	***	146	***	216	***

^{*} THE WESTERN BAY OF BENGAL AND ARABIAN SEA WERE NOT INCLUDED IN THE JTWC AREA OF RESPONSIBILITY UNTIL THE 1975 TROPICAL CYCLONE SEASON.

^{**} THE TECHNIQUE FOR CALCULATING RIGHT-ANGLE ERROR WAS REVISED IN 1981. THEREFORE, A DIRECT COMPARISON IN RIGHT-ANGLE ERROR STATISTICS CANNOT BE MADE BETWEEN ERRORS COMPUTED BEFORE 1981 AND THOSE COMPUTED SINCE 1981.

^{***} IN 1986, RIGHT-ANGLE ERROR WAS REPLACED BY CROSS-TRACK ERROR. (SEE

TABLE 5-6A INITIAL POSITION AND FORECAST ERRORS (NM) FOR THE SOUTH PACIFIC AND SOUTH INDIAN OCEANS
1989 SIGNIFICANT TROPICAL CYCLONES (1 JULY 1988 - 30 JUNE 1989)

TROPICAL	INITIAL POSIT			-HOUR		HOUR	48-HR		HOUR		-HOUR
CYCLONE		FCST		G-TRACK		-TRACK	FCST		TRACK		TRACK
CICIONE	ERROR	ERROR	MEAN*	MEDIAN	MEAN*	MEDIAN	ERROR	MEAN*	MEDIAN	MEAN*	MEDIAN
TC 01S	83	235	209	**	.80	**	384	349	**	134	**
TC 02S	25	98	75	-21	45	-4	169	127	-59	79	-43
TC 03S	14	106	54	**	67	**	203	122	**	125	**
TC 04P	20	74	27	**	66	**	110	80	**	76	**
TC 05P	30	130	94	**	83	**	464	408	**	222	**
TC 06S	18	100	87	**	39	**	156	113	**	99	**
TC 07S	29	141	64	**	102	**	322	170	**	244	**
TC 08S	23	105	90	**	40	**	201	166	**	81	**
TC 09S	27	162	66	**	83	**	313	116	**	193	**
TC 10P	23	111	79	-54	57	-9	269	205	-164	138	14
TC 11S	27	92	54	-39	62	34	180	119	-87	106	57
TC 12S	33	154	107	**	86	**	266	158	**	192	**
TC 13P	50	120	89	-53	59	51	207	174	**	88	**
TC 14P	34	139	80	**	94	**	238	144	**	167	**
TC 15P	22	160	123	**	87	**	390	191	**	321	**
TC 16S	35	229	219	**	69	**	***	***	***	***	***
TC 17S	13	92	32	**	86	**	332	286	**	169	**
TC 18S	40	220	182	**	55	**	400	355	**	184	**
TC 19S	25	113	58	-6	89	55	184	81	**	151	**
TC 20S	22	108	59	12	80	-24	202	134	129	123	-32
TC 21S	27	144	91	-67	101	73	282	173	-167	167	95
TC 22P	56	158	103	**	110	**	386	247	**	221	**
TC 23P	27	108	86	**	65	**	172	136	**	82	**
TC 24S	64	260	78	**	237	**	455	118	**	419	**
TC 25P	23	104	88	**	43	**	217	165	**	119	**
TC 26S	19	105	86	**	40	**	225	188	**	94	**
TC 27P	21	134	103	-31	75	-51	287	189	-152	175	-178
TC 28P	31	135	68	**	92	**	197	180	**	52	**
MEAN	31	125	85	-43	73	7	242	167	-104	137	-12
STANDARD											
DEVIATIONS	33	74	102	N/A	94	N/A	124	186	N/A	176	N/A
* THE	MEAN WAS	COMPUTED	FROM A	ARSOLUTE	VALUES						

^{*} THE MEAN WAS COMPUTED FROM ABSOLUTE VALUES.

SEE TABLE 5-1B FOR EXPLANATIONS OF THE TERMS MEAN, MEDIAN, ALONG-TRACK ERROR AND CROSS-TRACK ERROR.

^{**} THE MEDIAN WAS NOT COMPUTED FOR INSTANCES OF TEN CASES OR LESS.

^{***} NOT ENOUGH WARNINGS WERE ISSUED TO VERIFY THE FORECAST.

SEE TABLE 5-18 FOR EXPLANATIONS OF THE TERMS MEAN MEDIAN A

SOUTH PACIFI	NUMBER OF WARNI C AND SOUTH IN JLY 1988 - 30 J	DIAN OCEANS 19	89
TROPICAL CYCLONE	INITIAL POSITION	24-HOUR FORECAST	48-HOUR FORECAST
TC 01S ADELININA TC 02S BARISAONA	9	8	6
TC 02S BARISAONA	26	8 24	22
TC D3S LLONA	l i		6
TC 04P DELILAH TC 05P GINA** TC 06S TC 07S EDME	. 4,	3	1
TC 05P GINA**	6	4	2
TC 06S	9	7	2
TC 07S EDME	11	10	8
TC 08S FIRINGA	14	10	9
TC 08S FIRINGA TC 09S KIRRILY TC 10P HARRY	9	10 7	5
TC 10P HARRY	24	23	21
TC 11S HANITRA	23	21	19
TC 12S GIZELA	9	7	5
TC 13P IVY	13	7 11	9
TC 12S GIZELA TC 13P IVY TC 14P**	11	9	6
TC 15P JUDY**	8	6	4
TC 16S	3	1	0
TC 17S MARCIA	3	2	1
TC 15P JUDY** TC 16S TC 17S MARCIA TC 18S TC 19S JINABO	4	3	_ 1
TC 19S JINABO	13	11	3
TC 20S NED	19	15	11
TC 21S KRISSY	19 18 5 8	17	16
TC 21S KRISSY TC 22P KERRY	5	4	3
TC 23P AIVU	8	7	4
TC 24S LEZISSY TC 25P LILI TC 26S ORSON	6	4	2
TC 25P LILI	9	8	8
TC 26S ORSON	12	ğ	7
TC 27P MEENA	16	-	12
		4	4
TC 28P ERNIE*	5 4	3	í
	312	261	198
* REGENERATED			
** NWOC SYSTEM			




Figure 5-5. Annual mean forecast errors (nm) for all significant tropical cyclones in the South Pacific and South Indian Oceans.

	24-	HOUR	48-	HOUR
YEAR	FORECAST	RIGHT-ANGLE	FORECAST	RIGHT-ANGLE
1981	165	119	315	216
1982	144	91	274	174
1983	154	84	288	150
1984	133	73	231	124
1985	138	78	242	133
1986	133	**	268	**
1987	145	**	280	**
1988	146	**	290	**
1989	125	**	242	**

5.2 COMPARISON OF OBJECTIVE TECHNIQUES

5.2.1 GENERAL — JTWC uses a variety of objective techniques as guidance in the warning development process. A variety of techniques are required because each technique has particular strengths and weaknesses which vary by basin, time of year, synoptic situation, and forecast period. The techniques can be divided into six general categories: extrapolation, climatology and analogs, statistical, dynamic, empirical and analytical, and blends of the previous categories.

Since September 1981, JTWC has initialized its objective forecast techniques from the six-hour old preliminary best track position (interpolated) rather than the forecast (extrapolated) warning position, e.g. the 0600Z warning is supported by objective techniques developed from the 0000Z preliminary best track position. This ensures the techniques are in-hand for a longer evaluation time and has resulted in lower 24-hour forecast errors because of more accurate direction and speed of movement.

5.2.2 DESCRIPTION OF OBJECTIVE TECHNIQUES

- 5.2.2.1 EXTRAPOLATION (XTRP) Forecast positions for 24, 48, and 72 hours are derived from the extension of a straight line that connects the most recent and 12-hour old preliminary best track positions.
- 5.2.2.2 CLIMATOLOGY (CLIM) A climatological aid providing 24-, 48-, and 72-hour tropical cyclone forecast positions (and intensities in the western North Pacific) based upon the position of the tropical cyclone. The output is based upon data records from 1945 to 1978 for the western North Pacific Ocean and 1900 to 1981 for the North Indian Ocean and Southern Hemisphere.

- 5.2.2.3 HALF PERSISTENCE AND CLIMATOLOGY (HPAC) Forecast positions are generated from the blend of equally weighted persistence (XTRP) and climatology (CLIM) forecast positions.
- 5.2.2.4 ANALOGS The program scans the climatology for tropical cyclones with a similar history (within specified spatial and temporal windows) to the current tropical cyclone. For the western North Pacific Ocean, two forecasts of position and intensity are provided at 24, 48. and 72 hours: RECR - a weighted mean of all tropical cyclones that were categorized as "recurving" during their best track period; TOTL - a weighted mean of all accepted tropical cyclones. In addition the program produces a list of the five tropical cyclones with the least variance from the current storm. For the North Indian Ocean and Southern Hemisphere, a single (total) forecast track is provided for the 24-hour intervals to 72 hours.
- 5.2.2.5 CLIMATOLOGY / PERSISTENCE (CLIPER) A statistical regression technique, adapted from Xu and Neuman (1985), based on climatology, current intensity and position, and past movement. This technique is used as a crude measure of real forecast skill when verifying forecast accuracy.
- 5.2.2.6 CYCLOPS OBJECTIVE STEERING MODEL OUTPUT STATISTICS (COSMOS) A Model Output Statistics (MOS) (Allen, 1982) routine based on the geostrophic steering at the 850-, 700-, and 500-mb levels. The steering is derived from the HATTRACK point advection model run using NOGAPS forecast fields. The MOS forecast is then blended with the six-hour past movement to generate the forecast track.
- 5.2.2.7 COLORADO STATE UNIVERSITY MODEL (CSUM) A statistical-synoptic method developed by Matsumoto (1984). Tropical cyclones are stratified in the basins North Indian Ocean, South China Sea, and western North Pacific based on the tropical cyclones position relative to the 500 mb ridge

axis (determined from the direction of recent movement). A separate set of multiple regression equations using synoptic parameters are used depending on whether the tropical cyclone is south, on, or north of the ridge axis.

5.2.2.8 ONE-WAY INTERACTIVE TROP-ICAL CYCLONE MODEL (OTCM) — A coarse-mesh, three-layer, primitive equation model with a 205 km grid spacing over a 6400 x 4700 km domain. The model's fields are computed around a bogused, digitized cyclone vortex using FNOC analyses. The past motion of the tropical cyclone is compared to initial steering fields and a bias correction is computed and applied to the model. The resultant forecast positions are derived by locating the 850 mb vortex at six-hour intervals to 72 hours. Forecast boundary conditions are updated from NOGAPS.

5.2.2.9 TYPHOON ACCELERATION PRE-DICTION TECHNIQUE (TAPT) — An empirical technique (Weir, 1982) that utilizes upper-tropospheric and surface wind fields to estimate acceleration associated with the tropical cyclone's interaction with the midlatitude westerlies. It includes guidelines for the duration of acceleration, upper-limits, and probable path of the cyclone.

5.2.2.10 COMBINED CONFIDENCE WEIGHTED FORECASTS (CCWF) — An optimal blend of objective techniques produced by the ATCF. The ATCF blends the selected techniques by using the inverse of the covariance matrices computed from historical and real-time cross-track and along-track errors as the weighting function.

5.2.2.11 DVORAK — An estimation of tropical cyclone's current and 24-hour forecast intensity is made from the interpretation of satellite imagery (Dvorak, 1984). These intensity estimates are used with other intensity related data and trends to forecast tropical cyclone intensity.

5.2.2.12 HOLLAND/MARTIN — The technique adapts an earlier work (Holland, 1980) and specifically addresses the need for realistic 30-, 50- and 100-kt wind radii around tropical cyclones. It solves equations for basic gradient wind relations within the tropical cyclone area, using input parameters obtained from enhanced infrared satellite imagery. For the first time, diagnosis also includes an asymmetric area of winds caused by tropical cyclone movement. Size and intensity parameters are also used to diagnose internal steering components of tropical cyclone motion known collectively as "beta-drift".

5.2.2.13 FNOC BETA AND ADVECTION MODEL (FBAM) — FNOC's implementation of NMC's Beta and Advection Model. The model uses the output from NOGAPS, current observations, and an analytic description of the tropical cyclone.

5.2.2.14 NAVY OPERATIONAL REGIONAL PREDICTION SYSTEM (NRPS) — The Advanced Tropical Cyclone Model (ATCM) produced from NORAPS fields.

5.3 TESTING AND RESULTS

A comparison of selected techniques is included in Tables 5-8A, 5-8B, and 5-8C for all western North Pacific tropical cyclones; Table 5-9 for all North Indian Ocean tropical cyclones and Table 5-10 for the Southern Hemisphere. In these tables, "x-axis" refers to techniques listed vertically. For example (Table 5-8A) in the 629 cases available for a (homogeneous) comparison, the average forecast error at 24 hours was 131 nm (243 km) for HPAC and 130 nm (241 km) for COSM. The difference of 1 nm (2 km) is shown in the lower right. (Differences are not always exact, due to computational round-off which occurs for each of the cases available for comparison).

TABLE 5-8A 1989 ERROR STATISTICS FOR SELECTED OBJECTIVE TECHNIQUES IN THE WESTERN NORTH PACIFIC

24-HOUR MEAN FORECAST ERROR (NM)

	JTWC		CLIP		OTCM	I	CSUM		RECE	ł	TOTI	•	COSM	I	HPAC	:	CLIM		XTRP		NRPS	;	CCWF	1	FBAM	Í
JTWC	625 120	120 0																								
CLIP	587 119	118 1	683 122	122 0																						
OTCM	548 141	114 27	630 141	118 23	647 141	141 0																				
CSUM	526 119	117 2	591 120	120 0	575 117	140 -23	594 120	120							_			·								
RECR	516 146	116 30	588 149	117 32	558 144	140 4	521 148	117 31	594 149	149 0						NUMI OI CAS	F	TEC	K-AXIS CHNIQ ERROF	UE						
TOTL	534 126	114 12	605 131	116 15	576 127	139 -12	536 129	116 13	594 133	149 -16	613 131	131 0			т	Y-AX ECHN	KIS IQUE		RROF							
COSM	556 128	117 11	636 130	122 8	592 131	139 -8	573 127	119 8	551 127	150 -23	566 126	132 -6	644 137	137	丿	ERR	OŘ		(Y-X)							
НРАС	583 128	117 11	673 131	121 10	626 127	141 -14	581 129	120 9	586 129	149 -20	605 128	131 -3	629 131	130 1	679 131	131										
CLIM	585 179	117 62	674 182	121 61	636 178	141 37	583 181	120 61	589 179	149 30	608 178	131 47	635 182	138 44	677 183	131 52	689 182	182								
XTRP	587 129	117 12	680 133	121 12	629 128	141 -13	588 129	119 10	588 128	148 -20	606 128	131 -3	635 133	130 3	675 133	131	677 133	183 -50	683 133	133 0						
NRPS	114 112	125 -13	116 111	127 -16	103 115	148 -33	104 115	114 1	104 109	150 -41	107 109	125 -16		131 -19	114 110	131 -21	115 111	168 -57	115 111	141 -30	118 111	111 0				
CCWF	378 128	128 0	449 129	131 -2	443 127	137 -10	405 127	129 -2	400 128	157 -29	407 127	145 -18	419 128	134 -6	448 129	139 -10		194 -65	449 129	139 -10	50 139	130 9	455 129	129 0		
FBAM	84 112	95 17	94 117	93 24	92 119	125 -6	90 118	86 32	80 125	114 11	85 119	122 -3	88 116	99 17	92 117	104 13		137 -20	94 117	106 11	4 44	174 ~130	65 114	88 26	94 117	117

CLIP - CLIMATOLOGY/PERSISENCE

OTCM - ONE-WAY TROPICAL CYCLONE MODEL

CSUM - COLORADO STATE UNIVERSITY MODEL

RECR - RECURVE ANALOG

TOTL - TOTAL ANALOG

COSM - COSMOS

HPAC - HALF PERSISTENCE AND CLIMATOLOGY

CLIM - CLIMATOLOGY

XTRP - EXTRAPOLATION

NRPS - ADVANCED TROPICAL CYCLONE MODEL

CCWF - COMBINED CONFIDENCE WEIGHTED FORECAST

FRAM - FNOC BETA AND ADVECTION MODEL

TABLE 5-8B 1989 ERROR STATISTICS FOR SELECTED OBJECTIVE TECHNIQUES IN THE WESTERN NORTH PACIFIC

48-HOUR MEAN FORECAST ERROR (NM)

	JTWC		CLIP		OTCM		CSUM		RECR		TOTL	•	COSM		HPAC		CLIM	!	XTRP		NRPS	3	CCWE		FBAM	1
JTWC	481 231	231 0																								
CLIP	461 252	227 25	575 264	264 0																						
OTCM	431 288	224 64	529 284	257 27	546 284	284 0																				
CSUM	416 250	226 24	494 250	263 -13	477 241	283 -42	498 251	251 0									MBER OF		X-A: TECHN							
RECR	409 307	226 81	491 318	252 66	465 315	286 29	431 320	247 73	498 318	318 0						C.	ASES	_	ERR	OŘ						
TOTL	422 245	223 22	508 265	250 15	483 260	284 -24	445 262	243 19	498 271	318 -47	517 265	265 0				TEC	AXIS HNIQU RROR	JE I	ERR OFFER (Y-)	ENCE						
COSM	436 255	223 32	533 267	267 0	497 269	281 -12	482 262	249 13	461 264	319 -55	475 263	264 -1	542 274	274	/						1					
HPAC	458 241	226 15	566 253	261 -8	52 8 250	284 -34	486 249	249 0	490 254	319 -65	509 251	265 -14	528 253	265 -12	573 254	254 0					•					
CLIM	461 316	227 89	568 331	261 70	538 329	284 45	489 333	250 83	493 335	319 16	512 334	265 69	535 331	273 58	572 332	254 78	584 332	332 0								
XTRP	462 276	225 51	573 291	263 28	531 283	285 -2	493 283	249 34	492 283	318 -35	510 282	265 17	534 291	267 24	570 292	254 38	572 291	333 -42	577 290	290 0						
NRPS	66 229	193 36	72 220	241 -21	59 220	311 -91	65 227	217 10	65 216	300 -84	68 216	233 -17	73 220	245 -25	71 217	244 -27	72 217	311 -94	72 220	276 -56	73 220	220 0				
CCWF	316 475	248 227	399 478	283 195	391 490	272 218	35 8 305	266 39	351 520	333 187	359 510	287 223	370 284	278 6	399 485	264 221	399 484	349 135	400 477	305 172	20 246	201 45	406 485	48 5 0		
FBAM	70 250	177 73	82 253	202 51	80 257	317 -60	78 255	143 112	68 274	205 -11	73 263	237 26	77 255	222 33	80 255	187 68	80 255	225 30	82 255	225 30	4 98	343 -245	62 270	413 -143	82 253	253 0

CLIP - CLIMATOLOGY/PERSISENCE

OTCH - ONE-WAY TROPICAL CYCLONE MODEL

CSUM - COLORADO STATE UNIVERSITY MODEL

RECR - RECURVE ANALOG

TOTL - TOTAL ANALOG

COSM - COSMOS

HPAC - HALF PERSISTENCE AND CLIMATOLOGY

CLIM - CLIMATOLOGY

XTRP - EXTRAPOLATION

NRPS - ADVANCED TROPICAL CYCLONE MODEL

CCMF - COMMINED CONFIDENCE WEIGHTED FORECAST

FRAM - FNOC BETA AND ADVECTION MODEL

TABLE 5-8C 1989 ERROR STATISTICS FOR SELECTED OBJECTIVE TECHNIQUES IN THE WESTERN NORTH PACIFIC

72-HOUR MEAN FORECAST ERROR (NM)

	JTWC		CLIP		OTCM		CSUM		RECR		TOTL		COSM		HPA	C	CLIM		XTRP		NRPS	3	CCWF		NRPS	
JTWC	363 350	350 0																								
CLIP	347 371	346 25	458 402	402 0																						
OTCM	307 459	339 120	397 449	390 59	411 446	446 0																				
CSUM	313 365	334 31	393 370	402 -32	354 361	448 -87	395 370	370 0							г			1								
RECR	309 479	348 131	389 495	383 112	348 502	452 50	341 503	362 141	395 496	496 0						NUM O CA	F	TE	X-AXI CHNIC ERRO	QUE						
TOTL	315 395	348 47	396 421	384 37	355 412	454 -42	347 416	361 55	395 424	496 -72	404 422	422 0				TECH	XIS NIQUE		ERRO FERE	NCE						
COSM	328 401	337 64	421 427	403 24	373 415	440 -25	382 428	369 59	361 415	492 -77	368 417	411 6	430 424	424 0	人	ERI	ROR	<u> </u>	(Y-X)							
HPAC	335 363	348 15	440 380	393 -13	387 377	449 -72	376 376	370 6	387 376	499 - 123	396 374	422 -48	407 377	419 -42	446 381											
CLIM	338 434	347 87	442 451	393 58	398 452	445 7	378 460	370 90	391 461	498 -37	400 461	422 39	414 453	418 35	446 453		457 451	451 0								
XTRP	350 434	345 89	457 455	401 54	398 445	449 -4	393 443	370 73	390 440	497 -57	398 440	422 18	422 449	426 23	444 460		446 458	453 5	461 454	454 0						
NRPS	49 440	307 133	55 413	358 55	44 430	537 -107	51 430	299 131		516 -113	52 403	377 26	57 410	368 42	53 401		54 397	485 -88	56 413	406 7	57 410	410 0				
CCWF	238 377	359 18	319 393	406 -13	292 391	406 -15	281 386	372 14	282 381	494 -113	288 380	433 -53	290 382	419 -37	317 394		318 394	455 -61	320 393	466 -73	15 403	358 45	324 395	395 0		
FBAM	59 416	265 151	71 408	327 81	62 379	526 -147	68 409	193 216	55 432	419 13	57 442	389 53	66 409	473 -64	62 432			303 129	71 408	353 55		632 -482	55 450	386 64	71 408	408 0

CLIP - CLIMATOLOGY/PERSISENCE

OTCM - ONE-WAY TROPICAL CYCLONE MODEL

CSUM - COLORADO STATE UNIVERSITY MODEL

RECR - RECURVE ANALOG

TOTL - TOTAL ANALOG

COSM - COSMOS

HPAC - HALF PERSISTENCE AND CLIMATOLOGY

CLIM - CLIMATOLOGY

XTRP - EXTRAPOLATION

NRPS - ADVANCED TROPICAL CYCLONE MODEL

COMF - COMBINED CONFIDENCE WEIGHTED FORECAST

FRAM - FNOC BETA AND ADVECTION MODEL

	ABLE 5-9 1989 ERROR STATISTICS FOR SELECTED OBJECTIVE TECHNIQUES IN THE NORTH INDIAN OCEAN 24-HOUR MEAN FORECAST ERROR (NM)														
TABLE	5-9		1	1989 ERRC	OR STATIS										
ŀ						24-HOUR ME.	an Forecas	T ERROR (NM	D .						
	JTV	к	OTCM	CSUM	HPAC	CLIM	XTRP	CCWF	FRAM						
JTWC	33 88	88													
ОТСМ	33 110	88 22	36 116 116 0												
CSUM	33 105	88 17	36 116 113 -3	36 113 113 0											
HPAC	32 100	85 15	35 115 102 -13	35 111 102 -9	35 102 102 0				NUMBER X-AXIS OF TECHNIQUE						
CLIM	32 159	85 74	35 115 159 44	35 111 159 48	35 102 159 57	35 159 159 0			CASES ERROR						
XTRP	32 70	85 -15	35 115 76 -39	35 111 76 - 35	35 102 76 -26	35 159 76 -8 3	35 76 76 0		Y-AXIS ERROR TECHINQUE DIFFERENCE ERROR (Y-X)						
CCWF	5 93	118 -25	7 121 111 -10	7 124 111 -13	7 110 111 1	7 134 111 -23	7 107 111 4	7 111 111 0	/						
FBAM	21 75	76 -1	21 119 75 -44	21 68 75 7	21 114 75 -39	21 191 75 -116	21 62 75 13	0 0	21 75 75 0						
						48-HOUR ME.	an forecas	T ERROR (NM	0						
	JT	F C	OTCM	CSUM	HPAC	CLIM	XTRP	CCWF	FBAM						
JTWC	146 0 OTCM 17 146 25 304 JTMC - OFFICIAL JTMC FORECAST														
335 189 304 0 OCCM - ONE-WAY TROPICAL CYCLONE MODEL CSUM 17 146 25 304 26 194 HEAC - HALF PERSISTENCE AND CLIMATOLOGY BLEND															
CSUM	17 136	146 10	25 304 199 -105	26 194 194 0				CILIDA -	HALF PERSISTENCE AND CLIMATOLOGY BLEND CLIMATOLOGY 12-HOUR EXTRAPOLATION						
HPAC	17 224	146 78	24 307 205 -102	25 191 199 8	25 199 199 0				COMBINED CONFIDENCE WEIGHTED FORECAST FNCC BETA AND ADVECTION MODEL						
CLIM	17 379	146 233	24 307 305 -2	25 191 296 105	25 199 2 9 6 97	25 296 296 0		<u> </u>							
XTRP	17 120	146 -26	24 307 151 -156	25 191 146 - 45	25 199 146 -53	25 296 146 -150	25 146 146 0								
CCME	0	0	6 240 202 -38	7 290 179 -111	7 147 179 32	7 121 179 58	7 202 179 -23	7 179 179 0							
FBAM	17 167	146 21	17 335 167 -168	17 136 167 31	17 224 167 -57	17 379 167 -212	17 120 167 47	0 0	17 167 167 0						
						72-HOUR ME.	an forecas	T ERROR (NM	0						
	JTW		ОТСМ	CSUM	HPAC	CLIM	XTRP	CCMF	FBAM						
JTWC	216	216													
отсм		276	18 463 463 0												
CSUM	206	216 -10	18 463 291 -172	18 291 291 0											
НРАС		27	16 474 246 -228	16 291 246 -45	16 246 246 0										
CLIM	387	210 177	16 474 343 -131	16 291 343 52	16 246 343 97	16 343 343 0									
XTRP		216 -64	17 473 203 -270	17 284 203 -81	16 246 195 - 51	16 343 195 -148	17 203 203 0								
CCMF	0	0	4 373 333 -40	4 511 333 -178	4 250 333 83	4 163 333 170	4 388 333 -55	4 333 333 0							
PBAM		216 46	13 504 274 - 230	13 214 274 60	12 245 281 36	12 403 281 -122	13 146 274 128	0 0	13 274 274 0						

TABLE 5	-10			19 1	989 EI N THI	RROR E SOU	STAT THER	ISTIC N HE	S FOR MISPI	SELI IERE	ECTED 1989 (1	OBJE JULY	CTIV 1988	E TECH 30 JUN	NIQUES E 1989)	
							24-	HOUR	MEAN	FORE	CAST E	RROR	(NM)			
	JTWC	:	CLI	(P	orc	M	НЕ	PAC	C	LIM	XI	'RP	cc	WF		
JTWC	261 125	125 0														
CLIP	90 144	124 20	217 152	152 0										<u></u>		
OTCM	200 126	119 7	145 128	147 -19	381 123	123 0								UMBER OF CASES	X-AXIS TECHNIQUE ERROR	
HPAC	195 117	117 0	145 111	146 -35	369 116	123 -7	377 116	116 0					-			
CLIM	197 160	117 43	145 153	146 7	373 172	124 48	375 171	116 55	381 171	171 0			TE	Y-AXIS CHINQUE ERROR	ERROR DIFFERENCE (Y-X)	
XTRP	196 126	118 8	142 120	146 -26	368 123	123 0	372 123	116 7	373 123	172 -49	376 123	123	/		<u> </u>	
CCWF	78 101	110 -9		152 -56	151 101	107 -6	151 101	109 -8	151 101	153 -52	150 101	107 -6	151 101	101		
							48-	HOUR	MEAN	FORE	CAST E	RROR	(NM)			
	JTWC	:	CLIP	,	OTCM	ī	HPAC	:	CLI	1	XTRP	ı	CCWF			
JTWC	201 242	242 0														
CLIP	66 296	230 66	180 334	334 0											JIWC FORECAST INATOLOGY AND PERSISTEN	CIE)
OTCM	152 235	233 2	114 230	307 -77	309 239	239 0						HPAC	- HA		OPICAL CYCLONE MODEL STERCE AND CLIMATOLOGY I	BLEND
HPAC	148 229	233 -4	115 205	304 -99	292 219	237 -18	305 223	223 0							TRAPOLATION CONFIDENCE WEIGHTED FORE	CAST
CLIM	150 295	235 60	115 248	305 -57	296 294	238 56	303 300	224 76	309 301	301 0						
XTRP	152 260	232 28	112 250	303 -53	296 258	237 21	300 257	224 33	301 258	303 -45	309 257	257 0				
CCWF	67 197	236 -39		306 -137	134 193	207 -14	134 193	218 -25	134 193	275 -82	133 193	244 -51	134 193	193 0		
							72-	HOUR	MEAN	FORE	CAST E	RROR	(NM)			
	orc	M	НРА	C	CLI	M	XTR	lP	CCV	vF						
OTCM	222 350	350 0														
HPAC	209 309	352 -43	238 336	336 0												
CLIM	212 385	354 31	237 427	337 90	241 426	426 0										
	212 382	343 39	234 392	337 55		430 -38	241 388	388								
XTRP	302	•	3,72	-	-	•••		•								

Intentionally left blank.

6. NOARL TROPICAL CYCLONE SUPPORT SUMMARY

Tropical Cyclone Forecaster's Reference Guide

R. J. Miller and J-H. Chu

Development of a Tropical Cyclone Forecaster's Reference Guide has started at Naval Oceanographic and Atmospheric Research Laboratory (NOARL). The reference guide will be a computer-based information management system for JTWC forecasters. Using a mouse/menu interface, the user will have access to general tropical cyclone information, as well as current research results, thumb rules, definitions, case studies, etc. Since the guide will be computer-based, one can easily add new information to the system, or modify existing information.

Automated Tropical Cyclone Forecasting System (ATCF) Upgrade

D. M. Roesser, C. R. Sampson, and R. J. Miller

The ATCF has been operational at JTWC since August, 1988. The system runs on an IBM-AT compatible machine using the MS-DOS operation system. This current configuration limits the capabilities of the ATCF. For this reason, work is underway to adapt the ATCF software to a UNIX environment. The UNIX operating system runs more powerful applications and is capable of multitasking (running more than one program at once). Additionally, software developed for UNIX is portable to a wide variety of computer systems (personal computers, workstations, or mainframes).

Tropical Cyclone Expert System

C. R. Sampson and J-H. Chu

NOARL is developing an expert system for tropical cyclone forecasting. Using

forecasting thumb rules and research results such as objective technique error statistics, the expert system will objectively weigh the information based upon the current forecast situation and assist the forecaster in making decisions. More importantly, the expert system may alert the forecaster to possibilities not previously considered.

Personal Computer-Based Track Climatology

C. R. Sampson and R. J. Miller

Currently the Fleet Numerical Oceanography Center (FNOC) in Monterey, CA runs all of JTWC's computer objective forecast techniques on the mainframe computers. With the increased power and use of personal computers, it is now feasible to run some of these forecast techniques locally at JTWC. NOARL is adapting the tropical cyclone track climatology forecast technique to run on a PC. The global data base contains best tracks since 1945 to present. At the end of each tropical cyclone season, new best tracks can easily be added to the data base.

NORAPS/ATCM Development

C-S. Liou

Since the Advanced Tropical Cyclone Model (ATCM) is a special application of the Navy Operational Regional Atmospheric Prediction System (NORAPS), any changes made to NORAPS will also affect ATCM performance. In 1989-1990, NORAPS development efforts are focused on improving lateral boundary conditions, radiation calculation, and initialization procedures. The improvements are aimed at reducing forecast errors due to ill-posed lateral boundary conditions, to reduce large bias errors, and to reduce errors due to vertical interpolation between sigma and pressure levels.

Intentionally left blank.

7. TROPICAL CYCLONE WARNING STATISTICS, TRACK AND FIX DATA

7.1 GENERAL

Due to the rapid growth of microcomputers in the meteorological community and to save publishing costs, tropical cyclone track data (with best track, initial warning, 24-, 48and 72-hour JTWC forecasts) and fix data (satellite, aircraft, radar and synoptic) are now available separately upon request. The data will be in ASCII format on 5.25 inch floppy diskettes. The data sets are available on two diskettes. These include the western North Pacific Ocean (1 January - 31 December 1989) on one and North Indian Ocean (1 January - 31 December), South Indian and western South Pacific Oceans (1 July 1988 - 30 June 1989) on the other. Agencies or individuals desiring these data sets should send the appropriate number of floppy diskettes (two if both data sets are desired) to NAVOCEANCOMCEN/JTWC Guam with their request. When the request is received, the data will be copied onto your diskettes and returned with the explanation of the data formats. The use of floppy diskettes should facilitate the transfer of these rather large data files to your computer.

7.2 WARNING VERIFICATION STATISTICS

7.2.1 WESTERN NORTH PACIFIC

This section includes verification statistics for each warning in the western North Pacific Ocean during 1989. Pre- and postwarning best track positions are not printed, but are available on floppy diskettes by request.

		•	TWC FORE	AST TRAC	OK AND	Intensi	TY ERROR	RS BY W	RNING			
Tropical	Storm Wir	ona (01)	n	00h	24h	48h	<u>72h</u>					
•		,,,,,,	Average	25	171	346	507					
			# Cases	13	10	6	5					
			, 04000		+0	•	J					
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89011800	1	16.5N	153.8E	16	63	225	304	40	-5	-10	15	35
89011806	2	16.4N	151.8E	5	100	314	318	45	-10	-10	25	40
89011812	3	16.2N	150.0E	18	265	527	674	50	0	5	35	45
89011818	4	15.8N	148.0E	37	279	482	718	50	Ō	15	35	50
89011900	5	15.2N	145.7E	8	181	254	521	55	0	25	40	45
89011906	6	14.6N	142.9E	11	177	271	N\A	55	0	35	45	N\A
89011912	7	14.0N	140.0E	18	108	N\A	N/A	55	-10	0	N\A	N\A
89011918	8	13.8N	137.2E	25	N\A	N\A	N\A	45	-5	N\A	N\A	N\A
89012006*	9	13.5N	132.3E	5	169	N\A	N\A	30	0	20	N\A	N\A
89012012	10	13.5N	130.5E	24	196	N\A	N\A	30	0	20	N\A	N\A
89012018	11	13.3N	128.9E	65	176	N\A	N\A	30	0	10	N\A	N\A
89012100	12	13.1N	127.7E	37	N\A	N/A	N\A	30	0	N\A	N\A	N\A
89012106	13	12.3N	126.3E	51	N\A	N\A	N\A	25	0	N\A	N\A	N\A
*	Regenerat	.ed										
Super Typ	hoon Andy	(02W)		00h	24h	48h	<u>72h</u>					
			Average	12	111	290	569					
			# Cases	26	26	22	18					
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89041718	1	8.1N	147.0E	51	125	254	605	35	-5	-15	-30	-80
89041800	2	8.7N	146.4E	18	18	101	346	40	5	10	5	-65
89041806	3	9.2N	145.9E	13	157	216	413	45	0	15	-10	-75

Super Typi	noon Andy		continued	1)								
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72_ER
89041812	4	9.6N	145.3E	8	126	291	664	45	5	-5	-45	-75
89041818	5	9.7N	144.5E	11	164	463	872	50	~ 5	-20	-70	-60
89041900	6	9.7N	143.9E	13	65	317	692	55	0	-10	-50	-65
89041906	7	9.7N	143.5E	21	165	475	857	60	-15	-45	-80	-60
89041912	8	9.9N	143.3E	8	181	559	960	70	-5	-45	-50	-20
89041918	9	10.1N	143.3E	0	89	357	617	75	0	-45	-45	-15
89042000	10	10.5N	143.5E	21	148	372	533	85	-5	-50	-45	-5
89042006 89042012	11 12	10.9N	143.8E	11 6	196	473	653	100	~5 5	-25	-5	35
89042018	13	11.5N 12.0N	144.1E 145.0E	0	242 125	479 267	614 343	120 135	-5	5 -25	35 0	85
89042100	14	12.6N	145.0E	5	162	307	384	140	-5 -5	10	45	55 70
89042106	15	12.6N 13.4N	145.9E	5	84	192	402	140	-5	-5	25	35
89042112	16	14.2N	148.2E	0	121	245	449	140	-10	-5	40	30
89042118	17	15.4N	149.4E	18	66	280	509	135	-5	0	50	30
89042200	18	16.4N	150.5E	5	62	164	330	130	-10	15	35	10
89042206	19	17.4N	151.5E	8	41	168	N/A	120	-10	10	25	N/A
89042212	20	18.5N	152.5E	6	90	175	N/A	110	0	40	35	N/A
89042218	21	19.6N	152.3E	18	85	128	N/A	100	ő	40	25	N/A
89042300	22	20.8N	154.3E	16	100	96	N/A	85	5	25	15	N/A
89042306	23	21.6N	155.1E	12	17	N/A	N/A	65	10	15	N/A	N/A
89042312	24	22.5N	155.6E	12	44	N/A	N/A	45	15	15	N/A	N/A
89042318	25	23.4N	156.1E	17	128	N/A	N/A	35	15	5	N/A	N/A
89042400	26	24.4N	156.7E	16	95	N/A	N/A	30	5	5	N/A	N/A
Typhoon Bi	renda (03	3W)		<u>00h</u>	24h	<u>48h</u>	<u>72h</u>					
			Average	31	133	227	251					
			# Cases	20	18	12	9					
DTG	Wå	ም ም ፕልጥ	POT TON	DOG ED	24 FR	48 FB	72 170	PU MV	WW PD	24 FD	AR FD	72 50
<u>DTG</u> 89051518	₩# 1	BT LAT	BT LON 130.2E	POS ER	24 ER 283	48 ER 406	72 ER 411	<u>BT WN</u> 30	<u>WW ER</u> -5	24 ER 0	48 ER 30	72 ER 25
89051518	1	9.8N	130.2E	95	283	406	411	30	-5	0	30	25
	1 2	9.8N 10.4N	130.2E 129.1E	95 147	283 268	406 339	411 268	30 30	-5 5	0	30 20	25 20
89051518 89051600	1	9.8N 10.4N 11.0N	130.2E	95	283	406	411	30	-5	0	30 20 15	25 20 15
89051518 89051600 89051606	1 2 3	9.8N 10.4N	130.2E 129.1E 128.0E	95 147 36	283 268 190	406 339 261	411 268 223	30 30 35	-5 5 10	0 5 15	30 20	25 20
89051518 89051600 89051606 89051612	1 2 3 4	9.8N 10.4N 11.0N 11.7N	130.2E 129.1E 128.0E 126.6E	95 147 36 81	283 268 190 247	406 339 261 306	411 268 223 329	30 30 35 40	-5 5 10 10	0 5 15 5	30 20 15 5	25 20 15 0
89051518 89051600 89051606 89051612 89051618	1 2 3 4 5	9.8N 10.4N 11.0N 11.7N 12.3N	130.2E 129.1E 128.0E 126.6E 125.2E	95 147 36 81 26	283 268 190 247 156	406 339 261 306 203	411 268 223 329 247	30 30 35 40 45	-5 5 10 10	0 5 15 5 0	30 20 15 5 -10	25 20 15 0 -15
89051518 89051600 89051606 89051612 89051618 89051700	1 2 3 4 5	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E	95 147 36 81 26 40	283 268 190 247 156 90	406 339 261 306 203 60	411 268 223 329 247 82	30 30 35 40 45 50	-5 5 10 10 0 5	0 5 15 5 0 25	30 20 15 5 -10 15	25 20 15 0 -15 -20
89051518 89051600 89051606 89051612 89051618 89051700 89051706 89051712	1 2 3 4 5 6 7 8	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E	95 147 36 81 26 40 18	283 268 190 247 156 90 106	406 339 261 306 203 60 130	411 268 223 329 247 82 252	30 30 35 40 45 50	-5 5 10 10 0 5	0 5 15 5 0 25 15	30 20 15 5 -10 15 20	25 20 15 0 -15 -20 -15
89051518 89051600 89051606 89051612 89051618 89051700 89051706 89051712 89051718	1 2 3 4 5 6 7 8 9	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E	95 147 36 81 26 40 18	283 268 190 247 156 90 106 21	406 339 261 306 203 60 130 57	411 268 223 329 247 82 252 247	30 30 35 40 45 50 50	-5 5 10 10 0 5 0	0 5 15 5 0 25 15	30 20 15 5 -10 15 20	25 20 15 0 -15 -20 -15 -5
89051518 89051600 89051606 89051612 89051618 89051700 89051716 89051712 89051718 89051800 89051806	1 2 3 4 5 6 7 8 9 10	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E	95 147 36 81 26 40 18 13	283 268 190 247 156 90 106 21 45 51	406 339 261 306 203 60 130 57	411 268 223 329 247 82 252 247 202	30 35 40 45 50 50 40 35	-5 5 10 10 0 5 0	0 5 15 5 0 25 15 10 -5	30 20 15 5 -10 15 20 10 -10	25 20 15 0 -15 -20 -15 -5 -10 N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051806	1 2 3 4 5 6 7 8 9 10 11	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E	95 147 36 81 26 40 18 13 18 11 29	283 268 190 247 156 90 106 21 45 51 174 73	406 339 261 306 203 60 130 57 54 92 N/A 228	411 268 223 329 247 82 252 247 202 N/A N/A	30 30 35 40 45 50 50 40 35 35 45	-5 5 10 10 0 5 0 5 0 5	0 5 15 5 0 25 15 10 -5 0	30 20 15 5 -10 15 20 10 -10 -5 N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051812 89051818	1 2 3 4 5 6 7 8 9 10 11 12	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E 117.7E	95 147 36 81 26 40 18 13 18 11 29 8	283 268 190 247 156 90 106 21 45 51 174 73	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A	30 30 35 40 45 50 50 40 35 35 45 45	-5 5 10 10 0 5 0 5 0 5	0 5 15 5 0 25 15 10 -5 0 10 -10	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051812 89051818 89051900	1 2 3 4 5 6 7 8 9 10 11 12 13	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E 117.7E	95 147 36 81 26 40 18 13 18 11 29 8 16	283 268 190 247 156 90 106 21 45 51 174 73 84 213	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584	411 268 223 329 247 82 252 247 202 N/A N/A N/A	30 30 35 40 45 50 50 40 35 35 45 45 50 55	-5 5 10 10 0 5 0 5 0 5 0 -5 -5	0 5 15 5 0 25 15 10 -5 0 10 -10 -20	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051812 89051818 89051900 89051906	1 2 3 4 5 6 7 8 9 10 11 12 13 14	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E 117.7E 117.2E 116.7E	95 147 36 81 26 40 18 13 18 11 29 8 16 18	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 35 45 45 50 55	-5 5 10 10 0 5 0 5 0 5 0 -5 -5	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051812 89051818 89051900 89051912	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E 117.7E 117.2E 116.7E	95 147 36 81 26 40 18 13 18 11 29 8 16 18	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 35 45 45 50 55 65	-5 5 10 10 0 5 0 5 0 5 0 -5 -5 0	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A 0 N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051812 89051818 89051900 89051912 89051912	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E 117.7E 117.2E 116.7E 116.0E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 45 45 50 55 55 65	-5 5 10 10 0 5 0 5 0 -5 -5 0 0	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5 15	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A 0 N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051812 89051818 89051900 89051912 89051912 89051918 89052000	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N 19.8N 20.5N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E 117.7E 117.2E 116.7E 116.0E 115.2E 114.4E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 45 45 50 55 55 65 75	-5 5 10 10 0 5 0 5 0 -5 -5 0 0	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5 15	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051806 89051812 89051818 89051900 89051912 89051912 89051918 89052000 89052006	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N 19.8N 20.5N 21.1N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 117.2E 116.7E 116.0E 115.2E 114.4E 113.8E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105 N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 45 45 50 55 55 65 75 75	-5 5 10 10 0 5 0 5 0 -5 -5 0 0 -10	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5 15 0 N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051812 89051818 89051900 89051912 89051912 89051918 89052000	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N 19.8N 20.5N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 118.2E 117.7E 117.2E 116.7E 116.0E 115.2E 114.4E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 45 45 50 55 55 65 75	-5 5 10 10 0 5 0 5 0 -5 -5 0 0	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5 15	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051806 89051812 89051818 89051900 89051912 89051912 89051918 89052000 89052006	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N 19.8N 20.5N 21.1N 21.6N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 117.2E 116.7E 116.0E 115.2E 114.4E 113.8E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5	283 268 190 247 156 90 106 21 45 51 174 213 102 86 90 105 N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 45 45 50 55 55 65 75 75	-5 5 10 10 0 5 0 5 0 -5 -5 0 0 -10	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5 15 0 N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051806 89051812 89051818 89051900 89051912 89051912 89051918 89052000 89052006	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N 19.8N 20.5N 21.1N 21.6N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 116.0E 115.2E 114.4E 113.8E 113.1E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105 N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 45 45 50 55 55 65 75 75	-5 5 10 10 0 5 0 5 0 -5 -5 0 0 -10	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5 15 0 N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051800 89051806 89051812 89051818 89051900 89051912 89051912 89051918 89052000 89052006	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 16.5N 17.1N 17.7N 18.4N 19.1N 19.8N 20.5N 21.1N 21.6N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 117.2E 116.7E 116.0E 115.2E 114.4E 113.8E 113.1E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5 6 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105 N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 45 45 50 55 55 65 75 75	-5 5 10 10 0 5 0 5 0 -5 -5 0 0 -10	0 5 15 5 0 25 15 10 -5 0 10 -10 -20 -35 -5 15 0 N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051712 89051712 89051718 89051806 89051812 89051818 89051900 89051906 89051912 89051918 89052000 89052006 89052012	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 17.1N 17.7N 18.4N 19.1N 19.1N 20.5N 21.1N 21.6N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 116.7E 116.0E 115.2E 114.4E 113.8E 113.1E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5 6 5	283 268 190 247 156 90 106 21 45 51 174 213 102 86 90 105 N/A N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A 584 N/A N/A N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A N/A N/A	30 30 35 40 45 50 40 35 45 55 55 75 75 70	-5 5 10 10 0 5 0 5 0 -5 -5 0 0 -10 0 5	0 5 15 5 0 25 15 10 -5 0 10 -20 -35 -5 -5 15 0 N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051706 89051712 89051718 89051806 89051812 89051818 89051900 89051906 89051912 89051918 89052000 89052006 89052012 Typhoon Ca	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 17.1N 17.7N 18.4N 19.1N 20.5N 21.1N 21.6N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 116.7E 116.0E 115.2E 114.4E 113.8E 113.1E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5 6 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105 N/A N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A N/A N/A N/A N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A N/A N/A N/A	30 30 35 40 45 50 40 35 35 45 55 55 75 70 70	-5 5 10 10 0 5 0 5 0 -5 -5 0 -10 0 5	0 5 15 5 0 25 15 10 -5 0 10 -20 -35 -5 -5 15 0 N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051706 89051712 89051718 89051806 89051812 89051818 89051900 89051906 89051912 89051918 89052000 89052012 Typhoon Ca	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 17.1N 17.7N 18.4N 19.1N 19.1N 20.5N 21.1N 21.6N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 116.7E 116.0E 115.2E 114.4E 113.8E 113.1E Average * Cases	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5 6 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105 N/A N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A N/A N/A N/A N/A N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A	30 30 35 40 45 50 50 40 35 35 45 55 55 75 70 70	-5 5 10 10 0 5 0 5 0 -5 -5 0 0 -10 0 5	0 5 15 5 0 25 15 10 -5 0 10 -20 -35 -5 15 0 N/A N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A N/A
89051518 89051600 89051606 89051612 89051618 89051700 89051706 89051712 89051718 89051806 89051812 89051818 89051900 89051906 89051912 89051918 89052000 89052006 89052012 Typhoon Ca	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	9.8N 10.4N 11.0N 11.7N 12.3N 12.8N 13.4N 13.9N 14.5N 15.2N 15.8N 17.1N 17.7N 18.4N 19.1N 20.5N 21.1N 21.6N	130.2E 129.1E 128.0E 126.6E 125.2E 123.8E 122.6E 121.4E 120.5E 119.6E 118.8E 117.7E 116.7E 116.0E 115.2E 114.4E 113.8E 113.1E	95 147 36 81 26 40 18 13 18 11 29 8 16 18 11 12 25 5 6 5	283 268 190 247 156 90 106 21 45 51 174 73 84 213 102 86 90 105 N/A N/A	406 339 261 306 203 60 130 57 54 92 N/A 228 N/A N/A N/A N/A N/A N/A N/A	411 268 223 329 247 82 252 247 202 N/A N/A N/A N/A N/A N/A N/A N/A	30 30 35 40 45 50 40 35 35 45 55 55 75 70 70	-5 5 10 10 0 5 0 5 0 -5 -5 0 -10 0 5	0 5 15 5 0 25 15 10 -5 0 10 -20 -35 -5 -5 15 0 N/A	30 20 15 5 -10 15 20 10 -10 -5 N/A -40 N/A N/A N/A N/A	25 20 15 0 -15 -20 -15 -5 -10 N/A N/A N/A N/A N/A N/A N/A

Typhoon Co	nil (04)) (conti	nued)									
DTG	₩ ‡	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	DOD SANT	DEC TOD	24 170	48 ER	72 ER
	_							BT WN	WW ER	24 ER		
89052312	4	15.2N	111.5E	21	154	338	N/A	55	0	-5	20	N/A
89052318	5	15.5N	111.0E	21	190	374	N/A	60	-5	0	20	N/A
89052400	6	15.7N	110.4E	13	120	N/A	N/A	65	-10	10	N/A	N/A
89052406	7	15.7N	109.7E	11	30	N/A	N/A	70	-5	30	N/A	N/A
89052412	8	15.8N	109.2E	18	58	N/A	N/A	75	0	35	N/A	N/A
89052418	9	15.8N	108.6E	6	N/A	N/A	N/A	70	-5	N/A	N/A	N/A
				-	2., 22	,	,		_	,	51,55	
Typhoon Do	t (05W)			00h	24h	<u>48h</u>	72h					
			Average	16	78	148	163					
			# Cases	25	23	17	11					
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89060500	1	9.8N	130.7E	17	95	216	236	30	-5	15	10	-10
89060506	2	10.2N	129.3E	34	79	187	161	30	0	20	- 5	-25
89060512	3	10.5N	127.9E	18	21	24	59	35	-5	-10	-10	-35
89060518	4	11.0N	126.7E	13	39	41	91	35	Ö	-15	-10	-40
89060600	5	11.4N	125.7E	26	169	191	180	40	5	0	-20	-40
89060606	6	11.4N	124.5E	35	157	138	98	40	5	- 5	-20 -5	-30
89060612			124.3E	17	42	47	81		5			
	7	12.2N						45		5	-20	-25
89060618	8	12.6N	121.5E	8	47	107	173	50	5	15	-15	-30
89060700	9	13.1N	120.1E	21	120	192	260	50	0	10	-20	-35
89060706	10	13.6N	119.1E	8	53	153	204	55	0	5	-20	-40
89060712	.11	14.3N	118.4E	6	82	221	252	55	0	-10	-25	-30
89060718	12	14.9N	117.6E	12	103	252	N/A	55	0	-20	-40	N/A
89060800	13	15.3N	116.7E	13	87	164	N/A	60	-5	-25	-45	N/A
89060806	14	15.7N	115.9E	8	91	203	N/A	65	0	-10	-45	N/A
89060812	15	16.1N	115.1E	17	180	N/A	N/A	85	-20	-5	N/A	N/A
89060818	16	16.4N	114.4E	18	103	N/A	N/A	95	-5	5	N/A	N/A
89060900	17	16.6N	113.6E	5	61	158	N/A	100	0	5	25	N/A
89060906	18	16.9N	112.8E	18	36	132	N/A	100	ō	-10	10	N/A
89060912	19	17.2N	111.9E	6	37	84	N/A	95	ŏ	25	35	N/A
89060918	20	17.6N	111.1E	6	41	N/A	N/A	95	Ö	25	N/A	N/A
89061000	21	18.1N	110.2E	12	70	-		95	- 5	-5		
	22					N/A	N/A		_		N/A	N/A
89061006		18.6N	109.2E	13	29	N/A	N/A	80	-15	-15	N/A	N/A
89061012	23	19.0N	108.2E	11	47	N/A	N/A	60	-5	0	N/A	N/A
89061018	24	19.4N	107.3E	21	N/A	N/A	N/A	55	-10	N/A	N/A	N/A
89061100	25	20.2N	106.5E	48	N/A	N/A	N/A	55	-10	N/A	N/A	N/A
Tropical St	-Arm 211	ie (new		<u>00h</u>	244	48h	72h					
Trobrown 9	~	(OOM)	A		24h 347							
			Average	33		N/A	N/A					
•			# Cases	6	6	0	0					
DTG	Wŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89062006†	1	16.4N	128.9E	24	240	N/A	N/A	25	0	5	N/A	N/A
89062018†	2	17.3N	127.4E	65	266	N/A	N/A	25	ő	5	N/A	N/A
89062218*	3	20.0N	126.1E	11	463	N/A	N/A	30	Ö	ō	N/A	N/A
89062300	3 4	20.0N 21.0N	126.1E	42					0	0	N/A	N/A
					653	N/A	N/A	35				
89062306	5	23.2N	127.9E	36	336	N/A	N/A	35	0	- 5	N/A	N/A
89062312	6	25.4N	128.8E	18	125	N/A	N/A	35	- 5	-10	N/A	N/A

[†] Tropical Depression Warning * Regenerated

Tropical	Storm Fa	ıye (07W)		<u>00h</u> 25	24h 72	48h	72h					
			Average # Cases	25	18	124 12	220 10					
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89070606	1	15.4N	129.6E	13	72	33	114	25	0	0	10	-10
89070612	2	15.9N	129.2E	43	75	42	150	25	5	-5	-5	-5
89070618	3	16.3N	128.7E	74	90	83	194	25	ō	-10	10	ō
89070700	4	16.7N	128.1E	60	59	185	310	30	ō	-5	5	10
89070706	5	16.9N	127.4E	18	53	207	280	35	0	-5	0	20
89070712	6	17.0N	126.5E	24	81	169	248	35	0	-5	10	40
89070718	7	17.0N	125.7E	16	74	124	160	40	-5	15	25	40
89070800	8	16.7N	124.6E	11	77	183	257	45	0	10	35	60
89070806	9	16.7N	123.5E	24	55	124	230	55	0	20	40	50
89070812	10	16.9N	122.4E	30	82	166	257	60	0	20	40	45
89070818	11	17.2N	120.8E	62	69	135	N/A	40	0	25	45	N/A
89070900	12	17.3N	119.1E	11	41	32	N/A	45	0	35	30	N/A
89070906	13	17.5N	117.6E	17	62	N/A	N/A	45	0	∽ 5	N/A	N/A
89070912	14	17.7N	116.5E	29	146	N/A	N/A	45	-5	-5	N/A	N/A
89070918	15	18.2N	115.4E	43	135	N/A	N/A	40	0	0	N/A	N/A
89071000	16	18.7N	114.0E	13	17	N/A	N/A	40	0	-5	N/A	N/A
89071006	17	19.1N	112.7E	5	88	N/A	N/A	35	0	-10	N/A	N/A
89071012	18	19.5N	111.4E	8	25	N/A	N/A	35	0	0	N/A	N/A
89071018	19	20.0N	110.3E	6	N/A	N/A	N/A	30	5	N/A	N/A	N/A
89071100	20	20.5N	109.1E	17	N/A	N/A	N/A	30	0	N/A	N/A	N/A
89071106	21	21.2N	107.7E	0	n/A	N/A	N/A	30	0	N/A	N/A	N/A
Super Tyr	shoon Goz	rdon (08W)	Average	<u>00h</u> 13	24h 68	48h 118	<u>72h</u> 146					
			# Cases	30	26	24	18					
					20		20					
DTG	₩ŧ	BT LAT	BT LON	POS ER	24_ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
<u>DTG</u> 89071106	₩# 1	BT LAT 18.6N	BT LON 147.3E	POS ER 72	24 ER 33	48 ER 80	72 ER 120	<u>BT WN</u> 30	WW ER	24 ER -10	48 ER -15	72 ER -35
89071106	1	18.6N	147.3E	72	33	80	120	30	0	-10	-15	-35
89071106 89071112	1 2	18.6N 18.5N	147.3E 145.3E	72 13	33 30	80 70	120 138	30 30	0	-10 -5	-15 -10	-35 -35
89071106 89071112 89071118	1 2 3	18.6N 18.5N 18.3N	147.3E 145.3E 144.0E	72 13 24	33 30 23	80 70 93	120 138 121	30 30 30	0 0 0	-10 -5 -10	-15 -10 -15	-35 -35 -50
89071106 89071112 89071118 89071200	1 2 3 4	18.6N 18.5N 18.3N 18.1N	147.3E 145.3E 144.0E 142.6E	72 13 24 22	33 30 23 8	80 70 93 90	120 138 121 96	30 30 30 35	0 0 0 5	-10 -5 -10 -10	-15 -10 -15 -20	-35 -35 -50 -65
89071106 89071112 89071118 89071200 89071206	1 2 3 4 5	18.6N 18.5N 18.3N 18.1N 18.0N	147.3E 145.3E 144.0E 142.6E 141.3E	72 13 24 22 12	33 30 23 8 53	80 70 93 90 123	120 138 121 96 105	30 30 30 35 40	0 0 0 5 5	-10 -5 -10 -10 5	-15 -10 -15 -20 -15	-35 -35 -50 -65 -50
89071106 89071112 89071118 89071200 89071206 89071212	1 2 3 4 5	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E	72 13 24 22 12 0	33 30 23 8 53 62	80 70 93 90 123 98	120 138 121 96 105 55	30 30 30 35 40 45	0 0 0 5 5	-10 -5 -10 -10 5	-15 -10 -15 -20 -15 -25	-35 -35 -50 -65 -50
89071106 89071112 89071118 89071200 89071206 89071212 89071218	1 2 3 4 5 6 7 8 9	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E	72 13 24 22 12 0 8	33 30 23 8 53 62 72	80 70 93 90 123 98 96	120 138 121 96 105 55 47	30 30 35 40 45 50	0 0 0 -5 5 0 -5	-10 -5 -10 -10 5 0	-15 -10 -15 -20 -15 -25 -40	-35 -35 -50 -65 -50 -50
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300	1 2 3 4 5 6 7 8	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.9N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E	72 13 24 22 12 0 8	33 30 23 8 53 62 72 124	80 70 93 90 123 98 96 179	120 138 121 96 105 55 47 214	30 30 35 40 45 50	0 0 0 -5 5 0 -5 0 5	-10 -5 -10 -10 5 0 -5 -10	-15 -10 -15 -20 -15 -25 -40 -50	-35 -35 -50 -65 -50 -50 -55
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318	1 2 3 4 5 6 7 8 9 10	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.9N 17.6N 17.6N 17.6N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E	72 13 24 22 12 0 8 12 8 12 5	33 30 23 8 53 62 72 124 117 85 25	80 70 93 90 123 98 96 179 149 183 116	120 138 121 96 105 55 47 214 192 284 165	30 30 35 40 45 50 55 60 65 70	0 0 -5 5 0 -5 0 5 5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75	-35 -35 -50 -65 -50 -50 -55 -35 -20 -10
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400	1 2 3 4 5 6 7 8 9 10 11	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E	72 13 24 22 12 0 8 12 8 12 5	33 30 23 8 53 62 72 124 117 85 25	80 70 93 90 123 98 96 179 149 183 116	120 138 121 96 105 55 47 214 192 284 165 142	30 30 35 40 45 50 55 60 65 70	0 0 -5 5 0 -5 0 5 -5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406	1 2 3 4 5 6 7 8 9 10 11 12 13	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.4N 16.3N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E	72 13 24 22 12 0 8 12 8 12 5 6	33 30 23 8 53 62 72 124 117 85 25 5	80 70 93 90 123 98 96 179 149 183 116 67	120 138 121 96 105 55 47 214 192 284 165 142 188	30 30 35 40 45 50 55 60 65 70 75	0 0 -5 5 0 -5 0 5 -5 0	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412	1 2 3 4 5 6 7 8 9 10 11 12 13 14	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.3N 16.3N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E	72 13 24 22 12 0 8 12 8 12 5 6	33 30 23 8 53 62 72 124 117 85 25 5 49	80 70 93 90 123 98 96 179 149 183 116 67 157	120 138 121 96 105 55 47 214 192 284 165 142 188 172	30 30 35 40 45 50 55 60 65 70 75 90	0 0 0 -5 5 0 -5 0 5 -5 0 -5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.3N 16.3N 16.4N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E	72 13 24 22 12 0 8 12 8 12 5 6 8 5	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119	80 70 93 90 123 98 96 179 149 183 116 67 157 136	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152	30 30 35 40 45 50 55 60 65 70 75 90 100	0 0 0 -5 5 0 -5 0 5 -5 0 -5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35 -15	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071418	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 16.5N 16.3N 16.3N 16.4N 16.6N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E	72 13 24 22 12 0 8 12 5 6 8 5	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152	30 30 35 40 45 50 55 60 65 70 75 90 100 115	0 0 0 -5 5 0 -5 0 -5 0 -5 10 -5 0	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35 -15 -15	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071506	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 16.5N 16.3N 16.3N 16.4N 16.6N 17.0N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110	30 30 35 40 45 50 55 60 65 70 75 90 100 115 125	0 0 0 -5 5 0 -5 0 -5 0 -5 10 -5 0	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35 -15 -15	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071506 89071512	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 16.5N 16.4N 16.3N 16.4N 16.6N 17.0N 17.0N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143	30 30 35 40 45 50 55 60 65 70 75 90 100 115 125 140	0 0 0 -5 5 0 -5 0 -5 10 -5 0 -5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35 -15 -35 -15 30	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071506 89071512	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 16.5N 16.4N 16.3N 16.4N 16.6N 17.0N 17.0N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A	30 30 35 40 45 50 55 60 65 70 75 90 100 115 125 140 140	0 0 0 -5 5 0 -5 0 -5 10 -5 0 -5 -5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -35 -15 30 25	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 -5 N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071506 89071512 89071518	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 16.5N 16.4N 16.3N 16.4N 16.6N 17.0N 17.5N 17.9N 17.9N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 12	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A	30 30 35 40 45 50 55 60 65 70 75 90 100 115 125 140 140 120	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -5 -5 -5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5 20 10	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35 -15 -25 10 15 30 25 15	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 -5 N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071506 89071518 89071600 89071600	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 16.5N 16.4N 16.3N 16.4N 16.6N 17.0N 17.5N 17.9N 17.9N 17.8N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 12 13	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 98 94 98	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A	30 30 30 35 40 45 50 55 60 65 70 75 90 100 115 125 140 140 120 110	0 0 0 -5 5 0 -5 0 -5 10 -5 0 -5 -5 -5 -5	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5 20 10 20	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35 -15 -25 10 15 30 25 15 -25	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 -5 N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071506 89071518 89071600 89071606 89071612	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 16.5N 16.4N 16.3N 16.4N 16.6N 17.0N 17.5N 17.9N 17.9N 18.2N 18.3N 18.5N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 12 13 13 5 6	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A	30 30 30 35 40 45 50 55 60 65 70 75 90 100 115 125 140 140 120 110	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -5 -5 -25 -30 -15	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5 20 10 20 30	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -55 -35 -15 -25 -25 -20	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 -0 10 15 20 25 -5 -5 N/A N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071306 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071506 89071512 89071518 89071600 89071606 89071612 89071618	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.4N 16.3N 16.3N 16.6N 17.0N 17.5N 18.3N 18.5N 18.5N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E 117.6E	72 13 24 22 12 0 8 12 5 6 8 13 12 13 12 13 13 15 6	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33 83	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116 250	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A N/A	30 30 30 35 40 45 50 55 60 65 70 100 115 125 140 140 120 110 100 90	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -5 -25 -30 -15	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5 20 10 20 30 35	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -30 15 30 25 15 -25 -20 -10	-35 -35 -50 -65 -50 -55 -35 -20 -10 15 20 25 -5 N/A N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071312 89071318 89071400 89071402 89071418 89071418 89071500 89071512 89071518 89071500 89071600 89071618 89071618	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.3N 16.3N 16.3N 16.3N 16.3N 16.3N 16.3N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E 117.6E 116.6E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 12 13 13 15 6	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33 83 26	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116 250 126	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A N/A	30 30 30 35 40 45 50 55 60 65 70 100 115 125 140 140 120 110 90 80	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -5 -25 -30 -15	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -60 -40 -30 -5 20 10 20 30 35 30	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -15 -25 -20 -10	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 -0 10 15 -5 -5 N/A N/A N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071312 89071318 89071400 89071406 89071412 89071418 89071500 89071512 89071518 89071500 89071600 89071600 89071612 89071612 89071618 89071700 89071700	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.4N 16.3N 16.3N 16.6N 17.0N 17.5N 18.3N 18.5N 18.5N 18.5N 18.5N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E 117.6E 116.6E 115.6E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 12 13 13 15 6 6 12	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33 83 26 81	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116 250 126 N/A	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A N/A	30 30 30 35 40 45 50 55 60 65 70 100 115 125 140 140 120 110 90 80 75	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -5 -25 -30 -15 0 0	-10 -5 -10 -10 5 0 -5 -10 0 -5 -40 -35 -60 -40 -30 -5 20 10 20 30 35 30 -5	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -15 -25 -20 -10 5 N/A	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 N/A N/A N/A N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071312 89071318 89071400 89071412 89071412 89071500 89071512 89071512 89071518 89071600 89071606 89071612 89071618 89071700 89071700 89071706	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.4N 16.3N 16.3N 16.6N 17.0N 17.5N 18.3N 18.5N 18.5N 18.1N 18.2N 18.3N 18.5N 18.5N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E 117.6E 116.6E 115.6E 114.7E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 13 13 5 6 6 12 16 8	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33 83 26 81	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116 250 126 N/A	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A N/A N/A	30 30 30 35 40 45 50 55 60 65 70 100 115 125 140 140 120 110 90 80 75 70	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -5 -25 -30 -15 0 0	-10 -5 -10 -10 -5 -10 -10 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5 20 10 20 30 35 30 -5 -20	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -15 -25 -20 -10 5 N/A	-35 -35 -50 -65 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 N/A N/A N/A N/A N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071312 89071318 89071400 89071406 89071412 89071418 89071506 89071512 89071518 89071600 89071606 89071612 89071618 89071718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.4N 16.3N 16.3N 16.6N 17.0N 17.5N 18.3N 18.5N 18.2N 18.3N 18.5N 18.6N 19.1N 19.7N 20.4N 20.8N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E 117.6E 116.6E 115.6E 114.7E 113.6E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 13 13 5 6 6 12	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33 83 26 81 115 N/A	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116 250 126 N/A N/A	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A N/A N/A	30 30 30 35 40 45 50 55 60 65 70 100 115 125 140 140 120 110 90 80 75 70 65	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -25 -30 -15 0 0	-10 -5 -10 -10 -5 -10 -10 -5 -10 0 -5 -40 -35 -40 -35 -60 -40 -30 -5 20 10 20 30 35 30 -5 -20 N/A	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -15 30 25 15 -25 -20 -10 5 N/A	-35 -35 -50 -65 -50 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 N/A N/A N/A N/A N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071312 89071318 89071400 89071406 89071412 89071418 89071506 89071512 89071512 89071518 89071600 89071606 89071612 89071618 89071700 89071718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.3N 16.3N 16.3N 16.3N 16.3N 16.3N 16.3N 17.0N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 17.5N 16.3N 16.3N 16.3N 16.4N 17.5N 18.2N 18.3N 18.3N 18.5N 18.6N 19.1N 19.7N 20.4N 20.4N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.8N 20.1N 20.1N 20.8N 20.8N 20	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E 117.6E 116.6E 115.6E 114.7E 113.6E 112.5E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 13 15 6 12 16 8 6	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33 83 26 81 115 N/A	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116 250 126 N/A N/A	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A N/A N/A N/A	30 30 30 35 40 45 50 55 60 65 70 100 115 125 140 140 120 110 90 80 75 70 65 60	0 0 0 -5 5 0 -5 0 -5 0 -5 -5 -25 -25 -30 -15 0 0 0	-10 -5 -10 -10 -5 -10 -5 -10 0 -5 -40 -35 -30 -15 -60 -40 -30 -5 20 10 20 30 35 30 -5 -20 N/A N/A	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -15 30 25 15 -25 -20 -10 N/A N/A	-35 -35 -50 -65 -50 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 N/A N/A N/A N/A N/A N/A N/A
89071106 89071112 89071118 89071200 89071206 89071212 89071218 89071300 89071312 89071318 89071400 89071406 89071412 89071418 89071506 89071512 89071518 89071600 89071606 89071612 89071618 89071718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27	18.6N 18.5N 18.3N 18.1N 18.0N 17.9N 17.8N 17.6N 17.6N 16.5N 16.4N 16.3N 16.3N 16.6N 17.0N 17.5N 18.3N 18.5N 18.2N 18.3N 18.5N 18.6N 19.1N 19.7N 20.4N 20.8N	147.3E 145.3E 144.0E 142.6E 141.3E 139.9E 138.3E 136.7E 135.1E 133.8E 132.6E 131.4E 130.2E 128.8E 127.4E 126.2E 125.1E 124.0E 122.6E 121.3E 120.1E 118.8E 117.6E 116.6E 115.6E 114.7E 113.6E	72 13 24 22 12 0 8 12 5 6 8 5 13 12 13 13 13 5 6 6 12	33 30 23 8 53 62 72 124 117 85 25 5 49 104 119 132 116 30 97 111 34 33 83 26 81 115 N/A	80 70 93 90 123 98 96 179 149 183 116 67 157 136 112 151 130 20 98 94 98 116 250 126 N/A N/A	120 138 121 96 105 55 47 214 192 284 165 142 188 172 152 185 110 143 N/A N/A N/A N/A	30 30 30 35 40 45 50 55 60 65 70 100 115 125 140 140 120 110 90 80 75 70 65	0 0 0 -5 5 0 -5 0 -5 10 -5 -5 -25 -30 -15 0 0	-10 -5 -10 -10 -5 -10 -10 -5 -10 0 -5 -40 -35 -40 -35 -60 -40 -30 -5 20 10 20 30 35 30 -5 -20 N/A	-15 -10 -15 -20 -15 -25 -40 -50 -40 -65 -75 -35 -15 -15 30 25 15 -25 -20 -10 5 N/A	-35 -35 -50 -65 -50 -50 -55 -35 -20 -10 -15 0 10 15 20 25 -5 N/A N/A N/A N/A N/A N/A

Tropical	Storm H	lope (09W)	Average	<u>00h</u> 21	24h 112	48h 224	<u>72h</u> 309					
			# Cases	21	17	14	5					
DTG	W#	BT LAT	BT LON	POS ER	24_ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89071600	1	20.8N	134.8E	103	194	273	398	30	-5	0	0	-20
89071606	2	21.0N	134.0E	18	98	158	257	.30	0	0	15	-15
89071612	3	21.1N	133.0E	16	111	212	324	30	5	0	15	-30
89071618	4	21.5N	131.8E	24	167	248	277	35	0	5	-10	-30
89071700	5	22.2N	130.8E	42	137	208	29	35	5	15	-15	-30
89071706	6	23.0N	130.0E	0	91	150	N/A	40	-5	-15	-10	N/A
89071712	7	23.6N	128.8E	21	134	175	N/A	40	-5	-10	-25	N/A
89071718	8	24.2N	127.9E	10	129	287	N/A	45	-5	~5	-25	N/A
89071800	9	24.5N	127.0E	0	89	235	N/A	45	0	10	-25	N/A
89071806	10	24.9N	126.4E	13	32	171	N/A	50	0	15	-15	N/A
89071812	11	25.3N	125.8E	12	60	146	N/A	50	0	15	-5	N/A
89071818	12	25.8N	125.2E	18	54	207	N/A	55	- 5	0	20	N/A
89071900	13	26.6N	124.6E	16	86	276	N/A	55	0	-5	15	N/A
89071906	14	27.2N	124.1E	21	112	383	N/A	55	0	0	15	N/A
89071912	15	27.8N	123.7E	5	72	N/A	N/A	5 5	-10	0	N/A	N/A
89071918	16	28.4N	123.3E	16	150	N/A	N/A	55	-10	0	N/A	N/A
89072000	17	28.6N	122.9E	43	181	N/A	N/A	55	-10	0	N/A	N/A
89072006	18	28.7N	122.5E	31	N/A	N/A	N/A	45 35	-5	N/A	N/A	N/A
89072012	19	28.8N	122.0E	23	N/A	N/A	N/A		0	N/A	N/A	N/A
89072018	20 21	28.9N 29.0N	121.5E 121.1E	6 0	N/A N/A	N/A N/A	N/A N/A	30 30	0	N/A N/A	N/A N/A	N/A N/A
89072100	21	29.0N	121.15	v	W/A	N/A	N/A	30	Ü	MA	W/A	M/A
Tropical	Storm 1	rving (10W		<u>00h</u>	24h	48h	<u>72h</u>					
			Average	21	90	152	232					
			# Cases	14	9	4	2					
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89072100	1	15.0N	116.7E	21	174	264	389	30	-5	0	5	5
89072106	2	15.1N	115.0E	17	8	29	74	35	0	10	15	5
89072112	3	15.0N	113.4E	30	163	254	N/A	40	0	20	-20	N/A
89072118	4	15.0N	112.2E	29	166	N/A	N/A	40	5	0	N/A	N/A
89072200	5	15.5N	111.3E	8	56	N/A	N/A	40	5	-10	N/A	N/A
89072206	6	16.4N	110.7E	40	49	62	N/A	40	-5	-10	-10	N/A
89072212	7	16.7N	110.2E	20	49	N/A	N/A	40	-5	-10	N/A	N/A
89072218	8	16.8N	109.5E	24	47	N/A	N/A	40	-5	-20	N/A	N/A
89072300	9	17.1N	108.6E	25	101	N/A	N/A	45	-10	-30	N/A	N/A
89072306	10	17.5N	107.7E	8	N/A	N/A	N/A	45	-15	N/A	N/A	N/A
89072312	11	18.1N	107.0E	16	N/A	N/A	N/A	45	-15	N/A	N/A	N/A
89072318	12	18.6N	106.3E	36	N/A	N/A	N/A	55	-30	N/A	N/A	N/A
89072400	13	19.2N	105.7E	18	N/A	N/A	N/A	55	-20	N/A	N/A	N/A
89072406	14	19.7N	104.9E	0	N/A	N/A	N/A	40	-10	N/A	N/A	N/A
Typhoon J	Tudy (11	LW)		<u>00h</u>	24h	48h	<u>72h</u>					
			Average	15	85	195	323					
			# Cases	28	24	20	16					
DTG	W#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER 0	72 ER
89072206	1	14.8N	138.8E	18	119	290	446	25 25	0	5 0	-10	-20 -40
89072212	2	15.4N	138.3E	52 31	67	39 24	106	30	0 -5	-5	-10 -25	-45
89072218	3	16.1N	138.0E	31	23 60	43	136 85	35	-5	-3	-25	-35
89072300 89072306	4 5	16.5N 17.0N	138.0E 138.0E	26 32	30	24	139	35	0	-5	-25 -35	-30
89072312	6	17.5N	138.0E	13	90	174	277	35	0	-5 -5	-35	-15
89072318	7	17.5N 18.2N	138.1E	30	90 87	180	296	35	5	-10	-30	-15
89072318	8	18.2N 18.9N	138.1E 138.2E	30 6	84	95	241	50	0	-10 -10	-30	-13 25
090/2400	0	10.AN	136.ZE	•			241	50	J	10	J	2.5
					2	27						

Typhoon J	Judy (11W) (contin	ued)									
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89072406	9	19.6N	138.3E	13	42	125	308	55	0	-15	10	<u> 12 ER</u> 25
89072412	10	20.2N	138.4E	11	48	103	272					
89072418	11	20.2N	138.4E	11	55			55	0	-20	10	0
89072500	12	21.8N	138.4E	11		111	316	65	0	-10	10	0
89072506	13	22.8N			41	146	389	80	0	10	30	30
89072512			138.3E	8	69	274	485	90	0	20	30	40
	14	23.9N	138.0E	10	87	376	652	95	0	25	30	40
89072518	15	24.9N	137.9E	5	123	383	578	95	0	25	5	25
89072600	16	26.0N	137.5E	8	150	388	437	90	0	5	10	30
89072606	17	26.8N	136.9E	0	155	375	N/A	90	0	0	0	N/A
89072612	18	27.6N	136.3E	8	227	398	N/A	85	0	0	0	N/A
89072618	19	28.4N	135.2E	6	195	328	N/A	85	0	-5	10	N/A
89072700	20	29.2N	134.1E	5	27	30	N/A	85	0	0	5	N/A
89072706	21	30.1N	132.8E	0	74	N/A	N/A	90	-5	0	N/A	N/A
89072712	22	30.8N	131.2E	7	81	N/A	N/A	90	0	5	N/A	N/A
89072718	23	31.8N	130.0E	20	43	N/A	N/A	90	-15	10	N/A	N/A
89072800	24	32.7N	129.2E	7	52	N/A	N/A	65	0	5	N/A	N/A
89072806	25	33.5N	128.4E	15	N/A	N/A	N/A	60	5	N/A	N/A	N/A
89072812	26	34.6N	127.6E	20	N/A	N/A	N/A	50	5	N/A	N/A	N/A
89072818	27	36.4N	127.3E	30	N/A	N/A	N/A	40	10	N/A	N/A	N/A
89072900	28	38.0N	128.0E	7	N/A	N/A	N/A	30	0	N/A	N/A	
03072300		30.014	120.05	•	II/A	N/A	N/A	30	U	N/A	N/A	N/A
Tropical	Depressi	on 12W		00h	24h	48h	<u>72h</u>					
			Average	14	61	N/A	N/A					
			# Cases	3	2	0	0					
			* 02363	,	2	U	J					
DTG	Wŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89072912	1	24.8N	124.0E	0	12	N/A	N/A	30	0	10		
89072918	2	25.0N	122.8E	Ö	110						N/A	N/A
89073000	3	25.2N	122.0E	43	N/A	N/A N/A	N/A N/A	30	0 -5	10 N/A	N/A	N/A
030/3000	3	23.ZN	IZZ.Ur.	4.1		N/A	N/A	30		N/A	N/A	N/A
					21/22	и/ п	14/11		-5	III/A	II/A	14/12
					11/11	11/11	14,11	50	-3	II/A	M/A	M/ A
Twoicel	Storm Yo							30	-5	M/A	N/A	N/A
Tropical	Storm Ke		3W-14W)	<u>00h</u>	24h	48h	72h	30	-5	M/ A	N/A	M/A
Tropical	Storm Ke		3W-14W) Average	<u>00h</u> 38	24h 193	48h 313	72h 382	30	-3	M/ A	N/A	M/ A
Tropical	Storm Ke		3W-14W)	<u>00h</u>	24h	48h	72h	30	-3	N, A	M/A	N/A
_		n-Lola (1	3W-14W) Average † Cases	00h 38 23	24h 193 18	48h 313 14	72h 382 10					
DIG	₩ŧ	n-Lola (1: BT LAT	3W-14W) Average # Cases BT LON	00h 38 23 POS ER	24h 193 18 24 ER	48h 313 14 48 ER	72h 382 10	BT_WN	WW ER	24 ER	48 ER	72_ER
DTG 89073000	₩ # 1	n-Lola (1 BT LAT 24.3N	3W-14W) Average Cases BT LON 136.0E	00h 38 23 POS ER 20	24h 193 18 24 ER 221	48h 313 14 48 ER 509	72h 382 10 72 ER 519	BT WN 30	WW ER	24 ER -5		
DTG 89073000 89073006	₩ ‡ 1 2	n-Lola (1: BT LAT 24.3N 25.1N	3W-14W) Average Cases ET LON 136.0E 137.3E	00h 38 23 POS ER 20 43	24h 193 18 24 ER 221 199	48h 313 14 48 ER 509 450	72h 382 10 72 ER 519 546	BT WN 30 45	<u>WW_ER</u> 0 0	24 ER -5 5	48 ER 5 0	72 ER 10 -10
DTG 89073000 89073006 89073012	₩ ‡ 1 2 3	n-Lola (1: BT LAT 24.3N 25.1N 26.5N	3W-14W) Average	00h 38 23 POS ER 20 43 31	24h 193 18 24 ER 221 199 397	48h 313 14 48 ER 509 450 449	72h 382 10 72 ER 519	BT WN 30	WW ER	24 ER -5 5 5	48 ER 5	72_ER 10 -10 -10
DTG 89073000 89073006 89073012 89073018	₩# 1 2 3 4	BT LAT 24.3N 25.1N 26.5N 27.7N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141	24h 193 18 24 ER 221 199 397 409	48h 313 14 48 ER 509 450 449 414	72h 382 10 72 ER 519 546 306 241	BT WN 30 45 45 45	WW ER 0 0 0	24 ER -5 5 5 5	48 ER 5 0	72 ER 10 -10 -10 -10
DTG 89073000 89073006 89073012 89073018 89073100	₩ ‡ 1 2 3 4 5	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246	24h 193 18 24 ER 221 199 397 409 N/A	48h 313 14 48 ER 509 450 449 414 N/A	72h 382 10 72 ER 519 546 306 241 N/A	BT WN 30 45 45 45 45	WW ER 0 0 0	24 ER -5 5 5 5 N/A	48 ER 5 0 5 10 N/A	72_ER 10 -10 -10 -10 N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112*	₩ ‡ 1 2 3 4 5	BT LAT 24.3N 25.1N 26.5N 27.7N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141	24h 193 18 24 ER 221 199 397 409	48h 313 14 48 ER 509 450 449 414	72h 382 10 72 ER 519 546 306 241	BT WN 30 45 45 45	WW ER 0 0 0	24 ER -5 5 5 5	48 ER 5 0 5	72 ER 10 -10 -10 -10
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118	W# 1 2 3 4 5 6 7	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16	24h 193 18 24 ER 221 199 397 409 N/A	48h 313 14 48 ER 509 450 449 414 N/A	72h 382 10 72 ER 519 546 306 241 N/A	BT WN 30 45 45 45 45	WW ER 0 0 0 0	24 ER -5 5 5 5 N/A	48 ER 5 0 5 10 N/A	72_ER 10 -10 -10 -10 N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118 89080100	₩ ‡ 1 2 3 4 5	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59	24h 193 18 24 ER 221 199 397 409 N/A 425	48h 313 14 48 ER 509 450 449 414 N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A	BT WN 30 45 45 45 45 50	WW ER 0 0 0 0	24 ER -5 5 5 5 N/A 10	48 ER 5 0 5 10 N/A N/A	72_ER 10 -10 -10 -10 N/A N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118	W# 1 2 3 4 5 6 7	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16	24h 193 18 24 ER 221 199 397 409 N/A 425 187	48h 313 14 48 ER 509 450 449 414 N/A N/A 363	72h 382 10 72 ER 519 546 306 241 N/A N/A	BT WN 30 45 45 45 45 50	WW ER 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15	48 ER 5 0 5 10 N/A N/A 5	72_ER 10 -10 -10 -10 N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118 89080100	W# 1 2 3 4 5 6 7 8	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290	72h 382 10 72 ER 519 546 306 241 N/A N/A N/A 335 378	BT WN 30 45 45 45 45 50 50 50	WW ER 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 15	48 ER 5 0 5 10 N/A N/A 5 5	72_ER 10 -10 -10 -10 N/A N/A N/A -10
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118 89080100 89080106	W# 1 2 3 4 5 6 7 8 9	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285	72h 382 10 72 ER 519 546 306 241 N/A N/A N/A 335	BT WN 30 45 45 45 45 50 50	WW ER 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 15	48 ER 5 0 5 10 N/A N/A 5 5	72_ER 10 -10 -10 -10 N/A N/A N/A -10 5 0
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118 89080100 89080106 89080112	W# 1 2 3 4 5 6 7 8 9 10 11	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 26.8N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346	72h 382 10 72 ER 519 546 306 241 N/A N/A N/A 335 378 386 345	BT WN 30 45 45 45 45 50 50 50 45 40	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 15 10 10	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5	72_ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118 89080100 89080106 89080112 89080118	W# 1 2 3 4 5 6 7 8 9 10 11 12	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403	72h 382 10 72 ER 519 546 306 241 N/A N/A N/A 335 378 386 345 438	BT WN 30 45 45 45 45 50 50 50 45 40 40	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 10 -5	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5	72_ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89080100 89080106 89080112 89080118 89080200 89080206	W# 1 2 3 4 5 6 7 8 9 10 11 12 13	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.0N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403 311	72h 382 10 72 ER 519 546 306 241 N/A N/A N/A 335 378 386 345 438 324	BT WN 30 45 45 45 45 50 50 50 45 40 40 45	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 -5 10	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 40	72_ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89073118 89080100 89080106 89080112 89080118 89080200	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.0N 28.5N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403 311 39	72h 382 10 72 ER 519 546 306 241 N/A N/A N/A 335 378 386 345 438 324 N/A	BT WN 30 45 45 45 45 50 50 50 45 40 40 45 45	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 N/A 10 15 10 10 -5 10 10	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 40 5	72_ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89080100 89080106 89080112 89080118 89080200 89080206 89080212 89080218	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.7N 28.5N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403 311 39 76	72h 382 10 72 ER 519 546 306 241 N/A N/A N/A 335 378 386 345 438 324 N/A N/A	BT WN 30 45 45 45 45 50 50 50 45 40 40 45 45 45	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 -5 10 15	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 40 5 10	72_ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89080100 89080106 89080112 89080118 89080200 89080206 89080212 89080218 89080300	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.0N 26.8N 27.7N 28.5N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403 311 39 76 83	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A	BT WN 30 45 45 45 45 50 50 50 40 40 45 45 45	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 -5 10 15 10	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 40 5 10	72_ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89080100 89080106 89080112 89080118 89080200 89080206 89080212 89080218 89080300 89080306	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.5N 26.8N 27.0N 26.8N 27.7N 28.5N 29.5N 30.0N 30.4N	3W-14W) Average	90h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403 311 39 76 83 N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A	BT WN 30 45 45 45 45 50 50 50 40 40 45 45 45 50 50	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 -5 -10 -10	24 ER -5 5 5 5 N/A 10 15 10 10 -5 10 15 10 5	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 40 5 10	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89080100 89080106 89080112 89080118 89080200 89080206 89080212 89080218 89080300 89080306 89080312	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 27.7N 28.5N 29.5N 30.0N 30.4N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18 36	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106 85	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403 311 39 76 83 N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A	BT WN 30 45 45 45 50 50 50 45 40 45 45 45 50 50	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 -5 -10 -10	24 ER -5 5 5 N/A 10 15 10 10 10 15 10 10 5 0 5	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 5 10 5 10 40 5 N/A	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073100 89073112* 89080100 89080106 89080112 89080112 89080118 89080206 89080212 89080218 89080218 89080300 89080306 89080312	W± 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.7N 28.5N 29.5N 30.0N 30.4N 30.7N 31.1N	3W-14W) Average	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18 36 11	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106 85 51	48h 313 14 48 ER 509 450 449 414 N/A N/A 363 290 285 362 346 403 311 39 76 83 N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A	BT WN 30 45 45 45 50 50 50 45 40 40 45 45 45 50 50 50	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 -5 -10 -10 -5	24 ER -5 5 5 N/A 10 15 10 10 -5 10 15 10 0 0	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 5 N/A	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073110 89073112* 89080100 89080106 89080112 89080112 89080118 89080206 89080212 89080218 89080218 89080306 89080318 89080318 89080318	W± 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.5N 27.0N 26.8N 27.7N 28.5N 27.7N 28.5N 29.5N 30.0N 30.4N 30.7N 31.1N 31.3N	3W-14W) Average Cases ET LON 136.0E 137.3E 138.5E 136.7E 135.0E 130.9E 129.9E 129.9E 129.5E 129.2E 129.0E 128.4E 127.7E 126.9E 126.0E 123.8E 122.6E 121.3E	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18 36 11 21	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106 85 51 N/A	48h 313 14 48 ER 509 450 449 414 N/A 363 290 285 362 346 403 311 39 76 83 N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A N/A	BT WN 30 45 45 45 50 50 50 45 40 45 45 45 45 45 45 45 45	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 -5 -10 -10 -5 -5	24 ER -5 5 5 5 N/A 10 15 10 10 -5 10 15 10 0 N/A	48 ER 5 0 5 10 N/A N/A 5 5 10 -5 5 10 5 N/A N/A	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073110 89073112* 89080100 89080106 89080112 89080112 89080118 89080200 89080212 89080218 89080218 89080310 89080312 89080318 89080318 89080400 89080400	W± 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.7N 28.5N 29.5N 30.0N 30.4N 30.7N 31.1N 31.3N 31.8N	3W-14W) Average Cases ET LON 136.0E 137.3E 138.5E 136.7E 135.0E 130.9E 129.9E 129.9E 129.2E 129.0E 129.2E 129.0E 128.4E 127.7E 126.9E 126.0E 123.8E 122.6E 121.3E 120.0E	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18 36 11 21 43	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106 85 51 N/A	48h 313 14 48 ER 509 450 449 414 N/A 363 290 285 362 346 403 311 39 76 83 N/A N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A N/A	BT WN 30 45 45 45 45 50 50 40 40 45 45 45 45 45 45 45 40 30	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 10 15 10 10 15 10 10 N/A N/A	48 ER 5 0 5 10 N/A N/A 5 5 10 40 5 10 5 N/A N/A	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073110 89073112* 89080100 89080112 89080112 89080112 89080112 89080212 89080212 89080212 89080218 89080300 89080306 89080312 89080318 89080400 89080406 89080412	W± 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.7N 28.5N 29.5N 30.0N 30.4N 30.7N 31.1N 31.3N 31.8N 32.0N	3W-14W) Average Cases ET LON 136.0E 137.3E 138.5E 136.7E 135.0E 130.9E 129.9E 129.9E 129.5E 129.2E 129.0E 128.4E 127.7E 126.9E 126.0E 123.8E 122.6E 121.3E 120.0E 119.0E	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18 36 11 21 43 5	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106 85 51 N/A N/A	48h 313 14 48 ER 509 450 449 414 N/A 363 290 285 362 346 403 311 39 76 83 N/A N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A N/A	BT WN 30 45 45 45 50 50 50 45 40 45 45 45 45 45 45 30 30	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 10 15 10 10 15 10 10 N/A N/A N/A	48 ER 5 0 5 10 N/A N/A 5 5 10 40 5 10 5 N/A N/A N/A	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073110 89073112* 89080106 89080112 89080112 89080118 89080206 89080212 89080218 89080212 89080218 89080306 89080312 89080318 89080312 89080318 89080312 89080318 89080406 89080412	W± 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.7N 28.5N 29.5N 30.0N 30.4N 30.7N 31.1N 31.3N 31.8N 32.0N 32.1N	3W-14W) Average Cases ET LON 136.0E 137.3E 138.5E 136.7E 135.0E 130.9E 129.9E 129.5E 129.3E 129.0E 128.4E 127.7E 126.9E 126.0E 123.8E 122.6E 121.3E 120.0E 119.0E 118.0E	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18 36 11 21 43 5	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106 85 51 N/A N/A N/A	48h 313 14 48 ER 509 450 449 414 N/A 363 290 285 362 346 403 311 39 76 83 N/A N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A N/A N/A	BT WN 30 45 45 45 45 50 50 40 45 45 45 45 45 45 45 45 45 45 45 45 45	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 10 15 10 10 15 10 10 N/A N/A	48 ER 5 0 5 10 N/A N/A 5 5 10 40 5 10 5 N/A N/A	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A N/A N/A
DTG 89073000 89073006 89073012 89073018 89073110 89073112* 89080106 89080112 89080112 89080118 89080206 89080212 89080218 89080212 89080218 89080306 89080312 89080318 89080312 89080318 89080312 89080318 89080406 89080412	W± 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23	BT LAT 24.3N 25.1N 26.5N 27.7N 28.5N 29.1N 28.2N 27.5N 27.0N 26.8N 27.0N 26.8N 27.7N 28.5N 29.5N 30.0N 30.4N 30.7N 31.1N 31.3N 31.8N 32.0N	3W-14W) Average Cases ET LON 136.0E 137.3E 138.5E 136.7E 135.0E 130.9E 129.9E 129.5E 129.3E 129.0E 128.4E 127.7E 126.9E 126.0E 123.8E 122.6E 121.3E 120.0E 119.0E 118.0E	00h 38 23 POS ER 20 43 31 141 246 59 16 10 26 43 32 0 18 7 37 12 18 36 11 21 43 5	24h 193 18 24 ER 221 199 397 409 N/A 425 187 173 151 221 242 259 171 30 92 51 106 85 51 N/A N/A N/A	48h 313 14 48 ER 509 450 449 414 N/A 363 290 285 362 346 403 311 39 76 83 N/A N/A N/A	72h 382 10 72 ER 519 546 306 241 N/A N/A 335 378 386 345 438 324 N/A N/A N/A N/A N/A	BT WN 30 45 45 45 45 50 50 40 45 45 45 45 45 45 45 45 45 45 45 45 45	WW ER 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	24 ER -5 5 5 5 N/A 10 15 10 10 10 15 10 10 15 10 10 N/A N/A N/A	48 ER 5 0 5 10 N/A N/A 5 5 10 40 5 10 5 N/A N/A N/A	72 ER 10 -10 -10 -10 N/A N/A N/A -10 5 0 5 15 30 N/A N/A N/A N/A N/A N/A

Typhoon Mac	: (15W)		Average # Cases	00h 17 28	24h 167 26	48h 335 23	72h 520 19					
DTG	Wŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW_ER	24 ER	48 ER	72 ER
89080100	1	21.2N	151.0E	36	120	230	279	30	5	15	15	10
89080106	2	21.8N	151.0E	21	73	221	299	30	10	15	5	10
89080112	3	22.5N	150.9E	12	141	244	426	35	5	15	0	10
89080118	4	23.2N	150.7E	12	137	352	551	40	5	15	-5	10
89080200	5	24.ON	150.2E	13	112	320	447	45	0	5	0	10
89080206	6	25.0N	149.8E	0	153	274	150	45	0	-5	0	10
89080212	7	26.1N	149.2E	16	227	325	283	45	5	-10	0	10
89080218	8	26.8N	148.2E	26	235	411	555	50	-5	-15	0	15
89080300	9	27.0N	147.1E	12	142	276	438	60	-5	0	10	25
89080306	10	26.9N	146.1E	6	119	264	465	70	5	20	15	30
89080312	11	26.7N	145.4E	0	110	347	622	75	0	10	15	50
89080318	12	26.5N	145.0E	10	139	435 520	725 792	80 75	-5 0	5	15	60
89080400	13	26.3N	144.6E	24 16	167 232	560	803	75 75	0	5 0	25 30	60 50
89080406 89080412	14 15	26.3N 26.6N	144.3E 144.1E	24	292	622	839	75 75	0	0	40	50 50
89080412	16	27.1N	144.1E	13	229	490	624	75 75	0	5	45	50
89080500	17	27.1N 27.9N	143.9E	28	290	544	686	75	ő	10	40	45
89080506	18	29.2N	143.7E	15	272	475	660	75	Ö	20	40	20
89080512	19	30.8N	143.2E	16	122	251	226	75	-5	20	20	15
89080518	20	32.6N	142.6E	19	46	212	N/A	70	5	30	5	N/A
89080600	21	34.2N	141.8E	19	34	169	N/A	65	5	10	10	N/A
89080606	22	35.8N	140.9E	12	98	35	N/A	50	15	5	5	N/A
89080612	23	37.4N	140.0E	11	136	125	N/A	40	5	5	5	N/A
89080618	24	39.1N	139.3E	24	274	N/A	N/A	30	5	5	N/A	N/A
89080700	25	40.4N	138.6E	36	230	N/A	N/A	30	10	5	N/A	N/A
89080706	26	41.2N	137.7E	21	224	N/A	N/A	30	5	-5	N/A	N/A
89080712	27	42.7N	136.6E	27	N/A	N/A	N/A	30	0	N/A	N/A	N/A
89080718	28	43.6N	137.0E	11	N/A	N/A	N/A	25	0	N/A	N/A	N/A
Typhoon Owe	n (16W)	•	Average	<u>00h</u> 21	24h 115	48h 239	<u>72h</u> 380					
			# Cases	28	27	23	19					
<u>DTG</u> 89081100†	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72_ER	BT WN	WW ER -5	24 ER	48 ER N/A	72 ER
89081100† 89081106†	1 2	17.8N 18.6N	143.4E 144.1E	119 39	317 48	N/A N/A	N/A N/A	30 30	-3 0	0 -5	N/A N/A	N/A N/A
89081112†	3	19.2N	144.8E	42	53	N/A	N/A	30	Ö	5	N/A	N/A
89081200	4	19.4N	147.1E	24	38	96	446	30	-5	-15	-30	-30
89081206	5	19.3N	147.6E	5	82	141	402	30	Ö	-5	-25	-30
89081212	6	19.2N	148.1E	18	74	163	463	35		-15	-30	-30
89081218	7	18.8N	148.5E	30	155	318	548	35	0	-20	-30	-25
89081300	8	18.6N	149.2E	24	156	381	554	45	0	-5	-5	5
89081306	9	18.3N	150.1E	13	210	418	592	45	0	-5	-5	5
89081312	10	18.9N	151.1E	37	253	432	553	55	0	0	5	20
89081318	11	19.7N	151.7E	8	161	279	390	60	0	-5	5	30
89081400	10	20.8N	152.3E	12	76	165	368	65	0	0	15	20
89081406	12					216	437	70	0	10	10	10
	13	22.2N	152.2E	8	95	216						_
89081412	13 14	22.2N 23.7N	152.2E 151.8E	13	95	230	292	75	0	10	10	5
89081412 89081418	13 14 15	22.2N 23.7N 25.2N	152.2E 151.8E 151.2E	13 12	95 140	230 236	292 220	75 75	0 5	10 15	10 20	15
89081412 89081418 89081500	13 14 15 16	22.2N 23.7N 25.2N 26.2N	152.2E 151.8E 151.2E 150.6E	13 12 8	95 140 87	230 236 177	292 220 96	75 75 75	0 5 0	10 15 5	10 20 15	15 15
89081412 89081418 89081500 89081506	13 14 15 16 17	22.2N 23.7N 25.2N 26.2N 27.2N	152.2E 151.8E 151.2E 150.6E 150.1E	13 12 8 12	95 140 87 102	230 236 177 162	292 220 96 93	75 75 75 75	0 5 0 0	10 15 5 0	10 20 15 5	15 15 15
89081412 89081418 89081500 89081506 89081512	13 14 15 16 17 18	22.2N 23.7N 25.2N 26.2N 27.2N 28.4N	152.2E 151.8E 151.2E 150.6E 150.1E 149.5E	13 12 8 12 7	95 140 87 102 138	230 236 177 162 168	292 220 96 93 145	75 75 75 75 75	0 5 0 0	10 15 5 0 -10	10 20 15 5 -10	15 15 15 -5
89081412 89081418 89081500 89081506 89081512 89081518	13 14 15 16 17 18 19	22.2N 23.7N 25.2N 26.2N 27.2N 28.4N 29.3N	152.2E 151.8E 151.2E 150.6E 150.1E 149.5E 148.7E	13 12 8 12 7 7	95 140 87 102 138 46	230 236 177 162 168 48	292 220 96 93 145 172	75 75 75 75 75 70	0 5 0 0 0	10 15 5 0 -10 -5	10 20 15 5 -10 -5	15 15 15 -5 -5
89081412 89081418 89081500 89081506 89081512 89081518 89081600	13 14 15 16 17 18 19 20	22.2N 23.7N 25.2N 26.2N 27.2N 28.4N 29.3N 30.4N	152.2E 151.8E 151.2E 150.6E 150.1E 149.5E 148.7E 148.0E	13 12 8 12 7 7	95 140 87 102 138 46 78	230 236 177 162 168 48 301	292 220 96 93 145 172 542	75 75 75 75 75 70 70	0 5 0 0 0 -5	10 15 5 0 -10 -5 0	10 20 15 5 -10 -5 5	15 15 15 -5 -5
89081412 89081418 89081500 89081506 89081512 89081518 89081600 89081606	13 14 15 16 17 18 19 20 21	22.2N 23.7N 25.2N 26.2N 27.2N 28.4N 29.3N 30.4N 31.5N	152.2E 151.8E 151.2E 150.6E 150.1E 149.5E 148.7E 148.0E 147.4E	13 12 8 12 7 7 24 28	95 140 87 102 138 46 78 31	230 236 177 162 168 48 301 259	292 220 96 93 145 172 542 501	75 75 75 75 75 70 70 65	0 5 0 0 0 -5	10 15 5 0 -10 -5 0	10 20 15 5 -10 -5 0	15 15 15 -5 -0 0
89081412 89081418 89081500 89081506 89081512 89081518 89081600 89081606 89081612	13 14 15 16 17 18 19 20 21	22.2N 23.7N 25.2N 26.2N 27.2N 28.4N 29.3N 30.4N 31.5N 32.4N	152.2E 151.8E 151.2E 150.6E 150.1E 149.5E 148.7E 148.0E	13 12 8 12 7 7 24 28 13	95 140 87 102 138 46 78	230 236 177 162 168 48 301	292 220 96 93 145 172 542	75 75 75 75 75 70 70	0 5 0 0 0 -5	10 15 5 0 -10 -5 0	10 20 15 5 -10 -5 5	15 15 15 -5 -5

						•						
	Owen (16W)											
DTG	₩ŧ	BT LAT	BT LON	POS ER	<u>24 ER</u>	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	<u>72 ER</u>
89081618	23	33.3N	146.4E	7	103	311	N/A	55	0	-5	-5	N/A
89081700	24	34.7N	145.7E	24	198	367	N/A	55	-5	0	0	N/A
89081706	25	35.9N	145.8E	15	124	155	N/A	55	0	5	5	N/A
89081712	26	37.0N	146.3E	9	69	235	N/A	55	0	0	5	N/A
89081718	27	38.7N	147.1E	11	111	N/A	N/A	45	0	0	N/A	N/A
89081800	28	40.2N	147.9E	10	N/A	N/A	N/A	40	0	N/A	N/A	N/A
Typhoon I	Nancy (17%	7)	_	<u>00h</u>	24h	48h	72h					
			Average	19	146	348	510					
			# Cases	22	20	19	16					
DTG	₩#	וויים דאות	DOT TOM	DOC ED	0.4 ED	40 ED	70 PD	DO LDI	tal DD	04.55	40.55	70
89081106		BT LAT 20.9N	BT LON 155.1E	POS ER 50	24 ER 139	48 ER 163	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89081112	1 2	20.9N 20.6N	155.1E 156.0E				414	25	0	0	-20	-15
	3			36	108	189	503	25	0	-10	-30	-25
89081118	3 4	20.3N	156.8E	16	104	354	672	30	0	-15	-35	-25
89081200		20.5N	157.6E	12	69	285	572	30	0	-20	-35	-20
89081206	5	21.1N	157.9E	23	42	342	624	35	-5	-25	-25	-15
89081212	6	21.7N	157.9E	8	155	477	708	45	-5	-20	-15	5
89081218	7	22.5N	157.8E	36	260	559	771	50	-5	-20	-10	5
89081300	8	23.4N	157.5E	20	240	515	713	55	0	-10	0	25
89081306	9	24.6N	157.0E	12	148	299	520	65	0	0	15	40
89081312	10	26.1N	156.4E	18	164	307	504	70	0	5	20	50
89081318	11	27.6N	155.2E	20	122	360	553	75	0	10	25	55
89081400	12	29.2N	154.0E	10	85	318	453	75	0	5	10	20
89081406	13	30.5N	151.7E	10	153	400	350	75	0	0	10	20
89081412	14	31.7N	149.9E	7	187	326	354	75	-5	-15	5	5
89081418	15	32.9N	148.4E	19	125	167	195	75	-10	-15	5	5
89081500	16	34.2N	147.0E	19	172	239	259	70	0	-5	10	10
89081506	17	35.7N	146.2E	6	128	174	N/A	65	0	5	15	N/A
89081512	18	37.3N	145.7E	7	148	515	N/A	65	0	15	20	N/A
89081518	19	38.9N	145.2E	9	142	628	N/A	65	-5	10	10	N/A
89081600	20	40.3N	145.2E	21	232	N/A	N/A	55	0	5	N/A	N/A
89081606	21	41.5N	145.4E	52	N/A	N/A	N/A	45	5	N/A	N/A	N/A
89081612	22	42.5N	145.6E	0	N/A	N/A	N/A	35	0	N/A	N/A	N/A
Tropical	Storm Peg	or /196/\		00h	24h	48h	.72h					
TOPAGE		AT (TOW)	Average	24	240 143	335 480	<u> 120</u> 506					
			# Cases	9	143	333	2					
			, cases	,	Ü	U	2					
DTG	W#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24_ER	48 ER	72 ER
89081600	<u> </u>	19.3N	148.8E	12	132	353	583	25	0	0	10	40
89081606	2	20.4N	148.8E	6	44	244	428	30	ō	5	20	50
89081612	3	21.5N	148.7E	12	92	287	N/A	35	ő	10	30	N/A
89081618	4	22.4N	148.4E	17	150	361	N/A	35	ő	10	35	N/A
89081700	5	23.0N	148.1E	11	226	400	N/A	35	Ö	5	30	N/A
89081706	6	23.3N	147.6E	16	161	364	N/A	35	0	5	30	N/A
89081712	7	23.6N	147.1E	42	174	N/A	N/A	35	0	10	N/A	N/A
89081718	8	23.7N	146.2E	56	162	N/A	N/A	35	0	15	N/A	N/A
89081800	ğ	23.7N	145.3E	44	N/A	N/A	N/A	35	0	N/A	N/A	N/A N/A
22222000	-		1-1-1-U	77	11/15	H/A	M/A	33	J	M/A	H/D	M/M

Tropical D	epressi	on 19W		<u>00h</u>	24h	<u>48h</u>	<u>72h</u>					
			Average	19	95	N/A	N/A					
			# Cases	6	4	0	0					
DTG	Wž	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	tata tero	24 ER	40 50	72 ER
89081700†	1	29.3N	124.2E	27	105	N/A	12 ER N/A	25	WW ER	0	48 ER N/A	N/A
89081712†	2	29.3N 28.1N	123.7E	40	160	N/A	N/A	25	5	0	N/A	N/A
89081800†	3	27.3N	123.7E	17	68	N/A	N/A	30	0	Ö	N/A	N/A
89081812†	4	27.3N 27.2N	123.2E	12	47	N/A	N/A	30	0	5	N/A	N/A
89081900†	5	27.2N	121.8E	12	N/A	N/A	N/A	30	0	N/A	N/A	N/A
89081912†	6	26.8N	121.6E	5	N/A	N/A	N/A	25	0	N/A	N/A	N/A
· ·		Depresio		_	N/A	N/A	N/A	25	U	N/A	N/A	N/A
1 4	ropredi	. Deptesio	warning									
Tropical S	tozm Ro	ger (20W)		<u>00h</u>	24h	<u>48h</u>	<u>72h</u>					
			Average	32	223	473	949					
			# Cases	14	12	7	3					
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89082412†	1	25.3N	124.0E	94	266	N/A	N/A	30	-5	~5	N/A	N/A
89082500	2	25.1N	124.7E	24	172	422	823	35	-5	0	-5	15
89082506	3	24.8N	125.6E	26	254	543	937	35	-5	0	5	15
89082512	4	24.5N	126.8E	28	345	708	1087	35	-5	0	5	15
89082518	5	24.4N	128.0E	33	412	816	N/A	35	-5	-15	0	N/A
89082600	6	26.1N	130.0E	17	- 165	406	N/A	40	-10	-20	-15	N/A
89082606	7	28.2N	131.2E	60	236	107	N/A	40	5	-10	-15	N/A
89082612	8	30.2N	131.9E	23	213	312	N/A	40	5	-10	-15	N/A
89082618	9	31.7N	133.0E	31	211	N/A	N/A	45	0	-10	N/A	N/A
89082700	10	33.3N	134.1E	12	208	N/A	N/A	50	0	0	N/A	N/A
89082706	11	35.2N	135.7E	18	105	N/A	N/A	40	5	0	N/A	N/A
89082712	12	37.0N	137.3E	33	92	N/A	N/A	40	5	-5	N/A	N/A
89082718	13	39.2N	139.3E	54	N/A	N/A	N/A	40	0	N/A	N/A	N/A
89082800	14	41.6N	140.9E	0	N/A	N/A	N/A	40	Ō	N/A	N/A	N/A
† T :	ropical	Depressi		a	,	-	•			·	•	•
	-	-		•								
Tropical D	onressi	on 21W		00h	24h	48h	<i>7</i> 2h					
Trop-our D	-b		Average	23	135	N/A	N/A					
			# Cases	7	6	0	0					
			# Cases	•	Ū	Ū	·					
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89082506†	1	28.5N	151.6E	47	109	N/A	N/A	25	5	0	N/A	N/A
89082518†	2	30.1N	153.9E	13	143	N/A	N/A	30	Ö	5	N/A	N/A
89082606†	3	31.4N	155.7E	15	62	N/A	N/A	30	Ö	ő	N/A	N/A
89082618†	4	31.4N	158.8E	33	81	N/A	N/A	30	Ö	ŏ	N/A	N/A
89082706†	5	32.0N	161.0E	28	111	N/A	N/A	30	Ö	5	N/A	N/A
89082718†	6	32.2N	161.7E	11	303	N/A	N/A	30	0	-5	N/A	N/A
89082806†	7	32.7N	161.7E	16	N/A	N/A	N/A	25	0	N/A	N/A	N/A
		Depressi			N/A	N/A	M/A	2.5	·	147.21	11,71	21/22
, 1.	ropical	Debiessi	OII WAIIIII	y								
						4.01	=4,					
Typhoon Sa	ran (22	:W}	_	<u>00h</u>	24h	48h	<u>72h</u>					
			Average	28	165	302	450					
			# Cases	33	29	25	21					
	_											:
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89090600	1	20.9N	140.8E	16	180	313	790	30	-5	-5	-10	-5
89090606	2	20.6N	139.2E	11	108	164	355	30	0	-10	-10	-10
89090612	3	20.2N	137.8E	16	24	217	284	30	0	-15	-15	-5
89090618	4	20.0N	136.6E	13	76	145	24	35	0	-10	-10	5
89090700	5	20.0N	135.6E	6	172	186	12	40	-5	-5	-5	10

Page	Typhoon S	arah (22W) (conti	nued)									
89090706 6 20.1N 134.6E 24 220 136 145 45 0 5 10 30 89090712 7 20.5N 133.2E 16 231 220 124 50 -5 5 15 20 89090718 8 21.1N 131.4E 47 234 303 484 55 0 10 -5 -5 58 89090806 9 21.4N 129.1E 44 256 310 474 55 0 10 -5 -5 58 89090806 10 20.8N 126.9E 42 301 497 688 55 0 5 25 -35 89090806 11 19.7N 125.3E 34 321 586 726 60 -5 10 15 -75 89090818 12 11 19.7N 125.3E 34 321 586 726 60 -5 10 15 -75 89090818 12 18.5N 124.6E 61 90 354 507 65 0 20 5 -5 -5 10 89090900 13 17.9N 124.3E 6 162 387 511 65 0 5 5 -55 -10 89090906 14 17.7N 123.9E 36 238 430 574 65 0 0 -60 5 8909091 15 17.7N 123.9E 36 238 430 574 65 0 0 -60 5 8909091 15 17.7N 123.8E 17 91 83 366 542 55 10 -45 -5 40 89091006 17 19.1N 123.8E 17 91 83 366 542 55 10 -45 -5 40 89091006 18 19.9N 123.8E 18 66 148 406 55 10 -45 -5 40 8909101 19 20.6N 123.2E 13 97 240 467 65 0 -40 30 60 89091018 20 21.1N 123.2E 6 18 66 148 406 55 10 -45 15 45 8909101 2 21.8N 123.2E 6 13 97 240 467 65 0 -5 45 65 89091108 20 21.1N 123.2E 6 13 97 240 467 65 0 -5 5 5 5 95 89091108 20 21.1N 123.2E 6 13 97 240 467 65 0 -40 30 60 89091108 20 21.1N 123.2E 6 13 97 240 467 65 0 -40 55 95 80091106 22 22.2R 81 122.7E 12 167 384 N/A 120 0 55 70 N/A 89091118 24 23.0N 121.2E 45 71 22 22 4483 75 0 -5 45 65 89091106 22 22.2N 12.2E 12 22.5E 13 97 240 467 65 0 -40 55 95 80091106 22 22.2N 12.2E 12 22.5E 13 97 N/A 90 0 45 50 N/A 89091218 28 25.1N 120.9E 39 138 148 30 0 10 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	DTG	W#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89090712	89090706	6	20.1N										
89090718 8 21.1N 131.4E 47 234 303 484 55 0 10 -5 -5 -40 89090806 9 21.4N 129.1E 44 265 310 474 55 0 10 -5 -5 890 89090806 10 20.8N 126.9E 42 301 497 688 55 0 5 5 25 -35 89090812 11 19.7N 125.3E 34 3021 586 726 60 -5 10 15 -5 -890 89090818 12 18.5N 124.6E 61 90 354 507 65 0 20 5 -10 89090906 14 17.7N 123.9E 36 6238 430 574 65 0 0 -6 0 5 -55 -10 89090906 14 17.7N 123.9E 36 238 430 574 65 0 0 -6 0 5 -5 5 -10 89090906 14 17.7N 123.9E 36 238 430 574 65 0 0 -6 0 5 5 890 8909010 17 19.1N 123.8E 37 253 419 517 60 5 -20 -65 1 5 890 8909100 17 19.1N 123.8E 17 91 83 360 55 10 -30 -30 25 25 890 8909100 17 19.1N 123.8E 17 91 83 360 55 10 -45 -5 4 8 8 8 8 8 8 148 4 406 55 10 -45 -5 4 6 8 8 8 8 8 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 148 8 8 8	89090712	7	20.5N	133.2E	16	231	220	124		-5	5		
89090800 9 21.4N 129.1E 44 265 310 474 55 0 10 5-5-55 890908012 11 19.7N 125.3E 34 301 497 688 55 0 5 0 10 5-5-55 89090812 11 19.7N 125.3E 34 321 586 726 60 5-5 10 15 5-75 89090813 12 18.5N 124.6E 61 90 354 507 65 0 20 5 5-10 89090900 13 17.9N 124.3E 6 162 387 511 65 0 5 5-55 10 89090900 13 17.9N 124.3E 6 162 387 511 65 0 5 5-55 10 89090900 14 17.7N 123.9E 36 238 430 574 65 0 0 5 5-55 10 890909012 15 17.9N 123.6E 39 253 419 517 60 5 0 -20 -65 10 89090900 14 17.7N 123.8E 18 68 164 552 55 10 5-30 -90 25 89091000 17 19.1N 123.8E 17 91 83 360 551 10 -45 1-5 40 89091000 17 19.1N 123.8E 18 68 148 406 55 10 -45 1-5 40 89091010 12 19 20.6N 123.6E 13 97 240 467 65 10 -45 1-5 40 8909110 21 19 20.6N 123.6E 13 97 240 467 65 10 -45 1-5 40 8909110 22 11. 123.2E 6 78 224 423 75 0 -5 4 35 66 8909110 22 12.1N 123.2E 6 78 224 423 75 0 -5 4 35 66 8909110 22 12.1N 123.2E 12 167 384 N/A 120 0 55 70 N/A 89091112 23 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091118 24 23.0N 121.2E 45 71 292 N/A 90 0 45 50 N/A 89091218 24 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091228 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 65 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 25 10 N/A N/A 89091310 33 26.7N 120.9E 39 137 N/A N/A 25 5 N/A N/A N/A 89091310 33 22.7N 120.9E 39 137 N/A N/A N/A 25 5 N/A N/A N/A 89091310 33 24.5N 120.9E 39 137 N/A N/A N/A 25 5 N/A N/A N/A 89091310 33 24.5N 120.9E 39 137 N/A N/A N/A 25 5 N/A N/A N/A 89091310 8 29 25.1N 120.9E 39 137 N/A N/A N/A 25 5 N/A N/A N/A 89091310 8 29 25.1N 120.9E 39 37 298 226 375 30 0 N/A N/A N/A N/A 89091310 8 29 25.1N 120.0E 78 24 28 8 ER 72 ER 8 N/A N/A N/A 89091310 8 29 25.1N 120.9E 37 298 226 375 30 0 N/A N/A N/A N/A 89091310 8 29 25.1N 150.0E 78 24 174 N/A N/A N/A N/A N/A 8909100 5 28.2N 150.0E 78 24 174 N/A	89090718	8	21.1N	131.4E	47	234	303	484	55	0	10	-5	-40
89090806 10	89090800	9	21.4N	129.1E	44	265	310	474		0		-5	-55
89990812 11 19.7N 125.3E 34 321 556 726 60 -5 10 15 -75 899909081 12 18.5N 124.6E 61 90 354 507 65 0 20 5 -10 89990900 13 17.9N 124.3E 66 162 387 511 65 0 5 -55 -10 89990906 14 17.7N 123.9E 36 238 430 574 65 0 0 -65 -55 89909090 14 17.7N 123.6E 39 253 419 517 60 5 -20 -65 10 89909090 15 15 17.9N 123.6E 78 39 253 419 517 60 5 -20 -65 10 89909090 16 18 19.9N 123.8E 18 68 148 406 555 10 -45 -5 40 89909100 17 19.1N 123.6E 17 91 83 360 55 10 -45 -5 40 89909100 17 19.1N 123.8E 18 68 148 406 55 10 -45 15 45 89901102 19 20.6N 123.6E 13 97 240 467 65 0 0 -45 15 40 89901102 19 20.6N 123.6E 13 97 240 467 65 0 0 -45 15 40 89901100 21 21.8N 123.8E 18 68 148 406 55 10 -45 15 40 89901100 22 21.8N 123.1E 0 191 422 640 115 0 -5 45 65 89901110 22 22.8N 122.7E 12 167 384 N/A 125 0 60 75 N/A 89901112 23 23.3N 122.0E 12 255 443 N/A 125 0 60 75 N/A 89901112 23 23.0N 121.2E 12 255 443 N/A 125 0 60 75 N/A 89001128 24 23.0N 121.6E 13 146 269 N/A 80 0 45 55 N/A N/A 8900122 7 24.5N 121.3E 20 18 190 N/A N/A 65 0 25 N/A N/A 8900122 7 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 8900122 7 24.5N 121.3E 20 154 N/A N/A N/A 65 0 25 N/A N/A 8900122 8 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A N/A 8909130 29 25.7N 120.3E 32 27 N/A N/A N/A 0 5 10 N/A N/A N/A 8909130 29 25.7N 120.3E 32 27 N/A N/A N/A 0 5 10 N/A N/A N/A 8909130 3 26.5N 129.6E 41 N/A		10	20.8N	126.9E	42	301	497	688	55	0	5		
890990818 12 18.5N 124.6E 61 90 354 507 65 0 20 5 -10 890990906 13 17.9N 124.3E 6 6162 387 511 65 0 5 -55 -10 89090906 14 17.7N 123.9E 36 238 430 574 65 0 0 -60 5 -55 8909012 15 17.9N 123.9E 36 238 430 574 65 0 0 -60 5 5 8909018 16 18.4N 123.6E 39 253 419 517 60 5 -20 -65 10 89090018 16 18.4N 123.6E 78 281 386 542 55 10 -30 -30 25 89091000 17 19.1N 123.8E 17 91 83 380 55 10 -45 -5 40 89091006 18 19.9N 123.8E 18 68 148 406 55 10 -45 15 45 89091012 19 20.6N 123.6E 13 97 240 467 65 0 -40 30 60 8909102 19 20.6N 123.6E 13 97 240 467 65 0 -40 30 60 8909100 21 21.8N 123.1E 0 191 422 640 115 0 50 85 99 8909100 21 21.8N 123.1E 0 191 422 640 115 0 50 85 99 89091100 21 21.8N 123.1E 0 191 422 640 115 0 50 85 99 89091112 23 23.3N 122.0E 12 225 443 N/A 120 0 55 70 N/A 89091112 23 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 66 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 870 30 10 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 870 30 10 0 55 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 870 30 0 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 870 30 0 N/A N/A 89091313 31 27.1N 119.6E 41 N/A N/A N/A 40 5 10 N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A 40 5 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A 30 0 N/A N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A N/A 25 5 N/A N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091300 5 28.2N 153.9E 71 369 318 385 25 0 10 20 30 20 5 20 20 5 20 20 20 20 20 30 20 20 20 30 20 20 20 30 20 20 5 20 20 20 30 20 20 5 20 20 30 20 20 5 20 20 30 20 20 5 20 20 30 20 20 5 20 30 30 20 10 20 30 30 60 10 20 30 00 10 20 20 30 30 60 10 20 30 30 60 10 20 30 00 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 20 20 30 30 10 10 2	89090812	11	19.7N			321	586	726		-5			
89099000 13 17.9N 124.3E 6 162 387 511 65 0 5 5 -55 -10 890909012 15 17.7N 123.6E 39 238 430 574 65 0 0 -60 5 890909012 15 17.9N 123.6E 39 253 419 517 60 5 -20 -65 10 89090100 17 19.1N 123.6E 17 91 83 360 55 10 -45 -5 40 8909100 17 19.1N 123.8E 17 91 83 360 55 10 -45 -5 40 8909100 18 19.9N 123.6E 13 97 240 467 65 0 -40 30 60 8909101 20 12 12.1N 123.2E 6 78 224 483 75 0 -5 45 65 8909101 21 21.8N 123.1E 0 191 422 640 115 0 50 85 95 8909110 21 21.8N 123.1E 0 191 422 640 115 0 50 85 95 8909110 22 22.8N 122.7E 12 167 384 N/A 120 0 55 70 N/A 89091118 24 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091118 24 23.0N 121.2E 45 71 292 N/A 90 0 45 50 N/A 8909120 25 23.0N 121.6E 13 146 269 N/A 80 0 0 40 55 N/A 8909120 26 24.1N 122.0E 18 190 N/A N/A 65 0 25 N/A N/A 89091210 28 25.7N 120.9E 39 137 N/A N/A 65 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A 40 0 0 N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A 40 0 0 N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A 40 0 0 N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A 40 0 0 N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A 40 0 0 N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A 40 0 0 N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A 40 0 0 N/A N/A N/A 8909130 30 29 25.7N 120.9E 39 137 N/A N/A N/A 25 0 N/A N/A N/A 8909130 30 28.7N 150.6E 13 N/A N/A N/A N/A 25 0 N/A N/A N/A 8909130 30 28.7N 150.6E 0 18 N/A N/A N/A 30 0 N/A N/A N/A 8909130 30 28.7N 150.6E 0 18 N/A N/A N/A N/A 25 0 0 N/A N/A N/A 8909130 30 28.7N 150.6E 0 133 55 0 0 0 N/A N/A N/A 8909130 5 28.2N 155.0E 0 78 183 418 30 0 10 20 20 30 890900 6 2 22.1N 154.9E 37 288 226 375 30 0 N/A N/A N/A 8909100 7 29.3N 153.9E 77 369 318 385 25 0 10 0 0 N/A N/A 8909100 7 29.3N 153.9E 77 369 318 385 55 0 0 0 0 N/A N/A N/A 8909100 7 29.3N 150.0E 20 213 477 800 35 0 20 30 20	89090818	12	18.5N	124.6E	61		354		65		20		
89090906 14 17.7N 123.9E 36 238 430 574 65 0 0 0 -60 5 10 89090912 15 17.9N 123.6E 39 253 419 517 60 5 -20 -65 10 89090918 16 18.4N 123.6E 78 281 386 542 55 10 -30 -30 25 40 8909100 17 19.1N 123.8E 17 91 83 360 55 10 -45 -5 40 8909100 17 19.1N 123.8E 17 91 83 360 55 10 -45 -5 40 8909100 18 19.9N 123.8E 18 68 148 406 55 10 -45 15 45 8909101 19 20.6N 123.6E 13 97 240 467 65 0 -40 30 60 89091018 20 21.1N 123.2E 6 78 224 483 75 0 -5 45 65 89091100 21 21.8N 123.1E 0 191 422 640 115 0 55 70 N/A 89091110 21 21.8N 123.1E 10 191 422 640 115 0 55 70 N/A 89091112 23 23.3N 122.0E 12 225 443 N/A 120 0 55 70 N/A 89091112 23 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091112 23 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 66 0 25 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A 40 60 0 25 N/A N/A 89091301 31 27.1N 119.6E 41 N/A N/A N/A 40 50 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 25 5 0 10 20 30 N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 25 5 0 10 20 30 N/A N/A 89091300 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 25 5 0 10 20 30 N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 25 5 0 10 20 30 N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091300 30 26.3N 119.6E 50 N/A N/A N/A N/A 35 5 0 10 20 30 0 N/A N/A 89091300 5 26.2N N 151.0E 32 26 26 375 30 0 N/A N/A N/A 89091300 5 26.2N N 151.0E 32 26 30 30 0 10 20 20 20 5 20 20 20 20 20 20 20 20 20 20 20 20 20	89090900	13	17.9N	124.3E	6	162	387	511	65	0	5	-55	
99090912 15 17.9N 123.6E 39 253 419 517 60 5 -20 -65 10 89090918 16 18.4N 123.6E 78 281 386 542 55 10 -30 -30 25 89090100 17 19.1N 123.8E 17 91 83 360 55 10 -45 -5 40 89091000 17 19.1N 123.8E 18 68 148 406 55 10 -45 -5 45 89091012 19 20.6N 123.6E 13 97 240 467 65 0 -40 30 60 89091012 19 20.6N 123.6E 13 97 240 467 65 0 -40 30 60 89091012 19 20.6N 123.6E 13 97 240 467 65 0 -5 45 55 89091100 21 21.8N 123.1E 0 191 422 640 115 0 50 85 95 89091100 21 21.8N 123.1E 0 191 422 640 115 0 50 85 95 89091106 22 22.8N 122.7E 12 167 384 N/A 120 0 55 70 N/A 89091118 24 23.3N 122.0E 12 225 M/A 94 125 0 60 75 N/A 89091118 24 23.3N 121.2E 45 71 292 N/A 90 0 45 50 N/A 89091118 24 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091206 26 24.1N 122.0E 18 190 N/A N/A N/A 60 0 25 N/A N/A 89091218 28 25.1N 120.9E 18 190 N/A N/A N/A 60 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A N/A 60 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A N/A 60 0 25 N/A N/A 89091306 30 26.3N 119.8E 48 N/A N/A N/A N/A 40 5 10 30 N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091312 31 27.1N 119.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091306 30 26.3N 119.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091306 30 26.3N 119.8E 48 N/A N/A N/A N/A N/A 25 5 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A N/A 25 5 N/A N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A N/A 25 5 N/A N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A N/A 25 5 N/A N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 25 5 N/A N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 125 5 N/A N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A N/A 89091312 31 27.9N 119.8E 48 N/A N/A N/A N/A 35 00 N/A N/A N/A N/A 89091312 31 27.9N 119.8E 48 N/A N/A N/A N/A 35 00 N/A N/A N/A N/A 89091312 31 27.9N 119.8E 48 N/A N/A N/A N/A 35 00 N/A N/A N/A N/A 89091312 31 27.9N 119.8E 48 N/A N/A N/A N/A 35 00 N/A N/A N/A N/A 8909100 6 2 22.1N 150.0E 27 28 00 00 00 N/A N/A N/A N/	89090906	14	17.7N	123.9E	36					0	0		
89090918 16 18.4M 123.6E 78 281 386 542 55 10 -30 -30 -30 25 89091000 17 19.1N 123.8E 17 91 83 386 551 10 -45 -5 40 89091006 18 19.9M 123.8E 18 68 148 406 55 10 -45 15 45 89091012 19 20.6M 123.6E 13 97 240 467 65 0 -40 30 60 89091018 20 21.1N 123.2E 6 78 224 463 75 0 -5 45 65 89091100 21 21.8M 123.1E 0 191 422 640 115 0 55 70 N/A 89091110 21 21.8M 123.1E 0 191 422 640 115 0 55 70 N/A 89091112 23 23.3M 122.0E 12 225 443 N/A 120 0 55 70 N/A 89091112 23 23.3M 122.0E 12 225 443 N/A 120 0 55 70 N/A 89091112 23 23.0M 121.2E 45 71 292 N/A 90 0 45 55 N/A 89091200 25 23.0M 121.6E 13 146 269 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5M 121.3E 20 154 N/A N/A 65 0 0 25 N/A N/A 89091212 27 24.5M 121.3E 20 154 N/A N/A 65 0 0 25 N/A N/A 89091212 27 24.5M 121.3E 20 154 N/A N/A 65 10 30 N/A N/A 89091300 29 25.7M 120.9E 39 137 N/A N/A 40 5 10 30 N/A N/A 89091300 30 26.3M 119.6E 41 N/A N/A N/A 40 5 10 30 N/A N/A 89091318 32 27.9M 119.6E 41 N/A N/A N/A 30 0 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A 35 10 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A 35 0 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A 35 0 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A N/A 35 0 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A N/A 35 0 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A N/A 35 0 N/A N/A N/A 89091318 32 27.9M 119.6E 48 N/A N/A N/A N/A 35 0 0 N/A N/A N/A 89091006 6 28.9M 151.0E 37 298 226 375 30 0 0 N/A N/A N/A N/A 89091007 1 20.3M 153.9E 71 369 318 365 25 0 10 20 30 20 8909000 1 20.3M 153.9E 71 369 318 365 25 0 10 20 30 20 89091006 6 28.9M 151.0E 32 281 335 582 35 0 20 2 55 20 89091007 1 20.3M 153.9E 71 268 648 N/A N/A N/A 55 0 -5 N/A N/A 89091112 11 33.0M 151.1E 7 268 648 N/A N/A N/A 55 0 -15 N/A N/A 89091110 9 30.4M 150.4E 6 24 N/A N/A N/A 35 5 0 -10 N/A N/A 89091110 11 33.0M 151.1E 7 268 648 N/A N/A 35 5 0 -10 N/A N/A 8909110	89090912	15	17.9N	123.6E	39	253	419			5	-20		
89091000 17 19.1N 123.8E 17 91 83 360 55 10 -45 -5 40 89091012 19 20.6N 123.8E 18 68 148 406 55 10 -45 15 45 89091012 19 20.6N 123.6E 13 97 240 467 65 0 -40 30 60 89091012 12 11.8N 123.2E 6 78 224 463 75 0 -5 45 55 85 89091100 21 21.8N 123.1E 0 191 422 640 115 0 50 85 95 89091106 22 22.8N 122.7E 12 167 384 N/A 125 0 60 75 N/A 89091118 24 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091118 24 23.0N 121.2E 45 71 292 N/A 90 0 45 50 N/A 89091118 24 23.0N 121.2E 45 71 292 N/A 90 0 45 50 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 66 0 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 8091330 29 25.7N 120.3E 32 27 N/A N/A N/A 45 10 30 N/A N/A 89091312 31 27.1N 120.9E 39 137 N/A N/A N/A 45 10 30 N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 20 0 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 20 0 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 20 0 N/A N/A N/A 89091312 31 27.1N 14.6E 41 N/A N/A N/A N/A 20 0 N/A N/A N/A 89091312 31 27.1N 14.6E 41 N/A N/A N/A N/A 20 0 N/A N/A N/A 89091312 31 27.1N 14.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 14.6E 41 N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89091312 31 27.1N 14.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A N/A 89091312 31 27.1N 154.9E 37 288 26 375 30 0 N/A N/A N/A N/A N/A 89091312 31 27.3N 153.9E 71 369 318 385 25 0 10 20 20 30 20 89090906 1 20.3N 153.9E 71 369 318 385 55 0 5 0 10 20 20 30 800909012 3 24.5N 155.0E 0 78 183 418 30 0 0 10 20 20 20 89090906 1 20.3N 153.9E 71 268 648 N/A N/A N/A 35 50 0 50 50 0 20 25 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 20 25 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 0 20 25 5 0 0 10 89091018 8 29.8N 151.0E 32 281 335 582 35 0 0 20 25 5 0 0 10 89091018 8 29.8N 151.0E 32 281 335 582 35 0 0 20 25 5 0 0 10 89091010 9 30.4N 150.4E 6 24 N/A N/A N/A 35 5 0 0 5 0 0 10 89091010	89090918	16	18.4N	123.6E	78	281	386	542	55				
89091006 18 19.9N 123.6E 18 68 148 406 55 100 -45 15 45 89091012 19 20.6N 123.6E 13 97 240 467 65 0 -40 30 66 89091108 20 21.1N 123.2E 6 78 224 483 75 0 -5 45 65 89091100 21 21.8N 123.1E 0 191 422 640 115 0 50 85 95 89091106 22 22.8N 122.7E 12 167 384 N/A 120 0 55 70 N/A 89091112 23 23.3N 122.0E 12 225 443 N/A 125 0 66 75 N/A 89091112 23 23.0N 121.2E 45 71 292 N/A 90 0 45 55 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 60 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 60 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 60 0 25 N/A N/A 89091300 29 25.7N 120.9E 39 137 N/A N/A 60 0 25 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A 60 0 25 N/A N/A 89091306 30 26.3N 119.8E 56 N/A N/A N/A N/A 60 0 0 15 10 N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 35 10 N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A 35 10 N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A 25 5 N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9N 159.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9N 159.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9N 159.8E 48 N/A N/A N/A N/A 89091306 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A 8909000 1 20.3N 153.9E 71 369 318 385 25 0 10 20 30 89090006 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A 89090100 5 28.2N 152.3E 0 0 07 315 490 35 0 20 35 20 89090100 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091007 1 23.6N 150.0E 20 213 477 800 35 0 5 0 10 20 20 20 89091008 8 22.8N 150.0E 20 213 477 800 35 0 5 0 10 20 20 20 89091009 1 3 35.0N 151.1E 7 268 648 N/A 35 5 0 10 -0 N/A N/A 89091110 11 33.0N 151.1E 7 268 648 N/A 35 5 0 10 -0 N/A N/A 89091110 11 33.0N 151.1E 7 268 648 N/A N/A 35 5 0 10 -0 N/A N/A 89091110 17 36.6N 150.0E 20 213 477 N/A N/A 35 5 0 10 0 N/A N/A 89091110 17 36.6N 150.0E 15 163 N/A N/A N/A 55 0 0 0 N/	89091000	17	19.1N		17			360	55	10			
890910102	89091006	18		123.8E	18	68	148	406					
890910108 20	89091012	19	20.6N	123.6E	13	97	240	467	65	0			
89091100 21 21.8N 123.IE 0 191 422 640 115 0 50 85 95 89091106 22 22.8N 122.7E 12 167 384 N/A 125 0 60 75 N/A 89091112 23 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091118 24 23.0N 121.2E 45 71 292 N/A 90 0 45 50 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091206 26 24.1N 122.0E 18 190 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A 40 5 10 N/A N/A 89091306 30 26.3N 119.8E 56 N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A 30 0 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 30 0 N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89090900 1 20.3N 153.9E 71 369 318 365 25 0 10 20 30 30 30 30 30 30 3	89091018		21.1N			78							
89091112 23 23 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091118 24 23.0N 121.2E 45 71 292 N/A 90 0 45 55 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091206 26 24.1N 122.0E 18 190 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091310 29 25.7N 120.3E 32 27 N/A N/A 40 5 10 N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 30 0 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 30 0 N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A 8909130 30 26.3N 15.8E 71 15.8E 48 N/A N/A N/A N/A 20 0 N/A N/A N/A 89091312 31 27.1N 15.6E 41 N/A N/A N/A N/A N/A 20 0 N/A N/A N/A 89091312 31 27.1N 15.6E 41 N/A N/A N/A N/A N/A 20 0 N/A N/A N/A 8909130 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 8909130 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 8909130 30 26.7N 150.0E 0 78 183 48 30 0 N/A N/A N/A N/A 89090906 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A N/A 89090918 4 26.7N 154.0E 0 113 258 392 30 0 15 25 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89090101 7 29.3N 150.0E 20 213 477 800 35 0 20 30 20 89090102 7 29.3N 150.0E 20 213 375 582 35 0 20 5 5 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 5 0 -5 N/A N/A 89091101 1 33.0N 151.1E 7 268 648 N/A 35 5 -10 N/A N/A 89091101 1 33.0N 151.1E 7 268 648 N/A 35 5 -10 N/A N/A 89091120 1 33.0N 151.1E 7 268 648 N/A N/A 35 5 -15 N/A N/A 89091121 15 36.0N 150.5E 4 174 N/A N/A 35 5 -15 N/A N/A 89091221 15 36.0N 150.5E 4 174 N/A N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 150.5E 4 174 N/A N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 150.6E 50 120 474 N/A N/A 50 0 0 0 N/A N/A	89091100	21	21.8N	123.1E	0	191	422	640	115	0			
99091112 23 23.3N 122.0E 12 225 443 N/A 125 0 60 75 N/A 89091112 24 23.0N 121.2E 45 71 292 N/A 90 0 45 50 N/A 89091200 25 23.0N 121.5E 13 146 269 N/A 80 0 40 55 N/A 89091206 26 24.1N 122.0E 18 190 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 66 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A N/A 45 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 30 0 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 30 0 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A N/A 55 5 N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89091912 3 24.5N 155.9E 71 369 318 385 25 0 10 20 30 89090906 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A N/A 89090912 3 24.5N 155.0E 0 78 113 258 392 30 0 15 25 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 8909012 7 29.3N 150.0E 20 213 374 502 28909100 6 28.2N 151.0E 32 281 335 582 35 0 20 25 5 0 10 89091012 7 29.3N 150.0E 20 213 477 800 35 0 20 25 20 8909100 9 30.4N 150.4E 6 24 N/A N/A N/A 35 5 0 5 0 10 N/A N/A 89091100 9 30.4N 150.4E 6 24 N/A N/A N/A 35 5 0 5 0 10 N/A N/A 89091100 9 30.4N 150.4E 6 24 N/A N/A N/A 35 5 0 5 0 10 N/A N/A 89091101 11 33.0N 151.1E 7 268 648 N/A N/A 35 5 -15 N/A N/A 89091101 11 33.0N 151.1E 7 268 648 N/A N/A 35 5 -15 N/A N/A 89091102 13 35.0N 151.8E 7 327 N/A N/A N/A 35 5 -15 N/A N/A 89091118 12 34.0N 151.1E 11 256 565 N/A N/A 35 5 -15 N/A N/A 89091120 13 35.0N 151.8E 7 327 N/A N/A N/A 35 5 -15 N/A N/A 89091120 13 35.0N 151.5E 7 327 N/A N/A N/A 35 5 -15 N/A N/A 89091120 13 35.0N 151.5E 7 327 N/A N/A N/A 35 5 -15 N/A N/A 89091121 15 36.0N 154.5E 4 174 N/A N/A N/A 45 0 -10 N/A N/A 89091200 13 35.0N 151.5E 7 132 N/A N/A N/A 35 5 -15 N/A N/A N/A 89091300 17 36.6N 156.6E 9 214 N/A N/A N/A N	89091106	22	22.8N	122.7E	12	167	384	N/A	120	0	55	70	N/A
89091218 24 23.0N 121.2E 45 71 292 N/A 90 0 45 50 N/A 89091200 25 23.0N 121.6E 13 146 269 N/A 80 0 40 55 N/A 89091216 26 24.1N 122.0E 18 190 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 65 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A 45 10 30 N/A N/A 89091300 30 26.3N 119.8E 56 N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A 30 0 N/A N/A N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A 30 0 N/A N/A N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89091306 30 26.3N 120.0E 50 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A N/A 89091306 30 26.3N 153.9E 71 369 318 31 22 0 0 N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89091000 1 20.3N 153.9E 71 369 318 385 25 0 10 20 30 89090900 1 20.3N 153.9E 71 369 318 385 25 0 10 20 30 89090918 4 26.7N 155.0E 0 78 183 418 30 0 10 20 20 89090918 4 26.7N 155.0E 0 78 183 418 30 0 10 20 20 89090918 4 26.7N 155.0E 0 78 183 418 30 0 10 20 20 8909100 5 28.2N 155.3E 0 207 315 490 35 0 20 30 20 8909100 6 28.2N 155.3E 0 20 27 315 490 35 0 20 25 20 8909100 7 29.3N 150.2E 78 172 323 575 35 0 20 5 5 10 8909101 7 29.3N 150.0E 20 213 477 800 35 0 20 25 20 8909100 9 30.4N 150.4E 6 24 N/A N/A N/A 35 5 0 10 -20 N/A N/A 89091100 10 31.6N 150.0E 5 120 474 N/A 35 5 -15 N/A N/A 89091101 11 33.0N 151.1E 7 268 648 N/A 35 5 -15 N/A N/A 89091102 13 35.6N 151.1E 11 256 565 N/A N/A 35 5 -15 N/A N/A 8909121 15 36.6N 151.5E 4 174 N/A N/A 45 0 -10 N/A N/A 8909120 17 36.6N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 8909120 17 36.6N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 8909130 17 36.6N 156.6E 9 214 N/A N/A N/A 50 0 0 0 N/A N/A N/A 8909130 17 36.6N 156.6E 9 214 N/A N/A N/A 50 0 0 0 N/A N/A N/A	89091112	23	23.3N	122.0E	12	225	443			0	60	75	
B9091200 25	89091118	24	23.ON	121.2E	45	71	292	N/A	90	0	45	50	
89091206 26 24.1N 122.0E 18 190 N/A N/A 65 0 25 N/A N/A 89091212 27 24.5N 121.3E 20 154 N/A N/A 66 0 0 25 N/A N/A 89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A 40 5 10 N/A N/A N/A 89091306 30 26.3N 119.8E 56 N/A N/A N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A N/A 35 10 N/A N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A N/A 25 5 N/A N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A N/A 25 5 N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A N/A N/A N/A N/A 8909120 12 2.2.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A N/A N/A 89099090 1 20.3N 153.9E 71 369 318 385 25 0 10 20 30 89090906 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A N/A 8909912 3 24.5N 155.0E 0 78 183 418 30 0 10 20 20 89090912 3 24.5N 155.0E 0 78 183 418 30 0 10 20 20 89090918 4 26.7N 154.0E 0 113 258 392 30 0 15 25 20 8909100 5 28.2N 152.3E 0 207 315 490 35 0 20 30 28909100 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 8909100 6 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 8909100 7 29.3N 150.2E 78 172 323 575 35 0 20 25 20 8909100 9 30.4N 150.4E 6 24 N/A N/A 35 5 0 -5 N/A N/A N/A 8909110 9 30.4N 150.4E 6 24 N/A N/A 35 5 0 -5 N/A N/A 8909110 1 33.50 N 151.1E 11 256 565 N/A N/A 35 5 0 -10 N/A N/A 8909110 1 33.50 N 151.1E 11 256 565 N/A N/A 35 5 -10 N/A N/A 8909110 1 33.50 N 151.1E 11 256 565 N/A N/A 35 5 -10 -10 N/A 8909110 1 33.50 N 151.1E 11 256 565 N/A N/A 35 5 -15 N/A N/A 8909110 1 33.50 N 151.1E 11 256 565 N/A N/A 35 5 -15 N/A N/A 8909110 1 3 35.0N 151.1E 11 256 565 N/A N/A 35 5 -15 N/A N/A 8909120 13 35.0N 151.1E 11 256 565 N/A N/A 35 5 -15 N/A N/A 8909120 13 35.0N 151.1E 11 256 565 N/A N/A 35 5 -10 -10 N/A 8909120 13 35.0N 151.1E 11 256 565 N/A N/A 35 5 -15 N/A N/A 8909120 13 35.0N 151.1E 11 256 565 N/A N/A 35 5 -10 -10 N/A 8909120 13 35.0N 151.1E 11 256 565 N/A N/A N/A 45 0 -10 N/A N/A 8909120 13 36.6N 155.7E 18 249 N/A N/A N/A 45 0 -10 N/A N/A 8909130 17 36.6N 155.7E 18 249 N/A N/A N/A 45 0 -10 N/A N/A 8909130 17 36.6N 155.7E 18 249 N/A	89091200	25	23.ON	121.6E	13	146	269	N/A	80	0	40		
89091212 27	89091206	26	24.1N	122.0E	18	190	N/A		65	0	25	N/A	
89091218 28 25.1N 120.9E 39 137 N/A N/A 45 10 30 N/A N/A 89091300 29 25.7N 120.3E 32 27 N/A N/A 40 5 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 25 5 N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A	89091212	27	24.5N	121.3E	20	154	N/A	N/A	60	0	25		
89091300 29 25.7N 120.3E 32 27 N/A N/A 40 5 10 N/A N/A 89091306 30 26.3N 119.8E 56 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091312 31 27.1N 119.6E 41 N/A N/A N/A N/A 35 10 N/A N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A N/A 25 5 N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A	89091218	28	25.1N	120.9E	39	137	N/A	N/A	45	10	30		
89091306 30	89091300	29	25.7N	120.3E	32	27		N/A			10		
89091312 31 27.1N 119.6E 41 N/A N/A N/A 30 0 N/A N/A N/A N/A 89091318 32 27.9N 119.8E 48 N/A N/A N/A N/A 25 5 N/A N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A 20 0 N/A	89091306	30	26.3N	119.8E	56	N/A	N/A	N/A	35	10	N/A		
89091318 32 27.9N 119.8E 48 N/A N/A N/A 25 5 N/A N/A N/A N/A 89091400 33 28.7N 120.0E 50 N/A N/A N/A N/A N/A 20 0 N/A	89091312	31	27.1N	119.6E	41		N/A	N/A	30	0			
Tropical Storm Tip (23W)	89091318	32	27.9N	119.8E	48	N/A		N/A	25	5			
Tropical Storm Tip (23W) Average 23 204 374 502						/		/-		_			
DTG W± BT LAT BT LON POS ER 24 ER 48 ER 72 ER BT WN WW ER 24 ER 48 ER 72 ER 89090900 1 20.3N 153.9E 71 369 318 385 25 0 10 20 30 89090902 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A 89090912 3 24.5N 155.0E 0 78 183 418 30 0 10 20 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 25 20	89091400	33	28.7N	120.0E	50	N/A	N/A	N/A	20	0	N/A	N/A	N/A
89090900 1 20.3N 153.9E 71 369 318 385 25 0 10 20 30 89090906 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A N/A 89090912 3 24.5N 155.0E 0 78 183 418 30 0 10 20 20 89090918 4 26.7N 154.0E 0 113 258 392 30 0 15 25 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 5 -10 89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 11 256 565 N/A 35 0 -15 N/A N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091200 13 35.6N 152.7E 18 249 N/A N/A 45 0 -10 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091212 15 36.6N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091210 17 36.6N 159.0E 15 143 N/A N/A N/A 50 0 0 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A N/A 50 0 0 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091300 18 36.5N 161.1E 20 163 N/A N/A N/A 50 0 0 N/A N/A 89091300 18 36.5N 161.1E 20 163 N/A N/A N/A 50 0 0 N/A N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A N/A N/A 45 0 N/A N/A				Average	<u>00h</u> 23	24h 204	<u>48h</u> 374	<u>72h</u> 502	20	O	N/A	N/A	N/A
89090900 1 20.3N 153.9E 71 369 318 385 25 0 10 20 30 89090906 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A N/A 89090912 3 24.5N 155.0E 0 78 183 418 30 0 10 20 20 89090918 4 26.7N 154.0E 0 113 258 392 30 0 15 25 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 5 -10 89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 11 256 565 N/A 35 0 -15 N/A N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091200 13 35.6N 152.7E 18 249 N/A N/A 45 0 -10 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091212 15 36.6N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091210 17 36.6N 159.0E 15 143 N/A N/A N/A 50 0 0 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A N/A 50 0 0 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091300 18 36.5N 161.1E 20 163 N/A N/A N/A 50 0 0 N/A N/A 89091300 18 36.5N 161.1E 20 163 N/A N/A N/A 50 0 0 N/A N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A N/A N/A 45 0 N/A N/A				Average	<u>00h</u> 23	24h 204	<u>48h</u> 374	<u>72h</u> 502	20	O	N/A	N/A	N/A
89090906 2 22.1N 154.9E 37 298 226 375 30 0 N/A N/A N/A 89090912 3 24.5N 155.0E 0 78 183 418 30 0 10 20 20 89090918 4 26.7N 154.0E 0 113 258 392 30 0 15 25 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.0E 20 213 477 800 35 0 20 5 -10 89091100 9 30.4N 150.0E 20 213 477 800 35 0 -5 N/A N/A	Tropical	Storm Tip	(23W)	Average	00h 23 20	24h 204 18	48h 374 11	72h 502 8					
89090912 3 24.5N 155.0E 0 78 183 418 30 0 10 20 20 89090918 4 26.7N 154.0E 0 113 258 392 30 0 15 25 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 5 -10 89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 N/A N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A N/A 35 5 -15 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091200 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A N/A 50 0 0 N/A N/A	Tropical	Storm Tip W#	(23W) BT_LAT	Average # Cases BT_LON	00h 23 20 POS ER	24h 204 18	48h 374 11 48 ER	72h 502 8	BI WN	www.er	24 ER	48 ER	72 ER
89090918 4 26.7N 154.0E 0 113 258 392 30 0 15 25 20 89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 5 -10 89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A	Tropical DTG 89090900	Storm Tip W# 1	(23W) BT_LAT 20.3N	Average Cases BT LON 153.9E	00h 23 20 POS ER 71	24h 204 18 24 ER 369	48h 374 11 48 ER 318	72h 502 8 72 ER 385	BT WN 25	WW ER	24 ER 10	48 ER 20	72 ER 30
89091000 5 28.2N 152.3E 0 207 315 490 35 0 20 30 20 89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 5 -10 89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A </td <td>Tropical DTG 89090900 89090906</td> <td>Storm Tip W# 1 2</td> <td>(23W) BT LAT 20.3N 22.1N</td> <td>Average Cases ET LON 153.9E 154.9E</td> <td>00h 23 20 POS ER 71 37</td> <td>24h 204 18 24 ER 369 298</td> <td>48h 374 11 48 ER 318 226</td> <td>72h 502 8 72 ER 385 375</td> <td>BT WN 25 30</td> <td><u>ww_er</u> 0 0</td> <td>24 ER 10 N/A</td> <td>48 ER 20 N/A</td> <td>72 ER 30 N/A</td>	Tropical DTG 89090900 89090906	Storm Tip W# 1 2	(23W) BT LAT 20.3N 22.1N	Average Cases ET LON 153.9E 154.9E	00h 23 20 POS ER 71 37	24h 204 18 24 ER 369 298	48h 374 11 48 ER 318 226	72h 502 8 72 ER 385 375	BT WN 25 30	<u>ww_er</u> 0 0	24 ER 10 N/A	48 ER 20 N/A	72 ER 30 N/A
89091006 6 28.9N 151.0E 32 281 335 582 35 0 20 25 20 89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 5 -10 89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 -15 N/A 89091200 13 35.0N 151.8E 7 327 N/A	Tropical DTG 89090900 89090906 89090912	Storm Tip W# 1 2 3	(23W) BT LAT 20.3N 22.1N 24.5N	Average	00h 23 20 POS ER 71 37 0	24h 204 18 24 ER 369 298 78	48h 374 11 48 ER 318 226 183	72h 502 8 72 ER 385 375 418	BT WN 25 30 30	WW ER 0 0	24 ER 10 N/A 10	48 ER 20 N/A 20	72 ER 30 N/A 20
89091012 7 29.3N 150.2E 78 172 323 575 35 0 20 5 -10 89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 -15 N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A	Tropical DTG 89090900 89090906 89090912 89090918	Storm Tip W# 1 2 3 4	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N	Average	00h 23 20 POS ER 71 37 0	24h 204 18 24 ER 369 298 78 113	48h 374 11 48 ER 318 226 183 258	72h 502 8 72 ER 385 375 418 392	BT WN 25 30 30 30	WW ER 0 0 0	24 ER 10 N/A 10 15	48 ER 20 N/A 20 25	72 ER 30 N/A 20 20
89091018 8 29.8N 150.0E 20 213 477 800 35 0 5 0 10 89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 -15 N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A N/A 40 10 -15 N/A N/A 89091212 15 36.6N 156.6E 9 214 N/A	Tropical DTG 89090900 89090906 89090912 89090918 89091000	Storm Tip W# 1 2 3 4 5	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N	Average	00h 23 20 POS ER 71 37 0 0	24h 204 18 24 ER 369 298 78 113 207	48h 374 11 48 ER 318 226 183 258 315	72h 502 8 72 ER 385 375 418 392 490	BT WN 25 30 30 30 35	WW ER 0 0 0 0	24 ER 10 N/A 10 15 20	48 ER 20 N/A 20 25 30	72 ER 30 N/A 20 20 20
89091100 9 30.4N 150.4E 6 24 N/A N/A 35 0 -5 N/A N/A 89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 -15 N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A N/A 40 10 -15 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091218 16 36.6N 156.6E 9 214 N/A <td>Tropical DTG 89090900 89090906 89090912 89090918 89091000 89091006</td> <td>Storm Tip W# 1 2 3 4 5 6</td> <td>(23W) BT LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N</td> <td>Average</td> <td>00h 23 20 POS ER 71 37 0 0 0</td> <td>24h 204 18 24 ER 369 298 78 113 207 281</td> <td>48h 374 11 48 ER 318 226 183 258 315 335</td> <td>72h 502 8 72 ER 385 375 418 392 490 582</td> <td>BT WN 25 30 30 30 35 35</td> <td>WW ER 0 0 0 0</td> <td>24 ER 10 N/A 10 15 20 20</td> <td>48 ER 20 N/A 20 25 30 25</td> <td>72 ER 30 N/A 20 20 20 20</td>	Tropical DTG 89090900 89090906 89090912 89090918 89091000 89091006	Storm Tip W# 1 2 3 4 5 6	(23W) BT LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N	Average	00h 23 20 POS ER 71 37 0 0 0	24h 204 18 24 ER 369 298 78 113 207 281	48h 374 11 48 ER 318 226 183 258 315 335	72h 502 8 72 ER 385 375 418 392 490 582	BT WN 25 30 30 30 35 35	WW ER 0 0 0 0	24 ER 10 N/A 10 15 20 20	48 ER 20 N/A 20 25 30 25	72 ER 30 N/A 20 20 20 20
89091106 10 31.6N 151.0E 5 120 474 N/A 35 5 0 -10 N/A 89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 -15 N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A N/A 40 10 -15 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091218 16 36.6N 156.6E 9 214 N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/	DTG 89090900 89090906 89090912 89090918 89091000 89091006 89091012	## 1 2 3 4 5 6 7	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N	Average	00h 23 20 POS ER 71 37 0 0 0 32 78	24h 204 18 24 ER 369 298 78 113 207 281 172	48h 374 11 48 ER 318 226 183 258 315 335 323	72h 502 8 72 ER 385 375 418 392 490 582 575	BT WN 25 30 30 35 35 35	WW ER 0 0 0 0 0	24 ER 10 N/A 10 15 20 20	48 ER 20 N/A 20 25 30 25 5	72 ER 30 N/A 20 20 20 20
89091112 11 33.0N 151.1E 7 268 648 N/A 35 5 -10 -20 N/A 89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 -15 N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A N/A 40 10 -15 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091218 16 36.6N 156.6E 9 214 N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N	DTG 89090900 89090906 89090912 89090918 89091000 89091006 89091012 89091018	## 1 2 3 4 5 6 7 8	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N	Average Cases ET LON 153.9E 154.9E 155.0E 154.0E 152.3E 151.0E 150.2E 150.0E	00h 23 20 POS ER 71 37 0 0 0 32 78 20	24h 204 18 24 ER 369 298 78 113 207 281 172 213	48h 374 11 48 ER 318 226 183 258 315 335 323 477	72h 502 8 72 ER 385 375 418 392 490 582 575 800	BT WN 25 30 30 35 35 35 35	WW ER 0 0 0 0 0	24 ER 10 N/A 10 15 20 20 20 5	48 ER 20 N/A 20 25 30 25 5	72 ER 30 N/A 20 20 20 20 -10 10
89091118 12 34.0N 151.1E 11 256 565 N/A 35 0 -15 -15 N/A 89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A N/A 40 10 -15 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091218 16 36.6N 156.6E 9 214 N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A 45 0 N/A N/A N/A 89091312 19 36.6N 163.1E 15 N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091100	## 1 2 3 4 5 6 7 8 9	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N	Average Cases ET LON 153.9E 154.9E 155.0E 154.0E 152.3E 151.0E 150.2E 150.0E 150.4E	00h 23 20 POS ER 71 37 0 0 0 32 78 20 6	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A	BT WN 25 30 30 35 35 35 35	WW ER 0 0 0 0 0 0	24 ER 10 N/A 10 15 20 20 5 -5	48 ER 20 N/A 20 25 30 25 5 0 N/A	72 ER 30 N/A 20 20 20 20 -10 10 N/A
89091200 13 35.0N 151.8E 7 327 N/A N/A 35 5 -15 N/A N/A 89091206 14 35.6N 152.7E 18 249 N/A N/A 40 10 -15 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091218 16 36.6N 156.6E 9 214 N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A 50 0 0 N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A 45 0 N/A N/A N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091100 89091106	## 1 2 3 4 5 6 7 8 9 10	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N 31.6N	Average Cases ET LON 153.9E 154.9E 155.0E 154.0E 152.3E 151.0E 150.2E 150.0E 150.4E 151.0E	00h 23 20 POS ER 71 37 0 0 0 32 78 20 6 5	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A	BT WN 25 30 30 35 35 35 35 35	WW ER 0 0 0 0 0 0 0	24 ER 10 N/A 10 15 20 20 5 -5	48 ER 20 N/A 20 25 30 25 5 0 N/A -10	72 ER 30 N/A 20 20 20 20 -10 10 N/A N/A
89091206 14 35.6N 152.7E 18 249 N/A N/A 40 10 -15 N/A N/A 89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091218 16 36.6N 156.6E 9 214 N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A 50 0 0 N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A 45 0 N/A N/A N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091100 89091106 89091112	## 1 2 3 4 5 6 7 8 9 10 11	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N 31.6N 33.0N	Average Cases ET LON 153.9E 154.9E 155.0E 154.0E 150.2E 150.0E 150.4E 151.0E 151.1E	00h 23 20 POS ER 71 37 0 0 0 32 78 20 6 5	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120 268	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A	BT WN 25 30 30 35 35 35 35 35 35	WW ER 0 0 0 0 0 0 0 0 0 5 5	24 ER 10 N/A 10 15 20 20 5 -5 0 -10	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20	72 ER 30 N/A 20 20 20 20 -10 10 N/A N/A
89091212 15 36.0N 154.5E 4 174 N/A N/A 45 0 -10 N/A N/A 89091218 16 36.6N 156.6E 9 214 N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A 50 0 0 N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A 45 0 N/A N/A N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091100 89091112 89091118	## 1 2 3 4 5 6 7 8 9 10 11 12	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N 31.6N 33.0N 34.0N	Average Cases BT LON 153.9E 154.9E 155.0E 154.0E 152.3E 151.0E 150.2E 150.0E 151.1E 151.1E	90h 23 20 POS ER 71 37 0 0 0 32 78 20 6 5 7	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120 268 256	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648 565	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A N/A	BT WN 25 30 30 35 35 35 35 35 35 35	WW ER 0 0 0 0 0 0 0 0 0 5 5	24 ER 10 N/A 10 15 20 20 5 -5 0 -10 -15	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20 -15	72 ER 30 N/A 20 20 20 20 -10 10 N/A N/A N/A
89091218 16 36.6N 156.6E 9 214 N/A N/A 45 0 -10 N/A N/A 89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A 50 0 0 N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A 45 0 N/A N/A N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091106 89091112 89091118 89091200	## 1 2 3 4 5 6 7 8 9 10 11 12 13	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N 31.6N 33.0N 34.0N 35.0N	Average Cases ET LON 153.9E 154.9E 155.0E 154.0E 152.3E 151.0E 150.2E 150.0E 151.1E 151.1E 151.8E	00h 23 20 POS ER 71 37 0 0 0 32 78 20 6 5 7 11	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120 268 256 327	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648 565 N/A	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A N/A	BT WN 25 30 30 35 35 35 35 35 35 35	WW ER 0 0 0 0 0 0 0 0 0 5 5	24 ER 10 N/A 10 15 20 20 5 -5 0 -10 -15 -15	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20 -15 N/A	72 ER 30 N/A 20 20 20 20 -10 10 N/A N/A N/A
89091300 17 36.6N 159.0E 15 143 N/A N/A 50 0 0 N/A N/A 89091306 18 36.5N 161.1E 20 163 N/A N/A 50 0 0 N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A 45 0 N/A N/A N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091106 89091112 89091118 89091120 89091200 89091206	## 1 2 3 4 5 6 7 8 9 10 11 12 13 14	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N 31.6N 33.0N 34.0N 35.0N 35.6N	Average Cases ET LON 153.9E 154.9E 155.0E 154.0E 150.2E 150.0E 150.4E 151.0E 151.1E 151.1E 151.8E	00h 23 20 POS ER 71 37 0 0 0 32 78 20 6 5 7 11 7	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120 268 256 327 249	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648 565 N/A N/A	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A N/A	BT WN 25 30 30 35 35 35 35 35 35 35 35	WW ER 0 0 0 0 0 0 0 0 0 5 5 0 5	24 ER 10 N/A 10 15 20 20 5 -5 0 -10 -15 -15	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20 -15 N/A N/A	72 ER 30 N/A 20 20 20 -10 10 N/A N/A N/A N/A N/A
89091306 18 36.5N 161.1E 20 163 N/A N/A 50 0 0 N/A N/A 89091312 19 36.6N 163.1E 15 N/A N/A N/A 45 0 N/A N/A N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091106 89091112 89091118 89091118 89091200 89091206 89091212	## 1 2 3 4 5 6 6 7 8 9 10 11 12 13 14 15	(23W) BT_LAT 20.3N 22.1N 24.5N 26.7N 28.2N 29.3N 29.8N 30.4N 31.6N 33.0N 34.0N 35.0N 35.6N 36.0N	Average Cases BT LON 153.9E 154.9E 155.0E 154.0E 150.2E 150.0E 150.4E 151.0E 151.1E 151.1E 151.8E 152.7E	00h 23 20 POS ER 71 37 0 0 0 32 78 20 6 5 7 11 7 18 4	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120 268 256 327 249 174	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648 565 N/A N/A	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A N/A N/A	BT WN 25 30 30 35 35 35 35 35 35 35 40 45	WW ER 0 0 0 0 0 0 0 0 5 5 0 5	24 ER 10 N/A 10 15 20 20 5 -5 0 -10 -15 -15 -15	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20 -15 N/A N/A	72 ER 30 N/A 20 20 20 -10 10 N/A N/A N/A N/A N/A
89091312 19 36.6N 163.1E 15 N/A N/A N/A 45 0 N/A N/A N/A	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091106 89091112 89091118 89091118 89091200 89091206 89091212 89091218	## 1 2 3 4 5 6 6 7 8 9 10 11 12 13 14 15 16	(23W) BT LAT 20.3N 22.1N 24.5N 26.7N 28.2N 29.3N 29.8N 30.4N 31.6N 33.0N 35.0N 35.6N 36.6N	Average Cases BT LON 153.9E 154.9E 155.0E 154.0E 150.2E 150.0E 150.4E 151.0E 151.1E 151.1E 151.8E 152.7E 154.5E	00h 23 20 POS ER 71 37 0 0 32 78 20 6 5 7 11 7 18 4	24h 204 18 24 ER 369 298 113 207 281 172 213 24 120 268 256 327 249 174 214	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648 565 N/A N/A N/A	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A N/A N/A	BT WN 25 30 30 35 35 35 35 35 35 35 40 45	WW ER 0 0 0 0 0 0 0 0 5 5 0 5	24 ER 10 N/A 10 15 20 20 20 5 -5 0 -10 -15 -15 -15 -10 -10	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20 -15 N/A N/A	72 ER 30 N/A 20 20 20 -10 10 N/A N/A N/A N/A N/A N/A
, , , , , , , , , , , , , , , , , , , ,	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091106 89091112 89091118 89091118 89091200 89091212 89091218 89091218	## 1 2 3 4 5 6 6 7 8 9 10 11 12 13 14 15 16 17	(23W) BT LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N 31.6N 33.0N 35.0N 35.6N 36.6N 36.6N	Average Cases ET LON 153.9E 154.9E 155.0E 154.0E 150.2E 150.0E 150.4E 151.1E 151.1E 151.1E 151.8E 152.7E 154.5E 156.6E 159.0E	00h 23 20 POS ER 71 37 0 0 32 78 20 6 5 7 11 7 18 4 9	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120 268 256 327 249 174 214	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648 565 N/A N/A N/A	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A N/A N/A N/A	BT WN 25 30 30 35 35 35 35 35 35 35 40 45 45	WW ER 0 0 0 0 0 0 0 5 5 0 0 5 10 0 0 0 0 0 0	24 ER 10 N/A 10 15 20 20 5 -5 0 -10 -15 -15 -15 -10 -10	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20 -15 N/A N/A N/A N/A	72 ER 30 N/A 20 20 20 -10 10 N/A N/A N/A N/A N/A N/A
	DTG 89090900 89090906 89090912 89090918 89091006 89091012 89091018 89091106 89091112 89091118 89091200 89091206 89091218 89091218 89091218 89091300 89091306	## 1 2 3 4 5 6 6 7 8 9 10 11 12 13 14 15 16 17 18	(23W) BT LAT 20.3N 22.1N 24.5N 26.7N 28.2N 28.9N 29.3N 29.8N 30.4N 31.6N 33.0N 35.0N 35.6N 36.6N 36.6N 36.5N	Average	00h 23 20 POS ER 71 37 0 0 32 78 20 6 5 7 11 7 18 4 9 15 20	24h 204 18 24 ER 369 298 78 113 207 281 172 213 24 120 268 256 327 249 174 214 143 163	48h 374 11 48 ER 318 226 183 258 315 335 323 477 N/A 474 648 565 N/A N/A N/A N/A	72h 502 8 72 ER 385 375 418 392 490 582 575 800 N/A N/A N/A N/A N/A	BT WN 25 30 30 35 35 35 35 35 35 40 45 45 50	WW ER 0 0 0 0 0 0 0 5 5 0 0 5 10 0 0 0 0 0 0	24 ER 10 N/A 10 15 20 20 5 -5 0 -10 -15 -15 -15 -10 0 0	48 ER 20 N/A 20 25 30 25 5 0 N/A -10 -20 -15 N/A N/A N/A N/A	72 ER 30 N/A 20 20 20 -10 10 N/A N/A N/A N/A N/A N/A N/A N/A

Tropical S	Storm 7	/era (24W)	Average # Cases		00h 25 16	24h 173 13	48h 381 10	72h 662 7				
DTG	W#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89091206	1	18.0N	144.2E	42	397	652	895	30	0	-10	10	35
89091212	2	18.7N	142.7E	12	181	355	653	35	0	~5	15	35
89091218	3	19.6N	140.9E	32	256	533	729	40	5	25	60	90
89091300	4	20.3N	139.2E	18	110	362	590	45	5	20	60	90
89091306	5	20.8N	137.5E	17	128	359	536	50	5	30	60	95
89091312	6	21.3N	137.3E	51	293	518	650	50	0	20	40	65
89091318	7	21.9N	133.7E	39	144	352	582	45	0	20	40	25
89091400	8	22.7N	131.9E	12	141	260	N/A	45	0	20	40	N/A
89091406	9	23.4N	129.9E	12	72	136	N/A	45	0	0	5	N/A
89091412	10	24.2N	129.9E	28	110	285	N/A	45	0	٥	10	N/A
89091418	11	24.2N	126.2E	12	122	N/A	N/A	40	0	5	N/A	N/A
89091500	12	26.2N	124.5E	12	101	N/A	N/A	40	0	10	N/A	N/A
89091506	13	27.3N	124.5E	12	198	N/A	N/A	40	ő	10	N/A	N/A
89091512	14	28.4N	121.6E	28	N/A	N/A	N/A	40	-5	N/A	N/A	N/A
89091518	15	29.3N	121.0E	33	N/A	N/A	N/A	30	0	N/A	N/A	N/A
89091600	16	30.2N	119.9E	35	N/A	N/A	N/A	30	ő	N/A	N/A	N/A
Typhoon Wa				<u>00h</u>	24h	48h	<i>72</i> h			,	2,, 22	
			Average	19	231	623	N/A					
			# Cases	12	10	4	0					
DTG	₩ŧ	BT_LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72_ER
89091706†	1	23.7N	124.9E	5	115	N/A	N/A	25	0	-10	N/A	N/A
89091718	2	24.1N	125.1E	87	348	N/A	N/A	30	-5	-25	N/A	N/A
89091800	3	25.3N	125.2E	5	424	N/A	N/A	35	0	-20	-20	N/A
89091806	4	26.6N	125.3E	16	144	593	N/A	40	-5	-20	-20	N/A
89091812	5	27.7N	125.8E	12	292	753	N/A	45	0	-15	-20	N/A
89091818	6	29.0N	127.1E	16	344	720	N/A	55	0	-10	-5	N/A
89091900	7	30.3N	128.6E	15	309	N/A	N/A	65	. 0	-15	N/A	N/A
89091906	8	31.5N	131.4E	6	157	N/A	N/A	65	0	5	N/A	N/A
89091912	9	32.9N	134.6E	0	290	N/A	N/A	65	0	10	N/A	N/A
89091918	10	34.4N	138.6E	23	284	N/A	N/A	60	-5	5	N/A	N/A
89092000	11	36.3N	143.0E	20	N/A	N/A	N/A	55	0	N/A	N/A	N/A
89092006	12	38.4N	147.8E	26	N/A	N/A	N/A	50	0	N/A	N/A	N/A
† 1	ropica	al Depressi	on Warnin	g								
Super Typh	roou ya	agela (26W)		<u>00h</u>	24h	48h	<u>72h</u>					
			Average	8	68	165	293					
			# Cases	46	43	39	35					
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89092906	1	13.5N	139.7E	8	104	276	293	30	0	5	-25	-25
89092912	2	14.3N	139.3E	13	98	207	348	30	0	0	-35	-45
89092918	3	15.1N	139.0E	11	116	233	395	35	0	-10	-35	-45
89093000	4	15.5N	138.6E	5	30	165	421	40	0	-35	-45	-45
89093006	5	15.8N	138.4E	5	61	226	477	40	0	-30	-45	-45
89093012	6	16.0N	138.3E	8	103	321	653	45	0	-35	-45	-35
89093018	7	16.4N	138.1E	6	117	355	666	65	0	-5	-5	5
89100100	8	16.5N	137.7E	5	157	393	686	90	0	0	-5	-20
89100106	9	16.7N	137.3E	8	109	154	300	90	0	0	-15	-25
89100112	10	16.8N	136.7E	5	123	255	529	100	0	-5	-15	-20
89100118	11	17.1N	136.1E	8	203	392	812	105	0	-5	-10	-30
89100200	12	17.3N	135.2E	5	37	70	267	115	0	-15	-20	-40
89100206	13	17.5N	134.2E	23	45	66	242	115	0	0	-10	-35
89100212	14	17.8N	133.4E	12	66	191	412	120	0	10	-5	-35

Super Typ	hoon An	gela (26W)	(continu	ed)								
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89100218	15	18.ON	132.7E	0	81	218	436	120	0	15	-15	-35
89100300	16	18.1N	131.9E	5	85	115	92	120	0	0	-20	-35
89100306	17	18.2N	131.2E	6	32	126	216	120	-5	0	-25	-25
89100312	18	18.2N	130.7E	8	63	156	204	120	-5	0	-25	20
89100318	19	18.2N	130.1E	8	97	188	227	115	0	-15	-30	15
89100400	20	18.2N	129.4E	5	125	263	388	115	-5	-30	-45	5
89100406	21	18.2N	128.5E	0	39	72	54	115	0	-15	-50	5
89100412	22	18.2N	127.3E	17	41	68	87	115	0	-20	-10	10
89100418	23	18.2N	126.0E	0	53	87	132	125	0	-35	- 5	15
89100500	24	18.1N	125.0E	6	74	118	193	125	0	-60	-20	-25
89100506	25	18.1N	123.9E	8	75	121	180	130	0	-40	-5	-40
89100512	26	18.2N	122.9E	20	71	114	173	130	0	0	0	-45
89100518	27	18.4N	122.0E	0	47	188	298	130	0	0	0	-45
89100600	28	18.6N	121.1E	13	49	108	125	125	0	35	15	-30
89100606	29	18.7N	120.1E	12	75	141	126	115	0	20	-20	-50
89100612	30	18.7N	119.3E	5	75	128	101	75	-10	-10	-45	-60
89100618	31	18.6N	118.6E	13	30	47	33	75	0	-10	-45	-55
89100700	32	18.5N	117.9E	8	16	68	146	75	0	-15	-50	-60
89100706	33	18.3N	117.2E	12	25	94	177	70	0	-35	-60	-60
89100712	34	18.2N	116.5E	8	13	86	144	65	0	-45	-55	-35
89100718	35	18.2N	115.8E	12	78	149	213	65	0	-45	-50	-5
89100800	36	18.2N	115.1E	8	51	114	N/A	70	0	-10	-10	N/A
89100806	37	18.1N	114.4E	12	80	160	N/A	85	0	-5	0	N/A
89100812	38	17.9N	113.5E	12	86	154	N/A	90	0	-5	15	N/A
89100818	39	17.7N	112.5E	5	12	58	N/A	90	0	-10	0	N/A
89100900	40	17.6N	111.6E	6	17	N/A	N/A	90	0	-15	N/A	N/A
89100906	41	17.5N	110.7E	8	38	N/A	N/A	95	0	-5	N/A	N/A
89100912	42	17.5N	109.6E	8	29	N/A	N/A	90	0	-15	N/A	N/A
89100918	43	17.4N	108.6E	6	12	N/A	N/A	85	0	20	N/A	N/A
89101000	44	17.4N	107.8E	11	N/A	N/A	N/A	85	-10	N/A	N/A	N/A
89101006	45	17.4N	106.9E	20	N/A	N/A	N/A	80	-5	N/A	N/A	N/A
89101012	46	17.4N	106.0E	8	N/A	N/A	N/A	60	0	N/A	N/A	N/A
Typhoon B	rian (2	7W)	Average # Cases	00h 16 13	24h 104 10	48h 135 5	72h N/A N/A					
DTG	₩ŧ	BT_LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48_ER	72_ER
89093006†	1	20.0N	115.5E	45	197	N/A	N/A	25	0	-25	N/A	N/A
89093018	2	19.9N	115.2E	16	142	190	N/A	35	0	-10	-40	N/A
89100100	3	19.5N	114.8E	5	130	123	N/A	45	0	0	-45	N/A
89100106	4	19.2N	114.3E	12	29	142	N/A	55	0	-5	-45	N/A
89100112	5	18.9N	113.7E	12	20	95	N/A	55	0	-15	-5	N/A
89100118	6	18.6N	113.1E	0	41	124	N/A	65	0	-20	10	N/A
89100200	7	18.4N	112.4E	5	108	N/A	N/A	65	0	-20	N/A	N/A
89100206	8	18.4N	111.5E	23	165	N/A	N/A	70	-5	-20	N/A	N/A
89100212	و	18.4N	110.5E	34	184	N/A	N/A	80	-5	15	N/A	N/A
89100218	10	18.4N	109.3E	11	20	N/A	N/A	75	0	0	N/A	N/A
89100300	11	18.5N	107.8E	18	N/A	N/A	N/A	75	Ō	N/A	N/A	N/A
89100306	12	18.7N	106.4E	8	N/A	N/A	N/A	75	0	N/A	N/A	N/A
89100312	13	19.1N	105.1E	16	N/A	N/A	N/A	45	0	N/A	N/A	N/A
t		al Depressi			, -	• -	• -			, -		• -

Typhoon Col	.leen (28W)	Average	00h 18	24h 153	<u>48h</u> 207	<u>72h</u> 303					
			# Cases	27	24	20	16					
DTG	₩#	BT LAT	BT LON	POS ER	24_ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89100118	1	11.6N	150.3E	16	85	286	447	30	0	10	15	15
89100200	2	11.7N	149.3E	13	179	365	511	35	0	15	15	20
89100206	3	12.0N	148.4E	41	239	402	549	35	5	15	10	20
89100212	4	12.5N	147.9E	29	217	387	519	35	5	15	10	15
89100218	5	13.1N	147.5E	18	217	270	322	40	0	5	5	20
89100300	6	14.0N	147.3E	18	123	127	147	45	0	5	10	20
89100306	7	15.1N	147.1E	34	79	236	312	45	0	-10	-10	-25
89100312	8	16.1N	146.5E	39	191	228	134	50	0	-5	-5	0
89100318	9	17.2N	145.9E	32	80	142	147	55	0	-5	0	0
89100400 89100406	10 11	18.1N 18.9N	145.5E 145.1E	12 5	91	117 150	142	60	0	10	15	20
89100406	12	10.9N 19.6N	145.1E 144.8E	5 8	119 94	141	184 91	65 70	0 -5	10	15	20
89100412	13	20.2N	144.6E	29	155	251	135	70 75	-5 0	5 15	15 25	20 20
89100500	14	20.7N	144.5E	13	38	143	182	75	5	25	30	20
89100506	15	21.2N	144.2E	8	82	115	410	75	0	25	30	20
89100512	16	21.9N	143.8E	17	133	70	616	80	-5	25	15	-5
89100518	17	22.7N	143.2E	27	174	37	N/A	75	ō	25	15	N/A
89100600	18	23.6N	142.6E	0	97	81	N/A	75	ō	0	-10	N/A
89100606	19	24.6N	141.8E	16	102	111	N/A	75	Ō	-5	-15	N/A
89100612	20	25.4N	141.1E	10	80	479	N/A	75	0	-5	-10	N/A
89100618	21	26.4N	140.5E	6	163	N/A	N/A	75	0	-5	N/A	N/A
89100700	22	27.7N	140.7E	28	337	N/A	N/A	70	5	-5	N/A	N/A
89100706	23	29.3N	141.5E	5	183	N/A	N/A	70	0	-10	N/A	N/A
89100712	24	31.0N	143.0E	13	419	N/A	N/A	70	0 .	-5	N/A	N/A
89100718	25	33.4N	145.4E	13	N/A	N/A	N/A	70	0	N/A	N/A	N/A
89100800	26	36.5N	148.5E	4	N/A	N/A	N/A	70	0	N/A	N/A	N/A
89100806	27	40.4N	153.3E	37	N/A	N/A	N/A	70	0	N/A	N/A	N/A
Typhoon Dan	(29W)			<u>00h</u>	24h	<u>48h</u>	<u>72h</u>					
	•		Average	16	105	222	375					
			# Cases	21								
DMC	7.7 #			4.4	18	13	10					
<u>DTG</u> 89100812	₩#	DM 73.00	DM 7.017									
03100012	1	BT LAT	BT ION	POS ER	24 ER	48 ER	72_ER	BT WN	WW ER	24 ER	48 ER	72 ER
89100818	1	10.3N	138.4E	POS ER 58	24 ER 260	48 ER 459	72 ER 663	25	0	-20	-10	15
89100818 89100900	2	10.3N 10.5N	138.4E 136.9E	POS ER 58 24	24 ER 260 136	48 ER 459 345	72 ER 663 576	25 30	0	-20 -10	-10 -10	15 15
89100818 89100900 89100906		10.3N	138.4E	POS ER 58	24 ER 260 136 113	48 ER 459 345 277	72 ER 663 576 438	25 30 40	0 0 -10	-20 -10 -15	-10 -10 -10	15 15 10
89100900	2 3 4	10.3N 10.5N 10.7N 10.9N	138.4E 136.9E 135.4E 133.7E	POS ER 58 24 8 13	24 ER 260 136 113 126	48 ER 459 345 277 311	72 ER 663 576 438 438	25 30 40 50	0 0 -10 -15	-20 -10 -15 -10	-10 -10 -10 10	15 15 10 0
89100900 89100906	2 3	10.3N 10.5N 10.7N	138.4E 136.9E 135.4E	POS ER 58 24 8	24 ER 260 136 113	48 ER 459 345 277	72 ER 663 576 438 438 357	25 30 40 50 55	0 0 -10	-20 -10 -15 -10 5	-10 -10 -10 10	15 15 10 0
89100900 89100906 89100912 89100918 89101000	2 3 4 5	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N	138.4E 136.9E 135.4E 133.7E 131.9E	POS ER 58 24 8 13	24 ER 260 136 113 126 59	48 ER 459 345 277 311 260	72 ER 663 576 438 438	25 30 40 50	0 0 -10 -15 -10	-20 -10 -15 -10	-10 -10 -10 10	15 15 10 0
89100900 89100906 89100912 89100918 89101000 89101006	2 3 4 5 6 7 8	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E	POS ER 58 24 8 13 12 24 16	24 ER 260 136 113 126 59	48 ER 459 345 277 311 260 152	72 ER 663 576 438 438 357 216	25 30 40 50 55 55 55	0 0 -10 -15 -10 0 -5	-20 -10 -15 -10 5 -5	-10 -10 -10 10 0 15 10	15 15 10 0 0 35 25 25
89100900 89100906 89100912 89100918 89101000 89101006 89101012	2 3 4 5 6 7 8 9	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E	POS ER 58 24 8 13 12 24 16 18	24 ER 260 136 113 126 59 8 133	48 ER 459 345 277 311 260 152 270	72 ER 663 576 438 438 357 216 331	25 30 40 50 55 55	0 0 -10 -15 -10 0 -5 0 5	-20 -10 -15 -10 5 -5 5	-10 -10 -10 10 0 15	15 15 10 0 0 35 25 25 35
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101018	2 3 4 5 6 7 8 9	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E	POS ER 58 24 8 13 12 24 16 18 5	24 ER 260 136 113 126 59 8 133 134 100 94	48 ER 459 345 277 311 260 152 270 235 145 101	72 ER 663 576 438 438 357 216 331 308 258 170	25 30 40 50 55 55 55 65 65	0 0 -10 -15 -10 0 -5 0 5	-20 -10 -15 -10 5 -5 5 15 20	-10 -10 -10 10 0 15 10 10 15 25	15 15 10 0 0 35 25 25 35
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101018 89101100	2 3 4 5 6 7 8 9 10	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E	POS ER 58 24 8 13 12 24 16 18 5 31	24 ER 260 136 113 126 59 8 133 134 100 94 70	48 ER 459 345 277 311 260 152 270 235 145 101 120	72 ER 663 576 438 438 357 216 331 308 258 170 N/A	25 30 40 50 55 55 55 65 65 65	0 0 -10 -15 -10 0 -5 0 5	-20 -10 -15 -10 5 -5 5 15 20 25	-10 -10 -10 10 0 15 10 10 15 25	15 15 10 0 35 25 25 35 15 N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101018 89101100 89101106	2 3 4 5 6 7 8 9 10 11 12	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0	24 ER 260 136 113 126 59 8 133 134 100 94 70 68	48 ER 459 345 277 311 260 152 270 235 145 101 120 114	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A	25 30 40 50 55 55 65 65 65 65	0 0 -10 -15 -10 0 -5 0 5 5	-20 -10 -15 -10 5 -5 5 15 20 25 15	-10 -10 -10 0 15 10 10 15 25 20	15 15 10 0 35 25 25 35 15 N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101018 89101100 89101106 89101112	2 3 4 5 6 7 8 9 10 11 12 13	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A	25 30 40 50 55 55 65 65 65 65 60	0 0 -10 -15 -10 0 -5 0 5 5	-20 -10 -15 -10 5 -5 5 15 20 25 15	-10 -10 -10 0 15 10 10 15 25 20 20	15 15 10 0 35 25 25 35 15 N/A N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101100 89101100 89101112 89101118	2 3 4 5 6 7 8 9 10 11 12 13	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N 16.4N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E 115.1E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24 37	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114 223	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91 N/A	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A N/A	25 30 40 50 55 55 65 65 65 65 60 60	0 0 -10 -15 -10 0 -5 0 5 5 5	-20 -10 -15 -10 5 -5 5 15 20 25 15 10 15 -15	-10 -10 -10 0 15 10 10 15 25 20 20 -5 N/A	15 15 10 0 35 25 25 35 15 N/A N/A N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101100 89101100 89101112 89101118 89101200	2 3 4 5 6 7 8 9 10 11 12 13 14 15	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N 16.4N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E 115.1E 113.5E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24 37	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114 223 47	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91 N/A	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A N/A N/A	25 30 40 50 55 55 65 65 65 60 60 60	0 0 -10 -15 -10 0 -5 0 5 5 0 5	-20 -10 -15 -10 5 -5 5 15 20 25 15 10 15 -15	-10 -10 -10 0 15 10 10 15 25 20 20 -5 N/A	15 15 10 0 35 25 25 35 15 N/A N/A N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101100 89101100 89101112 89101118 89101200 89101206	2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N 16.4N 16.5N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E 115.1E 113.5E 112.3E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24 37 13 5	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114 223 47 93	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91 N/A N/A	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A N/A N/A N/A	25 30 40 50 55 55 65 65 65 60 60 60	0 0 -10 -15 -10 0 -5 0 5 5 0 5 5	-20 -10 -15 -10 5 -5 5 15 20 25 15 10 15 -15	-10 -10 -10 0 15 10 15 25 20 20 -5 N/A N/A	15 15 10 0 35 25 25 35 15 N/A N/A N/A N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101100 89101100 89101112 89101118 89101200 89101206 89101212	2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N 16.4N 16.5N 16.7N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E 115.1E 113.5E 112.3E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24 37 13 5	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114 223 47 93 74	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91 N/A N/A N/A	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A N/A N/A N/A	25 30 40 50 55 55 65 65 65 60 60 60 67 70	0 0 -10 -15 -10 0 -5 0 5 5 5 0 5	-20 -10 -15 -10 5 -5 5 15 20 25 15 10 15 -15	-10 -10 -10 0 15 10 10 15 25 20 -5 N/A N/A N/A	15 15 10 0 35 25 25 35 15 N/A N/A N/A N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101100 89101106 89101112 89101118 89101200 89101206 89101212 89101218	2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N 16.4N 16.5N 16.7N 17.0N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E 115.1E 113.5E 112.3E 111.1E 109.8E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24 37 13 5 13	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114 223 47 93 74	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91 N/A N/A N/A N/A	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A N/A N/A N/A N/A	25 30 40 50 55 55 65 65 65 60 60 60 65 70	0 0 -10 -15 -10 0 -5 0 5 5 5 0 5 5 0	-20 -10 -15 -10 5 -5 5 15 20 25 15 10 15 -15 10	-10 -10 -10 0 15 10 15 25 20 -5 N/A N/A N/A	15 15 10 0 35 25 25 35 15 N/A N/A N/A N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101100 89101106 89101112 89101118 89101200 89101206 89101212 89101218 89101300	2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N 16.4N 16.5N 16.7N 17.0N 17.4N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E 115.1E 113.5E 112.3E 111.1E 109.8E 108.6E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24 37 13 5 13 8 5	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114 223 47 93 74 45 N/A	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91 N/A N/A N/A N/A	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A N/A N/A N/A N/A N/A	25 30 40 50 55 55 65 65 65 60 60 60 65 70 70 65	0 0 -10 -15 -10 0 -5 0 5 5 5 0 0 0 5	-20 -10 -15 -10 5 -5 5 15 20 25 15 10 15 -15 10 20 20 N/A	-10 -10 -10 0 15 10 15 25 20 -5 N/A N/A N/A N/A	15 15 10 0 35 25 25 35 15 N/A N/A N/A N/A N/A
89100900 89100906 89100912 89100918 89101000 89101006 89101012 89101100 89101106 89101112 89101118 89101200 89101206 89101212 89101218	2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	10.3N 10.5N 10.7N 10.9N 11.1N 11.4N 11.8N 12.4N 12.9N 13.5N 14.2N 15.2N 16.0N 16.4N 16.5N 16.7N 17.0N	138.4E 136.9E 135.4E 133.7E 131.9E 130.0E 128.1E 126.2E 124.3E 122.6E 120.7E 118.8E 116.8E 115.1E 113.5E 112.3E 111.1E 109.8E	POS ER 58 24 8 13 12 24 16 18 5 31 18 0 24 37 13 5 13	24 ER 260 136 113 126 59 8 133 134 100 94 70 68 114 223 47 93 74	48 ER 459 345 277 311 260 152 270 235 145 101 120 114 91 N/A N/A N/A N/A	72 ER 663 576 438 438 357 216 331 308 258 170 N/A N/A N/A N/A N/A N/A	25 30 40 50 55 55 65 65 65 60 60 60 65 70	0 0 -10 -15 -10 0 -5 0 5 5 5 0 5 5 0	-20 -10 -15 -10 5 -5 5 15 20 25 15 10 15 -15 10	-10 -10 -10 0 15 10 15 25 20 -5 N/A N/A N/A	15 15 10 0 35 25 25 35 15 N/A N/A N/A N/A

Super Typhoon Elsie (30W)		3	<u>00h</u>	24h	48h	<u>72h</u>						
			Average # Cases	12 34	75 31	145 27	231 23					
DTG	₩ŧ	BT LAT	DOL TON	DOC ED	04.770	40 DD	30 m	TOTAL TANK	EW DD	04 55	40 FD	70 m
89101400	1	16.4N	BT LON 132.2E	POS ER	24 ER 138	48 ER 288	72 ER 392	<u>BT WN</u> 30	WW ER	24 ER 0	48 ER -15	72 ER
89101406	2	16.4N	132.2E 131.8E	8	121	288 272	353	30	5	0	-15 -15	-55 -50
89101412	3	16.3N	131.6E	13	24	272 54	333 44	35	0	-10		
89101412	4	16.2N 16.2N	131.6E	11	29	75	44	35	0	-10 -10	-40 -45	-65 -60
89101418	5	16.2N 16.1N	131.4E	17	46	62	40	40	-5	-10 -10	-43 -50	-60 -55
89101506	6	16.1N	131.2E	12	54	56	12	45	-5 -5	-10 -20	-55	-60
89101508	7	16.1N	130.9E	21	67	54	42	50	-5 -5	-20 -35		
89101512	8	16.1N	130.8E	11	48	29	71	55	_3 0	-30	~60 ~35	-55 -40
89101518	9	16.1N	130.7E	8	66	63	135	60	-5	-35	-35 -35	-40
89101606	10	16.2N	130.3E	12	65	98	201	70	-5	-35 -35	-33 -40	20
89101606	11	16.5N 16.7N	130.3E	5	69	109	201	90	-5 0	-35 -10	-10	20 60
89101618	12	16.7N 16.9N	130.0E	5	66	77	242	100	0	-10	-10 -10	75
89101700	13	16.9N	129.4E 128.8E	12	74	114	311	110	0	-40	-65	25
89101706	14	16.9N	128.1E	13	74	71	261	115	-5	-30	-63 -5	20
89101712	15	16.7N	127.5E	26	79	119	243	125	-15	-30 -30	15	20 35
89101718	16	16.4N	127.5E	26	52	93	175	125	-13 -5	-30	25	45
89101718	17	16.4N	126.4E	8	42	173	252	125	-5 -5	-30 -40	25	45
89101806	18	16.1N	125.7E	13	137	260	348	130	0	40	15	50
89101812	19	16.2N	123.7E	21	176	289	395	130	0	60	20	55
89101818	20	16.4N	124.3E	5	142	254	374	140	-5	20	30	65
89101010	21	16.6N	124.1E	8	111	220	387	140	-5	30	40	65
89101906	22	16.7N	121.5E	23	123	236	398	80	40	35	45	65
89101900	23	16.8N	119.9E	13	62	217	374	60	20	40	55	80
89101918	24	16.8N	119.9E	11	65	222	N/A	55	30	40	65	N/A
89102000	25	16.9N	117.1E	6	36	156	N/A	55 55	35	45	70	N/A
89102006	26	16.9N	116.0E	8	42	152	N/A	55	15	10	15	N/A
89102012	27	17.0N	114.8E	11	60	104	N/A	55	5	10	5	N/A
89102018	28	17.2N	113.7E	13	87	N/A	N/A	55	0	15	N/A	N/A
89102100	29	17.5N	112.5E	8	45	N/A	N/A	55	Ö	5	N/A	N/A
89102106	30	17.8N	111.4E	6	70	N/A	N/A	50	ő	5	N/A	N/A
89102112	31	18.2N	109.9E	11	54	N/A	N/A	40	ő	10	N/A	N/A
89102118	32	18.3N	108.5E	13	N/A	N/A	N/A	35	5	N/A	N/A	N/A
89102200	33	18.3N	107.2E	12	N/A	N/A	N/A	35	Ö	N/A	N/A	N/A
89102206	34	18.3N	105.9E	29	N/A	N/A	N/A	35	-5	N/A	N/A	N/A
Typhoon Fo	errest	(31W)	Average	<u>00h</u> 22 30	93		318					
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89102200	1	8.9N	150.2E	34	124	248	359	30	0	0	0	15
89102206	2	9.8N	149.5E	5	109	213	304	30	ŏ	-5	5	20
89102212	3	10.7N	149.0E	13	122	223	303	35	0	-5	5	30
89102218	4	11.5N	148.5E	34	104	180	248	40	0	ō	10	30
89102300	5	12.2N	148.1E	8	55	100	165	45	0	5	15	20
89102306	6	12.9N	147.6E	12	72	105	212	50	ō	10	20	45
89102312	7	13.4N	147.0E	13	64	133	240	55	ŏ	10	15	45
89102318	8	13.8N	146.4E	- 8	64	122	253	60	Ō	10	10	40
89102400	ğ	14.3N	145.8E	13	72	168	313	60	ō	-5	0	5
89102406	10	15.0N	145.1E	16	36	86	216	60	Ö	-5	5	5
89102412	11	15.6N	144.4E	49	66	42	198	65	ŏ	-5	5	5
89102418	12	16.1N	143.7E	24	164	282	361	70	Ö	Ö	20	30
89102500	13	16.6N	142.8E	6	96	210	358	75	-5	Ö	15	20
89102506	14	17.2N	141.9E	5	49	98	283	80	-5	5	15	20
89102512	15	17.9N	141.0E	8	53	124	386	85	Ö	20	20	25
89102518	16	18.6N	140.3E	26	109	186	513	90	Ö	20	25	30
89102600	17	19.4N	139.6E	0	16	132	457	90	0	5	10	20

Typhoon Fo			tinued)									
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89102606	18	20.4N	139.1E	12	34	31	558	90	0	5	20	20
89102612	19 20	21.1N	138.5E	24	247	679	N/A	90	-5	-30	-30	N/A
89102618 89102700	21	21.9N 22.7N	138.1E 137.7E	20	116 70	261 139	N/A	90	-5	-15	-20	N/A
89102706	22	22.7N 23.6N	137.7E	0 18	33		N/A	95	0	-5	0	N/A
89102708	23	23.6N 24.6N	137.3E 137.4E	18	33 99	96 33	N/A N/A	95 95	0	0	0	N/A
89102718	23 24	24.6N 25.8N	137.4E	20	106	33 N/A	N/A N/A	95 90	0	-10 -5	-5 N/A	N/A
89102710	25	27.1N	137.3E	41	94	N/A N/A	N/A N/A	90	0	-5 5	N/A N/A	N/A
89102806	26	28.4N	130.1E	33	155	N/A	N/A	80	0	0	N/A N/A	N/A N/A
89102812	27	29.9N	141.4E	43	180	N/A	N/A	75	0	-5	N/A N/A	N/A
89102818	28	31.7N	144.3E	70	N/A	N/A	N/A	70	0	N/A	N/A	N/A
89102900	29	33.9N	144.3E	50	N/A	N/A	N/A	60	0	N/A	N/A	N/A
89102906	30	36.8N	153.0E	48	N/A	N/A	N/A	60	-10	N/A	N/A	N/A
03102300	55	30.01	100.02		.,,	.,,	11,11	•	10	11/11	11/14	M/A
Typhoon Ga	v (32W	n		<u>00h</u>	24h	<u>48h</u>	72h					
-25	2 ,	•	Average	11		132						
			# Cases	34		25						
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89110200	1	8.2N	102.2E	5	63	N/A	N/A	35	-10	-35	N/A	N/A
89110206	2	8.3N	102.0E	17	72	54	37	35	0	-25	-50	-25
89110212	3	8.7N	101.9E	13	46	43	111	35	0	-45	-20	-35
89110218	4	9.1N	101.8E	0	24	94	205	45	-10	-50	-25	-35
89110300	5	9.3N	101.5E	8	16	79	200	65	-20	-45	-35	-30
89110306	6	9.8N	101.2E	0	26	90	224	75	-20	-30	-25	-15
89110312	7	10.2N	100.8E	0	37	123	264	90	-30	-5	-20	-10
89110318	8	10.4N	100.3E	0	31	112	253	95	-30	-10	-15	-5
89110400	9	10.5N	99.9E	11	100	213	283	100	-30	5	5	10
89110406	10	10.7N	99.2E	17	102	206	288	100	-15	0	5	5
89110412	11	11.2N	98.3E	0	59	204	291	65	15	5	15	10
89110418	12	11.3N	97.5E	11	47	181	274	75	5	5	15	5
89110500	13	11.4N	96.8E	13	91	210	294	85	0	5	10	0
89110506	14	11.7N	95.9E	8	121	211	279	90	0	5	5	-10
89110512	15	12.0N	94.8E	8	113	169	196	95	-5	5	0	-15
89110518	16	12.2N	93.8E	18	100	149	168	95	-5	5	-5	-20
89110600	17	12.4N	92.6E	17	83	110	151	95	-5	-10	-35	-10
89110606	18	13.0N	91.4E	38	67	102	173	95	- 5	-25	-55	25
89110612	19 20	13.4N	90.2E	0	24	51	158	95	-10	-35	-65	5
89110618 89110700	21	13.7N	89.1E	11	21 25	77	162	95 100	-5 0	-35	-75 -5	0
1177111		13.9N	88.1E	0		105	159	100	0	-20		10
89110706 89110712	22 23	14.2N 14.5N	87.1E	0	56 77	137	N/A	105	-5 10	-30 -35	25	N/A
89110712	23 24	14.5N 14.6N	86.1E 85.0E	0		141	N/A	110	-10 -5	-55	15	N/A N/A
89110718	25	14.6N 14.6N		8	79	128	N/A	115	-5 -5		20 10	
89110806	26	14.6N	83.8E 82.6E	13	77 30	121	N/A	120 130		-20 35	25	N/A N/A
89110808	27	14.5N 14.7N	81.5E	5 18	75	180 N/A	N/A N/A	135	10 10	35 35	N/A	N/A N/A
89110812	28	14.7N 14.8N	80.4E	6	102	N/A N/A	N/A N/A	140	0	20	N/A N/A	N/A N/A
89110900	29	14.6N 15.1N	79.1E	13	130	N/A	N/A	90	15	30	N/A	N/A
89110906	30	15.1N 15.4N	77.7E	18	109	N/A	N/A	45	45	20	N/A	N/A
89110912	31	15.4N 15.8N	76.5E	16	N/A	N/A	N/A	35	35	N/A	N/A	N/A
89110918	32	16.6N	75.5E	43	N/A	N/A	N/A	25	25	N/A	N/A	N/A
89111000	33	17.6N	74.6E	49	N/A	N/A	N/A	20	15	N/A	N/A	N/A
89111006	34	18.1N	74.0E	0	N/A	N/A	N/A	15	15	N/A	N/A	N/A

Typhoon E	tunt (33)	Ŧ)	Average # Cases	00h 14 27		173	207					
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89111612	1	12.0N	132.7E	18	92	250	434	25	0	5	-10	-40
89111618	2	12.0N	131.7E	18	165	309	486	25	Ö	ō	-20	-40
89111700	3	11.9N	131.0E	31	128	242	402	25	Ö	-5	-30	-40
89111706	4	11.8N	130.6E	24	102	181	250	30	Ō	-15	-45	-40
89111712	5	11.8N	130.0E	13	105	222	290	30	0	-20	-40	-40
89111718	6	12.1N	129.4E	17	109	260	306	35	0	-15	-35	-35
89111800	7	12.5N	128.9E	18	109	217	278	40	0	-15	-25	-25
89111806	8	13.0N	128.4E	6	113	245	300	50	0	-20	-20	-10
89111812	9	13.5N	127.9E	13	119	285	278	60	0	-15	-30	-20
89111818	10	14.0N	127.5E	24	55	133	119	65	0	-15	-15	-30
89111900	11	14.3N	127.2E	8	107	146	157	75	0	0	0	-5
89111906	12	14.6N	127.0E	8	84	116	121	90	0	10	10	15
89111912	13	15.0N	127.0E	5	35	52	42	90	0	10	10	25
89111918	14	15.4N	126.9E	11	47	67	36	90	0	10	0	30
89112000 89112006	15 16	15.4N 15.4N	126.5E 126.1E	18 5	86 91	80 103	57 63	90 90	0	0	25 40	30 35
89112008	17	15.4N 15.3N	125.7E	8	95	98	63	90	0	0	40	35 40
89112018	18	15.3N	125.7E	16	81	89	84	90	0	-5	35	35
89112110	19	15.2N	124.2E	5	106	179	174	90	0	-5	30	25
89112106	20	15.1N	123.3E	13	117	191	N/A	90	ő	15	30	N/A
89112112	21	15.2N	122.5E	11	123	212	N/A	90	Ö	25	30	N/A
89112118	22	15.5N	121.7E	18	88	136	N/A	90	-5	25	25	N/A
89112200	23	15.9N	121.1E	8	69	171	N/A	75	0	20	30	N/A
89112206	24	16.1N	120.3E	35	140	N/A	N/A	55	0	15	N/A	N/A
89112212	25	16.3N	119.6E	11	75	N/A	N/A	40	0	0	N/A	N/A
89112218	26	16.4N	119.2E	12	N/A	N/A	N/A	35	0	N/A	N/A	N/A
89112300	27	16.5N	118.7E	5	N/A	N/A	N/A	30	0	N/A	N/A	N/A
Super Typ	hoon Im	na (34W)	Average	00h 18 . 39	24h 112 37	48h 212 27	72h 394 23					
			# Cases	. 39	112 37	212 27	394 23			04.77		20
DTG	<u>W</u> #	BT_LAT	# Cases BT LON	18 . 39 POS ER	112 37 24 ER	212 27 48 ER	394 23 72 ER	BT WN	WW ER	24_ER	48 ER	72 ER
<u>DTG</u> 89112106 1	<u>₩#</u> 1	BT LAT 17.7N	# Cases BT LON 164.8E	18 . 39 POS ER 11	112 37 24 ER 181	212 27 48 ER N/A	394 23 <u>72 ER</u> N/A	<u>BT WN</u> 25	-5	0	N/A	N/A
DTG 89112106† 89112118†	₩# 1 2	BT LAT 17.7N 19.2N	# Cases BT LON 164.8E 163.0E	18 . 39 POS ER 11 30	112 37 24 ER 181 120	212 27 48 ER N/A N/A	394 23 <u>72 ER</u> N/A N/A	BT WN 25 25	-5 0	0	N/A N/A	N/A N/A
DTG 89112106† 89112118† 89112206†	₩# 1 2 3	BT LAT 17.7N 19.2N 19.7N	# Cases BT LON 164.8E 163.0E 162.3E	18 . 39 POS ER 11 30 12	112 37 24 ER 181 120 160	212 27 48 ER N/A N/A N/A	394 23 <u>72 ER</u> N/A N/A N/A	BT WN 25 25 25 25	-5 0 -5	0 0 -10	N/A N/A N/A	N/A N/A N/A
DTG 89112106† 89112118† 89112206† 89112500*	W# 1 2 3 4	BT LAT 17.7N 19.2N 19.7N 13.7N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E	18 . 39 POS ER 11 30 12 26	112 37 24 ER 181 120 160 55	212 27 48 ER N/A N/A N/A	394 23 72 ER N/A N/A N/A	BT WN 25 25 25 25 30	-5 0 -5 -5	0 0 -10 0	N/A N/A N/A N/A	N/A N/A N/A N/A
DTG 89112106† 89112118† 89112206† 89112500*	₩# 1 2 3 4 5	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E	18 . 39 POS ER 11 30 12 26 26	112 37 24 ER 181 120 160 55 205	212 27 48 ER N/A N/A N/A N/A	394 23 72 ER N/A N/A N/A N/A	BT WN 25 25 25 25 30 30	-5 0 -5 -5	0 0 -10 0 -5	N/A N/A N/A N/A	N/A N/A N/A N/A
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112600†	₩# 1 2 3 4 5	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E	18 . 39 POS ER 11 30 12 26 26 17	112 37 24 ER 181 120 160 55 205 110	212 27 48 ER N/A N/A N/A N/A N/A	394 23 72 ER N/A N/A N/A N/A N/A	BT WN 25 25 25 30 30 30	-5 0 -5 -5 0	0 0 -10 0 -5 -15	N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112600†	₩# 1 2 3 4 5 6 7	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E	18 . 39 POS ER 11 30 12 26 26 17 16	112 37 24 ER 181 120 160 55 205 110 94	212 27 48 ER N/A N/A N/A N/A N/A N/A	394 23 72 ER N/A N/A N/A N/A N/A N/A 213	BT WN 25 25 25 30 30 30 35	-5 0 -5 -5	0 0 -10 0 -5 -15	N/A N/A N/A N/A	N/A N/A N/A N/A N/A N/A
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112600†	₩# 1 2 3 4 5	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E	18 . 39 POS ER 11 30 12 26 26 17	112 37 24 ER 181 120 160 55 205 110 94 117	212 27 48 ER N/A N/A N/A N/A N/A N/A 144 168	394 23 72 ER N/A N/A N/A N/A N/A 213 249	BT WN 25 25 25 30 30 30 35 35	-5 0 -5 -5 0 0	0 0 -10 0 -5 -15	N/A N/A N/A N/A N/A N/A	N/A N/A N/A N/A N/A
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112600† 89112612	₩# 1 2 3 4 5 6 7 8	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E	18 . 39 POS ER 11 30 12 26 26 17 16 24	112 37 24 ER 181 120 160 55 205 110 94	212 27 48 ER N/A N/A N/A N/A N/A N/A	394 23 72 ER N/A N/A N/A N/A N/A N/A 213	BT WN 25 25 25 30 30 30 35	-5 0 -5 -5 0 0 -5 0	0 0 -10 0 -5 -15 -15	N/A N/A N/A N/A N/A -25	N/A N/A N/A N/A N/A -45
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112600 89112612 89112618	₩# 1 2 3 4 5 6 7 8 9	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E	18 . 39 POS ER 11 30 12 26 26 17 16 24	112 37 24 ER 181 120 160 55 205 110 94 117 32	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163	BT WN 25 25 25 30 30 30 35 35 45	-5 0 -5 -5 0 0 -5	0 0 -10 0 -5 -15 -15 -10 5	N/A N/A N/A N/A N/A -25 -20	N/A N/A N/A N/A N/A -45 -60
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112700 89112706	W# 1 2 3 4 5 6 7 8 9 10 11 12	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E	18 39 POS ER 11 30 12 26 26 17 16 24 8	112 37 24 ER 181 120 160 55 205 110 94 117 32 64	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125 172	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163 186	BT WN 25 25 25 30 30 30 35 45 45 50 55	-5 0 -5 -5 0 0 -5 0	0 0 -10 0 -5 -15 -15 -10 5	N/A N/A N/A N/A N/A -25 -20 -10	N/A N/A N/A N/A N/A -45 -60 -25
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112700 89112706 89112712	W# 1 2 3 4 5 6 7 8 9 10	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125 172 236	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163 186 251	BT WN 25 25 25 30 30 30 35 35 45 45 50	-5 0 -5 -5 0 0 -5 0	0 0 -10 0 -5 -15 -15 -10 5 0	N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112700 89112706 89112712 89112718 89112718	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N 10.0N 10.1N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125 172 236 152 181 177	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163 186 251 174 186 142	BT WN 25 25 25 30 30 30 35 35 45 45 60 65	-5 0 -5 -5 0 0 -5 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0	N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112700 89112706 89112712 89112718 89112718 89112800 89112806	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 10.2N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E 141.9E 141.0E 140.0E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8 8	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92	BT WN 25 25 25 30 30 30 35 45 45 50 55 60 65 70	-5 0 -5 -5 0 0 -5 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15	N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112700 89112706 89112712 89112718 89112718 89112800 89112806 89112812	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 10.8N 11.3N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E 141.9E 140.0E 138.9E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8 8	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105	BT WN 25 25 25 30 30 30 35 35 45 45 50 55 60 65 70 75	-5 0 -5 -5 0 0 -5 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35	N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112706 89112706 89112712 89112718 89112718 89112800 89112812 89112818 89112900	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 10.8N 11.3N 11.8N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E 141.9E 141.0E 140.0E 138.9E 137.8E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8 8	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107	BT WN 25 25 25 30 30 30 35 35 45 45 50 55 60 65 70 75 100	-5 0 -5 -5 0 0 -5 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15	N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15
DTG 89112106† 89112118† 89112206† 89112512† 89112612 89112612 89112700 89112706 89112712 89112718 89112718 89112800 89112812 89112818 89112818 891128100 891128100	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 10.8N 11.3N 11.8N 12.3N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E 141.9E 141.0E 140.0E 138.9E 137.8E 136.7E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8 8	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26 32 37	212 27 48 ER N/A N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34 36	394 23 72 ER N/A N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107 125	BT WN 25 25 25 30 30 30 35 35 45 45 50 65 70 75 100 105	-5 0 -5 -5 0 0 -5 0 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15	N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15 -5
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112706 89112706 89112712 89112718 89112718 89112800 89112812 89112818 89112818 89112900 89112906 89112912	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 10.8N 11.3N 11.8N 12.3N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E 141.9E 141.0E 140.0E 138.9E 137.8E 136.7E 135.7E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8 6 11 0 5	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26 32 37 48	212 27 48 ER N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34 36 115	394 23 72 ER N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107 125 256	BT WN 25 25 25 30 30 30 35 45 45 50 55 60 65 70 75 100 105	-5 0 -5 -5 0 0 -5 0 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15 -15	N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5 -5	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15 -5 -5
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112700 89112706 89112712 89112718 89112718 89112800 89112812 89112818 89112818 89112900 89112906 89112912	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 10.8N 11.3N 11.8N 12.3N 12.6N 12.9N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E 141.9E 141.0E 140.0E 138.9E 137.8E 136.7E 135.0E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8 8 6 11 0 5	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26 32 37 48 40	212 27 48 ER N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34 36 115 77	394 23 72 ER N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107 125 256 250	BT WN 25 25 25 30 30 30 35 45 45 50 55 60 65 70 75 100 105 105 125	-5 0 -5 -5 0 0 -5 0 0 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15 -15 -15	N/A N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5 -5 -40 -30	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15 -5 -25 -25
DTG 89112106† 89112118† 89112206† 89112512† 89112612 89112612 89112706 89112706 89112718 89112708 89112806 89112812 89112818 89112906 89112912 89112918	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.4N 10.1N 10.0N 10.1N 10.2N 10.2N 10.4N 11.3N 11.3N 11.8N 12.3N 12.6N 12.9N 13.2N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 145.2E 144.5E 144.0E 143.4E 142.7E 141.9E 141.0E 140.0E 138.9E 137.8E 136.7E 135.7E 135.0E 134.2E	18 39 POS ER 11 30 12 26 26 17 16 24 8 0 41 18 8 8 6 11 0 5	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26 32 37 48 40 36	212 27 48 ER N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34 36 115 77	394 23 72 ER N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107 125 256 250 358	BT WN 25 25 25 30 30 30 35 45 45 50 65 70 75 100 105 105 125 140	-5 0 -5 -5 0 0 -5 0 0 0 0 0 0 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15 -15 -15 -20 -40 -5	N/A N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5 -5 -40 -30 0	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15 -5 -25 -25
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112700 89112706 89112718 89112718 89112800 89112818 89112818 89112900 89112912 89112918 89112918 89113000 89113006	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.4N 10.1N 10.0N 10.1N 10.2N 10.4N 10.2N 10.4N 11.3N 11.3N 11.8N 12.3N 12.6N 12.9N 13.2N 13.5N	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 144.5E 144.5E 144.0E 142.7E 141.9E 141.0E 138.9E 136.7E 135.7E 135.0E 134.2E 133.4E	18 39 POS ER 11 30 12 26 26 27 16 24 8 0 41 18 8 8 8 6 11 0 5	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26 32 37 48 40	212 27 48 ER N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34 36 115 77	394 23 72 ER N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107 125 256 250	BT WN 25 25 25 30 30 30 35 45 45 50 55 60 65 70 75 100 105 105 125	-5 0 -5 -5 0 0 -5 0 0 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15 -15 -15	N/A N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5 -5 -40 -30	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15 -5 -25 -25
DTG 89112106† 89112118† 89112206† 89112500* 89112512† 89112612 89112618 89112706 89112718 89112718 89112718 89112806 89112812 89112818 89112906 89112912 89112918 89113000 89113006 †	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 Tropical	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 11.3N 11.8N 11.3N 11.8N 12.3N 12.6N 12.9N 13.5N Depressi	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 144.5E 144.5E 144.0E 142.7E 141.9E 141.0E 138.9E 136.7E 135.7E 135.0E 134.2E 133.4E	18 39 POS ER 11 30 12 26 26 27 16 24 8 0 41 18 8 8 8 6 11 0 5	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26 32 37 48 40 36	212 27 48 ER N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34 36 115 77	394 23 72 ER N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107 125 256 250 358	BT WN 25 25 25 30 30 30 35 45 45 50 65 70 75 100 105 105 125 140	-5 0 -5 -5 0 0 -5 0 0 0 0 0 0 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15 -15 -15 -20 -40 -5	N/A N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5 -5 -40 -30 0	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15 -5 -25 -25
DTG 89112106† 89112106† 89112206† 89112500* 89112512† 89112612 89112618 89112706 89112718 89112718 89112718 89112806 89112812 89112818 89112906 89112912 89112918 89113000 89113006 †	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22	BT LAT 17.7N 19.2N 19.7N 13.7N 12.8N 11.7N 10.4N 10.1N 10.0N 10.0N 10.1N 10.2N 10.4N 11.3N 11.8N 11.3N 11.8N 12.3N 12.6N 12.9N 13.5N Depressi	# Cases BT LON 164.8E 163.0E 162.3E 150.6E 148.4E 147.0E 145.9E 144.5E 144.5E 144.0E 142.7E 141.9E 141.0E 138.9E 136.7E 135.7E 135.0E 134.2E 133.4E	18 39 POS ER 11 30 12 26 26 27 16 24 8 0 41 18 8 8 8 6 11 0 5	112 37 24 ER 181 120 160 55 205 110 94 117 32 64 143 74 130 135 71 26 32 37 48 40 36	212 27 48 ER N/A N/A N/A N/A 144 168 125 172 236 152 181 177 100 84 34 36 115 77 112 206	394 23 72 ER N/A N/A N/A N/A 213 249 163 186 251 174 186 142 92 105 107 125 256 250 358	BT WN 25 25 25 30 30 30 35 45 45 50 65 70 75 100 105 105 125 140	-5 0 -5 -5 0 0 -5 0 0 0 0 0 0 0 0 0 0	0 0 -10 0 -5 -15 -15 -10 5 0 0 -20 -20 -15 -35 -15 -15 -15 -20 -40 -5	N/A N/A N/A N/A N/A N/A N/A -25 -20 -10 -15 -15 -30 -40 -40 -30 -45 -5 -5 -40 -30 0	N/A N/A N/A N/A N/A -45 -60 -25 -25 -30 -25 -5 5 10 -15 -5 -25 -25

Comor Theo	boon T	/2 ATUS										
DTG	hoon Izma <u>W#</u>	BT LAT	continued BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89113012	23	13.8N	132.5E	5	100	235	546	140	0	20	20	10
89113018	24	14.1N	132.0E	12	54	238	590	135	Ö	10	0	-10
89120100	25	14.3N	131.6E	8	105	343	782	120	5	0	-5	0
89120106	26	14.5N	131.2E	32	123	428	906	115	Ö	-5	0	10
89120112	27	14.7N	131.0E	5	132	481	933	110	Ö	-5	-5	15
89120118	28	14.9N	130.7E	11	135	498	946	105	Ō	-10	-5	25
89120200	29	15.2N	130.6E	11	195	614	1027	100	Ō	-10	ŏ	30
89120206	30	15.6N	130.7E	23	196	516	N/A	95	-5	-15	0	N/A
89120212	31	16.1N	130.9E	8	13	31	N/A	90	0	5	15	N/A
89120218	32	16.7N	131.3E	21	43	117	N/A	90	0	0	25	N/A
89120300	33	17.2N	131.9E	16	78	108	N/A	85	0	-5	35	N/A
89120306	34	18.1N	132.8E	11	30	N/A	N/A	80	0	10	N/A	N/A
89120312	35	19.1N	133.7E	8	94	N/A	N/A	75	0	15	N/A	N/A
89120318	36	20.1N	134.5E	21	189	N/A	N/A	75	0	15	N/A	N/A
89120400	37	21.0N	136.1E	21	694	N/A	N/A	65	0	20	N/A	N/A
89120406	38	21.7N	137.4E	43	N/A	N/A	N/A	55	5	N/A	N/A	N/A
89120412	39	22.5N	138.8E	131	N/A	N/A	N/A	45	0	N/A	N/A	N/A
Tropical	Depression	3.5W		00h	24h	<u>48h</u>	<u>72h</u>					
			Average	73	212	439	N/A					
			# Cases	9	5	1	0					
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89120700	1	11.0N	139.1E	106	232	439	N/A	30	-5	5	25	N/A
89120706	2 3	10.9N	138.7E	40	46	N/A	N/A	30	0	10	N/A	N/A
89120712 89120718	4	10.9N 11.0N	138.4E 138.2E	79 97	129 272	N/A	N/A	30	0	10	N/A	N/A
89120718	5	11.0N 11.1N	138.2E	144	381	N/A N/A	N/A N/A	30 30	0	10 15	N/A N/A	N/A
89120806	6	11.1N 11.5N	138.0E	64	N/A	N/A N/A	N/A N/A	30	0	N/A	N/A N/A	N/A N/A
89120812	7	12.2N	138.3E	61	N/A	N/A	N/A	30	0	N/A N/A	N/A N/A	N/A N/A
89120818	8	12.8N	138.7E	5	N/A	N/A	N/A	30	Ö	N/A	N/A	N/A
89120900	9	13.5N	139.0E	61	N/A	N/A	N/A	25	Ö	N/A	N/A	N/A
					,		,			,		
Markage T	(2 <i>6</i> 77)			001	0.41	401	701					
Typhoon J	ack (36W)			<u>00h</u>	24h	48h	<u>72h</u>					
			Average # Cases	28 21	· 95 20	167 18	317 14					
			# Cases	21	20	10	14					
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89122300	1	10.2N	152.7E	6	98	N/A	N/A	30	-5	-35	N/A	N/A
89122306	2	10.9N	151.9E	0	108	191	338	35	0	-20	-50	-55
89122312	3	11.5N	151.2E	13	133	258	458	45	0	-25	-50	-60
89122318	4	11.9N	150.9E	47	6	58	215	55	0	-15	-40	-55
89122400	5	12.2N	150.5E	13	48	105	304	65	0	-15	-35	-25
89122406	6	12.5N	150.1E	8	26	138	336	70	-5	-25	-35	-10
89122412	7	12.7N	149.6E	18	37	168	355	80	-5	-20	-20	25
89122418	8	12.8N	149.2E	8	102	217	352	90	0	-25	-15	45
89122500	9	12.9N	148.8E	0	94	222	234	100	-5 -	-10	15	75
89122506 89122512	10 11	13.4N	148.5E	18	87	212	168	110	-5 -10	-5 -5	30 60	80 95
89122512	11 12	13.6N 13.7N	148.3E	8 11	88 81	198 159	193 303	120 125	-10 -5	-5 5	60 75	85 80
89122518	13	13.7N 13.8N	148.2E 148.1E	8	81 75	159 56	303 303	125	-5 0	20	75 85	75
89122606	14	13.8N	148.0E	5	56	36	371	125	~5	30	85	75 75
89122612	15	13.8N	148.0E	5	51	139	511	125	-5	50	85	80
89122618	16	13.7N	147.9E	13	44	200	N/A	120	-5	65	75	N/A
89122700	17	13.5N	147.7E	11	67	198	N/A	105	ő	60	65	N/A
89122706	18	13.4N	147.4E	0	165	194	N/A	90	ō	40	40	N/A
89122712	19	13.5N	147.0E	46	209	259	N/A	65	10	20	25	N/A
89122718	20	14.0N	146.5E	120	328	N/A	N/A	45	10	10	N/A	N/A
89122800	20	14.014	140.00	120	320	M/B	H/A	10			14/11	.,,

7.2.2 NORTH INDIAN OCEAN

This section includes verification statistics for each warning in the North Indian

Ocean during 1989. Pre- and post- warning best track positions are not printed, but are available on floppy diskettes by request.

JIWC FORECAST TRACK AND INTENSITY ERRORS	BY	WARNING	
--	----	---------	--

Tropical	Cyclone	01B	Average # Cases	00h 23 14	24h 106 11	48h N/A 0	72h N/A 0					
<u>DTG</u>	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW_ER	24 ER	48 ER	72 ER
89052312	1	18.1N	89.8E	30	169	N/A	N/A	30	0	10	N/A	N/A
89052318	2	18.7N	89.5E	11	135	N/A	N/A	30	0	5	N/A	N/A
89052400	3	19.4N	89.0E	28	188	N/A	N/A	30	0	-15	N/A	N/A
89052406	4	19.6N	88.6E	37	N/A	N/A	N/A	35	-5	N/A	N/A	N/A
89052412	5	19.6N	88.3E	32	139	N/A	N/A	35	-5	-15	N/A	N/A
89052418	6	19.5N	87.9E	37	78	N/A	N/A	40	-5	-5	N/A	N/A
89052500	7	19.5N	87.8E	13	71	N/A	N/A	45	0	-20	N/A	N/A
89052506	8	19.6N	87.8E	11	51	N/A	N/A	45	5	-20	N/A	N/A
89052512	9	19.8N	87.9E	29	26	N/A	N/A	45	-5	-10	N/A	N/A
89052518	10	20.2N	87.6E	11	5 5	N/A	N/A	45	0	-5	N/A	N/A
89052600	11	20.3N	'87.5E	8	111	N/A	N/A	50	-5	0	N/A	N/A
89052606	12	20.7N	87.4E	45	139	N/A	N/A	50	-5	0	N/A	N/A
89052612	13	21.3N	87.3E	23	N/A	N/A	N/A	55	-10	N/A	N/A	N/A
89052618	14	21.9N	87.2E	8	N/A	N/A	N/A	50	5	N/A	N/A	N/A
Tropical Cyclone 02A		Average # Cases	00h 41 5	24h 134 1	48h N/A 0	72h N/A 0						
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	72 ER	BT WN	WW ER	24 ER	48 ER	72 ER
89061206	1	21.4N	65.7E	39	134	N/A	N/A	35	0	25	N/A	N/A
89061212	2	21.3N	64.9E	33	N/A	N/A	N/A	35	0	N/A	N/A	N/A
89061218	3	21.3N	64.2E	45	N/A	N/A	N/A	35	0	N/A	N/A	N/A
89061300	4	21.4N	63.8E	68	N/A	N/A	N/A	30	5	N/A	N/A	N/A
89061306	5	21.5N	63.4E	20	N/A	N/A	N/A	25	0	N/A	N/A	N/A

Tropical Cyclone 32W (Gay): Please see page 237 for data.

7.2.3 SOUTHERN HEMISPHERE

This section includes verification statistics for each warning in the South Indian and western South Pacific Oceans from 1 July

1988 to 30 June 1989. Pre- and post- warning best track positions are not printed, but are available on floppy diskettes by request.

JIWC FORECAST TRACK AND INTENSITY ERRORS BY WARNING

Average	Tropical	Cvclone	01S (Adel	inina)	00h	24h	48h				
		-,	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	•							
DTG				_							
Selioloo				. 00000	_	•	·				
SB110100	DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 ER	48 ER
Selicition	88110100		8.75	76.7E		48	281	50	-5		-10
Seliozoo	88110112	2	9.1S	76.6E	62	133	407	55	5	5	0
Rel10300 S	88110200	3	9.85	76.7E	13	264	562	55	. 0	-10	-5
88110312 6 14.0S 80.4E 16 210 576 75 00 -10 -10 88110400 7 14.6S 81.7E 87 367 N/A 75 -10 -5 N/A 88110412 8 14.3S 82.7E 211 579 N/A 55 -20 -15 N/A 88110418 9 14.0S 83.2E 275 N/A N/A 55 -30 N/A	88110212	4	11.0S	77.6E	21	146	175	65	0	10	25
Selidado	88110300	5	12.78	79.0E	35	131	300	75	0	10	45
Reliquia	88110312	6	14.0S	80.4E	16	210	576	75	0	-10	-10
Result R	88110400	7	14.65	81.7E	87	367	N/A	75	-10	-5	N/A
Tropical Cyclone 02S (Barisaona)	88110412	8	14.38	82.7E	211	579	N/A	65	-20	-15	N/A
Tropical Cyclone 028 (Barisaona)	88110418	9	14.08	83.2E	275	N/A	N/A	55	-30	N/A	N/A
Note										•	- •
Note											
Note											
Cases 26	Tropical	Cyclone	02S (Bari	saona)	<u>00h</u>	24h	48h				
DTG W# BT LAT BT LON POS ER 24 ER 48 ER BT WN WW ER 24 WE 48 WE 88110806 1 6.9S 96.3E 24 25 90 45 -10 -15 -5 88110916 3 6.9S 94.5E 0 78 130 55 0 10 20 88110912 4 6.7S 94.1E 13 74 131 55 0 10 20 88111010 5 6.3S 93.0E 5 26 48 55 0 10 -25 88111012 6 6.1S 92.2E 23 37 96 55 -5 -10 -25 88111110 7 6.1S 91.2E 30 111 173 55 -5 -10 -25 88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 881120	-	_	•	Average	25	98					
DTG W# BT LAT BT LON POS ER 24 ER 48 ER BT WN WW ER 24 WE 48 WE 88110806 1 6.9S 96.3E 24 25 90 45 -10 -15 -5 88110916 3 6.9S 94.5E 0 78 130 55 0 10 20 88110912 4 6.7S 94.1E 13 74 131 55 0 10 20 88111000 5 6.3S 93.0E 5 26 48 55 0 -10 -25 88111100 7 6.1S 92.2E 23 37 96 55 -5 -10 -25 881111100 7 6.1S 91.2E 30 111 173 55 -5 -10 -25 88111210 9 6.7S 88.4E 26 96 231 65 0 5 5 8811				# Cases	26	24	22				
88110806 1 6.9S 96.3E 24 25 90 45 -10 -15 -5 88110818 2 6.9S 95.4E 5 45 112 55 -5 5 15 88110906 3 6.9S 94.5E 0 78 130 55 0 10 20 88110912 4 6.7S 94.1E 13 74 131 55 0 10 20 88111001 6 6.1S 92.2E 23 37 96 55 -5 -10 -25 88111100 7 6.1S 91.2E 30 111 173 55 -5 -20 -25 88111120 9 6.7S 88.4E 26 96 231 65 0 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111210											
88110818 2 6.9S 95.4E 5 45 112 55 -5 5 15 88110906 3 6.9S 94.5E 0 78 130 55 0 10 20 88110912 4 6.7S 94.1E 13 74 131 55 0 10 20 88111000 5 6.3S 93.0E 5 26 48 55 0 -10 -25 88111012 6 6.1S 92.2E 23 37 96 55 -5 -10 -25 88111100 7 6.1S 91.2E 30 111 173 55 -5 -20 -25 88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 88111210 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111210 10	DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
88110906 3 6.9S 94.5E 0 78 130 55 0 10 20 88110912 4 6.7S 94.1E 13 74 131 55 0 10 20 88111000 5 6.3S 93.0E 5 26 48 55 0 -10 -25 8811100 7 6.1S 92.2E 23 37 96 55 -5 -10 -25 88111100 7 6.1S 91.2E 30 111 173 55 -5 -20 -25 88111120 9 6.7S 88.4E 26 96 231 65 0 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -25 88111400 <t< td=""><td>88110806</td><td></td><td>6.9S</td><td>96.3E</td><td>24</td><td>25</td><td>90</td><td>45</td><td>-10</td><td>-15</td><td>-5</td></t<>	88110806		6.9S	96.3E	24	25	90	45	-10	-15	-5
88110912 4 6.7S 94.1E 13 74 131 55 0 10 20 88111000 5 6.3S 93.0E 5 26 48 55 0 -10 -25 88111012 6 6.1S 92.2E 23 37 96 55 -5 -10 -25 88111110 7 6.1S 91.2E 30 111 173 55 -5 -20 -25 88111210 9 6.7S 88.4E 26 96 231 65 0 5 5 5 88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -25 88111400 13 10.1S 81.1E 76 104 97 65 0	88110818	2	6.98	95.4E	5	45	112	5 5	-5	5	15
88111000 5 6.3S 93.0E 5 26 48 55 0 -10 -25 88111012 6 6.1S 92.2E 23 37 96 55 -5 -10 -25 88111100 7 6.1S 91.2E 30 111 173 55 -5 -20 -25 88111110 8 6.4S 90.1E 18 90 156 55 -10 -25 -30 88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -40 88111410 13 10.1S 81.1E 76 104 97 65 0 -10 -25 88111410 14 10.4S 78.9E 30 96 193 75 0 5	88110906	3	6.9S	94.5E	0	78	130	55	0	10	20
88111012 6 6.1S 92.2E 23 37 96 55 -5 -10 -25 88111100 7 6.1S 91.2E 30 111 173 55 -5 -20 -25 88111210 8 6.4S 90.1E 18 90 156 55 -10 -25 -30 88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -40 88111312 12 9.2S 83.7E 18 166 259 65 0 -10 -25 88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -5 88111500 15 11.0S 77.1E 36 136 186 85 -20 -2	88110912	4	6.7S	94.1E	13	74	131	55	0	10	20
88111100 7 6.1S 91.2E 30 111 173 55 -5 -20 -25 88111112 8 6.4S 90.1E 18 90 156 55 -10 -25 -30 88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -40 88111312 12 9.2S 83.7E 18 166 259 65 0 -10 -25 88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -5 88111412 14 10.4S 78.9E 30 96 193 75 0 5 0 88111500 15 11.0S 77.1E 36 136 186 85 -20 -25<	88111000	5	6.35	93.0E	5	26	48	55	0	-10	-25
88111112 8 6.4S 90.1E 18 90 156 55 -10 -25 -30 88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -40 88111312 12 9.2S 83.7E 18 166 259 65 0 -10 -40 88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -25 88111412 14 10.4S 78.9E 30 96 193 75 0 5 0 88111500 15 11.0S 77.1E 36 136 186 85 -20 -25 -25 88111500 17 12.9S 73.4E 25 72 139 95 -20 -	88111012	6	6.1S	92.2E	23	37	96	55	-5	-10	-25
88111200 9 6.7S 88.4E 26 96 231 65 0 5 5 88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -40 88111312 12 9.2S 83.7E 18 166 259 65 0 -10 -25 88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -25 88111412 14 10.4S 78.9E 30 96 193 75 0 5 0 88111500 15 11.0S 77.1E 36 136 186 85 -20 -25 -25 88111600 17 12.9S 73.4E 25 72 139 95 -20 -25 -45 88111700 19 14.4S 71.0E 55 116 194 90 -5 <td< td=""><td>88111100</td><td>7</td><td>6.1S</td><td>91.2E</td><td>30</td><td>111</td><td>173</td><td>55</td><td>-5</td><td>-20</td><td>-25</td></td<>	88111100	7	6.1S	91.2E	30	111	173	55	-5	-20	-25
88111212 10 7.3S 86.6E 37 66 188 65 0 0 -30 88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -40 88111312 12 9.2S 83.7E 18 166 259 65 0 -10 -25 88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -5 88111412 14 10.4S 78.9E 30 96 193 75 0 5 0 88111500 15 11.0S 77.1E 36 136 186 85 -20 -25 -25 88111512 16 12.1S 75.0E 5 78 229 90 -10 -25 -40 88111600 17 12.9S 73.4E 25 72 139 95 -20 -25 -35 88111700 19 14.4S 71.0E 55 116 194 90 -5	88111112	8	6.4S	90.1E	18	90	156	55	-10	-25	-30
88111300 11 7.9S 85.3E 23 169 308 65 0 -10 -40 88111312 12 9.2S 83.7E 18 166 259 65 0 -10 -25 88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -5 88111412 14 10.4S 78.9E 30 96 193 75 0 5 0 88111500 15 11.0S 77.1E 36 136 186 85 -20 -25 -25 88111512 16 12.1S 75.0E 5 78 229 90 -10 -25 -40 88111600 17 12.9S 73.4E 25 72 139 95 -20 -25 -45 88111612 18 13.8S 71.8E 37 178 264 100 -5 -25 -35 88111712 20 15.1S 69.8E 16 122 206 95 -10 </td <td>88111200</td> <td>9</td> <td>6.7S</td> <td>88.4E</td> <td>26</td> <td>96</td> <td>231</td> <td>65</td> <td>0</td> <td>5</td> <td>. 5</td>	88111200	9	6.7S	88.4E	26	96	231	65	0	5	. 5
88111312 12 9.2S 83.7E 18 166 259 65 0 -10 -25 88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -5 88111412 14 10.4S 78.9E 30 96 193 75 0 5 0 88111500 15 11.0S 77.1E 36 136 186 85 -20 -25 -25 88111512 16 12.1S 75.0E 5 78 229 90 -10 -25 -40 88111600 17 12.9S 73.4E 25 72 139 95 -20 -25 -45 88111612 18 13.8S 71.8E 37 178 264 100 -5 -25 -35 88111700 19 14.4S 71.0E 55 116 194 90 -5 -15 -25 88111800 21 15.7S 68.9E 21 88 140 90 -5 </td <td>88111212</td> <td>10</td> <td>7.3S</td> <td>86.6E</td> <td>37</td> <td>66</td> <td>188</td> <td>65</td> <td>0</td> <td>0</td> <td>-30</td>	88111212	10	7.3S	86.6E	37	66	188	65	0	0	-30
88111400 13 10.1S 81.1E 76 104 97 65 0 -10 -5 88111412 14 10.4S 78.9E 30 96 193 75 0 5 0 88111500 15 11.0S 77.1E 36 136 186 85 -20 -25 -25 88111512 16 12.1S 75.0E 5 78 229 90 -10 -25 -40 88111600 17 12.9S 73.4E 25 72 139 95 -20 -25 -45 88111612 18 13.8S 71.8E 37 178 264 100 -5 -25 -35 88111700 19 14.4S 71.0E 55 116 194 90 -5 -15 -25 88111800 21 15.7S 68.9E 21 88 140 90 -5 -15 10 88111812 22 16.3S 68.3E 23 58 160 85 -5 </td <td>88111300</td> <td>11</td> <td>7.9S</td> <td>85.3E</td> <td>23</td> <td>169</td> <td>308</td> <td>65</td> <td>0</td> <td>-10</td> <td>-40</td>	88111300	11	7.9S	85.3E	23	169	308	65	0	-10	-40
88111412 14 10.4s 78.9e 30 96 193 75 0 5 0 88111500 15 11.0s 77.1e 36 136 186 85 -20 -25 -25 88111512 16 12.1s 75.0e 5 78 229 90 -10 -25 -40 88111600 17 12.9s 73.4e 25 72 139 95 -20 -25 -45 88111612 18 13.8s 71.8e 37 178 264 100 -5 -25 -35 88111700 19 14.4s 71.0e 55 116 194 90 -5 -15 -25 88111712 20 15.1s 69.8e 16 122 206 95 -10 -10 5 88111800 21 15.7s 68.9e 21 88 140 90 -5 -15 10 88111900 23 17.1s 67.7e 12 32 N/A 80 0<	88111312	12	9.28	83.7E	18	166	259	65	0	-10	_
88111500 15 11.0s 77.1e 36 136 186 85 -20 -25 -25 88111512 16 12.1s 75.0e 5 78 229 90 -10 -25 -40 88111600 17 12.9s 73.4e 25 72 139 95 -20 -25 -45 88111612 18 13.8s 71.8e 37 178 264 100 -5 -25 -35 88111700 19 14.4s 71.0e 55 116 194 90 -5 -15 -25 88111712 20 15.1s 69.8e 16 122 206 95 -10 -10 5 88111800 21 15.7s 68.9e 21 88 140 90 -5 -15 10 88111812 22 16.3s 68.3e 23 58 160 85 -5 15 25 88111900 23 17.1s 67.7e 12 32 N/A 80 <td< td=""><td>88111400</td><td>13</td><td>10.18</td><td>81.1E</td><td>76</td><td>104</td><td>97</td><td>65</td><td>0</td><td>-10</td><td></td></td<>	88111400	13	10.18	81.1E	76	104	97	65	0	-10	
88111512 16 12.1S 75.0E 5 78 229 90 -10 -25 -40 88111600 17 12.9S 73.4E 25 72 139 95 -20 -25 -45 88111612 18 13.8S 71.8E 37 178 264 100 -5 -25 -35 88111700 19 14.4S 71.0E 55 116 194 90 -5 -15 -25 88111712 20 15.1S 69.8E 16 122 206 95 -10 -10 5 88111800 21 15.7S 68.9E 21 88 140 90 -5 -15 10 88111812 22 16.3S 68.3E 23 58 160 85 -5 15 25 88111900 23 17.1S 67.7E 12 32 N/A 80 0 30 N/A 88111912 24 17.9S 66.6E 49 283 N/A 50 10				78.9E	30	96		75	0		
88111600 17 12.9S 73.4E 25 72 139 95 -20 -25 -45 88111612 18 13.8S 71.8E 37 178 264 100 -5 -25 -35 88111700 19 14.4S 71.0E 55 116 194 90 -5 -15 -25 88111712 20 15.1S 69.8E 16 122 206 95 -10 -10 5 88111800 21 15.7S 68.9E 21 88 140 90 -5 -15 10 88111812 22 16.3S 68.3E 23 58 160 85 -5 15 25 88111900 23 17.1S 67.7E 12 32 N/A 80 0 30 N/A 88111912 24 17.9S 66.6E 49 283 N/A 50 10 5 N/A 88112000 25 18.4S 65.8E 33 N/A N/A 40 5 </td <td>88111500</td> <td>15</td> <td>11.0s</td> <td>77.1E</td> <td>36</td> <td>136</td> <td>186</td> <td>85</td> <td>-20</td> <td>-25</td> <td>-25</td>	88111500	15	11.0s	77.1E	36	136	186	85	-20	-25	-25
88111612 18 13.85 71.8E 37 178 264 100 -5 -25 -35 88111700 19 14.4S 71.0E 55 116 194 90 -5 -15 -25 88111712 20 15.1S 69.8E 16 122 206 95 -10 -10 5 88111800 21 15.7S 68.9E 21 88 140 90 -5 -15 10 88111812 22 16.3S 68.3E 23 58 160 85 -5 15 25 88111900 23 17.1S 67.7E 12 32 N/A 80 0 30 N/A 88111912 24 17.9S 66.6E 49 283 N/A 50 10 5 N/A 88112000 25 18.4S 65.8E 33 N/A N/A 40 5 N/A N/A	88111512		12.15	75.0E	5			90			
88111700 19 14.4s 71.0e 55 116 194 90 -5 -15 -25 88111712 20 15.1s 69.8e 16 122 206 95 -10 -10 5 88111800 21 15.7s 68.9e 21 88 140 90 -5 -15 10 88111812 22 16.3s 68.3e 23 58 160 85 -5 15 25 88111900 23 17.1s 67.7e 12 32 N/A 80 0 30 N/A 88111912 24 17.9s 66.6e 49 283 N/A 50 10 5 N/A 88112000 25 18.4s 65.8e 33 N/A N/A 40 5 N/A N/A						_					
88111712 20 15.1s 69.8E 16 122 206 95 -10 -10 5 88111800 21 15.7s 68.9E 21 88 140 90 -5 -15 10 88111812 22 16.3s 68.3E 23 58 160 85 -5 15 25 88111900 23 17.1s 67.7E 12 32 N/A 80 0 30 N/A 88111912 24 17.9s 66.6E 49 283 N/A 50 10 5 N/A 88112000 25 18.4s 65.8E 33 N/A N/A 40 5 N/A N/A			13.85	71.8E	37				_		
88111800 21 15.7s 68.9E 21 88 140 90 -5 -15 10 88111812 22 16.3s 68.3E 23 58 160 85 -5 15 25 88111900 23 17.1s 67.7E 12 32 N/A 80 0 30 N/A 88111912 24 17.9s 66.6E 49 283 N/A 50 10 5 N/A 88112000 25 18.4s 65.8E 33 N/A N/A 40 5 N/A N/A											
88111812 22 16.3S 68.3E 23 58 160 85 -5 15 25 88111900 23 17.1S 67.7E 12 32 N/A 80 0 30 N/A 88111912 24 17.9S 66.6E 49 283 N/A 50 10 5 N/A 88112000 25 18.4S 65.8E 33 N/A N/A 40 5 N/A N/A				69.8E				-			
88111900 23 17.1S 67.7E 12 32 N/A 80 0 30 N/A 88111912 24 17.9S 66.6E 49 283 N/A 50 10 5 N/A 88112000 25 18.4S 65.8E 33 N/A N/A 40 5 N/A N/A									_		
88111912 24 17.9S 66.6E 49 283 N/A 50 10 5 N/A 88112000 25 18.4S 65.8E 33 N/A N/A 40 5 N/A N/A											
88112000 25 18.4S 65.8E 33 N/A N/A 40 5 N/A N/A									-		
• • • • • • • • • • • • • • • • • • • •			17.9S	66.6E		283	N/A	50			-
88112012 26 18.5S 65.4E 5 N/A N/A 30 0 N/A N/A			18.45	65.8E			N/A			-	-
	88112012	26	18.58	65.4E	5	N/A	N/A	30	0	N/A	N/A

Tropical	Cyclone	03S (Ilon	Average	00h 14	24h 106	48h 203				
			# Cases	11	8	6				
DTG	W#	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
88121312	1	16.5S	120.0E	54	197	299	35	0	0	0
88121400	2	16.0S	117.9E	8	12	71	45	-5	-10	-15
88121412	3	16.1S	116.4E	12	132	269	50	Ö	0	-5
88121500	4	16.2S	115.8E	5	38	191	55	ō	-5	-10
88121512	5	16.4S	115.4E	24	55	45	60	Ö	-15	-30
88121600	6	16.78	115.1E	29	120	346	70	-5	-10	35
88121612	7	17.2S	115.1E	5	106	N/A	75	.0	-10	N/A
88121700	8	18.3S	115.3E	16	183	N/A	85	0	35	N/A
88121706	* 9	19.1S	115.7E	5	N/A	N/A	85	0	N/A	N/A
88121712	10	20.28	116.0E	0	N/A	N/A	85	0	N/A	N/A
88121800	11	22.7S	117.0E	0	N/A	N/A	40	0	N/A	N/A
*	Intermed	diate Upda	te		-	•				
Tropical	Cvclone	04P (Deli	lah)	00h	24h	48h				
	-3	,	Average	20	74	110				
			# Cases	4	3	1				
			, 00000	•	ŭ	-				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89010118	1	18.7S	161.2E	38	106	110	45	-10	0	0
89010206	2	20.2S	165.0E	16	34	N/A	60	-20	-10	N/A
89010218	3	22.3S	167.8E	5	83	N/A	55	-20	-15	N/A
89010300	4	23.4S	168.8E	18	N/A	N/A	55	-20	N/A	N/A
Tropical	Cyclone	05P (Gina) Average # Cases	<u>00h</u> 30 6	24h 130 4	48h 464 2				
-	Cyclone	05P (Gina	Average	30	130	464				
DTG	- <u>₩</u> #	BT_LAT	Average	30	130	464	BT WN	ww er	24 WE	48 WE
DTG 89010706	₩ #	BT LAT 15.3S	Average # Cases BT_LON 172.1W	30 6 POS ER 18	130 4 24 ER 131	464 2 48 ER 445	BT WN 35	WW ER	24 WE -10	48 WE 0
DTG 89010706 89010718	₩ # 1 2	BT LAT 15.3s 16.4s	Average # Cases BT LON 172.1W 171.7W	30 6 POS ER 18 29	130 4 24 ER 131 131	464 2 48 ER 445 483	35 40	0	-10 5	0 20
DTG 89010706 89010718 89010806	W# 1 2 3	BT LAT 15.3S 16.4S 17.6S	Average # Cases BT LON 172.1W 171.7W 171.4W	30 6 POS ER 18 29 8	130 4 24 ER 131 131 112	464 2 48 ER 445 483 N\A	35 40 45	0 0 -5	-10 5 0	0 20 N\A
DTG 89010706 89010718 89010806 89010818	W# 1 2 3 4	BT LAT 15.3S 16.4S 17.6S 18.9S	Average # Cases BT LON 172.1W 171.7W 171.4W 171.1W	30 6 POS ER 18 29 8 33	130 4 24 ER 131 131 112 146	464 2 48 ER 445 483 N\A N\A	35 40 45 40	0 0 -5 0	-10 5 0 10	0 20 N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906	W# 1 2 3 4 5 5	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S	Average # Cases BT LON 172.1W 171.7W 171.4W 171.1W 172.8W	30 6 POS ER 18 29 8 33 8	130 4 24 ER 131 131 112 146 N\A	464 2 48 ER 445 483 N\A N\A	35 40 45 40 35	0 0 -5 0	-10 5 0 10 N\A	0 20 N\A N\A N\A
DTG 89010706 89010718 89010806 89010818	W# 1 2 3 4	BT LAT 15.3S 16.4S 17.6S 18.9S	Average # Cases BT LON 172.1W 171.7W 171.4W 171.1W	30 6 POS ER 18 29 8 33	130 4 24 ER 131 131 112 146	464 2 48 ER 445 483 N\A N\A	35 40 45 40	0 0 -5 0	-10 5 0 10	0 20 N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918	- 1 2 3 4 5	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S	Average # Cases BT LON 172.1W 171.7W 171.4W 171.1W 172.8W	30 6 POS ER 18 29 8 33 8 82	130 4 24 ER 131 131 112 146 N\A	464 2 48 ER 445 483 N\A N\A N\A	35 40 45 40 35	0 0 -5 0	-10 5 0 10 N\A	0 20 N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906	- 1 2 3 4 5	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S	Average # Cases BT LON 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W	30 6 POS ER 18 29 8 33 8 82	130 4 24 ER 131 131 112 146 N\A N\A	464 2 48 ER 445 483 N\A N\A N\A	35 40 45 40 35	0 0 -5 0	-10 5 0 10 N\A	0 20 N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918	- 1 2 3 4 5	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S	Average # Cases BT LON 172.1W 171.7W 171.4W 171.1W 172.8W	30 6 POS ER 18 29 8 33 8 82	130 4 24 ER 131 131 112 146 N\A	464 2 48 ER 445 483 N\A N\A N\A	35 40 45 40 35	0 0 -5 0	-10 5 0 10 N\A	0 20 N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918	W# 1 2 3 4 5 6 Cyclone	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S	Average # Cases BT ION 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases	30 6 POS ER 18 29 8 33 8 82	130 4 24 ER 131 131 112 146 N\A N\A	464 2 48 ER 445 483 N\A N\A N\A N\A	35 40 45 40 35 25	0 0 -5 0 0	-10 5 0 10 N\A N\A	0 20 N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918 Tropical	W# 1 2 3 4 5 6 Cyclone	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S	Average # Cases BT ION 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases BT ION	30 6 POS ER 18 29 8 33 8 82 OOh 18 9	130 4 24 ER 131 131 112 146 N\A N\A 100 7	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5	35 40 45 40 35 25	0 0 -5 0 10	-10 5 0 10 N\A N\A	0 20 N\A N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918 Tropical	W# 1 2 3 4 5 6 Cyclone	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S	Average # Cases BT ION 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases BT ION 40.9E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13	130 4 24 ER 131 131 112 146 N\A N\A 100 7	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5	35 40 45 40 35 25	0 0 -5 0 0 10	-10 5 0 10 N\A N\A	0 20 N\A N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918 Tropical DTG 89011018 89011106	W# 1 2 3 4 5 6 Cyclone	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S 06S	Average # Cases BT ION 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases BT ION 40.9E 41.2E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13 20	130 4 24 ER 131 131 112 146 N\A N\A 100 7 24h 100 7	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5 48 ER 106 N\A	35 40 45 40 35 25 25	0 0 -5 0 10	-10 5 0 10 N\A N\A -10 -25	0 20 N\A N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918 Tropical DTG 89011018 89011106 89011118	W# 1 2 3 4 5 6 Cyclone W# 1 2 3	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S 06S BT LAT 16.4S 16.9S 17.2S	Average # Cases BT ION 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases BT ION 40.9E 41.2E 41.6E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13 20 21	130 4 24 ER 131 131 112 146 N\A N\A 100 7 24 ER 38 204 132	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5 48 ER 106 N\A 271	35 40 45 40 35 25	0 0 -5 0 0 10	-10 5 0 10 N\A N\A	0 20 N\A N\A N\A N\A
DTG 89010706 89010718 89010806 89010818 89010906 89010918 Tropical DTG 89011018 89011106 89011118 89011206	W# 1 2 3 4 5 6 Cyclone W# 1 2 3 4	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S 06S BT LAT 16.4S 16.9S 17.2S 17.3S	Average # Cases BT ION 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases BT ION 40.9E 41.2E 41.6E 41.9E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13 20 21 12	130 4 24 ER 131 131 112 146 N\A N\A 100 7 24 ER 38 204 132 69	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5 48 ER 106 N\A 271 111	35 40 45 40 35 25 25 8T WN 45 55 65	0 0 -5 0 10 10	-10 5 0 10 N\A N\A -10 -25 -20 15	0 20 N\A N\A N\A N\A N\A -25 N\A -45 15
DTG 89010706 89010718 89010806 89010818 89010906 89010918 Tropical DTG 89011018 89011106 89011118 89011206 89011218	W# 1 2 3 4 5 6 Cyclone W# 1 2 3 4 5 5	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S 06S BT LAT 16.4S 16.9S 17.2S 17.3S 17.5S	Average # Cases BT ION 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases BT ION 40.9E 41.2E 41.6E 41.9E 42.2E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13 20 21 12 26	130 4 24 ER 131 131 112 146 N\A N\A N\A 24h 100 7 24 ER 38 204 132 69 38	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5 48 ER 106 N\A 271 111 156	35 40 45 40 35 25 25 8T WN 45 55 65 65 75	0 0 -5 0 10 10 WW ER 0 -10 -10 0 -10	-10 5 0 10 N\A N\A -10 -25 -20 15 0	0 20 N\A N\A N\A N\A N\A 15 5
DTG 89010706 89010718 89010806 89010918 89010918 Tropical DTG 89011018 89011106 89011118 89011206 89011218 89011306	W# 1 2 3 4 5 6 6	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S 06S BT LAT 16.4S 16.9S 17.2S 17.3S 17.5S 17.7S	Average # Cases ET_LON 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases ET_LON 40.9E 41.2E 41.6E 41.9E 42.2E 42.6E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13 20 21 12 26 20	130 4 24 ER 131 131 112 146 N\A N\A N\A 24h 100 7 24 ER 38 204 132 69 38 80	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5 48 ER 106 N\A 271 111 156 135	35 40 45 40 35 25 25 8T WN 45 55 65 65 75 75	0 0 -5 0 10 10 WW ER 0 -10 -10 0 -10	-10 5 0 10 N\A N\A -10 -25 -20 15 0	0 20 N\A N\A N\A N\A N\A 15 15 5 45
DTG 89010706 89010718 89010806 89010818 89010906 89010918 Tropical DTG 89011018 89011106 89011118 89011206 89011218 89011306 89011318	W# 1 2 3 4 5 6 7	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S O6S BT LAT 16.4S 16.9S 17.2S 17.3S 17.5S 17.7S 17.9S	Average # Cases ET LON 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases ET LON 40.9E 41.2E 41.6E 41.9E 42.2E 42.6E 42.8E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13 20 21 12 26 20 11	130 4 24 ER 131 131 112 146 N\A N\A N\A 24h 100 7 24 ER 38 204 132 69 38 80 135	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5 48 ER 106 N\A 271 111 156 135 N\A	35 40 45 40 35 25 25 BT WN 45 55 65 65 75 75	0 0 -5 0 10 10 WW ER 0 -10 -10 0 -10	-10 5 0 10 N\A N\A N\A -10 -25 -20 15 0 0 5	0 20 N\A N\A N\A N\A N\A
DTG 89010706 89010718 89010806 89010918 89010918 Tropical DTG 89011018 89011106 89011118 89011206 89011218 89011306	W# 1 2 3 4 5 6 6	BT LAT 15.3S 16.4S 17.6S 18.9S 19.7S 20.5S 06S BT LAT 16.4S 16.9S 17.2S 17.3S 17.5S 17.7S	Average # Cases ET_LON 172.1W 171.7W 171.4W 171.1W 172.8W 175.1W Average # Cases ET_LON 40.9E 41.2E 41.6E 41.9E 42.2E 42.6E	30 6 POS ER 18 29 8 33 8 82 00h 18 9 POS ER 13 20 21 12 26 20	130 4 24 ER 131 131 112 146 N\A N\A N\A 24h 100 7 24 ER 38 204 132 69 38 80	464 2 48 ER 445 483 N\A N\A N\A N\A 156 5 48 ER 106 N\A 271 111 156 135	35 40 45 40 35 25 25 8T WN 45 55 65 65 75 75	0 0 -5 0 10 10 WW ER 0 -10 -10 0 -10	-10 5 0 10 N\A N\A -10 -25 -20 15 0	0 20 N\A N\A N\A N\A N\A 15 15 5 45

Tropical	Cyclone	07S (Edme)		ooh	24h	<u>48h</u>				
			Average # Cases	29	141 10	322 8				
			# Cases	11	10	•				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24_ER	48 ER	BT WN	WW ER	24 WE	48 WE
89012018	1	13.6S	82.9E	102	312	429	35	5	0	-10
89012106	2	14.08	83.0E	17	132	182	45	0	-1	-30
89012118	3	15.08	83.3E	5	17	12	50	0	-10	-40
89012206	4	16.48	83.3E	33	147	369	65	-10	-35	-45
89012218	5	17.8S	82.8E	23	155	455	75	-10	~25	0
89012306	6	19.0S	82.0E	33	147	549	105	-10	10	40
89012318	7	19.58	81.3E	20	174	267	115	0	50	75
89012406	8	20.7S	79.8E	23	73	317	105	0	25	40
89012418	9	22.3S	77.9E	28	77	N\A	75	0	25	N\A
89012506	10	23.58	75.5E	33	172	N/A	55	-5	10	N\A
89012518	11	25.0S	72.5E	6	N\A	N\A	30	5	N\A	N\A

Tropical	Cyclone	08S (Firi	nga)	<u>00h</u>	24h	48h				
•	•		Average	23	105	201				
			# Cases	14	10	9				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89012600	1	12.9S	66.1E	33	88	232	35	0	0	-15
89012612	2	14.3S	65.8E	21	109	234	40	0	- 5	-25
89012700	3	15.2S	64.8E	5	134	232	45	0	-10	-30
89012712	4	16.4S	63.2E	32	149	212	55	-5	-10	-10
89012800	5	17.7S	60.9E	33	114	239	65	0	0	-10
89012806	6	18.2S	59.9E	8	50	129	70	0	0	0
89012818	7	19.6S	57.8E	16	87	169	90	0	20	40
89012906	8	20.5S	56.0E	28	121	156	90	5	5	15
89012918	. 9	21.6S	54.4E	23	98	208	85	0	15	10
89013006	10	23.0S	53.0E	108	N/A	N/A	65	5	N/A	N/A
89013018	11	24.3S	51.6E	8	100	N\A	50	10	5	N/A
89013106	12	25.98	50.7E	6	N/A	N/A	45	-5	N/A	N\A
89013112	13	26.9S	50.5E	0	N/A	N/A	40	0	N/A	N/A
89020100	14	29.38	50.3E	0	N/A	N/A	35	0	N/A	N/A
Tmoical	Cvclone	09S (Kirr	ilv)	00h	24h	48h				
promi	-1	/	Average	27	162	313				
			# Cases	9	7	5				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89020612		14.5S	109.9E	17	143	297	35	0	5	25
89020700	2	15.8S	109.8E	8	55	212	50	-5	5	-20
89020712		16.85	109.8E	12	82	279	50	0	0	-30
89020800		17.8S	109.7E	21	158	398	50	0	-25	-10
89020812		18.85	109.3E	30	185	382	45	-45	-25	10
89020900		19.98	108.0E	58	294	N\A	65	-65	-10	N\A
89020912		21.78	106.8E	18	221	N/A	70	5	40	N/A
89021000		23.75	105.1E	43	N\A	N/A	45	0	N\A	N\A
89021012		24.58	103.1E	37	N/A	N/A	25	10	N/A	N/A

Tropical	Cyclone	10P (Harr	y)	<u>00h</u>	24h	48h				
			Average	23	111	269				
			# Cases	24	23	21				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89020800	1	17.3S	161.4E	24	157	281	30	5	-5	-15
89020812	2	18.35	162.3E	28	198	307	45	0	-10	-55
89020900	3	18.25	163.7E	66	156	283	55	-10	-30	-65
89020912	4	18.3S	165.0E	12	100	308	60	0	-35	-30
89021000	5	18.75	165.6E	18	192	450	80	-5	-10	-50 -5
89021012	6	19.38	165.5E	13	155	348	110	0	20	-5 45
89021100	7	20.18	164.9E	5	112	306	115	Ö	5	0
89021106		20.58	164.4E	25	143	338	110	ŏ	0	-20
89021112	9	20.95	163.6E	5	145	352	105	-5	-10	-55
89021200	10	20.95	162.5E	Õ	74	214	95	5	-10 -5	-60
89021212	11	20.68	161.5E	6	55	99	80	0	-30	-65
89021300	12	20.08	160.6E	18	79	104	80	0	-40	-55
89021312	13	19.45	159.7E	13	57	145	95	-5	-40	-5
89021400	14	19.25	158.8E	24	74	221	115	0	20	30
89021412	15	19.05	157.9E	5	92	248	130	Ö	25	35
89021500	16	19.38	157.4E	11	152	376	120	-5	-10	10
89021512	17	19.58	157.5E	24	158	426	115	-5	-10	10
89021600	18	19.78	157.7E	28	140	375	110	5	10	-5
89021612	19	19.85	158.2E	11	96	237	95	0	-5	35
89021700	20	20.35	159.5E	17	21	111	80	ő	10	55
89021712	21	21.25	160.9E	21	37	120	80	10	45	45
89021800	22	22.35	162.6E	48	76	N\A	70	0	10	N/A
89021812	23	23.95	163.9E	47	80	N\A	55	Ö	0	N\A
89021900	24	25.8\$	165.4E	88	N\A	N\A	35	ő	N\A	N/A
		liate Updat			(•	24 (21	14 /12
		•								
Tropical	Cvclone	11S (Hanit	1	OOb	245	49b				
Tropical	Cyclone	11S (Hanit		<u>00h</u> 27	24h	48h				
Tropical	Cyclone	11S (Hanit	Average	27	92	180				
Tropical	Cyclone	11S (Hanit								
Tropical DTG	Cyclone W#	11S (Hanit	Average	27	92	180	BT WN	WW ER	24 WE	48. WE
-	-	•	Average # Cases	27 23	92 21	180 19	<u>BT WN</u> 35	WW ER	24 WE 5	48 WE 10
DTG 89021718 89021800	₩ŧ	BT LAT	Average # Cases BT LON	27 23 POS ER	92 21 24 ER	180 19 48 ER				
DTG 89021718 89021800 89021812	₩ # 1	BT LAT 13.9S	Average # Cases BT LON 96.9E	27 23 POS ER 8	92 21 24 ER 74	180 19 48 ER 147	35	0	5	10
DTG 89021718 89021800 89021812 89021900	₩± 1 2 3	BT LAT 13.9s 13.5s	Average # Cases BT ION 96.9E 95.8E	27 23 POS ER 8 47	92 21 24 ER 74 66	180 19 48 ER 147 61	35 45	0	5 15	10 15
DTG 89021718 89021800 89021812 89021900 89021912	₩# 1 2 3 4	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S	Average # Cases BT ION 96.9E 95.8E 93.6E	27 23 POS ER 8 47 29	92 21 24 ER 74 66 31	180 19 48 ER 147 61 59	35 45 55	0 0 -10	5 15 15	10 15 -30
DTG 89021718 89021800 89021812 89021900 89021912 89022000	₩ ‡ 1 2 3 4 5	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E	27 23 POS ER 8 47 29 18 36 24	92 21 24 ER 74 66 31 44	180 19 48 ER 147 61 59 23 83 216	35 45 55 50 55 75	0 0 -10 0 -5 -5	5 15 15 -10	10 15 -30 -35
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012	₩ ‡ 1 2 3 4 5 6 7	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S	Average # Cases BT ION 96.9E 95.8E 93.6E 91.3E 89.0E	27 23 POS ER 8 47 29 18 36	92 21 24 ER 74 66 31 44 48	180 19 48 ER 147 61 59 23 83	35 45 55 50 55	0 0 -10 0 -5 -5	5 15 15 -10 -45	10 15 -30 -35 -45
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100	₩ ‡ 1 2 3 4 5 6 7	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E	27 23 POS ER 8 47 29 18 36 24 18 37	92 21 24 ER 74 66 31 44 48 80 99 146	180 19 48 ER 147 61 59 23 83 216	35 45 55 50 55 75	0 0 -10 0 -5 -5 -15	5 15 15 -10 -45 -20	10 15 -30 -35 -45 -15
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112	₩ ‡ 1 2 3 4 5 6 7 8	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E	27 23 POS ER 8 47 29 18 36 24 18 37	92 21 24 ER 74 66 31 44 48 80 99	180 19 48 ER 147 61 59 23 83 216 216	35 45 55 50 55 75 105	0 0 -10 0 -5 -5 -15	5 15 15 -10 -45 -20	10 15 -30 -35 -45 -15 -10
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200	W# 1 2 3 4 5 6 7 8 9 10	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E	27 23 POS ER 8 47 29 18 36 24 18 37 13	92 21 24 ER 74 66 31 44 48 80 99 146 96 113	180 19 48 ER 147 61 59 23 83 216 216 265 133 174	35 45 55 50 55 75 105	0 0 -10 0 -5 -5 -15	5 15 15 -10 -45 -20 0	10 15 -30 -35 -45 -15 -10
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212	W# 1 2 3 4 5 6 7 8 9 10 11	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.8S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37	180 19 48 ER 147 61 59 23 83 216 216 265 133	35 45 55 50 55 75 105 110	0 0 -10 0 -5 -5 -15 -20 -25	5 15 15 -10 -45 -20 0 -25 -25	10 15 -30 -35 -45 -15 -10 -50 -25
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300	W# 1 2 3 4 5 6 7 8 9 10 11 12	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.8S 14.6S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91	180 19 48 ER 147 61 59 23 83 216 216 265 133 174	35 45 55 50 55 75 105 110 115	0 0 -10 0 -5 -5 -15 -20 -25 0	5 15 15 -10 -45 -20 0 -25 -25	10 15 -30 -35 -45 -15 -10 -50 -25
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312	W# 1 2 3 4 5 6 7 8 9 10 11 12 13	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.8S 14.6S 15.3S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75	180 19 48 ER 147 61 59 23 83 216 216 265 133 174 95	35 45 55 50 55 75 105 110 115 125	0 0 -10 0 -5 -5 -15 -20 -25 0 -35	5 15 15 -10 -45 -20 0 -25 -25 0	10 15 -30 -35 -45 -15 -10 -50 -25 5
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022400	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.8S 14.6S 15.3S 16.2S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E 79.5E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33	180 19 48 ER 147 61 59 23 83 216 216 265 133 174 95 213 97 111	35 45 55 50 55 75 105 110 115 125 125 125	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10	5 15 15 -10 -45 -20 0 -25 -25 0 -25 -20 -10	10 15 -30 -35 -45 -15 -10 -50 -25 5 -20 -25
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022400 89022412	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.8S 14.6S 15.3S 16.2S 16.9S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E 79.5E 78.1E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47	180 19 48 ER 147 61 59 23 83 216 216 265 133 174 95 213 97 111 156	35 45 55 50 55 75 105 110 115 125 125 125 120	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10 -10	5 15 15 -10 -45 -20 0 -25 -25 0 -25 -20 -10 -10 5	10 15 -30 -35 -45 -15 -10 -50 -25 5 -20 -25 -10
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022400 89022412 89022500	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16	BT LAT 13.9s 13.5s 13.1s 13.0s 12.6s 12.7s 12.7s 12.8s 12.9s 13.2s 13.8s 14.6s 15.3s 16.2s 16.9s 17.9s	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E 79.5E 78.1E 76.8E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47 143	180 19 48 ER 147 61 59 23 83 216 216 265 133 174 95 213 97 111 156 387	35 45 55 50 55 75 105 110 115 125 125 125 120 110	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10 -10	5 15 15 -10 -45 -20 0 -25 -25 0 -25 -20 -10	10 15 -30 -35 -45 -15 -10 -50 -25 5 -20 -25 -10 -5
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022400 89022412 89022500 89022512	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	BT LAT 13.9s 13.5s 13.1s 13.0s 12.6s 12.7s 12.7s 12.8s 12.9s 13.2s 13.8s 14.6s 15.3s 16.2s 16.9s 17.9s 19.1s	Average # Cases BT ION 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E 79.5E 78.1E 76.8E 75.4E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5 16 37	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47 143 82	180 19 48 ER 147 61 59 23 83 216 216 265 133 174 95 213 97 111 156 387 282	35 45 55 50 55 75 105 110 115 125 125 125 120	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10 -10 -5 -5	5 15 15 -10 -45 -20 0 -25 -25 0 -25 -20 -10 -10 5	10 15 -30 -35 -45 -15 -10 -50 -25 5 -20 -25 -10 -5
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022400 89022412 89022500 89022512 89022500	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	BT LAT 13.9s 13.5s 13.1s 13.0s 12.6s 12.7s 12.7s 12.8s 12.9s 13.2s 13.8s 14.6s 15.3s 16.2s 16.9s 17.9s 19.1s 20.4s	Average # Cases BT ION 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E 79.5E 78.1E 76.8E 75.4E 74.0E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5 16 37 12 28	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47 143 82 166	180 19 48 ER 147 61 59 23 83 216 216 265 133 174 95 213 97 111 156 387 282 402	35 45 55 50 55 75 105 110 115 125 125 120 110 105 90 80	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10 -10 -5 -5	5 15 15 -10 -45 -20 0 -25 -25 0 -25 -20 -10 -10 5	10 15 -30 -35 -45 -15 -10 -50 -25 5 -20 -25 -10 -5
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022112 89022200 89022112 89022300 89022312 89022400 89022412 89022500 89022512 89022600 89022612	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19	BT LAT 13.9s 13.5s 13.1s 13.0s 12.6s 12.7s 12.7s 12.8s 12.9s 13.2s 13.8s 14.6s 15.3s 16.2s 16.9s 17.9s 19.1s 20.4s 22.2s	Average # Cases BT ION 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.4E 81.8E 80.7E 79.5E 78.1E 76.8E 75.4E 74.0E 72.7E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5 16 37 12 28 62	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47 143 82 166 196	180 19 48 ER 147 61 59 23 83 216 265 133 174 95 213 97 111 156 387 282 402 304	35 45 55 50 55 75 105 110 115 125 125 120 110 105 90 80 75	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10 -10 -5 -10	5 15 15 -10 -45 -20 0 -25 -25 0 -25 -20 -10 -10 5 10 -5	10 15 -30 -35 -45 -15 -10 -50 -25 5 -20 -25 -10 -5 10 -5
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022300 89022312 89022400 89022412 89022500 89022512 89022600 89022612 89022700	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.2S 14.6S 15.3S 16.2S 16.9S 17.9S 19.1S 20.4S 22.2S 24.9S	Average # Cases BT ION 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E 79.5E 78.1E 76.8E 75.4E 74.0E 72.7E 71.7E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5 16 37 12 28 62 37	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47 143 82 166 196 140	180 19 48 ER 147 61 59 23 83 216 265 133 174 95 213 97 111 156 387 282 402 304 N\A	35 45 55 50 55 75 105 110 115 125 125 120 110 105 90 80 75 65	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10 -10 -5 -10 -15 -10	5 15 15 -10 -45 -20 0 -25 -25 -20 -10 -10 5 10 -5 -20	10 15 -30 -35 -45 -15 -10 -50 -25 5 -20 -25 -10 -5 10 -5
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022312 89022400 89022412 89022500 89022512 89022600 89022612 89022700 89022712	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.8S 14.6S 15.3S 16.2S 16.9S 17.9S 19.1S 20.4S 22.2S 24.9S 28.0S	Average # Cases BT LON 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.4E 81.8E 80.7E 79.5E 76.8E 74.0E 72.7E 71.7E 71.3E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5 16 37 12 28 62 37 26	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47 143 82 166 196 140 121	180 19 48 ER 147 61 59 23 83 216 265 133 174 95 213 97 111 156 387 282 402 304 N\A	35 45 55 50 55 75 105 110 115 125 125 120 110 105 90 80 75 65	0 0 -10 0 -5 -15 -20 -25 0 -35 -5 -10 -10 -5 -10 -15 -10	5 15 15 -10 -45 -20 0 -25 -25 -20 -10 -10 -5 -20 0 -5 10	10 15 -30 -35 -45 -15 -10 -50 -25 -20 -25 -10 -5 5 10 -5 NA N\A
DTG 89021718 89021800 89021812 89021900 89021912 89022000 89022012 89022100 89022112 89022200 89022212 89022300 89022312 89022300 89022312 89022400 89022412 89022500 89022512 89022600 89022612 89022700	W# 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20	BT LAT 13.9S 13.5S 13.1S 13.0S 12.6S 12.7S 12.7S 12.8S 12.9S 13.2S 13.2S 14.6S 15.3S 16.2S 16.9S 17.9S 19.1S 20.4S 22.2S 24.9S	Average # Cases BT ION 96.9E 95.8E 93.6E 91.3E 89.0E 86.8E 85.3E 84.1E 83.3E 82.8E 82.4E 81.8E 80.7E 79.5E 78.1E 76.8E 75.4E 74.0E 72.7E 71.7E	27 23 POS ER 8 47 29 18 36 24 18 37 13 24 18 8 24 5 16 37 12 28 62 37	92 21 24 ER 74 66 31 44 48 80 99 146 96 113 37 91 75 33 47 143 82 166 196 140	180 19 48 ER 147 61 59 23 83 216 265 133 174 95 213 97 111 156 387 282 402 304 N\A	35 45 55 50 55 75 105 110 115 125 125 120 110 105 90 80 75 65	0 0 -10 0 -5 -5 -15 -20 -25 0 -35 -5 -10 -10 -5 -10 -15 -10	5 15 15 -10 -45 -20 0 -25 -25 -20 -10 -10 5 10 -5 -20 0	10 15 -30 -35 -45 -15 -10 -50 -25 -20 -25 -10 -5 5 10 -5 5 N\A

		400 (0)								
Tropical	CACTOUG	12S (Gize	(Average	<u>00h</u> 33	24h 154	<u>48h</u> 266				
			# Cases	9	7	5				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89021812	1	15.8S	72.2E	117	125	114	45	-5	10	25
89021818	2	16.4S	72.1E	21	145	240	45	0	5	10
89021906	3	17.5S	72.0E	5	131	150	45	0	-10	5
89021918	4	18.1S	72.3E	6	62	293	60	-5	-10	15
89022006	5 6	19.18	72.9E	25	189	533	65	5	15	25
89022018	7	20.78	72.9E	42	266 162	N\A N\A	65 50	0	20	N\A
89022106		21.6S 22.1S	71.4E 69.5E	33 23	162 N\A	N\A		5 15	15 N\A	N\A N\A
89022118 89022206	8 9	23.85	69.JE	23	N\A N\A	N\A N\A	40 30	5	N\A	N\A N\A
03022200	,	23.03	00.05	2.1	n (A	N/A	30	3	A) N	14 /14
Tropical	Cyclone	13P (Ivy)		00h	24h	48h				
-	-	,	Average	50	120	207				
			# Cases	13	11	9				
<u>DTG</u>	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89022318	1	17.5S	166.8E	57	196	367	30	5	15	10
89022406	2	18.0S	166.0E	29	199	400	35	0	5	0
89022418	3	18.9S	166.7E	17	127	98	40	5	-15	-45
89022506	4	19.5S	167.2E	0	82	212	50	-5	-15	-45
89022518	5	19.9S	167.6E	8	84	183	60	-5	-25	-15
89022606	6	20.25	168.7E	18	74	88	70	20	25	15
89022618	7	20.95	170.1E	16	87	176	90	5	25	35
89022706	- 8	21.58	171.2E	6	21	157	90	0	-10	15
89022718	9	22.38	171.9E	21	30	179	90	0	0	25
89022806	10	22.98	172.7E	24	151	N\A	85	0	25	N\A
89022818	11	23.85	172.8E	12	268	N/A	70	5	25	N\A
89030106	12	23.58	171.4E	138	N/A	N/A	45	10 5	N\A	N\A
89030118	13	22.58	170.4E	310	A/N	A/N	30	, 3	N\A	N\A
Tropical	Cvclone	14P		<u>00h</u>	24h	48h				
	-2		Average	34	139	238				
			# Cases	11	9	6				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89022400	1	28.0S	137.4W	90	186	190	55	-15	-25	-40
89022412	2	27.0S	139.1W	12	145	204	65	0	10	25
89022500	3	26.78	140.1W	22	139	194	80	-5	20	5
89022512	4	26.9S	140.6W	26	228	445	90	-10	10	25
89022600	5	28.0S	141.0W	24	185	273	80	-15	-20	0
89022612	6	29.65	141.4W	72	44	123	75	-20	-20	- 5
89022700	7	31.48	141.8W	7	138	N/A	65	-15 -10	-10	N\A
89022712	8	32.38	141.2W	26	67	N/A	60	-10	-5 5	N\A N\A
89022800	9	32.7S 33.1S	140.3W	42	122	N/A	45	0	N/A	N\A N\A
89022812 89030100	10		139.5W	49 9	N\A	N\A N\A	40 30	0	N\A	N\A
89030100	11	33.98	138.4W	9	N\A	A/N	30	U	N/A	NA
Tropical	Cyclone	15P (Judy)	<u>00h</u>	24h	<u>48h</u>				
			Average # Cases	22 8	160 6	390 4				
משת	ra I	מא אותם	זייט ז ייים	DOC ED	24 55	40 ET	ימו חם	www en	24 WE	48 WE
DTG 89022400	₩ # 1	BT LAT 21.5S	BT LON 153.8W	POS ER 34	24 ER 139	48 ER 218	<u>BT_WN</u> 35	WW ER	24 WE -25	-40
89022400	2	21.55	153.8W 154.3W	34 6	266	568	35 55	0	-25 -10	-40 -30
	4.	44.73	101.01	10	200	700	JJ	J	-10	-50

TTOPTOPT	Circlone	15P (Judy) continu	and .						
DTG	W#	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89022500	3	23.05	155.2W	13	268	626	70	-5	-25	-20
89022512	4	22.75	156.2W	21	89	148	80	-15	-10	25
89022600	5	22.45	157.2W	28	47	N\A	90	-10	5	N\A
89022612	6	22.4S	158.3W	28	152	N\A	80	-10	30	N\A
89022700	7	22.85	159.6W	16	N\A	N\A	75	-5	N\A	N\A
89022712	8	24.7S	160.4W	32	N\A	N\A	45	15	N\A	N\A
Tropical	Cyclone	16S		<u>00h</u>	24h	48h				
-	-		Average	35	229	N\A				
			# Cases	3	1	0				
DTG	<u>W#</u>	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89022400	1	20.0S	117.3E	5	229	N\A	45	-10	15	N\A
89022412	2	21.9S	116.3E	94	N/A	N/A	30	5	N/A	N\A
89022500	3	23.68	117.9E	6	A/N	A/N	25	-5	A/N	N\A
		150 04								
Tropical	chcroue	17S (Marc	•	<u>00h</u>	24h	48h				
			Average # Cases	13 3	92 2	332 1				
			# Cases	3	2	1				
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89030300	1	17.1S	100.1E	0	80	332	30	0	15	30
89030312	2	18.5S	98.7E	18	104	N/A	35	-5	20	N/A
89030400	3	19.7S	97.6E	23	N/A	N/A	30	0	N/A	N/A
Tropical	Cyclone	188		<u>00h</u>	24h	48h				
-	-1		Average	40	220	185				
	-3		Average # Cases							
DTG	_		# Cases	40 4	220	185	BT WN	WW ER	24 WE	48 WE
	₩# 1	BT LAT 23.9S	_	40	220	185	<u>BT_WN</u> 35	WW ER	24 WE 5	48 WE 10
DTG	- ₩#	BT LAT	# Cases BT LON	40 4 POS ER	220 3 24 ER	185 1 48 ER				
DTG 89030906	- <u>W#</u> 1	BT LAT 23.9S	# Cases BT LON 42.2E	40 4 POS ER 63	220 3 24 ER 163	185 1 48 ER 185	35	0	5	10
DTG 89030906 89030918	- ₩# 1 2	BT LAT 23.9S 26.4S	# Cases BT LON 42.2E 43.3E	40 4 POS ER 63 30	220 3 24 ER 163 228	185 1 48 ER 185 N/A	35 35	0	5 0	10 N/A
DTG 89030906 89030918 89031006 89031018	- ₩# 1 2 3 4	BT LAT 23.9S 26.4S 28.9S 30.4S	# Cases BT LON 42.2E 43.3E 43.7E 44.7E	40 4 POS ER 63 30 37	220 3 24 ER 163 228 270	185 1 48 ER 185 N/A N/A	35 35 35	0 0 0	5 0 0	10 N/A N/A
DTG 89030906 89030918 89031006 89031018	- ₩# 1 2 3 4	BT LAT 23.9S 26.4S 28.9S	# Cases BT LON 42.2E 43.3E 43.7E 44.7E	40 4 POS ER 63 30 37 31	220 3 24 ER 163 228 270 N/A	185 1 48 ER 185 N/A N/A N/A	35 35 35	0 0 0	5 0 0	10 N/A N/A
DTG 89030906 89030918 89031006 89031018	- ₩# 1 2 3 4	BT LAT 23.9S 26.4S 28.9S 30.4S	# Cases BT LON 42.2E 43.3E 43.7E 44.7E	40 4 POS ER 63 30 37 31	220 3 24 ER 163 228 270 N/A	185 1 48 ER 185 N/A N/A N/A	35 35 35	0 0 0	5 0 0	10 N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical	₩# 1 2 3 4 Cyclone	BT LAT 23.9S 26.4S 28.9S 30.4S	# Cases BT LON 42.2E 43.3E 43.7E 44.7E bo) Average # Cases	40 4 POS ER 63 30 37 31	220 3 24 ER 163 228 270 N/A 24h 113 11	185 1 48 ER 185 N/A N/A N/A 184 3	35 35 35 30	0 0 0 0	5 0 0 N/A	10 N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical	₩# 1 2 3 4 Cyclone	BT LAT 23.9S 26.4S 28.9S 30.4S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION	40 4 POS ER 63 30 37 31 00h 25 13 POS ER	220 3 24 ER 163 228 270 N/A 24h 113 11	185 1 48 ER 185 N/A N/A N/A 184 3	35 35 35 30	0 0 0 0	5 0 0 N/A	10 N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500	W# 1 2 3 4 Cyclone	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina)	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E	900 ER 63 30 37 31 00h 25 13 POS ER 16	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164	185 1 48 ER 185 N/A N/A N/A 184 3	35 35 35 30 30 BT WN 35	0 0 0 0	5 0 0 N/A 24 WE -30	10 N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512	W# 1 2 3 4 Cyclone W# 1 2	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina)	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E	40 4 40 4 POS ER 63 30 37 31 00h 25 13 POS ER 16 29	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A	35 35 35 30 30 BT WN 35 55	0 0 0 0	5 0 N/A N/A 24 WE -30 -35	10 N/A N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512 89032600	W# 1 2 3 4 Cyclone W# 1 2 3 3 4 3 3 4 5 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E	900 ER 63 30 37 31 00h 25 13 POS ER 16 29 24	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A 215	35 35 30 30 BT WN 35 55 55	0 0 0 0	5 0 N/A N/A 24 WE -30 -35 -25	10 N/A N/A N/A N/A 48 WE N/A N/A -20
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512	W# 1 2 3 4 Cyclone	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E	900 ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A 215 N/A	35 35 30 30 BT WN 35 55 55 65	0 0 0 0	5 0 N/A N/A 24 WE -30 -35 -25 -35	10 N/A N/A N/A N/A -20 N/A
DTG 89030906 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612 89032618	W# 1 2 3 4 Cyclone W# 1 2 3 4 5	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E	900 ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A 215 N/A N/A	35 35 30 30 BT WN 35 55 55 65 65	0 0 0 0	5 0 N/A 24 WE -30 -35 -25 -35 -15	10 N/A N/A N/A N/A -20 N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612	W# 1 2 3 4 Cyclone W# 1 2 3 4 5 6	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S 20.3S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E 49.4E	900 ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32 12	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81 94	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A 215 N/A N/A	35 35 30 30 BT WN 35 55 65 65 65	0 0 0 0 0	5 0 0 N/A 24 WE -30 -35 -25 -35 -15 -10	10 N/A N/A N/A N/A -20 N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612 89032618 89032706	W# 1 2 3 4 Cyclone W# 1 2 3 4 5	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E	40 4 40 4 POS ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32 12 50	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81 94 N/A	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A 215 N/A N/A N/A	35 35 30 30 BT WN 35 55 65 65 65 60	0 0 0 0 0	5 0 N/A N/A 24 WE -30 -35 -25 -35 -15 -10 N/A	10 N/A N/A N/A N/A N/A -20 N/A N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612 89032618 89032706 89032718	₩# 1 2 3 4 Cyclone W# 1 2 3 4 5 6 7	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S 20.3S 20.8S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E 49.4E 49.3E	900 ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32 12	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81 94	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A N/A N/A N/A	35 35 30 30 BT WN 35 55 65 65 65 60 55	0 0 0 0 0	5 0 0 N/A 24 WE -30 -35 -25 -35 -15 -10	10 N/A N/A N/A N/A -20 N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612 89032618 89032706 89032718 89032800	W# 1 2 3 4 5 6 7 8	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S 20.3S 20.8S 20.8S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E 49.4E 49.3E 49.4E 49.4E 49.4E	905 ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32 12 50 11	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81 94 N/A 43 76	185 1 48 ER 185 N/A N/A N/A 3 48 ER N/A N/A 215 N/A N/A N/A N/A	35 35 30 30 BT WN 35 55 65 65 65 60	0 0 0 0 0	5 0 0 N/A 24 WE -30 -35 -25 -35 -15 -10 N/A -10	10 N/A N/A N/A N/A N/A N/A N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612 89032618 89032718 89032718 89032800 89032812	W# 1 2 3 4 5 6 7 8 9	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S 20.3S 20.8S 20.8S 20.8S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E 49.4E 49.3E 49.4E	905 ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32 12 50 11 8	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81 94 N/A	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A N/A N/A N/A	35 35 35 30 30 BT WN 35 55 65 65 65 60 55 55	0 0 0 0 0 0 -5 -20 0 0 -10 -5 -5	5 0 0 N/A 24 WE -30 -35 -25 -35 -15 -10 N/A -10 10	10 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A
DTG 89030906 89030918 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612 89032618 89032718 89032718 89032800 89032812 89032900	W# 1 2 3 4 Cyclone W# 1 2 3 4 5 6 7 8 9 10 11 12	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S 20.3S 20.8S 20.8S 20.8S 20.8S 20.9S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E bo) Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E 49.4E 49.3E 49.4E 49.4E 49.8E	905 ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32 12 50 11 8 53	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81 94 N/A 43 76 158	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A 215 N/A N/A N/A N/A 121 215	35 35 30 30 BT WN 35 55 65 65 65 60 55 55 45	0 0 0 0 0 0 -5 -20 0 0 -10 -5 -5	5 0 0 N/A 24 WE -30 -35 -25 -35 -15 -10 N/A -10 10 5	10 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A
DTG 89030906 89031006 89031018 Tropical DTG 89032500 89032512 89032600 89032612 89032618 89032718 89032718 89032800 89032812 89032900 89032912	W# 1 2 3 4 Cyclone W# 1 2 3 4 5 6 7 8 9 10 11	BT LAT 23.9S 26.4S 28.9S 30.4S 19S (Jina) BT LAT 16.6S 18.0S 19.0S 19.5S 19.9S 20.3S 20.8S 20.8S 20.8S 20.8S 20.9S 21.0S	# Cases BT ION 42.2E 43.3E 43.7E 44.7E 40.7E Average # Cases BT ION 52.7E 51.6E 51.2E 50.1E 49.8E 49.4E 49.3E 49.4E 49.4E 49.8E 50.4E	40 4 40 4 POS ER 63 30 37 31 00h 25 13 POS ER 16 29 24 24 32 12 50 11 8 53 5	220 3 24 ER 163 228 270 N/A 24h 113 11 24 ER 164 167 139 112 81 94 N/A 43 76 158 42	185 1 48 ER 185 N/A N/A N/A 184 3 48 ER N/A N/A 215 N/A N/A N/A N/A 121 215 N/A	35 35 35 30 30 BT WN 35 55 65 65 65 65 65 45 35	0 0 0 0 0 0 -5 -20 0 0 -10 -5 -5 0 5	5 0 0 N/A 24 WE -30 -35 -25 -35 -15 -10 N/A -10 10 5	10 N/A N/A N/A N/A N/A N/A N/A N/A N/A N/A

Tropical	Cyclone	20S (Ned)	Average # Cases	00h 22 19	24h 108 15	48h 202 11				
DTG	₩#	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89032612		17.4S	115.0E	29	8	49	35	0	-5	-30
89032700	2	17.88	113.5E	93	168	135	40	-5	-15	-40
89032706	* 3	18.1S	112.7E	37	121	208	45	0	-20	-35
89032712	4	18.45	111.8E	24	90	124	50	-5	-35	-30
89032718	5	18.85	110.9E	17	95	118	55	-5	-40	-20
89032800	6	19.25	110.2E	13	101	170	65	-10	-35	-5
89032806	7	19.55	109.7E	8	94	220	75	-5	-30	5
89032812	8	19.98	109.3E	5	108	246	90	-10	-5	45
89032818	9	20.38	109.1E	37	173	347	100	-10	10	45
89032900	10	20.7S	109.0E	5	74	337	100	5	15	35
89032906	11	21.1S	109.0E	13	.98	272	100	0	35	35
89032912		21.5S	108.9E	24	134	N/A	95	5	40	N/A
89032918		22.0S	108.8E	27	142	N/A	85	10	45	N/A
89033000	14	22.5S	108.7E	23	108	N/A	75	5	15	N/A
89033006		23.18	108.5E	12	105	N/A	55	10	15	N/A
89033012		23.98	108.4E	0	N/A	N/A	35	20	N/A	N/A
89033018		24.95	108.5E	6	N/A	N/A	30	20	N/A	N/A
89033100		26.0S	108.7E	10	N/A	N/A	30	5	N/A	N/A
89033106		27.0S	109.3E	30	N/A	N/A	30	0	N/A	N/A
*	6-hourl	y warnings	issued d	lue to th	reat.					
Tropical	Cyclone	21S (Kris	sv)	00h	24h	48h				
-	-	•	Average	27	144	282				
			# Cases	18	17	16				
DTG	₩ŧ					40 55	DD 733			40 177
		HOT LATE	HIT LINE	טמע אמט	74 WD					
		<u>BT_LAT</u> 12.25	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89033006	1	12.25	73.0E	67	115	204	55	-15	-10	-25
89033006 89033018	1 2	12.2S 12.4S	73.0E 72.3E	67 13	115 26	204 146	55 60	-15 -10	-10 -15	-25 -10
89033006 89033018 89033106	1 2 3	12.2S 12.4S 12.5S	73.0E 72.3E 71.5E	67 13 25	115 26 115	204 146 304	55 60 65	-15 -10 5	-10 -15 0	-25 -10 0
89033006 89033018 89033106 89033118	1 2 3 4	12.2S 12.4S 12.5S 12.6S	73.0E 72.3E 71.5E 70.7E	67 13 25 31	115 26 115 183	204 146 304 404	55 60 65 80	-15 -10 5 -10	-10 -15 0 -10	-25 -10 0 5
89033006 89033018 89033106	1 2 3 4 5	12.2S 12.4S 12.5S 12.6S 13.3S	73.0E 72.3E 71.5E 70.7E 70.1E	67 13 25 31 47	115 26 115 183 239	204 146 304 404 439	55 60 65 80 90	-15 -10 5 -10 -20	-10 -15 0 -10 -20	-25 -10 0 5 -20
89033006 89033018 89033106 89033118 89040106	1 2 3 4	12.25 12.45 12.55 12.65 13.35 14.35	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E	67 13 25 31 47 40	115 26 115 183 239 108	204 146 304 404 439 153	55 60 65 80 90 100	-15 -10 5 -10 -20 -5	-10 -15 0 -10 -20 -5	-25 -10 0 5 -20 -5
89033006 89033018 89033106 89033118 89040106 89040118	1 2 3 4 5 6	12.2s 12.4s 12.5s 12.6s 13.3s 14.3s 15.0s	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E	67 13 25 31 47 40 18	115 26 115 183 239 108 88	204 146 304 404 439 153 44	55 60 65 80 90 100	-15 -10 5 -10 -20 -5 10	-10 -15 0 -10 -20 -5	-25 -10 0 5 -20 -5 20
89033006 89033018 89033106 89033118 89040106 89040118 89040206	1 2 3 4 5 6	12.2S 12.4S 12.5S 12.6S 13.3S 14.3S 15.0S 15.6S	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E	67 13 25 31 47 40 18 36	115 26 115 183 239 108 88 111	204 146 304 404 439 153 44 210	55 60 65 80 90 100 95	-15 -10 5 -10 -20 -5 10 5	-10 -15 0 -10 -20 -5 0	-25 -10 0 5 -20 -5 20 5
89033006 89033018 89033106 89033118 89040106 89040118 89040206 89040218	1 2 3 4 5 6 7 8	12.2S 12.4S 12.5S 12.6S 13.3S 14.3S 15.0S 15.6S 16.5S	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E	67 13 25 31 47 40 18 36 8	115 26 115 183 239 108 88 111	204 146 304 404 439 153 44 210	55 60 65 80 90 100 95 90	-15 -10 5 -10 -20 -5 10 5	-10 -15 0 -10 -20 -5 0 5	-25 -10 0 5 -20 -5 20 5
89033006 89033018 89033106 89033118 89040106 89040118 89040206 89040218	1 2 3 4 5 6 7 8 9	12.2S 12.4S 12.5S 12.6S 13.3S 14.3S 15.0S 15.6S	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E	67 13 25 31 47 40 18 36 8	115 26 115 183 239 108 88 111	204 146 304 404 439 153 44 210 346 106	55 60 65 80 90 100 95 90 90	-15 -10 5 -10 -20 -5 10 5	-10 -15 0 -10 -20 -5 0 5 -5	-25 -10 0 5 -20 -5 20 5 -20
89033006 89033018 89033106 89033118 89040106 89040118 89040206 89040218 89040306 89040318	1 2 3 4 5 6 7 8 9	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E	67 13 25 31 47 40 18 36 8	115 26 115 183 239 108 88 111 186 53	204 146 304 404 439 153 44 210	55 60 65 80 90 100 95 90	-15 -10 5 -10 -20 -5 10 5	-10 -15 0 -10 -20 -5 0 5 -5 5	-25 -10 0 5 -20 -5 20 5 -20 5
89033006 89033018 89033106 89033118 89040106 89040118 89040206 89040218 89040306 89040318	1 2 3 4 5 6 7 8 9 10	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E	67 13 25 31 47 40 18 36 8 18	115 26 115 183 239 108 88 111 186 53 90	204 146 304 404 439 153 44 210 346 106 235	55 60 65 80 90 100 95 90 80 70	-15 -10 5 -10 -20 -5 10 5 0 5	-10 -15 0 -10 -20 -5 0 5 -5	-25 -10 0 5 -20 -5 20 5 -20 5
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040418	1 2 3 4 5 6 7 8 9 10 11	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E	67 13 25 31 47 40 18 36 8 18 5	115 26 115 183 239 108 88 111 186 53 90 128	204 146 304 404 439 153 44 210 346 106 235 275	55 60 65 80 90 100 95 90 80 70	-15 -10 5 -10 -20 -5 10 5 0 5	-10 -15 0 -10 -20 -5 0 5 -5 5 -15	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040418 89040418	1 2 3 4 5 6 7 8 9 10 11 12 13	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E	67 13 25 31 47 40 18 36 8 18 5 33	115 26 115 183 239 108 88 111 186 53 90 128 98	204 146 304 404 439 153 44 210 346 106 235 275 263	55 60 65 80 90 100 95 90 80 70 70 65	-15 -10 5 -10 -20 -5 10 5 0 5 5	-10 -15 0 -10 -20 -5 0 5 -5 5 -15	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040418 89040506	1 2 3 4 5 6 7 8 9 10 11 12 13 14	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E	67 13 25 31 47 40 18 36 8 18 5 33 21	115 26 115 183 239 108 88 111 186 53 90 128 98 163	204 146 304 404 439 153 44 210 346 106 235 275 263 324	55 60 65 80 90 100 95 90 80 70 70 65	-15 -10 5 -10 -20 -5 10 5 0 5 5	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040518 89040606 89040618	1 2 3 4 5 6 7 8 9 10 11 12 13 14	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E	67 13 25 31 47 40 18 36 8 18 5 33 21 32	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442	55 60 65 80 90 100 95 90 80 70 70 65 60	-15 -10 5 -10 -20 -5 10 5 5 5 5 5	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0 10 10	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5 10
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040618	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 56.8E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616	55 60 65 80 90 100 95 90 80 70 70 65 60 50	-15 -10 5 -10 -20 -5 10 5 5 5 10 5	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0 10 10 -10	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5 10 0
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040518 89040606 89040718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A	55 60 65 80 90 100 95 90 80 70 70 65 60 50 45	-15 -10 5 -10 -20 -5 10 5 5 5 10 5	-10 -15 0 -10 -20 -5 0 5 -15 0 10 10 -10 5	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5 10 0
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040518 89040606 89040718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A	55 60 65 80 90 100 95 90 80 70 70 65 60 50 45	-15 -10 5 -10 -20 -5 10 5 5 5 10 5	-10 -15 0 -10 -20 -5 0 5 -15 0 10 10 -10 5	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5 10 0
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040518 89040606 89040718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A	55 60 65 80 90 100 95 90 80 70 70 65 60 50 45	-15 -10 5 -10 -20 -5 10 5 5 5 10 5	-10 -15 0 -10 -20 -5 0 5 -15 0 10 10 -10 5	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5 10 0
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040518 89040606 89040718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A N/A	55 60 65 80 90 100 95 90 80 70 70 65 60 50 45	-15 -10 5 -10 -20 -5 10 5 5 5 10 5	-10 -15 0 -10 -20 -5 0 5 -15 0 10 10 -10 5	-25 -10 0 5 -20 -5 20 5 -20 5 -20 5 10 0
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040418 89040506 89040518 89040518 89040718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A N/A	55 60 65 80 90 100 95 90 80 70 65 60 50 45 35	-15 -10 5 -10 -20 -5 10 5 5 5 10 0	-10 -15 0 -10 -20 -5 0 5 -5 -15 0 10 10 -10	-25 -10 0 5 -20 -5 20 5 -20 5 10 0 N/A N/A
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040518 89040718	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E 7) Average # Cases	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A N/A	55 60 65 80 90 100 95 90 80 70 65 60 50 45 45 35	-15 -10 5 -10 -20 -5 10 5 5 5 10 0	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0 10 10 -10 10 5 N/A	-25 -10 0 5 -20 5 -20 5 -20 5 10 0 N/A N/A
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040518 89040506 89040518 89040718 Tropical	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	12.2S 12.4S 12.5S 12.6S 13.3S 14.3S 15.0S 15.6S 17.1S 17.2S 17.7S 18.6S 19.5S 20.0S 21.8S 23.4S 24.5S	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E 7) Average # Cases BT LON 179.8W	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A N/A	55 60 65 80 90 100 95 90 80 70 65 60 50 45 45 35	-15 -10 5 -10 -20 -5 10 5 5 5 10 0 0	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0 10 -10 10 N/A	-25 -10 0 5 -20 5 -20 5 -20 5 10 0 N/A N/A
89033006 89033018 89033118 89033118 89040106 89040118 89040206 89040218 89040306 89040418 89040406 89040518 89040618 89040718 Tropical	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58 ET LAT 19.38 21.08	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E 7) Average # Cases BT LON 179.8W 177.5E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A N/A *** *** *** *** *** *** *** *** *** *	55 60 65 80 90 100 95 90 80 70 65 60 50 45 45 35	-15 -10 5 -10 -20 -5 10 5 5 5 10 0 0	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0 10 10 -10 10 5 N/A	-25 -10 0 5 -20 5 -20 5 -20 5 10 0 N/A N/A
89033006 89033018 89033118 89040106 89040118 89040206 89040218 89040306 89040318 89040406 89040506 89040518 89040618 89040718 Tropical	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 Cyclone	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58 ET LAT 19.38 21.08 22.18	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E 7) Average # Cases BT LON 179.8W 177.5E 177.4E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A 24h 158 4 24 ER 131 147 116	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A N/A *** *** *** *** *** *** *** *** *** *	55 60 65 80 90 100 95 90 80 70 65 60 50 45 45 35	-15 -10 5 -10 -20 -5 10 5 5 5 10 0 0	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0 10 -10 10 -10 10 5 N/A	-25 -10 0 5 -20 5 -20 5 -20 5 10 0 N/A N/A
89033006 89033018 89033118 89033118 89040106 89040118 89040206 89040218 89040306 89040418 89040406 89040518 89040618 89040718 Tropical	1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18	12.28 12.48 12.58 12.68 13.38 14.38 15.08 15.68 16.58 17.18 17.28 17.78 18.68 19.58 20.08 21.88 23.48 24.58 ET LAT 19.38 21.08	73.0E 72.3E 71.5E 70.7E 70.1E 70.0E 70.2E 70.5E 70.4E 69.2E 67.4E 65.8E 63.7E 61.4E 58.6E 54.7E 53.2E 7) Average # Cases BT LON 179.8W 177.5E	67 13 25 31 47 40 18 36 8 18 5 33 21 32 17 50 33 0	115 26 115 183 239 108 88 111 186 53 90 128 98 163 223 191 332 N/A	204 146 304 404 439 153 44 210 346 106 235 275 263 324 442 616 N/A N/A *** *** *** *** *** *** *** *** *** *	55 60 65 80 90 100 95 90 80 70 65 60 50 45 45 35	-15 -10 5 -10 -20 -5 10 5 5 5 10 0 0	-10 -15 0 -10 -20 -5 0 5 -5 5 -15 0 10 10 -10 10 5 N/A	-25 -10 0 5 -20 5 -20 5 -20 5 10 0 N/A N/A

Tronical	Cuclone	23P (Aivu		0.0%	0.45	AOL				
roprogr	cletan	ZOF PALVO	Average	<u>00h</u> 27	24h 108	48h 172				
			# Cases	8	7	4				
						_				
DIG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89040100	1	10.35	152.7E	18	158	209	35	0	-5	-35
89040112	2	11.85	151.9E	31	167	190	45	0	-10	-45
89040200	-	13.98	150.8E	16	54	112	60	0	-25	0
89040212 89040300	4 5	15.6S	149.6E	18	174	175	75	0	-60	-15
89040312	6	16.4S 17.9S	149.2E 148.8E	5	56	N/A	110	0	0	N/A
89040400	7	17.9S 19.3S	140.0E	8 6	74 76	N/A	120 100	0	15	N/A
89040412	8	20.45	147.7E	116	N/A	N/A N/A	45	0 5	5 N/A	N/A
030.0122	Ū	20.30	140.95	110	M/A	N/A	43	3	N/A	N/A
Tropical	Cyclone	248 (Lezi	eev)	00h	24h	48h				
	olone	240 (2022	Average	64	260	455				
			# Cases	6	4	2				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89040612	1	11.98	73.8E	74	300	512	40	-5	10	40
89040700	2	12.85	72.1E	75	268	398	45	o	20	65
89040712	3	13.25	71.8E	57	233	N/A	45	-10	5	N/A
89040800	4	13.58	71.7E	130	237	N/A	45	0	20	N/A
89040812	5	14.2S	71.5E	42	N/A	N/A	35	5	N/A	N/A
89040900	6	15.58	70.3E	8	N/A	N/A	25	Õ	N/A	N/A
										•
Tropical	Cvclone	25P (Lili	١	00h	24h	48h				
	- 	,	, Average	23	104	217				
			# Cases	9	8	8				
DIG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89040700	1	12.1S	162.2E	72	155	237	30	5	-5	-20
89040712	2	13.15	163.9E	31	133	138	40	-5	-35	-50
89040800	3	13.8S	164.5E	18	88	150	60	5	-10	-10
89040812	4	14.45	164.7E	17	102	285	80	0	-5	30
89040900 89040912	5	15.6S	164.6E	16	54	151	95	5	5	65
89041000	6 7	17.18	164.6E	5	94	55	105	0	35	50
89041012	8	19.0S 21.1S	165.0E	8	63	136	100	10	20	10
89041100	9	23.15	166.2E 167.1E	12 24	145	584	70 25	-5	20	15
03041100	,	23.13	107.15	24	N/A	N/A	35	0	N/A	N/A
Tropical	Cvclone	268 (Orso	a)	<u>00h</u>	24h	48h				
-		, , , , , , , , , , , , , , , , , , , ,	Average	19	105	225				
			# Cases	12	9	7				
DTG	Wž	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW_ER	24 WE	48 WE
89041812	1	13.18	123.7E	23	76	148	35	0	-10	-10
89041900	2	12.85	122.3E	37	77	170	50	ŏ	-20	-40
89041912	3	12.35	121.0E	30	53	99	65	Ö	-10	-50
89042000	4	12.0S	119.9E	8	101	283	75	ō	-15	-30
89042012	5	12.35	118.7E	13	74	330	85	- 5	-20	-35
89042100	6	13.4S	117.7E	21	51	186	105	ō	5	0
89042112	7	14.68	116.8E	29	64	362	115	0	-40	35
89042200	8	16.4S	116.3E	0	162	N/A	125	0	10	N/A
89042212	9	18.6S	116.3E	12	287	N/A	140	0	45	N/A
89042218*		20.1S	116.3E	16	N/A	N/A	125	0	N/A	N/A
89042300	11	22.0S	116.6E	12	N/A	N/A	100	0	N/A	N/A
89042306	12	24.1S	117.4E	26	N/A	N/A	75	0	N/A	N/A
*	6-hourly	warnings	issued d	ue to th	reat.					

Tropical	Cyclone	27P (Meen	Average # Cases	00h 21 16	24h 134 15	48h 287 12				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89050300	1	11.85	161.3E	21	256	336	25		0	-10
89050312	2	11.15	161.9E	24	102	288	30	0	0	-15
89050400	3	12.0S	161.3E	6	42	306	30	0	-10	-15
89050412	4	12.8S	161.2E	13	128	394	35	0	0	0
89050500	5	13.6S	160.3E	34	205	482	45	-5	-10	-10
89050512	6	14.7S	159.0E	11	187	N/A	45	-10	-15	N/A
89050600	7	15.6S	156.9E	16	164	337	45	-5	- 5	0
89050612	8	14.7S	155.0E	74	290	408	45	0	0	0
89050700	9	13.4S	152.3E	25	66	330	40	-5	0	0
89050712	10	12.38	150.3E	24	109	46	35	5	0	10
89050800	11	12.5S	148.8E	5	101	193	35	0	15	5
89050812	12	12.4S	146.8E	46	46	204	35	0	5	10
89050900	13	12.5S	143.3E	8	97	123	30	5	5	10
89050912	14	12.6S	141.8E	6	134	N/A	20	10	10	N/A
89051000	15	11.4S	138.7E	12	90	N/A	25	0	10	N/A
89051012	16	11.4S	136.9E	8	A\N	N/A	25	5	N/A	N/A
Tropical	Cyclone	28P (Ernic	a }	00h	24h	48h				
<u>-</u>	_		Average	31	135	197				
			# Cases	9	7	5				
DTG	₩ŧ	BT LAT	BT LON	POS ER	24 ER	48 ER	BT WN	WW ER	24 WE	48 WE
89050706	1	12.45	169.9E	29	21	25	30	0	5	20
89050718	2	12.4S	167.3E	37	124	146	30	. 0	10	25
89050806	3	11.9S	164.9E	33	88	206	35	0	10	20
89050818	4	11.98	162.4E	5	97	247	30	5	10	0
89050906*		12.68	160.1E	18	N/A	N/A	30	0	N/A	N/A
89051018	6	12.45	151.5E	77	246	362	30	0	15	25
89051106	7	12.58	150.8E	41	289	N/A	30	-5	0	N/A
89051118	8	12.75	150.6E	11	76	N/A	30	0	5	N/A
89051206	9	12.65	150.2E	30	N/A	N/A	30	-5	N/A	N/A
*	Regenera	ated							,	

APPENDIX A DEFINITIONS

BEST TRACK - A subjectively smoothed path, versus a precise and very erratic fix-to-fix path, used to represent tropical cyclone movement.

CENTER - The vertical axis or core of a tropical cyclone. Usually determined by cloud vorticity patterns, wind and/or pressure distribution.

EPHEMERIS - Position of a body (satellite) in space as a function of time; used for gridding satellite imagery. Since ephemeris gridding is based solely on the predicted position of the satellite, it is susceptible to errors from vehicle wobble, orbital eccentricity and the oblateness of the Earth.

EXPLOSIVE DEEPENING - A decrease in the minimum sea-level pressure of a tropical cyclone of 2.5 mb/hr for 12 hours or 5.0 mb/hr for six hours (Dunnavun, 1981).

EXTRATROPICAL - A term used in warnings and tropical summaries to indicate that a cyclone has lost its "tropical" characteristics. The term implies both poleward displacement from the tropics and the conversion of the cyclone's primary energy source from the release of latent heat of condensation to baroclinic processes. It is important to note that cyclones can become extratropical and still maintain winds of typhoon or storm force.

EYE - The central area of a tropical eyclone when it is more than half surrounded by wall cloud.

FUJIWHARA EFFECT - A binary interaction where tropical cyclones within about 750 nm (1390 km) of each other begin to rotate about one another. When tropical cyclones are within about 400 nm (740 km) of each other, they may also begin to be drawn closer to one another (Brand, 1970) (Dong and Neumann, 1983).

INTENSITY - The maximum sustained 1-minute mean surface wind speed, typically within one degree of the center of a tropical cyclone.

MAXIMUM SUSTAINED WIND - The highest surface wind speed averaged over a one-minute period of time. (Peak gusts over water average 20 to 25 percent higher than sustained winds.)

RAPID DEEPENING - A decrease in the minimum sea-level pressure of a tropical cyclone of 1.25 mb/hr for 24-hours (Holliday and Thompson, 1979).

RECURVATURE - The turning of a tropical cyclone from an initial path toward the west and poleward to east and poleward.

SIGNIFICANT TROPICAL CYCLONE - A tropical cyclone becomes "significant" with the issuance of the first numbered warning by the responsible warning agency.

SIZE - The areal extent of a tropical cyclone, usually measured radially outward from the center to the outermost closed isobar.

STRENGTH - The average wind speed of the surrounding low-level wind flow, usually measured within one to three degrees of the center of a tropical cyclone.

SUBTROPICAL CYCLONE - a low pressure system that forms over the ocean in the subtropics and has some characteristics of a tropical circulation, but not a central dense overcast. Although of upper cold low or low-level baroclinic origins, the system can transition to a tropical cyclone.

SUPER TYPHOON - A typhoon with maximum sustained 1-minute mean surface winds of 130 kt (67 m/sec) or greater.

TROPICAL CYCLONE - A non-frontal, migratory low-pressure system, usually of synoptic scale, originating over tropical or subtropical waters and having a definite organized circulation.

TROPICAL DEPRESSION - A tropical cyclone with maximum sustained 1-minute mean surface winds of 33 kt (17 m/sec) or less.

TROPICAL DISTURBANCE - A discrete system of apparently organized convection, generally 100 to 300 nm (185 to 555 km) in diameter, originating in the tropics or subtropics, having a non-frontal, migratory character and having maintained its identity for 12- to 24-hours. It may or may not be associated with a detectable perturbation of the wind field. It is the basic generic designation which, in successive stages of development, may be classified as a tropical depression, tropical storm, typhoon or super typhoon.

TROPICAL STORM - A tropical cyclone with maximum sustained surface winds in the range of 34 to 63 kt (17 to 32 m/sec) inclusive.

TROPICAL UPPER-TROPOSPHERIC TROUGH (TUTT) - A dominant climatological system and a daily upper-level synoptic feature of the summer season, over the tropical North Atlantic, North Pacific and South Pacific Oceans (Sadler, 1979).

TYPHOON (HURRICANE) - A tropical cyclone with maximum sustained 1-minute mean surface winds of 64 to 129 kt (33 to 66 m/sec). West of 180 degrees longitude they are called typhoons and east of 180 degrees longitude hurricanes.

WALL CLOUD - An organized band of cumuliform clouds that immediately surrounds the central area of a tropical cyclone. The wall cloud may entirely enclose or partially surround the center.

APPENDIX B NAMES FOR TROPICAL CYCLONES (EFFECTIVE AFTER TY WAYNE (25W) 1989)

CAITLIN DOUG ELLIE FRED GLADYS HARRY IVY JOEL KINNA LUKE MIREILLE NAT ORCHID PAT RUTH SETH THELMA VERNE WILDA YURI	BOBBIE CHUCK DEANNA ELI FAYE GARY HELEN IRVING JANIS KENT LOIS MARK NINA OMAR POLLY RYAN SIBYL TED VAL WARD YVETTE
ZELDA	ZACK
VERNE WILDA YURI	VAL WARD YVETTE
	DOUG ELLIE FRED GLADYS HARRY IVY JOEL KINNA LUKE MIREILLE NAT ORCHID PAT RUTH SETH THELMA VERNE WILDA YURI

NOTE: Names are assigned in rotation and alphabetically. When the last name in Column 4 (ZACK) has been used, the sequence will begin again with the first name in Column 1 (ANGELA).

SOURCE: CINCPACINST 3140.1T

NAMES FOR TROPICAL CYCLONES (PRIOR TO TY ANGELA (26W) 1989)

Column 1 ANDY	Column 2 ABBY	Column 3 ALEX	Column 4 AGNES
BRENDA	BEN	BETTY	BILL
CECIL	CARMEN	CARY	CLARA
DOT	DOM	DINAH	DOYLE
ELLIS	ELLEN	ED	ELSIE
FAYE	FORREST	FREDA	FABIAN
GORDON	GEORGIA	GERALD	GAY
HOPE	HERBERT	HOLLY	HAL
IRVING	IDA	IAN	IRMA
JUDY	JOE	JUNE	JEFF
KEN	KIM	KELLY	KIT
LOLA	LEX	LYNN	LEE
MAC	MARGE	MAURY	MAMIE
NANCY	NORRIS	NINA	NELSON
OWEN	ORCHID	OGDEN	ODESSA
PEGGY	PERCY	PHYLLIS	PAT
ROGER	RUTH	ROY	RUBY
SARAH	SPERRY	SUSAN	SKIP
TIP	THELMA	THAD	TESS
VERA	VERNON	VANESSA	VAL
WAYNE	WYNNE	WARREN	WINONA

APPENDIX C

REFERENCES

- Allen, R. L., 1984: COSMOS: CYCLOPS Objective Steering Model Output Statistics. Postprints, 15th Conference on Hurricanes and Tropical Meteorology. Miami, FL, January 9-13, 1984, pp. 14-20.
- Atkinson, G. D. and C. R. Holliday, 1977: Tropical Cyclone Minimum Sea-Level Pressure and Maximum Sustained Wind Relationship for the Western North Pacific. *Monthly Weather Review*, Vol. 105, No. 4, pp. 421-427 (also FLEWEACEN TECH NOTE: JTWC 75-1).
- Brand, S., 1970: Interaction of Binary Tropical Cyclones of the Western North Pacific Ocean. *Journal of Applied Meteorology*, Vol. 9, pp. 433-441.
- Brand, S. and J. W. Blelloch, 1973: Changes in the Characteristics of Typhoons Crossing the Island of Taiwan. ENVPREDRSCHFAC Technical Paper No. 8-73, 21 pp.
- Brand, S. and C. P. Guard, 1978: Extratropical Storm Evolution from Tropical Cyclones in the Western North Pacific Ocean. NAVENVPREDRSCHFAC, TR78-02, 24 pp.
- Darwin RMC, 1989: Darwin Tropical Diagnostic Statement, July 1989, Vol. 8, No. 7, Fig. 4.
- Diercks, J. M., R. C. Weir and M. K. Kopper, 1982: Forecast Verification and Reconnaissance Data for Southern Hemisphere Tropical Cyclones (July 1980 through June 1982). NAVOCEANCOMCEN/JTWC TECH NOTE 82-1, 77 pp.
- Dong, K. and C. J. Neumann, 1983: On the Relative Motion of Binary Tropical Cyclones. *Monthly Weather Review*, Vol. 111, pp. 945-953.
- Dunnavan, G. M., 1981: Forecasting Intense Tropical Cyclones Using 700 mb Equivalent Potential Temperature and Central Sea-Level Pressure. NAVOCEACOMCEN/JTWC TECH NOTE 81-1, 12 pp.
- Dvorak, V. F., 1984: Tropical Cyclone Intensity Analysis Using Satellite Data. NOAA Technical Report NESDIS 11, U. S. Department of Commerce, National Oceanic and Atmospheric Administration, National Earth Satellite Service, Washington, D. C., 20233, 46 pp.
- Guard, C. P., 1983: A Study of Western North Pacific Tropical Storms and Typhoons that Intensify after Recurvature. 1WW/TN-83/002, 28 pp.

- Herbert, P. H. and K. O. Poteat, 1975: A Satellite Classification Technique for Subtropical Cyclones. NOAA Technical Memorandum NWS SR-83, 25 pp.
- Holland, G. R., 1980: An Analytical Model of Wind and Pressure Profiles in Hurricanes. *Monthly Weather Review*, Vol. 108, No. 8, pp. 1212-1218.
- Holliday, C. R. and A. H. Thompson, 1979: Climatological Characteristics of Rapidly Intensifying Typhoons. *Monthly Weather Review*, Vol. 107, pp. 1022-1034.
- Matsumoto, C. R., 1984: A Statistical Method for Oneto Three-Day Tropical Cyclone Track Prediction. Atmospheric Science Paper 379, Department of Atmospheric Science, Colorado State University, Fort Collins, Colorado, 201 pp.
- Sadler, J. C., 1974: A Role Of Tropical Upper Tropospheric Trough in the Early Season Typhoon Development. NAVENVPREDRSCHFAC Technical Paper No. 2-76, 104 pp.
- Sadler, J. C., 1979: Tropical Cyclone Initiation by the Upper-Tropospheric Trough. Naval Environmental Prediction Research Facility Technical Paper No. 2-76, 103 pp.
- Sikora, C. R., 1976: A Reevaluation of the Changes in Speed and Intensity of Tropical Cyclones Crossing the Philippines, FLEWEACEN TECH NOTE: JTWC 76-2, 11 pp.
- Tsui, T. L. and R. J. Miller, 1986: Evaluation of JTWC Tropical Cyclone Objective Forecast Aids (1978-85). Naval Environmental Prediction Research Facility Technical Report, TR 86-05, 44 pp.
- Weir, R. C., 1982: Predicting the Acceleration of Northward-moving Tropical Cyclones using Upper-Tropospheric Winds. NAVOCEANCOMCEN/JTWC TECH NOTE 82-2, 40 pp.
- Wirfel, W. P. and S. A. Sandgathe, 1986: Forecast Verification and Reconnaissance Data for Southern Hemisphere Tropical Cyclones (July 1982 through June 1984). NAVOCEANCOMCEN/JTWC TECH NOTE 86-1, 102 pp.
- Xu, Y. and C. J. Neumann, 1985: A Statistical Model for the Prediction of Western North Pacific Tropical Cyclone Motion. NOAA Technical Memorandum NWS NHC 28, 30 pp.

APPENDIX D

PAST ANNUAL TROPICAL CYCLONE REPORTS

Copies of the past Annual Tropical Cyclone Reports can be obtained through:

National Technical Information Service 5285 Port Royal Road Springfield, Virginia 22161

Refer to the following acquisition numbers when ordering:

YEAR	ACQUISITION NUMBER
1959	AD 786147
1960	AD 786148
1961	AD 786149
1962	AD 786128
1963	AD 786208
1964	AD 786209
1965	AD 786210
1966	AD 785891
1967	AD 785344
1968	AD 785251
1969	AD 785178
1970	AD 785252
1971	AD 768333
1972	AD 768334
1973	AD 777093
1974	AD 010271
1975	AD A023601
1976	AD A038484
1977	AD A055512
1978	AD A070904
1979	AD A082071
1980	AD A094668
1981	AD A112002
1982	AD A124860
1983	AD A137836
1984	AD A153395
1985	AD A168284
1986	AD A184082
1987	AD A191883
1988	AD A207206

Intentionally left blank.

77	7 1987	 4	 	 - 1 2 -	PAGE

REPORT DOCUMENTATION PAGE					Form Approved OMB No. 0704-0188
1a. REPORT SECURITY CLASSIFICATION UNCLASSIFIED		16. RESTRICTIVE MARKINGS			
2a. SECURITY CLASSIFICATION AUTHORITY 2b. DECLASSIFICATION / DOWNGRADING SCHEDULE		3. DISTRIBUTION/AVAILABILITY OF REPORT AS IT APPEARS IN THE REPORT/			
		DISTRIBUTION UNLIMITED			
4. PERFORMING ORGANIZATION REPORT NUMBER(S)		5. MONITORING ORGANIZATION REPORT NUMBER(\$)			
6a. NAME OF PERFORMING ORGANIZATION NAVOCEANCOMCEN/JTWC	6b. OFFICE SYMBOL (If applicable)	7a. NAME OF MONITORING ORGANIZATION NAVOCEANCOMCEN/JTWC			
6c. ADDRESS (City, State, and ZIP Code) COMNAVMAR BOX 12 FPO SAN FRANCISCO, CA 96630-2926		7b. ADDRESS (City, State, and ZIP Code) COMNAVMAR BOX 12 FPO SAN FRANCISCO, CA 96630-2926			
8a. NAME OF FUNDING/SPONSORING ORGANIZATION NAVOCEANCOMCEN/JTWC	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT INSTRUMENT IDENTIFICATION NUMBER			
8c. ADDRESS (City, State, and ZIP Code) COMNAVMAR BOX 12 FPO SAN FRANCISCO, CA 96630-2926		10. SOURCE OF FUNDING NUMBERS			
		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO.
11. TITLE (Include Security Classification) 1989 ANNUAL TROPICAL CYCLONE REPORT					
12. PERSONAL AUTHOR(S)					
13a. TYPE OF REPORT 13b. TIME (ANNUAL FROM J	14. DATE OF REPORT (Year, Month, Day) 15. PAGE COUNT 253 PLUS i-x				
16. SUPPLEMENTARY NOTATION					
17. COSATI CODES 18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)			
FIELD GROUP SUB-GROUP	TROPICAL CYCLO				
04 02	TROPICAL DEPRE	RESSIONS TYPHOONS/SUPER TYPHOONS LONE RESEARCH METEOROLOGICAL SATELLITES			
19. ABSTRACT (Continue on reverse if necessary and identify by block number)					
ANNUAL PUBLICATION SUMMARIZING TROPICAL CYCLONE ACTIVITY IN THE UESTERN NORTH PACIFIC, BAY OF BENGAL, ARABIAN SEA, WESTERN SOUTH PACIFIC AND SOUTH INDIAN OCEANS. A BEST TRACK IS PROVIDED FOR EACH SIGNIFICANT TROPICAL CYCLONE. A BRIEF NARRATIVE IS GIVEN FOR ALL TROPICAL CYCLONES IN THE WESTERN NORTH PACIFIC AND NORTH INDIAN OCEANS. ALL RECONNAISSANCE AND FIX DATA USED TO CONSTRUCT THE BEST TRACKS ARE PROVIDED, UPON REQUEST, ON FLOPPY DISKETTES. FORECAST VERIFICATION DATA AND STATISTICS FOR THE JOINT TYPHOON WARNING CENTER (JTWC) ARE SUBMITTED.					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT ☑ UNCLASSIFIED/UNLIMITED ☑ SAME AS RPT. ☐ DTIC USERS		21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED			
22a. NAME OF RESPONSIBLE INDIVIDUAL FRANK H. WELLS	22b. TELEPHONE (1 671–344–52	Include Area Code) 40	t .	FICE SYMBOL C/JTWC	

UNCLASSIFIED

BLOCK 18 CONTINUED

RADAR AUTOMA

AUTOMATIC WEATHER OBSERVING STATIONS

SYNOPTIC DATA

TROPICAL CYCLONE INTENSITY

TROPICAL CYCLONE BEST TRACK DATA

TROPICAL CYCLONE FORECASTING

TROPICAL CYCLONE RECONNAISSANCE

TROPICAL CYCLONE STEERING MODELS

OBJECTIVE FORECASTING TECHNIQUES

TROPICAL CYCLONE FIX DATA

MICROWAVE IMAGERY

DRIFTING BUOYS